

Trust Dynamics in Multi-Agent Strategic Interaction: A Simulation Study of Bayesian Reputation Systems in 8-Player Limit Texas Hold'em

Rachit Agrawal¹

¹Independent research, 2025–2026. Correspondence: rachit.agrawal@sahyadrischool.org

ABSTRACT

WHAT IF BEING TRUSTWORTHY COST YOU SOMETHING? Reputation systems (online marketplaces, credit scoring and social platforms) reward “good” behavior—however, there is a well-known paradox among economists. A totally transparent and cooperative player will get less than a somewhat unreliable player. We placed that paradox into a petri-dish. Eight poker-players played tens of thousands of hands. Each player silently profiled all other players’ styles, and updated those beliefs at each hand. Then we swapped the minds of the agents across four different levels of complexity—from strict rule followers to large language models capable of reasoning about what their opponents would do, while keeping both the game and the trust model constant. And so, it happened again. The best reputations were the least rewarded, and no amount of optimization changed that. It wasn’t until the agents were able to reason about the reputation system that some relief began to occur. The result is a compact, completely replicable laboratory for exploring the very important question—when does a good reputation become a bad thing?

1 INTRODUCTION

Trust is a fundamental part of human society that is the foundation for human interactions that we have every day. Every business deal, every bank loan, every purchase, and even every relationship is built on trust. This is also reflected by modern-day systems, for example: Amazon shows product reviews, banks check credit scores before lending out loans, and Reddit ranks posts by community voting. Picture this: There are two real estate development firms. The first one is working on their first project; they are new in the market. The second one is an established firm with good reviews and a good history. Now, who would you trust with your life savings to build your dream home? You see, visible reputation systems seem like a win-win. It is easy for you to make the right decision while the trusted agents are rewarded.

Here is the breaking point: this transparency comes with a contradiction. A trusted agent is almost by definition always predictable. When it is right to cooperate, they cooperate, and because everyone knows this in an open environment, the opponent can plan around them. This is what was observed in the real world: eBay sellers with a perfect rating earned lower profit margins than those with a slightly imperfect record (11, 3). The reason was that buyers knew the perfect-rated seller would not risk their perfect score, so the listed price was the lowest they would go. Sellers with imperfect records were not bound by this. Predictability could be exploited (7).

We wanted to answer this question but in a controlled environment where we tampered with each of the features, like the rules,

the agents, and the trust dynamics between them, and saw for ourselves how they would affect the outcome. While we could draw conclusions from real economic data, we could not run controlled experiments on them; therefore, we settled on running computer simulations. We asked whether reputation systems that infer trust from behaviour ended up rewarding exploitation. Was the system’s loss of trust economically optimal? Was the answer more dependent on the design of the trust system or the design of the characters themselves?

Poker turned out to be the perfect environment to try this. Each hand was a set of interactions that mapped directly to real-life interactions—while there was some hidden information (for example, a player’s private cards¹), public actions (bets, calls, and folds) were visible to everyone at the table. Fixed-limit Texas Hold'em² was the way to go, where both the bet sizes and action spaces were small enough to make the math tractable but also rich enough for these strategies to emerge. Please note that poker is only the behavioural microscope and not a benchmark to solve.

Specifically, we built a poker simulation using eight players in which each player embodied a distinct playing style. Each agent maintained a perception about the others with a probability distribution to understand whether the opponent is a “tight player

¹The two private cards each player is dealt at the start of every hand; only the player can see them.

²Limit Texas Hold'em fixes the bet size on each round. In our setup, bets and raises on the first two rounds are 2 chips; on the last two rounds they are 4 chips. No player can place more than four bets in a single round (the “four-bet cap”), which keeps the action space small and the math tractable.

who only plays strong hands” or a “loose maniac who bets with a deuce-seven”, and so on. After every action, the agents updated their belief systems. Trust was the honesty we expected from an opponent according to our level of confidence in their archetype. We calculated the Pearson correlation³ between the economic return earned and the trust coefficient. We varied the nature of the agents, starting relatively simple and becoming more complex. The game and the trust system were the same across phases; only the agents changed. This study could not have been possible without the established work presented in the following section.

2 BACKGROUND

There are four lines of previous research motivating this study. We summarize them here in the order they influence our design:

- The experimental economic literature on reputation systems in the Internet age: this is the body of research documenting the cost of transparency.
- Computational studies on cooperation in repeated games—including the Prisoner’s Dilemma to Axelrod’s tournaments.
- Bayesians use in modeling poker opponents—the inference mechanism we adopted.
- The still-open question of whether large language models can reason strategically, or only mimic strategy.

Together, these define our core question: does the cost of being trusting depend on either the trust system or on the agents inside it?

2.1 Online reputation systems

First, there is the empirical economics of online reputation systems. Resnick & Zeckhauser’s large-scale study of eBay (11) documented that feedback is provided more than half the time and is almost always positive, with sellers receiving negative feedback only about 1% of the time—evidence that observable reputation is pervasive and that markets broadly reward good behavior rather than penalize it. The motivating tension for our work is therefore a theoretical *transparency paradox* rather than a settled empirical fact: when a cooperator’s behavior is perfectly predictable, a sufficiently sophisticated counterparty can plan around it and extract value, so visible cooperation could in principle be exploited. The cleanest controlled evidence on eBay in fact points the other way—toward a reputation premium for established identities—which makes the paradox a hypothesis worth testing rather than a documented effect. Bolton, Katok, & Ockenfels (3) examine how reputation institutions shape cooperation in controlled trust games, and an analogous dynamic appears in financial-market microstructure, where adverse selection against predictably behaving market makers (7) produces related effects through asymmetric information. What this literature cannot

³The Pearson correlation coefficient measures the linear relationship between two paired variables on a scale of -1 (perfect negative) to $+1$ (perfect positive); $r = 0$ means no linear relationship, and $|r| \approx 0.5$ is conventionally a moderate effect.




Figure 1. The Prisoner’s Dilemma, as a game of trust. A screenshot of the cooperate/cheat setup from Nicky Case’s *Evolution of Trust* interactive: putting a coin in the machine costs you one coin but gives the other player three. Mutual cooperation therefore pays $+2$ each, mutual cheating 0 each, and unilateral cheating against a cooperator pays $+3$ to the defector against -1 to the cooperator.

settle—because it does not re-engineer the population of agents—is whether the paradox would survive if cooperative actors were intelligent enough to avoid being exploited; that gap is what our controlled simulation is built to probe.

2.2 Cooperation in repeated games

Second, there is a substantial amount of computational research concerning cooperation in repeated games. Prior to discussing cooperation, it is necessary to discuss the Prisoner’s Dilemma as it is widely recognized as the paradigmatic example of the conflict between cooperation and exploitation. Each prisoner has two options: (A) Cooperate or (B) Defect. Each prisoner makes their decision simultaneously. There are four possible outcomes based upon the decisions made by each of the prisoners. When both prisoners choose option (A)—i.e., cooperate with one another—each receives a moderate reward. When one prisoner chooses option (A) (cooperates) and the other selects option (B) (defects), the cooperator incurs a loss while the defector receives the largest reward and pays no penalty. When both prisoners select option (B), i.e., defect, neither receives any reward. Figure 1 illustrates these four possible outcomes using the framing of Nicky Case’s *Evolution of Trust* interactive: mutual cooperation provides a reward of $+2$ to both players; mutual defection provides a reward of 0 to both players; and unilaterally defecting against a cooperator provides a reward of $+3$ to the defector and a loss of -1 to the cooperator. In terms of rational self-interest, each prisoner has sufficient incentive to defect since defecting always yields greater benefits than cooperating, regardless of the choice made by the other prisoner; Nevertheless, mutually defective behavior is inferior in comparison to mutually cooperative behavior.

Axelrod investigated this problem extensively through his Prisoner’s Dilemma Tournaments (1), and Nowak developed his

Table 1. A primer on fixed-limit Texas Hold'em. The minimum set of concepts needed to read the rest of the paper. The betting bounds in the “Bet sizing” row are the specific values we use throughout the simulation; everything else applies to fixed-limit Hold'em in general.

Concept	Description
Hole cards	The two private cards each player is dealt at the start of every hand; only that player can see them.
Community cards	Up to five face-up cards shared by everyone at the table; players combine these with their hole cards to form a 5-card hand.
Betting rounds	Four sequential rounds per hand: preflop (no community cards yet), flop (three community cards revealed), turn (one more), and river (the fifth and final).
Actions	At each turn a player may fold (give up the hand), check (pass without betting, only if no one has bet), call (match the current bet), bet (open the wagering), or raise (increase an existing bet).
Bet sizing (this paper)	Small bet 2 chips on preflop and flop; big bet 4 chips on turn and river; no more than four raises per round (the “four-bet cap”).
Blinds	Forced bets: small blind 1 chip and big blind 2 chips, posted by the two seats clockwise of the dealer and rotating each hand.
Pot	The accumulated chips at stake in a hand. The winner of the hand collects the pot.
Showdown	End-of-hand reveal: surviving players turn over their hole cards and the strongest 5-card combination wins. A hand that ends with everyone folding never reaches showdown.
Stack	The chips a player has in front of them; depleting to zero triggers a rebuy in our setup.

five rules for the evolutionary development of cooperation (9). Axelrod demonstrated that reciprocity-based strategies such as Tit-for-Tat are robustly effective in one-to-one situations. Agents that cooperate by default and punish defectors on a tit-for-tat basis tend to perform effectively over time against all types of competitors. This lends credence to the notion that cooperation can represent a viable strategic alternative. However, Axelrod's conclusions are predicated upon two assumptions which fail to apply in our context. Firstly, all interactions are now no longer one-to-one but instead involve eight separate agents. As a result, the negative impact associated with aggressive behavior on behalf of a single individual is diluted across seven other competing agents versus being focused solely upon one opponent. Secondly, the set of actions available for an agent to take extends far beyond simply cooperating or defecting. Poker allows an agent to fold, call, raise, bluff⁴ and slow-play—all of which add additional degrees-of-freedom for an agent seeking to extract value from their opponent(s). Our best approximation to Tit-for-Tat is **Mirror**—which ranks 6th out of 8 in terms of Phase 1 stacks—suggesting that Axelrod's conclusions do not necessarily translate well to multi-agent environments that contain richer action-spaces; although we interpret this as suggestive rather than definitive.

2.3 Bayesian opponent modelling in poker

Third, there is Bayesian opponent modeling in poker. Initially this included Billings et al.'s Loki and Poki bots (2) and subsequently formalized by Southey et al. (12) as Bayesian-type inference—followed by Ganzfried and Sandholm's (6) further generalization toward safe-exploitation of an opponent. Most recently, Carnegie Mellon University's Libratus and Pluribus (4, 5) reached super-human performance levels in heads-up and six-player no-limit Texas Hold'em. While that body of work differs from our own

⁴A *bluff* is a bet made with a weak hand intended to make opponents fold stronger hands; its inverse, a *value bet*, is a bet with a strong hand intended to be called by weaker hands. *Fold equity* is the value an aggressor captures when opponents fold without reaching showdown.

objectives—specifically seeking optimal or safely exploitative behavior to win—we borrow their type-inference machinery and utilize poker as a controlled environment for examining how trust dynamics evolve under conditions of correct, transparent, and collective inference amongst many agents. Our poker engine is viewed as a microscope—not as an adversary.

2.4 Language models as strategic agents

Finally, we treat this last point as it relates to two of our phases, because these phases employ large language models. An increasing amount of work concerns how strategically large language models—used as agents in competitive and observable settings—behave. Current benchmarks for negotiation and game playing, such as AgentBench (8), and Park et al.'s study on generative agents (10), suggest that there is still much to learn about this issue. Phase 3 and phase 3.1 are both designed to examine the difference between how large language model-based agents actually behave and what they represent by way of textual strategies.

2.5 Ideas in mathematics used throughout

Two quantitative tools recur in every part of the analysis, and we introduce them once here so the rest of the paper can use them without further build-up.

Pearson correlation coefficient is the first one. Given n paired observations (x_i, y_i) with sample means $\bar{x}$ and $\bar{y}$, it is defined as

$$r = \frac{\sum_{i=1}^n (x_i - \bar{x})(y_i - \bar{y})}{\sqrt{\sum_{i=1}^n (x_i - \bar{x})^2} \sqrt{\sum_{i=1}^n (y_i - \bar{y})^2}}. \quad (1)$$

r ranges from -1 (perfectly anti-correlated) through 0 (no linear relationship) to $+1$ (perfectly correlated); the sign indicates the direction of the relationship and the magnitude its strength. We use r between an archetype's mean trust score and its final stack to measure how reputation maps to economic outcome—a value we call r_{tp} .

Bayesian updating is the second. Given a prior belief $P(t)$ that the opponent is of type t , and a likelihood $P(a | t)$ that a type- t

opponent would have taken the action a we just observed, Bayes' rule gives the posterior belief

$$P(t | a) = \frac{P(a | t) P(t)}{\sum_{t'} P(a | t') P(t')}. \quad (2)$$

Each agent maintains a categorical posterior distribution over the 8 archetypes for each other player at the table. They update their beliefs with Eq. 2 on every action they observe. In Section 3.3, we will revisit this belief-updating mechanism (including the noise floor and hand-forgetting) in detail.

A third concept—the honesty score $h(t)$ that converts a probability distribution over archetypes into a scalar trust score—is specific enough to our setup that we defer its definition to Section 3.2.

The next section describes the smallest controlled setup combining all four lines of prior work and using these two mathematical tools.

3 METHODOLOGY

Throughout every phase of this study, the only variable is the agent's mind. The underlying scaffolding includes three components: an 8-player version of fixed-limit Texas Hold'em; categorical belief about each player's archetype maintained by each player and updated after every round; and one single trust score computed based upon belief.

In phase 1, agents operate under pre-defined rule-based archetypes. In phase 2, agents allow their rules to evolve through limited hill climbing. In phase 3, agents replace their rules with a language model that represents themselves playing an archetype. In phase 3.1, agents add explicit reasoning—chain-of-thought, per-opponent memory, and self-generated strategy documentation. Since neither the environment nor the trust model ever changes throughout this experiment, differences in outcomes can be solely due to variations in agent capabilities.

First we describe the common environment, followed by descriptions of the eight archetypes (rules), belief updates, and finally the four agent implementations.

3.1 Game environment

The overall game setting remains constant for all phases of this study. We will utilize a fixed-limit version of eight player Texas Hold'em, where the small blind is 1, the large blind is 2, the small bet (2) can be made pre-flop or on the first round of cards (the “flop”⁵), the large bet (4) can be made on the second round of cards (“turn”) and third round of cards (“river”). There is a cap of four-bet⁶ allowed per round. At the beginning of each hand, each player has a chip count of 200 in their respective seat, and when a player's chips run out, he/she receives a rebuy. Side pots⁷ are

⁵The four betting rounds in Texas Hold'em, in order, are *preflop* (after each player receives two private “hole” cards but before any community cards), *flop* (after three community cards are dealt simultaneously), *turn* (after a fourth community card), and *river* (after a fifth and final community card).

⁶Fixed-limit Texas Hold'em permits at most four raises per betting round; further raises are not allowed.

⁷When a player goes all-in for fewer chips than the largest contributor, the engine creates a *side pot* for the excess so that the short-stacked player can

used to determine who wins a showdown⁸; a side pot is created by players contributing money at their individual betting level. Side pots are made and awarded depending on whether a player played chips into the respective pot and the remainder goes to the player who comes first from the dealer, going in clockwise direction.

3.2 The eight agent archetypes

The eight archetypes (cooperative vs. exploitative; static vs. adaptable; based on opponent vs. based on action type) span the axes identified by Game Theory and Behavioral Economics as “load bearing.” The policies for each agent are tables of probability distributions over actions per round given their hand strength bucket. The static types have fixed parameters during all simulations. Each of the eight types also has an *honesty* score $h = 1 - P(\text{bluff} | \text{weak})$, which is used as a weighting factor in computing the trust scores (Eq. 5). In addition, each of the names of the eight types is printed using its own colour scheme throughout the text so that you may be able to see which player we are referring to at each time. The preflop betting range⁹ for each of the eight types appears below; additional information about the policy limits per type is found in Table 2.

Oracle|Baseline|honesty 0.67

The honest “baseline” from which other players deviate. This player plays an approximate game-theoretic optimal mix and is used as the model by which all adaptive players are evaluated.

$br \in [.20, .45] \mid vbr \in [.80, 1.00] \mid cr \in [.20, .50]$

Sentinel|Honest (tight-aggressive, TAG)|honesty 0.92

The truthful player. Folds most hands and plays aggressively when it enters. It signals that its bet is strong, while signalling that its check is weak.

$br \in [.02, .18] \mid vbr \in [.85, 1.00] \mid cr \in [.25, .50]$

Firestorm|Maniac (loose-aggressive)|honesty 0.38

A cheater. Bets and raises very frequently, whatever the strength of its hand. Primarily wins due to opponents folding rather than winning at showdown.

$br \in [.40, .95] \mid vbr \in [.85, 1.00] \mid cr \in [.45, .90]$

Wall|Calling station|honesty 0.96

The player who never folds and never bluffs. The most-trusted player because it is so predictable; but in Phases 1 through 3 it is also the weakest economically for the same reason.

$br \in [.00, .05] \mid vbr \in [.40, .75] \mid cr \in [.65, .95]$

Phantom|Deceiver|honesty 0.48

An early aggressive bluffer that folds to resistance. Described as being placed in a vague region of the archetype space.

$br \in [.35, .85] \mid vbr \in [.45, .85] \mid cr \in [.10, .45]$

only win up to the amount they contributed; deeper-stacked players contest the remainder among themselves.

⁸A *showdown* is the end-of-hand reveal in which all still-active players turn over their hole cards to determine the winner; pots that end with all opponents folding to a single player do not reach showdown.

⁹Throughout the archetype descriptions, br = bluff rate (probability of betting on a weak hand), vbr = value-bet rate (probability of betting on a strong hand), and cr = call rate facing a bet on a medium hand. Ranges are the archetype's Phase 2 hill-climbing bound boxes around its Phase 1 starting parameters.

Predator|Opponent classifier|honesty 0.79

Based upon the posterior beliefs about an opponent's type, this player changes strategy to exploit them if they have greater than a 0.6 probability of being a non-TAG player. If the opponent has less than a 0.6 chance of being a non-TAG player, this player returns to its base-case behaviour of playing like the Sentinel.

$br \in [.10, .40] \mid vbr \in [.75, 1.00] \mid cr \in [.20, .50]$

Mirror|Tit-for-Tat|honesty 0.91

Takes the most-active opponent's behaviours and blends them with its own policy. In theory this represents the poker version of the Iterated Prisoner's Dilemma (IPD) Tit-for-Tat strategy; however, in practice it has been shown to work poorly in multi-player games.

$br \in [.03, .25] \mid vbr \in [.75, 1.00] \mid cr \in [.22, .52]$

Judge|Punishes bluffing|honesty 0.92

Maintains a record of how each opponent has interacted with it; after five instances of an opponent bluffing, this player takes revenge on that opponent. Models retaliation based upon perceived cheating or "bad faith."

$br \in [.02, .18] \mid vbr \in [.85, 1.00] \mid cr \in [.25, .50]$ (cooperative state)

3.3 Categorical posterior over types

Every agent maintains a length-8 categorical distribution over the archetype of every other seat. When agent i sees seat j perform action a in round r , the agent updates the distribution as

$$p_{i \rightarrow j}(t) \propto [(1 - \varepsilon)L(a \mid t, r) + \varepsilon / |\mathcal{T}|] p_{i \rightarrow j}^{\text{prior}}(t), \quad (3)$$

where $L(a \mid t, r)$ is a precomputed likelihood that a type- t agent emits action a in round r , $\mathcal{T}$ is the set of eight archetypes, and $\varepsilon = 0.05$ is a noise floor preventing any type from being fully eliminated. We characterize Eq. 3 as Bayes-flavoured but not strictly Bayesian. The noise floor is encoded into the likelihood function (a uniform contamination model). The likelihood function is computed from the analytic policy for each archetype, so it is well-specified. Equation 4 models the between-hand shrinking of the posteriors towards a uniform prior:

$$p_{i \rightarrow j} \leftarrow \lambda p_{i \rightarrow j} + (1 - \lambda) |\mathcal{T}|^{-1}, \quad \lambda = 0.95, \quad (4)$$

providing an effective memory of about 20 hands (approximately $1/(1 - \lambda)$). The trust score, our main dependent variable, is defined as

$$\text{trust}_{i \rightarrow j} = \sum_{t \in \mathcal{T}} p_{i \rightarrow j}(t) h(t), \quad (5)$$

where $h(t) = 1 - P(\text{bluff} \mid \text{weak})$ is the archetype's honesty score. For state-switching archetypes (**Predator**, **Judge**, **Mirror**), $h(t)$ is the archetype's canonical, nominal honesty—the value implied by its specified mean bluff rate, not its realized honesty in a particular state—so trust is the honesty an observer expects given the type it believes the agent to be. There are many reasonable ways to define the trust score; here we have chosen this simple form, and we report results under this definition throughout. In addition, in our limitations section we note that because our definition of the trust–profit relationship is mechanically tied to the above definition of the trust score, alternative definitions could produce different relationships. Three archetypes (**Sentinel**, **Mirror** in its default state, **Judge** in its cooperative state) are intentionally given near-identical mean parameters to demonstrate a controlled case of identifiability among indistinguishable types. Strictly, **Sentinel** and **Judge** are byte-identical, whereas **Mirror** differs only marginally and additionally blends toward its target at runtime, so its realized behavior diverges (Table 3). This is a design choice, not a finding.

3.4 Four agent architectures

The primary difference among these four phases is that the way each agent selects its decision-making rule varies. **Phase 1** (Frozen Rules Based on Archetypes): Parameters used to define each player's archetype remain static through each round. **Phase 2** (Bounded Online Optimisation): Players use a per cycle hill climbing method to update their parameter values every 200 hands. For the first 200 hands, players will randomly select either a round or a metric (and thus alter one (round/metric) pair) by $\delta = 0.03$. Then they will run 200 hand trials and accept the random selection if their total profit increased during those last 200 rounds. Random selections can be made anywhere within a "bound box" created around each player's archetype. **Phase 3** (LLM Personality Role-Players): All of a player's decisions are made via an API call to Anthropic's Claude Haiku 4.5. This call is made using the player's personality specification as the system prompt. **Phase 3.1** (LLM with Reasoning Scaffolding): Phase 3.1 also allows players to utilize chain-of-thought prompts limited to two sentences. Additionally, opponents' memory and the player's own updated strategy notes are refreshed after every ten and twenty-five hands, respectively. A sub-experiment called **Phase 2*** removes the bound boxes from hill climbers, increases the size of hill climbers' steps to $\delta = 0.15$, and reduces the number of hands hill climbers evaluate from 200 to fifty.

3.5 Experimental design

All four phases use the same five random seeds (42, 137, 256, 512, 1024), and all phases used the same eight archetypes. However, there was a huge difference in how many hands were played within each phase that can account for why r_{tp} differed so much among the different phases. Specifically, Phases 1, 2, and 2* each played 10 000 hands per seed; Phase 3 played 500 hands per seed (total 43 943 LLM calls, \$33.10); and Phase 3.1 played 150 hands per seed (total 11 953 calls, \$17). It is well understood that when comparing results from multiple phases of data collection using a similar model but at very different levels of sampling intensity, it will create both a capability effect as well as a statistical-power effect. Therefore, the differences in r_{tp} observed between the various phases also reflect a mix of these two effects. We discuss this issue explicitly in the discussion section (Limitations), and any future hand-count matched replications of the data collected here would provide a way to isolate one or both of these issues.

Sampling temperature. The Phase 3 and Phase 3.1 datasets generated in the Anthropic SDK by default have a temperature setting of 1.0. At present the codebase has been modified to pin the temperature value at 0.0 for deterministic re-runs of the experiments. Results presented as headline values throughout this manuscript were based on the runs made at a temperature of 1.0. A full description of this methodology caveat is provided in the Limitations.

3.6 Metrics

The key measure was the Pearson correlation coefficient r_{tp} per seed for the average degree of trust (final hand) and the number of chips in each player's stack at the end of all games (average number of chips in the stacks of all players) across the eight different types of players (8 pairs of measurements in total, one per type). Because these eight points are a fixed, designed set—with two or three archetypes clustered at nearly the same trust value—each per-seed r_{tp} is best read as a descriptive correlation over that design rather than a sample correlation drawn from a population.

We also present six auxiliary measures, including the index of ex-

ploitation of trust (TEI)¹⁰, sensitivity to context (CS)¹¹, adaptation by the opponent (OA)¹², non-stationarity (NS)¹³, unpredictability in strategy (SU), and awareness of manipulation of trust (TMA).

Awareness of manipulation of trust (TMA) is calculated as the correlation between a player's rolling trust delta and its rolling aggression delta. Positive values in this case can show patterns of building up trust during the initial stages of cooperation followed by increasing aggression after building trust (which we call “trust farming” in captions and further discussions).

These six auxiliary metrics were selected post-hoc rather than pre-registered. **We report them descriptively, not as inferential tests, so an individual value should be read as suggestive rather than as a significance claim.**

Throughout, a reported $\pm$ value denotes the standard deviation of r_{tp} across the five seeds. Confidence Intervals for the headline Pearson r_{tp} correlations are provided in two ways: a t -interval based upon the Student- t distribution with degrees-of-freedom equal to 4 ($T_{crit} = 2.776$) and a non-parametric percentile bootstrap with 10 000 iterations. Although there are potentially $n = 5$ seeds drawing from at most $\binom{2n-1}{n} = 126$ possible combinations of players, thus ensuring dense coverage of the sample space via the 10 000 iterations, it does not provide greater statistical power than what is available from the five actual observations.

4 RESULTS

We present results in order of agent capability: Phase 1 (frozen rule-based agents) establishes the baseline trap; Phase 2 (bounded hill-climbing) tests whether numerical adaptation can soften it; Phase 2* (unbounded hill-climbing) tests whether the bounds were the binding constraint; Phase 3 (LLM personality role-players) replaces the rule-based policies with a language model under a personality spec; and Phase 3.1 (LLM with reasoning scaffolding) augments that with chain-of-thought, per-opponent memory, and self-updated strategy notes. The four-tier headline ladder $-0.752 \rightarrow -0.637 \rightarrow -0.510 \rightarrow -0.094$ (Phase 2*, an unbounded-optimization robustness check on Phase 2, is reported separately and omitted from this headline sequence) frames the remainder of this section, which reports per-phase numbers, figures, and illustrative hands.

4.1 Phase 1: trust as a liability

Phase 1 produces $r_{tp} = -0.752$ across the five canonical seeds, with per-seed values $\{-0.774, -0.608, -0.792, -0.812, -0.776\}$. **Wall** (the most-trusted archetype, honesty 0.96) has the smallest mean stack and approximately 9.4 rebuys per seed. **Firestorm** (the least-trusted, honesty 0.38) has the largest mean stack and zero rebuys. Of the pots **Firestorm** wins, 87.1% are walkovers¹⁴; its showdown win rate is only 38.5%. **Firestorm** is not a strong poker player on the merits; it wins because it is hard to read. The trust–stack relationship appears in Fig. 2 (left panel).

¹⁰TEI (Trust Exploitation Index) is an agent's mean non-showdown profit per hand—value won through fold equity rather than at showdown.

¹¹CS (Context Sensitivity) is the absolute correlation between an opponent's recent aggression and the agent's own action.

¹²OA (Opponent Adaptation) is the variance of an agent's aggression rate across different opponents.

¹³NS (Non-Stationarity) gauges how much an agent's action distribution drifts over the run, comparing 500-hand windows against its overall distribution.

¹⁴A walkover (or “uncontested pot”) is a hand won without showdown—every other player folded before the cards had to be shown. It is the bread-and-butter outcome for aggressive players who win by making opponents fold rather than by holding the best hand.




Figure 2. Trust versus final stack across phases. (Left) Phase 1: the most-trusted archetypes cluster in the low-stack region and **Firestorm** (low trust) is the highest earner. (Right) Phase 3.1: the relationship dissolves and **Wall** becomes the top earner. Each point is one (archetype, seed) observation.

The mechanism is also visible in a single representative hand. (The hand below illustrates **Wall**'s calling-station leak specifically; **Firestorm** happens to hold a genuine hand here rather than running a bluff.) Box 1 reproduces hand #67 from seed 42: **Wall** is dealt $2\heartsuit 5\clubsuit$ (hand rank¹⁵ 6,749, the worst hand at the table) and calls every street of a 3-bet¹⁶ pot, paying 35 chips into a hand it had no chance to win. The illustrative hand we use here is drawn from the Phase 3 dataset so that we can show the trap holding even under a language-model implementation of **Wall**; the same dynamic occurs more frequently in Phase 1.

Box 1. An instance of the trap (Phase 3 hand #67, 30 actions, 110-chip pot)

Setup. Seed 42, hand 67. **Wall** (seat 3) is dealt $2\heartsuit 5\clubsuit$ —rank 6,749, the worst hand at the table. Final pot 110 chips, showdown.

Action sequence:

Seq	Seat	Round	Action	Amt	Pot	Notes
3	Judge	preflop	raise	4	7	
6	Firestorm	preflop	raise	6	13	3-bet
7	Wall	preflop	call	5	18	calls 3-bet pot with 2-5 off
9	Judge	preflop	call	2	20	
10–16	...	flop	...		38	Judge bets, Firestorm raises, Wall calls each street
17–23	...	turn	...		74	Same pattern
24–30	...	river	...		110	Wall calls the final two raises

Showdown. **Firestorm** $J\heartsuit J\heartsuit$ (rank 4042) wins 110. **Judge** $8\heartsuit 8\heartsuit$ (rank 4703). **Wall** $2\heartsuit 5\clubsuit$ (rank 6749). **Wall** pays 35 chips into a hand it had no chance to win. Every observer's posterior saturates near its ceiling—just short of 1, given the ϵ noise floor—on **Firestorm** being a firestorm and on **Wall** being a wall.

Classification accuracy. The **Predator** archetype, which reads its posterior to choose exploitation targets, reliably classifies only 2 of 7 opponents above the prespecified 0.60 confidence threshold after 1,000 hands—**Wall** ($p \approx 1.0$) and **Firestorm** ($p \approx 0.82$)—with **Phantom** only occasionally crossing the threshold ($p \approx 0.60$ in some seeds). The remaining four opponents fall below the threshold on every seed. Three of these (**Sentinel**, **Mirror** in its default state, **Judge** in its cooperative state) have near-identical mean parameters under the spec (**Sentinel** and **Judge** are byte-identical; **Mirror** differs only slightly and blends at

¹⁵Hand rank is taken from standard 7-card poker equity tables: rank 1 is the strongest possible hand and rank 7,462 is the weakest. Rank $\leq 1,000$ is roughly “top 15% of hands.”

¹⁶3-bet and 4-bet refer to successive re-raises. The big blind counts as the first bet; a raise is the 2-bet; a re-raise is the 3-bet; another re-raise is the 4-bet. Under our four-bet cap, no further raises are allowed in the same round.

Table 2. Per-archetype policy bounds (Table A). $P(\text{bet}|S)$, $P(\text{bet}|W)$ are the probabilities of betting with a strong or weak hand on a given street (preflop unless noted); $P(\text{fold}|W)$ is the probability of folding a weak hand to an opponent's bet. Static archetypes live at a fixed point inside the bound box. Under Phase 2's bounded hill-climber the agent may drift within the box; under Phase 2*'s unbounded variant the box is replaced by $[0, 1]$ on every dimension. Adaptive archetypes additionally read live state (opponent posterior or grievance ledger) and are described by the rule that produces the policy rather than by fixed bounds.

Archetype	$P(\text{bet} S)$	$P(\text{bet} W)$	$P(\text{fold} W)$	h	Adaptation rule
Oracle	[0.65, 0.85]	[0.15, 0.35]	[0.45, 0.65]	0.67	None — fixed mixed strategy
Sentinel	[0.90, 1.00]	[0.00, 0.10]	[0.80, 0.95]	0.92	None — tight value-bettor
Firestorm	[0.85, 1.00]	[0.45, 0.65]	[0.00, 0.20]	0.38	None — bets everything
Wall	[0.95, 1.00]	[0.00, 0.05]	[0.00, 0.05]	0.96	None — calls all, folds none
Phantom	[0.30, 0.50]	[0.60, 0.80] pre, [0.05, 0.20] post	[0.70, 0.90] post-flop after preflop bluff	0.48	Static but street-conditional
Predator	TAG default; exploit profile vs. target	0.05 default; 0.55 vs. classified target	0.65 default; 0.30 vs. classified target	0.79	Activates exploit profile when posterior on opponent > 0.60
Mirror	$0.5 \cdot \text{self} + 0.5 \cdot \text{target}$	same blend	same blend	0.91	Re-targets at each hand to highest-VPIP opponent
Judge	[0.88, 0.98] coop; [0.95, 1.00] retal.	[0.02, 0.10] coop; [0.30, 0.45] retal.	[0.78, 0.92] coop; [0.30, 0.50] retal.	0.92	Switches to retaliation after 5+ confirmed bluffs by an opponent

runtime), so the posterior over the cluster saturates at high uncertainty—up to $\log_2(3) \approx 1.58$ bits when all three are treated as indistinguishable, and at least $\log_2(2) = 1$ bit for the byte-identical **Sentinel/Judge** pair—a direct consequence of our design choice rather than an emergent finding.

4.2 Phase 2: bounded hill-climbing softens but does not close the trap

Phase 2 generates $r_{\text{tp}} = -0.637 \pm 0.125$ with per-seed values $\{-0.759, -0.424, -0.719, -0.717, -0.564\}$. The direction of movement from Phase 1 ($\Delta r_{\text{tp}} = +0.116$) agrees across all five seeds (directional movements of $+0.015, +0.184, +0.073, +0.095, +0.212$). The Opponent Adaptation metric also remains constant at $\text{OA} = 0.0003$ in both Phase 1 and Phase 2. As such, while Phase 2 optimises aggregate rewards and can alter parameter settings to fit within a bounding box, there is no way to construct a per-opponent strategy since the hill-climber does not have slots available for per-opponent parameters. Agents are shifted approximately 0.3 units of L_1 ¹⁷ in parameter space over 10,000 hands of play, so the bounded agents remain close to their initial locations. In this regard, the softening in Phase 2 is genuine; however, the mechanism by which it occurs is localised to the agents trimming off the least-effective components of an otherwise stationary policy without introducing anything fundamentally different.

¹⁷The L_1 distance between two parameter vectors is the sum of absolute differences across all 36 (round, action) slots. Larger L_1 means the agent has moved further from its starting parameters.




Figure 3. Bounded versus unbounded hill-climbing per seed. The left of each pair of bars is r_{tp} for bounded Phase 2 hill-climbing; the right is r_{tp} for aggressive Phase 2* hill-climbing, for each of the five canonical seeds. When the bounding constraints are relaxed and the optimiser's step size is increased fivefold, r_{tp} increases by only $+0.028$ on average, and across seeds the variance in r_{tp} nearly triples.

4.3 Phase 2*: unbounded hill-climbing fails the same way

Phase 2* yields $r_{\text{tp}} = -0.609 \pm 0.221$ with per-seed values $\{-0.354, -0.700, -0.344, -0.887, -0.759\}$. The mean increase in r_{tp} from Phase 2 is $+0.028$, well within the standard deviation associated with the seed-to-seed variation. With respect to movement in parameter space, the mean per-agent L_1 drift is 3.4 (i.e., eleven times more than in the bounded version); yet the trap persists.




Figure 4. The 8-agent population becomes dispersed in parameter space. Averaged pairwise L_1 distance between all eight agents in a 36-dimensional parameter space over 10,000 hands of unbounded hill-climbing. **(Left)** With weak HC ($\delta = 0.03$), agents barely move. **(Right)** Aggressive HC ($\delta = 0.15$) spreads the population out on every seed. A ratio of final-to-initial cluster spread > 1 implies the agents become more dispersed at end-of-run than at the start.

The explanation for why this occurs becomes apparent on examining the dispersal in cluster-spread space. The averaged pairwise L_1 distance between all eight agents in 36-dimensional parameter space expands from an initial 5.82 to ≥ 7.5 on every seed; the mean of the final-to-initial cluster-spread ratios is 1.324. While the agents are moving eleven times harder than in the bounded case, they are not converging on a common Nash-like profile.

Firestorm's mean stack continues to remain $\sim 6\times$ that of the next closest archetype; **Wall** still incurs ~ 28 rebuys per seed. The economic ordering does not change. We credit the lack of convergence to three structural causes that we expect would survive any specific optimizer choice—non-stationary feedback from the lagging trust posterior, the simultaneous actions of all eight agents, and axis-aligned coordinate descent in 36 dimensions—and we elaborate in the Discussion.

Phase 2 Unbounded — Preflop Bluff-Rate Drift Across Seeds




Figure 5. Per-archetype L_1 drift from Phase 1 starting parameters under aggressive unbounded hill-climbing. Each archetype moves significantly (mean drift 3.4), but no two archetypes converge on the same location. Trajectories are colour-coded by archetype.

4.4 Phase 3: language models alone do not break the trap

Phase 3 generates $r_{tp} = -0.510 \pm 0.268$ with per-seed values $\{-0.884, -0.525, -0.171, -0.712, -0.259\}$. This is a change from Phase 2 ($\Delta r_{tp} = +0.127$) of similar magnitude to the Phase 1 $\rightarrow$ Phase 2 step. The variance of r_{tp} among seeds is roughly double that of Phase 2 (0.268 vs. 0.125). Only two of six dimension-specific behavioral targets are achieved; three of the metrics move *backward* relative to Phases 1 and 2 (Table 3 reports per-archetype VPIP¹⁸, PFR¹⁹, and AF²⁰ fingerprints). Among the secondary metrics, CS drops from 0.142 to 0.076, NS collapses to 0, and SU²¹ falls from 1.88 to 1.19 bits.

Specifications describing personality characteristics inform an LLM *what* to do, but not *how* to reason about doing so. Absent supporting information about reasoning, the LLMs in our sample collapse onto a more generic, stereotyped canonical interpretation of each archetype, and thus become *more* classifiable than the explicitly stochastic rule-based versions. The primary reason for the softening between Phase 2 and Phase 3 is therefore output variability arising from sampling at temperature 1.0.

4.5 Phase 3.1: reasoning scaffolding attenuates the trap

Phase 3.1 generates $r_{tp} = -0.094 \pm 0.301$ with per-seed values $\{-0.289, -0.338, -0.327, +0.047, +0.435\}$. The directional shift from Phase 3 ($\Delta r_{tp} = +0.416$) is larger than that of any previous phase, but the small number of samples per seed ($n = 5$) and the short 150-hand

horizon create significant uncertainty: the 95% bootstrap interval for r_{tp} in Phase 3.1, $[-0.32, +0.20]$, is wide enough to encompass negative correlations of magnitudes comparable to those reported under bounded Phase 2. Thus, two of five seeds generate a per-seed correlation larger than zero ($+0.047$ at seed 512 and $+0.435$ at seed 1024); however, given $n = 8$ archetype pairs per seed, the Fisher- z interval for a per-seed $r_{tp} = +0.047$ spans roughly $[-0.7, +0.7]$, so individually positive seeds do not by themselves demonstrate inversion of the trust-profit relationship. Rather, collectively they indicate that the trust-profit relationship has been reduced at the rank-order level relative to all prior phases; nevertheless, due to insufficient power in this study, we cannot conclusively determine whether this reduction corresponds to complete elimination or merely a weakened but residual trap.

¹⁸VPIP (voluntarily put in pot) is the percentage of hands in which a player voluntarily put chips into the pot, excluding the forced blinds. High VPIP = loose; low VPIP = tight.

¹⁹PFR (preflop raise rate) is the percentage of hands in which a player raised before the flop. $PFR \leq VPIP$ by definition.

²⁰Aggression factor (AF) is the ratio (bets + raises)/calls. $AF > 2$ is aggressive; $AF < 1$ is passive.

²¹Strategic Unpredictability (SU) is the Shannon entropy in bits over each agent's action distribution. Higher SU = harder to predict.

Archetype	VPIP P1	VPIP P3.1	PFR P1	PFR P3.1	AF P1	AF P3.1
oracle	0.216	0.302	0.061	0.111	1.18	1.12
sentinel	0.149	0.120	0.083	0.080	2.12	2.53
firestorm	0.494	0.722	0.120	0.453	1.12	2.77
wall	0.539	0.626	0.015	0.067	0.13	0.33
phantom	0.279	0.437	0.092	0.162	1.45	1.29
predator	0.215	0.248	0.063	0.119	1.20	1.38
mirror	0.214	0.196	0.060	0.087	1.18	1.11
judge	0.149	0.174	0.083	0.098	2.10	1.87

Table 3. Phase 1 (frozen rules) vs. Phase 3.1 (LLM + reasoning) behavioral fingerprints. VPIP = voluntarily put in pot; PFR = preflop raise rate; AF = aggression factor ((bets+raises)/calls).




Figure 6. Economic ordering inverts from Phase 3 to Phase 3.1. Wall (trust ≈ 0.85 , highest of any archetype) was rank 8 of 8 in Phase 3 with ~ 9 rebuys per seed and becomes rank 1 of 8 in Phase 3.1 with zero rebuys. Firestorm climbs from rank 5 in Phase 3 to rank 2 in Phase 3.1.

Wall's mean stack rises from ~ 100 – 200 chips in Phases 1–3 to 280 in Phase 3.1; rebuy count drops from ~ 9.4 per seed to zero, consistent with the rank-order claim above. The right panel of Fig. 2 (introduced earlier) shows the trust–stack scatter under Phase 3.1: the negative slope visible in the Phase 1 panel is gone. The full per-archetype economic ordering is in Table 4.

Four of six secondary metric targets are met in Phase 3.1 (vs. two of six in Phase 3). Strategic Unpredictability rises from 1.19 to 1.55 bits, crossing the > 1.5 threshold for the first time across all phases. Trust Manipulation Awareness rises from $+0.164$ to $+0.242$, with six of eight archetypes showing positive TMA; Wall and Sentinel show the strongest signals at $+0.733$ and $+0.704$. We read the high TMA of these two honest archetypes (Wall, $h = 0.96$; Sentinel, $h = 0.92$) with caution: their reasoning-augmented river value-betting makes trust and aggression rise together without any deception, so the “farming” label overstates the case for them.




Figure 7. Trust Manipulation Awareness (TMA) per archetype in Phase 3.1. Positive TMA indicates an agent's rolling trust delta correlates with its rolling aggression delta—building trust through cooperative early play, then leveraging it for higher-aggression later moves. Six of eight archetypes show positive TMA; Wall ($+0.733$) and Sentinel ($+0.704$) are the strongest.

The mechanism underlying these values is best shown in a single hand. Box 2 reproduces Phase 3.1 hand #146: Wall, holding $K\heartsuit Q\heartsuit$ (rank 872), calls a flop continuation bet²² and a turn barrel from Firestorm, reads Firestorm's river check as a tell²³, places a value bet on the river, and wins 32 chips. Canonical Wall never makes a river bet anywhere in the Phase 1, Phase 2, or Phase 3 datasets; conversely, with chain-of-thought reasoning added to its decision-making during Phase 3.1, Wall does.

Box 2. The inversion in a single hand (Phase 3.1 hand #146, 17 actions, 32-chip pot)

Setup. Seed 42, hand 146. Wall (seat 3) is dealt $K\heartsuit Q\heartsuit$ – rank 872, a strong hand. Final pot 32 chips, showdown.

Action sequence:

²²A continuation bet (c-bet) is a bet made on the flop by the player who took the lead in betting preflop, regardless of whether the flop helped that player's hand. It is the most common bluff line in modern poker.

²³A tell is a behavioral signal that gives information about an opponent's hand. Wall reads Firestorm's river check as a tell because the canonical Firestorm policy bets every street with a real hand; a river check therefore signals that the bluff line has been abandoned.

Archetype	Trust	Stack	σ	Rebuys	Rank P3	Rank P3.1	Δ
wall	0.849	280	88	0.0	8	1	+7
firestorm	0.481	231	104	0.2	5	2	+3
phantom	0.748	230	61	0.2	1	3	-2
mirror	0.728	208	83	0.0	2	4	-2
judge	0.781	191	45	0.0	4	5	-1
sentinel	0.786	183	58	0.0	7	6	+1
predator	0.797	179	98	0.0	6	7	-1
oracle	0.625	175	64	0.0	3	8	-5

Table 4. Phase 3.1 economic outcomes by archetype (mean across 5 seeds, 150 hands each). Ranks are derived from final-stack ordering. Wall, the most-trusted archetype, climbs from rank 8 (Phase 3) to rank 1 (Phase 3.1), with zero rebuys.

Archetype	TMA	Direction
wall	+0.733	farming (heavy)
sentinel	+0.704	farming (heavy)
predator	+0.625	farming (heavy)
phantom	+0.286	farming
judge	+0.116	farming
oracle	+0.065	farming
mirror	-0.277	reactive
firestorm	-0.313	reactive

Table 5. Trust Manipulation Awareness (TMA) per archetype in Phase 3.1. Positive TMA = the agent gains trust before exploiting it. Six of eight archetypes farm, with Wall and Sentinel showing the strongest signals.

Seq	Seat	Round	Action	Amt	Pot	Notes
7	Firestorm	preflop	raise	3	10	
8	Wall	preflop	call	2	12	calls 3-bet with K-Q suited
11	Firestorm	flop	bet	2	14	c-bet
12	Wall	flop	call	2	16	
13	Firestorm	turn	bet	4	20	second barrel
14	Wall	turn	call	4	24	
15	Firestorm	river	check	0	24	tell — bluff line abandoned
16	Wall	river	bet	4	28	value bet against checked range
17	Firestorm	river	call	4	32	

Showdown. Wall $K\heartsuit Q\heartsuit$ (rank 872) wins 32. Firestorm $8\clubsuit Q\clubsuit$ (rank 6075). Canonical Wall never bets the river in any Phase 1, Phase 2, or Phase 3 dataset; Phase 3.1 Wall, augmented with chain-of-thought, per-opponent memory, and adaptive strategy notes, does.

5 DISCUSSION

The headline of this study is deliberately uncomfortable: across every agent design we tested, being trusted was a financial liability rather than an asset, and we could not optimise that liability away—we could only reason it away. That distinction is the paper’s central contribution. The sections below trace why the trap forms, why numerical adaptation cannot escape it, and why explicit reasoning can, while being candid about the limits of a five-seed study.

5.1 The mechanism behind the trap

The trust trap visible in Phase 1 admits a clean mechanistic explanation that the Phase 3.1 results then refine. Trust, as we measure it, is the expected honesty of an opponent under the posterior; a high trust score signals to opponents that the agent is most likely an archetype that

only bets with strong hands. For **Wall** (honesty 0.96) and **Sentinel** (honesty 0.92), this belief is *correct*, and that is precisely why it is costly: when opponents know an agent only bets with strong hands, they fold against its bets (denying value from those strong hands) and bet aggressively against its checks (exploiting the information that a check signals weakness). The agent’s honesty becomes a signal that opponents read and trade against. A low trust score, conversely, creates strategic ambiguity, and **Firestorm** uses that ambiguity to dominate the table. The phenomenon parallels what economists studying eBay-style reputation systems have called the *transparency paradox* (11): predictable cooperation is exploitable.

The mechanism by which **Firestorm** converts ambiguity into chips deserves comment because it differs structurally from the canonical Iterated Prisoner’s Dilemma result. In pairwise IPD, Always-Defect is outperformed by Tit-for-Tat because a defector faces concentrated retaliation. In our 8-player setting, **Firestorm**’s aggression cost is diffused across seven simultaneous opponents, so the same strategy that would lose heads-up wins at the full table. Our Tit-for-Tat analogue (**Mirror**) finishes sixth of eight in Phase 1’s economic ordering—suggestive but not definitive evidence that the IPD result fails to transfer to multi-agent settings with richer action spaces. We flag this as a direction for follow-up rather than a conclusion, since a single hand-crafted poker analogue is not a clean test of the IPD literature.

5.2 What numerical optimization can and cannot do

The next three phases of the experiment narrow the space of possible explanations for why the trap is hard to escape. We begin with a structural caveat: by construction, three of our eight archetypes (**Sentinel**, **Mirror**’s default, **Judge**’s cooperative state) share near-identical mean parameters (**Sentinel** and **Judge** byte-identically; **Mirror** differing only slightly before it blends at runtime), and the Bayesian posterior cannot reliably distinguish them regardless of algorithmic sophistication. Classification accuracy in that sub-space is bounded above by chance—1/3 for three indistinguishable types, 1/2 for the byte-identical pair. This is a definitional point about *our* archetype space, not an information-theoretic discovery about reputation systems in general; the empirical question of how rapidly classification accuracy degrades as inter-archetype distance shrinks toward zero would require experimentally varying that distance and is outside the scope of the present paper. Real-world monitoring systems—fraud detection, content moderation, credit scoring—face an analogous failure mode for moderately-behaved actors with overlapping profiles, but the analogy is suggestive rather than implied by our setup.

Within that caveat, the Phase 2 and Phase 2* results argue against two specific hypotheses about the trap’s origin. Phase 2 (bounded hill-climbing) softens r_{tp} by +0.116 while OA stays pinned at 0.0003: aggregate-reward optimization can move agent parameters but cannot,

by construction, produce per-opponent strategy because the hill-climber has no per-opponent parameter slot. Phase 2* (unbounded hill-climbing with $11\times$ greater parameter drift) softens r_{tp} by an additional $+0.028$ and produces a population that diverges rather than converges in 36-dimensional parameter space—evidence against the hypothesis that the archetype-shaped bound boxes are the binding constraint, though the sub-experiment varies three optimizer parameters at once (bounds removed, step size raised $5\times$, evaluation window shrunk $4\times$) and therefore does not cleanly isolate the parameter-space hypothesis. The non-convergence has three plausible structural causes that we expect would survive any specific optimizer choice: the trust posterior is non-stationary inside each agent’s optimization loop (with $\lambda = 0.95$, opponents take ~ 70 hands to update beliefs after a strategy change but the evaluation window is 50 hands), all eight agents climb simultaneously so each trial perturbation is evaluated against a moving joint behavior, and axis-aligned coordinate descent in 36 dimensions cannot discover joint optima even with larger steps. A CMA-ES or REINFORCE optimizer with $\sim 50,000$ cycles would search more efficiently, but the first two causes would survive any optimization substrate that respects the same observation contract.

Phase 3 (LLM personality role-players) softens r_{tp} by a further $+0.127$, but the diagnostic metrics suggest the mechanism is not categorically different from Phase 2’s: behavioral-dimension targets fail in three of four directions, with the LLMs collapsing onto a more stereotyped interpretation of each archetype than the explicitly stochastic rule-based versions. The personality specs tell the agents *what* to do but not *how* to reason; absent reasoning support the LLMs role-play the spec without spontaneously inventing opponent-conditional, time-varying, or unpredictable strategy. The Phase 3 softening may therefore be produced by output stochasticity at sampling temperature 1.0 rather than by a structural change in agent behavior.

5.3 What reasoning adds, and what we can and cannot claim outside poker

The Phase 3.1 result is consistent with an interpretation in which agent reasoning about the reputation system itself attenuates the trust–profit correlation. The chain-of-thought prompt allows a one-step lookahead; the per-opponent memory gives that reasoning concrete data to condition on; the adaptive strategy notes let the agent update its prior on what is working against which opponent. We claim that all three scaffolds are required, but this claim rests on an ablation reported in the supplementary validation suite rather than a dedicated main-text figure—the ablation deserves promotion in a future revision. The **Wall** hand reproduced in Box 2 illustrates the mechanism concretely in a single instance: **Wall** reads **Firestorm**’s river check as a tell, recognizes that K-Q high beats **Firestorm**’s bluffing range, and bets for value—a sequence that is impossible for the Phase 1 **Wall** and unreliable for the Phase 3 **Wall**. A distributional analysis across all Phase 3.1 hands, rather than a single illustrative case, is the natural follow-up.

These mechanisms suggest hypotheses for real-world reputation systems, but we emphasize the limit of the analogy: our testbed is a zero-sum game and the proposed exploitation mechanism (predictable cooperation extracted via fold equity) does not directly map to positive-sum marketplaces, where the buyer’s payoff is from the good rather than from out-thinking the seller. With that caveat, three implications follow as conjectures for cross-domain follow-up. *Behavioral reputation alone may be insufficient* without external enforcement, because observation-based trust can create perverse incentives that reward exploitative strategies. *Classification systems may have blind spots* for moderately-behaved actors with overlapping profiles, mirroring our identifiability sub-space. And *transparency itself may be costly* when

it makes cooperative strategies too easy to model and exploit. Each of these would require direct validation in a positive-sum domain to claim more than analogical inference.

5.4 Limitations

Three clusters of limitations remain after the revisions above.

Statistical power gaps. The headline correlations are computed across $n = 5$ random seeds. **The canonical test is a one-sample t -test of the five per-seed r_{tp} values against zero ($df = 4$, $T_{crit} = 2.776$); significance therefore depends on the between-seed standard deviation rather than on any fixed critical correlation, and we do not treat r_{tp} as though it were itself a five-point correlation.** The headline Phase 3.1 result has a 95% bootstrap interval $[-0.32, +0.20]$ that contains both a fully neutralized correlation and a moderate residual negative correlation, so we cannot statistically separate “trap broken” from “trap attenuated” at this sample size. Hand counts also differ across phases by an order of magnitude (10,000 hands/seed in Phases 1–2*, 500 in Phase 3, 150 in Phase 3.1), which mixes a capability effect with a statistical-power effect in the cross-phase ladder. The six secondary metrics (TEI, CS, OA, NS, SU, TMA) were chosen post hoc and are unadjusted for multiple comparisons. The single highest-leverage follow-up addressing all of these is an $n = 20$ Phase 3.1 replication at the 500-hand horizon, estimated at $\sim \$60$ in API spend.

Reproducibility and replication gaps. The canonical Phase 3 and 3.1 datasets were generated under the Anthropic SDK’s default sampling temperature of 1.0, while the released codebase now pins temperature to 0.0; the headline numbers are therefore not exactly reproducible from the current code without manual reversion. Phase 3 and 3.1 also use a single model family (Anthropic Haiku 4.5); a multi-model replication (Gemini Flash, GPT-4o-mini, or a comparable alternative) is needed to demonstrate that the attenuation is not model-specific. Finally, the Phase 3.1 three-scaffold deployment (chain-of-thought, memory, adaptive notes) is currently joint; a clean main-text ablation isolating each component’s contribution is the second-most-important missing experiment.

Design-choice gaps. Several of our methodological choices are load-bearing in ways that future work should disambiguate. The identifiability “floor” is a stipulated property of our archetype space (three archetypes share mean parameters), not an emergent finding; the honesty score $h(t) = 1 - P(\text{bluff} \mid \text{weak})$ is one of several plausible functional forms (a value-bet-weighted product form is another) and the trust–profit correlation is mechanically anchored on this choice; the rebuy economics underweight deep chip losses (**Wall**’s 9.4 mean rebuys per seed in Phase 1 represent $\sim 1,880$ chips of true loss not visible in the final-stack metric); the Phase 2* sub-experiment varies three optimizer parameters at once; and Limit Hold’em is zero-sum among players, while eBay marketplaces, social networks, and credit systems are positive-sum over trades, so direct cross-domain inference is rhetorical rather than warranted.

6 CONCLUSION

We have presented a controlled simulation study of trust dynamics in 8-player Limit Texas Hold’em. Across four agent architectures, the Pearson correlation between agent trust score and final stack falls along the ladder $-0.752 \rightarrow -0.637 \rightarrow -0.510 \rightarrow -0.094$, with each step accompanied by a confidence interval whose width exceeds the size of any single inter-phase Δr_{tp} . We characterize the rank ordering of the ladder as the robust finding and the absolute size of each step as a preliminary estimate requiring replication. An unbounded hill-climbing sub-experiment with $11\times$ greater parameter drift produces $\Delta r_{tp} = +0.028$ from bounded Phase 2 and yields a population that diverges rather than converges

in 36-dimensional parameter space—preliminary evidence against the hypothesis that the trap is a bound-box artifact, though Phase 2* varies three optimizer parameters at once and does not cleanly isolate the bounds.

Why should anyone care outside of cards? All systems where machines assess trust from observed behavior—Credit Scoring, Content Moderation, Multi-Agent Marketplaces, Automated Negotiation—inherit the same threat: if cooperation is apparent, it can be evaluated and exploited. Our results indicate that protection for cooperative agents will likely involve giving them the ability to think about the reputation system itself—rather than simply providing them with additional information about their counterparts. This poker framework serves as a compact, completely reproducible tool for studying the specific question—when does a good reputation become a bad thing?

Three follow-up experiments are the most important next steps. *First*, an $n = 20$ Phase 3.1 replication at 500 hands per seed (matching Phase 3) is the highest-leverage single experiment: it would tighten the confidence interval on the Phase 3.1 result by roughly a factor of two and distinguish “trap attenuated” from “trap broken”; estimated cost $\sim \$60$ in API spend. *Second*, a clean ablation of the three Phase 3.1 scaffolds (chain-of-thought, per-opponent memory, adaptive notes) is required to support the claim that all three are necessary. *Third*, a temperature-pinned re-run of Phase 3 and Phase 3.1 at $T = 0.0$ would resolve the open reproducibility caveat. Beyond these three, a multi-LLM replication, a no-limit Hold'em extension, and an experimental varying of inter-archetype distance would each strengthen the present findings.

SOURCES AND ACKNOWLEDGMENTS

Acknowledgments

We thank Anthropic for the API access that made Phases 3 and 3.1 feasible.

Funding. Anthropic API expenditure was self-funded by the author.

Author contributions. R.A. conceived the study, implemented the simulation, performed the analysis, and wrote the manuscript.

Competing interests. The author declares no competing interests.

Data and materials availability. The full simulation codebase, SQLite databases, figures, tables, and analysis scripts are available at https://github.com/RachitAgrawal146/Poker_trust.

References

REFERENCES

1. Robert Axelrod. *The Evolution of Cooperation*. Basic Books, 1984.
2. Darse Billings, Denis Papp, Jonathan Schaeffer, and Duane Szafron. Opponent modeling in poker. In *Proceedings of the National Conference on Artificial Intelligence (AAAI)*, pages 493–499, 1998.
3. Gary E. Bolton, Elena Katok, and Axel Ockenfels. How effective are electronic reputation mechanisms? An experimental investigation. *Management Science*, 50(11):1587–1602, 2004.
4. Noam Brown and Tuomas Sandholm. Superhuman AI for heads-up no-limit poker: Libratus beats top professionals. *Science*, 359(6374):418–424, 2018.

5. Noam Brown and Tuomas Sandholm. Superhuman AI for multi-player poker. *Science*, 365(6456):885–890, 2019.
6. Sam Ganzfried and Tuomas Sandholm. Safe opponent exploitation. *ACM Transactions on Economics and Computation*, 3(2):8:1–8:28, 2015.
7. Lawrence R. Glosten and Paul R. Milgrom. Bid, ask and transaction prices in a specialist market with heterogeneously informed traders. *Journal of Financial Economics*, 14(1):71–100, 1985.
8. Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, Huan Sun, Minlie Huang, Yuxiao Dong, and Jie Tang. AgentBench: Evaluating LLMs as agents. In *International Conference on Learning Representations (ICLR)*, 2024.
9. Martin A. Nowak. Five rules for the evolution of cooperation. *Science*, 314(5805):1560–1563, 2006.
10. Joon Sung Park, Joseph C. O'Brien, Carrie J. Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology (UIST)*, 2023.
11. Paul Resnick and Richard Zeckhauser. Trust among strangers in internet transactions: Empirical analysis of eBay's reputation system. *The Economics of the Internet and E-Commerce, Advances in Applied Microeconomics*, 11:127–157, 2002.
12. Finnegan Southey, Michael Bowling, Bryce Larson, Carmelo Piccione, Neil Burch, Darse Billings, and Chris Rayner. Bayes' bluff: Opponent modelling in poker. In *Proceedings of the Twenty-First Conference on Uncertainty in Artificial Intelligence (UAI)*, pages 550–558, 2005.

Supplementary Materials

- Bayesian update worked example: docs/worked_examples.md
- Identifiability ceiling derivation: docs/stage5_identifiability.md
- Phase 2* unbounded methodology footnote: paper_resources/notes/phase2_unbounded_writeup_aggressive.md
- Methods disclosures (temperature, side-pot, CIs): paper_resources/notes/methods_disclosures.md
- Bootstrap and Fisher-z CI table: paper_resources/data/r_bootstrap_ci.csv