

1. Elencare tutti i prodotti con le rispettive linee di prodotto
2. Dato un cliente elencare i suoi pagamenti
3. Dato un cliente elencare gli ordini
4. Dato un impiegato indicare l'ufficio dove lavora e i clienti che segue
5. Dato un cliente elencare i prodotti acquistati
6. Dato un cliente elencare i prodotti ordinati nel mese di maggio
7. Dato un ufficio elencare tutti i dipendenti che non hanno un capo
8. Elencare tutti gli ordini fatti dagli uffici di tokyo
9. Elencare di tutti i dipendenti con il loro padrone

- 1) `SELECT products.productCode, products.productName, productlines.productLine, productlines.textDescription FROM products INNER JOIN productlines ON products.productLine=productlines.productLine;`
- 2) `SELECT customers.customerNumber, customers.customerName, payments.amount FROM customers INNER JOIN payments ON customers.customerNumber=payments.customerNumber WHERE customers.customerNumber=103;.`
- 3) `SELECT customers.customerNumber, customers.customerName, orders.orderNumber FROM customers INNER JOIN orders ON customers.customerNumber=orders.customerNumber WHERE customers.customerNumber=103;`
- 4) `SELECT employees.employeeNumber, employees.firstName, offices.city, customers.salesRepEmployeeNumber, customers.customerName FROM employees INNER JOIN offices ON employees.officeCode=offices.officeCode INNER JOIN customers ON employees.employeeNumber=customers.salesRepEmployeeNumber WHERE employees.employeeNumber=1370;`
- 5) `SELECT orders.orderNumber FROM orders INNER JOIN customers ON orders.customerNumber=customers.customerNumber WHERE customers.customerNumber="167";`
- 6) `SELECT customers.customerNumber, customers.customerName, orders.orderNumber FROM customers INNER JOIN orders ON customers.customerNumber=orders.customerNumber WHERE customers.customerNumber=103 && month(orders.orderDate)=05;`
- 7) `SELECT offices.officeCode, offices.city, employees.employeeNumber, employees.firstName FROM offices INNER JOIN employees ON offices.officeCode=employees.officeCode WHERE employees.reportsTo IS NULL;`
- 8) `SELECT orders.orderNumber, offices.city FROM orders INNER JOIN customers ON orders.customerNumber=customers.customerNumber INNER JOIN employees ON customers.salesRepEmployeeNumber=employees.employeeNumber INNER JOIN offices ON offices.officeCode=employees.officeCode WHERE offices.city="Tokyo";`
- 9) `SELECT sslave.firstName AS fnSlave, sslave.lastName, mmaster.firstName, mmaster.lastName FROM employees AS sslave INNER JOIN employees AS mmaster ON sslave.reportsTo=mmaster.employeeNumber;`