

Membangun Sistem Informasi Laundry

Panduan Lengkap Laravel 13 + Tailwind CSS v4 — Ujikom Junior Web
Programming PPKD Jakarta Pusat

Panduan Mentoring Pengembangan Aplikasi

Tahun Ajaran 2026

Daftar Isi

Pendahuluan	3
Tentang Project	3
Aktor & Hak Akses	3
Alur Bisnis Sistem	3
Entity Relationship Diagram (ERD)	4
Tech Stack	4
Tema Desain “Laundry Fresh”	4
Bab 1 — Setup Project	5
1.1 Membuat Project Baru	5
1.2 Membuat Database	5
1.3 Konfigurasi Koneksi Database	5
1.4 Menjalankan Server	5
Bab 2 — Migration Database	6
2.1 Membuat Seluruh File Migration	6
2.2 Migration create_level_table	6
2.3 Migration create_customer_table	7
2.4 Migration create_type_of_service_table	7
2.5 Migration create_trans_order_table	8
2.6 Migration create_trans_order_detail_table	9
2.7 Migration create_trans_laundry_pickup_table	9
2.8 Migration Tambahan id_level untuk Tabel users	10
2.9 Menjalankan Migration	11
Bab 3 — Model & Relasi Eloquent	12
3.1 Membuat Seluruh Model	12
3.2 Model Level	12
3.3 Model User	13
3.4 Model Customer	13
3.5 Model TypeOfService	14
3.6 Model TransOrder	15
3.7 Model TransOrderDetail	15
3.8 Model TransLaundryPickup	16
Bab 4 — Seeder	18
4.1 Membuat File Seeder	18
4.2 LevelSeeder	18
4.3 UserSeeder	18
4.4 DatabaseSeeder	19
4.5 Menjalankan Migration + Seeder	20
4.6 Akun Default	20

Bab 5 — Autentikasi & Middleware Role	21
5.1 Controller AuthController	21
5.2 Middleware CheckRole	22
5.3 Middleware PreventBackHistory	23
5.4 Registrasi Middleware — bootstrap/app.php	23
5.5 Controller Dashboard per Role	24
5.6 Routing Dasar Autentikasi	25
Bab 6 — Master Data Administrator	27
6.1 Membuat Controller	27
6.2 CRUD Customer	27
6.3 CRUD Jenis Service	31
6.4 CRUD User	34
6.5 Routing Master Data	38
Bab 7 — Transaksi Laundry (Operator)	39
7.1 Controller TransOrderController	39
7.2 View Daftar Transaksi	41
7.3 View Form Transaksi Baru (Dinamis)	42
7.4 View Detail Transaksi	46
7.5 Routing Transaksi	47
Bab 8 — Transaksi Pengambilan Laundry (Operator)	48
8.1 Controller TransLaundryPickupController	48
8.2 View Daftar Siap Diambil	49
8.3 View Proses Pengambilan	50
8.4 Routing Pengambilan	52
Bab 9 — Laporan Penjualan (Pimpinan)	54
9.1 Controller LaporanController	54
9.2 View Daftar Laporan	55
9.3 View Detail Laporan	57
9.4 Routing Laporan	57
Bab 10 — Styling UI dengan Tailwind CSS v4	59
10.1 Instalasi Tailwind CSS v4 via Vite	59
10.2 Design Token — resources/css/app.css	59
10.3 Layout Guest — resources/views/components/layout-guest.blade.php	60
10.4 Halaman Login (dengan Realtime Clock)	61
10.5 Layout App — resources/views/components/layout-app.blade.php	63
10.6 Sidebar — resources/views/layouts/partials/sidebar.blade.php	64
10.7 Topbar — resources/views/layouts/partials/topbar.blade.php	65
10.8 Dashboard 3 Role	66
Bab 11 — Testing & Checklist Akhir	69
11.1 Perintah Build & Jalankan Server	69
11.2 Checklist Fungsional	69
11.3 Akun Default	69
11.4 Penutup	69

Pendahuluan

Tentang Project

Buku ini adalah panduan lengkap membangun **Sistem Informasi Laundry** menggunakan **Laravel 13** dan **Tailwind CSS v4**, disusun sebagai dokumentasi pengerjaan project Ujikom Junior Web Programming — PPKD Jakarta Pusat, Tahun Ajaran 2026.

Ketentuan utama pengerjaan:

- Nama project mengikuti format `WEB_[NAMA_ANDA]_LAUNDRY`
- Struktur database **tidak boleh diubah** (mengikuti ERD yang telah ditentukan)
- Waktu pengerjaan: 480 menit (8 jam)
- Boleh menggunakan template UI, namun pada panduan ini UI dibangun custom menggunakan Tailwind CSS v4

Aktor & Hak Akses

Role	Hak Akses
Administrator	Membuat master data (Customer, User, Jenis Service), menambah user baru dengan level Operator
Operator	Melakukan transaksi laundry, memproses pengambilan pakaian
Pimpinan	Melihat laporan penjualan (read-only)

Alur Bisnis Sistem

1. Customer datang ke lokasi laundry
2. Operator/Admin input data customer baru (jika belum terdaftar)
3. Jika sudah terdaftar, langsung buat transaksi laundry
4. Operator memilih jenis jasa:
 - a. Cuci dan Gosok Rp 5.000 / kg
 - b. Hanya Cuci Rp 4.500 / kg
 - c. Hanya Gosok Rp 5.000 / kg
 - d. Laundry Besar Rp 7.000 / kg
(selimut, karpet, mantel, spreii)
5. Subtotal = harga × qty
6. Transaksi baru → status kode 0
7. Saat customer mengambil → status berubah kode 1

Entity Relationship Diagram (ERD)

Struktur 7 tabel berikut adalah acuan utama dan tidak boleh diubah:

Tabel	Kolom Utama
level	id, level_name, created_at, updated_at, deleted_at
users	id, id_level, name, email, password, created_at, updated_at (<i>tabel bawaan Laravel + id_level</i>)
customer	id, customer_name, phone (varchar 13), address, created_at, updated_at, deleted_at
type_of_service	id, service_name, price, description, created_at, updated_at, deleted_at
trans_order	id, id_customer, order_code, order_date, order_end_date, order_status, created_at, updated_at, deleted_at, order_pay, order_change, total
trans_order_detail	id, id_order, id_service, qty, subtotal, notes, created_at, updated_at
trans_laundry_pickup	id, id_order, id_customer, pickup_date, notes, created_at, updated_at

Tech Stack

Kategori	Teknologi
Backend	Laravel 13 (PHP)
Database	MySQL
Frontend	Blade Template + Tailwind CSS v4 (via Vite)
Font	Baloo 2 (heading), Plus Jakarta Sans (body), IBM Plex Mono (angka/kode)
Autentikasi	Manual (Laravel Auth + custom Middleware role)

Tema Desain “Laundry Fresh”

Warna	Hex	Fungsi
Ink	#10192E	Teks utama & elemen gelap
Suds Blue	#2D8CFF	Warna primer (air/sabun)
Detergent Teal	#17B8A6	Warna sekunder (fresh/sukses)
Bubblegum	#FF5D8F	Aksen (highlight/hapus)
Sunbeam	#FFC94A	Aksen (status baru/warning)
Cloud	#F4F8FC	Background terang

Bab 1 — Setup Project

1.1 Membuat Project Baru

```
composer create-project laravel/laravel WEB_NAMA_ANDA_LAUNDRY
cd WEB_NAMA_ANDA_LAUNDRY
```

1.2 Membuat Database

```
CREATE DATABASE db_laundry;
```

1.3 Konfigurasi Koneksi Database

Edit file .env:

```
DB_CONNECTION=mysql
DB_HOST=127.0.0.1
DB_PORT=3306
DB_DATABASE=db_laundry
DB_USERNAME=root
DB_PASSWORD=
```

1.4 Menjalankan Server

```
php artisan serve
```

Buka <http://127.0.0.1:8000> — harus muncul halaman welcome Laravel.

Bab 2 — Migration Database

Migration dibuat sesuai urutan relasi (tabel independen dulu, baru tabel dengan foreign key), agar tidak terjadi error saat proses migrate.

2.1 Membuat Seluruh File Migration

```
php artisan make:migration create_level_table
php artisan make:migration create_customer_table
php artisan make:migration create_type_of_service_table
php artisan make:migration create_trans_order_table
php artisan make:migration create_trans_order_detail_table
php artisan make:migration create_trans_laundry_pickup_table
```

Catatan penting: migration untuk tabel users **tidak dibuat manual**. Kita memakai migration bawaan Laravel (0001_01_01_000000_create_users_table.php), lalu menambahkan kolom id_level lewat migration terpisah setelah tabel level ada. Ini dijelaskan di bagian 2.8.

2.2 Migration create_level_table

```
<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    // Fungsi untuk membuat tabel level (data role: Admin, Operator, Pimpinan)
    public function up(): void
    {
        Schema::create('level', function (Blueprint $table) {
            $table->id(); // primary key auto increment
            $table->string('level_name', 50); // nama level, contoh: Admin,
            // Operator, Pimpinan
            $table->timestamps(); // created_at & updated_at otomatis
            $table->softDeletes(); // kolom deleted_at, untuk soft delete
        });
    }
}
```

```

    public function down(): void
    {
        Schema::dropIfExists('level');
    }
};

```

2.3 Migration create_customer_table

```

<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    // Fungsi untuk membuat tabel customer (data pelanggan laundry)
    public function up(): void
    {
        Schema::create('customer', function (Blueprint $table) {
            $table->id(); // primary key auto increment
            $table->string('customer_name', 50); // nama customer
            $table->string('phone', 13); // no telepon customer, sesuai ERD
            ↪ varchar(13)
            $table->text('address'); // alamat customer
            $table->timestamps();
            $table->softDeletes();
        });
    }

    public function down(): void
    {
        Schema::dropIfExists('customer');
    }
};

```

2.4 Migration create_type_of_service_table

```

<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    // Fungsi untuk membuat tabel type_of_service (jenis jasa laundry & harga
    ↪ per kg)
    public function up(): void

```



```

{
    Schema::create('type_of_service', function (Blueprint $table) {
        $table->id();
        $table->string('service_name', 50); // nama jasa, contoh: Cuci &
        ↳ Gosok, Hanya Cuci, dll
        $table->integer('price'); // harga per kg
        $table->text('description')->nullable(); // deskripsi tambahan jasa
        $table->timestamps();
        $table->softDeletes();
    });
}

public function down(): void
{
    Schema::dropIfExists('type_of_service');
}
};

```

2.5 Migration create_trans_order_table

```

<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    // Fungsi untuk membuat tabel trans_order (header transaksi laundry)
    public function up(): void
    {
        Schema::create('trans_order', function (Blueprint $table) {
            $table->id();
            $table->foreignId('id_customer')->constrained('customer')->onDelete('cascade');
            ↳ >onDelete('cascade');
            $table->string('order_code', 30); // kode unik transaksi, contoh:
            ↳ TRX-20260701-001
            $table->date('order_date'); // tanggal masuk laundry
            $table->date('order_end_date')->nullable(); // tanggal
            ↳ estimasi/actual selesai
            $table->tinyInteger('order_status')->default(0); // status: 0 =
            ↳ baru, 1 = sudah diambil
            $table->integer('order_pay')->default(0); // jumlah uang dibayarkan
            ↳ customer
            $table->integer('order_change')->default(0); // kembalian
            $table->integer('total')->default(0); // total harga transaksi
            $table->timestamps();
            $table->softDeletes();
        });
    }
}

```

```

public function down(): void
{
    Schema::dropIfExists('trans_order');
}
};

```

2.6 Migration create_trans_order_detail_table

```

<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    // Fungsi untuk membuat tabel trans_order_detail (detail jasa per
    // transaksi)
    public function up(): void
    {
        Schema::create('trans_order_detail', function (Blueprint $table) {
            $table->id();
            $table->foreignId('id_order')->constrained('trans_order')-
            >onDelete('cascade');
            $table->foreignId('id_service')->constrained('type_of_service')-
            >onDelete('cascade');
            $table->integer('qty'); // berat/qty dalam kg
            $table->double('subtotal', 10, 2); // subtotal = harga jasa * qty
            $table->text('notes')->nullable();
            $table->timestamps();
        });
    }

    public function down(): void
    {
        Schema::dropIfExists('trans_order_detail');
    }
};

```

2.7 Migration create_trans_laundry_pickup_table

```

<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{

```

```

// Fungsi untuk membuat tabel trans_laundry_pickup (catatan pengambilan
↳ pakaian)
public function up(): void
{
    Schema::create('trans_laundry_pickup', function (Blueprint $table) {
        $table->id();
        $table->foreignId('id_order')->constrained('trans_order')-
↳ >onDelete('cascade');
        $table->foreignId('id_customer')->constrained('customer')-
↳ >onDelete('cascade');
        $table->dateTime('pickup_date'); // tanggal & jam pengambilan
        $table->text('notes')->nullable();
        $table->timestamps();
    });
}

public function down(): void
{
    Schema::dropIfExists('trans_laundry_pickup');
}
};

```

2.8 Migration Tambahan id_level untuk Tabel users

Karena kita memakai tabel users bawaan Laravel (bukan tabel custom singular), kolom id_level ditambahkan lewat migration terpisah **setelah** migration bawaan dan migration level, supaya foreign key valid.

```
php artisan make:migration add_id_level_to_users_table --table=users
```

```

<?php

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    // Fungsi untuk menambahkan kolom id_level ke tabel users bawaan Laravel,
    // supaya bisa relasi ke tabel level (Administrator/Operator/Pimpinan)
    ↳ sesuai ERD
    public function up(): void
    {
        Schema::table('users', function (Blueprint $table) {
            $table->foreignId('id_level')->nullable()->after('id')-
↳ >constrained('level')->onDelete('cascade');
        });
    }

    public function down(): void
    {
        Schema::table('users', function (Blueprint $table) {

```

```
        $table->dropForeign(['id_level']);  
        $table->dropColumn('id_level');  
    });  
}
```

2.9 Menjalankan Migration

```
php artisan migrate
```

Bab 3 — Model & Relasi Eloquent

3.1 Membuat Seluruh Model

```
php artisan make:model Level
php artisan make:model Customer
php artisan make:model TypeOfService
php artisan make:model TransOrder
php artisan make:model TransOrderDetail
php artisan make:model TransLaundryPickup
```

Model User sudah tersedia bawaan dari Laravel, tinggal disesuaikan isinya.

3.2 Model Level

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;

class Level extends Model
{
    use HasFactory, SoftDeletes;

    protected $table = 'level';

    protected $fillable = [
        'level_name',
    ];

    // Relasi: satu level bisa dimiliki banyak user
    public function users()
    {
        return $this->hasMany(User::class, 'id_level');
    }
}
```

3.3 Model User

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Foundation\Auth\User as Authenticatable;
use Illuminate\Notifications\Notifiable;

class User extends Authenticatable
{
    use HasFactory, Notifiable;

    // Tidak perlu $table, karena memakai tabel bawaan 'users' (plural)

    protected $fillable = [
        'id_level', // relasi ke tabel level, sesuai ERD
        'name',
        'email',
        'password',
    ];

    protected $hidden = [
        'password',
        'remember_token',
    ];

    protected function casts(): array
    {
        return [
            'email_verified_at' => 'datetime',
            'password' => 'hashed',
        ];
    }

    // Relasi: satu user dimiliki oleh satu level (Admin/Operator/Pimpinan)
    public function level()
    {
        return $this->belongsTo(Level::class, 'id_level');
    }
}
```

3.4 Model Customer

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
```

```

use Illuminate\Database\Eloquent\SoftDeletes;

class Customer extends Model
{
    use HasFactory, SoftDeletes;

    protected $table = 'customer';

    protected $fillable = [
        'customer_name',
        'phone',
        'address',
    ];

    public function transOrders()
    {
        return $this->hasMany(TransOrder::class, 'id_customer');
    }

    public function transLaundryPickups()
    {
        return $this->hasMany(TransLaundryPickup::class, 'id_customer');
    }
}

```

3.5 Model TypeOfService

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;

class TypeOfService extends Model
{
    use HasFactory, SoftDeletes;

    protected $table = 'type_of_service';

    protected $fillable = [
        'service_name',
        'price',
        'description',
    ];

    public function transOrderDetails()
    {
        return $this->hasMany(TransOrderDetail::class, 'id_service');
    }
}

```

```
}
```

3.6 Model TransOrder

```
<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\SoftDeletes;

class TransOrder extends Model
{
    use HasFactory, SoftDeletes;

    protected $table = 'trans_order';

    protected $fillable = [
        'id_customer',
        'order_code',
        'order_date',
        'order_end_date',
        'order_status',
        'order_pay',
        'order_change',
        'total',
    ];

    public function customer()
    {
        return $this->belongsTo(Customer::class, 'id_customer');
    }

    public function details()
    {
        return $this->hasMany(TransOrderDetail::class, 'id_order');
    }

    public function pickup()
    {
        return $this->hasOne(TransLaundryPickup::class, 'id_order');
    }
}
```

3.7 Model TransOrderDetail

```
<?php
```



```

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class TransOrderDetail extends Model
{
    use HasFactory;

    protected $table = 'trans_order_detail';

    protected $fillable = [
        'id_order',
        'id_service',
        'qty',
        'subtotal',
        'notes',
    ];

    public function order()
    {
        return $this->belongsTo(TransOrder::class, 'id_order');
    }

    public function service()
    {
        return $this->belongsTo(TypeOfService::class, 'id_service');
    }
}

```

3.8 Model TransLaundryPickup

```

<?php

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;

class TransLaundryPickup extends Model
{
    use HasFactory;

    protected $table = 'trans_laundry_pickup';

    protected $fillable = [
        'id_order',
        'id_customer',
        'pickup_date',
        'notes',
    ];
}

```

```
public function order()
{
    return $this->belongsTo(TransOrder::class, 'id_order');
}

public function customer()
{
    return $this->belongsTo(Customer::class, 'id_customer');
}
}
```

Bab 4 — Seeder

4.1 Membuat File Seeder

```
php artisan make:seeder LevelSeeder  
php artisan make:seeder UserSeeder
```

4.2 LevelSeeder

```
<?php  
  
namespace Database\Seeders;  
  
use App\Models\Level;  
use Illuminate\Database\Seeder;  
  
class LevelSeeder extends Seeder  
{  
    public function run(): void  
    {  
        Level::create(['level_name' => 'Administrator']);  
        Level::create(['level_name' => 'Operator']);  
        Level::create(['level_name' => 'Pimpinan']);  
    }  
}
```

4.3 UserSeeder

```
<?php  
  
namespace Database\Seeders;  
  
use App\Models\Level;  
use App\Models\User;  
use Illuminate\Database\Seeder;  
use Illuminate\Support\Facades\Hash;  
  
class UserSeeder extends Seeder  
{
```

```

public function run(): void
{
    $admin      = Level::where('level_name', 'Administrator')->first();
    $operator   = Level::where('level_name', 'Operator')->first();
    $pimpinan  = Level::where('level_name', 'Pimpinan')->first();

    User::create([
        'id_level' => $admin->id,
        'name'     => 'Admin',
        'email'    => 'admin@laundry.com',
        'password' => Hash::make('password'),
    ]);

    User::create([
        'id_level' => $operator->id,
        'name'     => 'Operator',
        'email'    => 'operator@laundry.com',
        'password' => Hash::make('password'),
    ]);

    User::create([
        'id_level' => $pimpinan->id,
        'name'     => 'Pimpinan',
        'email'    => 'pimpinan@laundry.com',
        'password' => Hash::make('password'),
    ]);
}
}

```

4.4 DatabaseSeeder

```

<?php

namespace Database\Seeders;

use Illuminate\Database\Seeder;

class DatabaseSeeder extends Seeder
{
    public function run(): void
    {
        $this->call([
            LevelSeeder::class,
            UserSeeder::class,
        ]);
    }
}

```

4.5 Menjalankan Migration + Seeder

```
php artisan migrate:fresh --seed
```

4.6 Akun Default

Role	Email	Password
Administrator	admin@laundry.com	password
Operator	operator@laundry.com	password
Pimpinan	pimpinan@laundry.com	password

Bab 5 — Autentikasi & Middleware Role

5.1 Controller AuthController

```
php artisan make:controller AuthController
```

```
<?php

namespace App\Http\Controllers;

use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;

class AuthController extends Controller
{
    public function showLoginForm()
    {
        return view('auth.login');
    }

    public function login(Request $request)
    {
        $request->validate([
            'email' => 'required|email',
            'password' => 'required',
        ]);

        if (Auth::attempt($request->only('email', 'password'))) {
            $request->session()->regenerate();

            $user = Auth::user()->load('level');

            return match ($user->level->level_name) {
                'Administrator' => redirect()->route('admin.dashboard'),
                'Operator'      => redirect()->route('operator.dashboard'),
                'Pimpinan'      => redirect()->route('pimpinan.dashboard'),
                default          => redirect('/')->with('error', 'Level tidak
                               ↳ dikenali'),
            };
        }
    }
}
```

```

        return back()->withErrors([
            'email' => 'Email atau password salah.',
        ])->onlyInput('email');
    }

    public function logout(Request $request)
    {
        Auth::logout();

        $request->session()->invalidate();
        $request->session()->regenerateToken();

        return redirect()->route('login');
    }
}

```

5.2 Middleware CheckRole

php artisan make:middleware CheckRole

```

<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Symfony\Component\HttpFoundation\Response;

class CheckRole
{
    public function handle(Request $request, Closure $next, ...$roles):
        ↪ Response
    {
        if (!Auth::check()) {
            return redirect()->route('login');
        }

        $userLevel = Auth::user()->load('level')->level->level_name;

        if (!in_array($userLevel, $roles)) {
            abort(403, 'Anda tidak memiliki akses ke halaman ini.');
```

5.3 Middleware PreventBackHistory

Middleware tambahan untuk mencegah browser menampilkan cache halaman setelah logout (mengatasi tombol *back* browser yang menampilkan halaman lama).

php artisan make:middleware PreventBackHistory

```
<?php

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;
use Symfony\Component\HttpFoundation\Response;

class PreventBackHistory
{
    public function handle(Request $request, Closure $next): Response
    {
        $response = $next($request);

        $response->headers->set('Cache-Control', 'no-cache, no-store,
            ↪ max-age=0, must-revalidate');
        $response->headers->set('Pragma', 'no-cache');
        $response->headers->set('Expires', 'Sat, 01 Jan 2000 00:00:00 GMT');

        return $response;
    }
}
```

5.4 Registrasi Middleware — bootstrap/app.php

```
<?php

use Illuminate\Foundation\Application;
use Illuminate\Foundation\Configuration\Exceptions;
use Illuminate\Foundation\Configuration\Middleware;

return Application::configure(basePath: dirname(__DIR__))
    ->withRouting(
        web: __DIR__.'/../routes/web.php',
        commands: __DIR__.'/../routes/console.php',
        health: '/up',
    )
    ->withMiddleware(function (Middleware $middleware) {
        $middleware->alias([
            'role' => \App\Http\Middleware\CheckRole::class,
            'prevent-back-history' =>
                ↪ \App\Http\Middleware\PreventBackHistory::class,
        ]);
    })
    ->withExceptions(function (Exceptions $exceptions) {
```



```
//  
})->create();
```

5.5 Controller Dashboard per Role

app/Http/Controllers/Admin/DashboardController.php:

```
<?php  
  
namespace App\Http\Controllers\Admin;  
  
use App\Http\Controllers\Controller;  
use App\Models\Customer;  
use App\Models\TypeOfService;  
use App\Models\User;  
  
class DashboardController extends Controller  
{  
    public function index()  
    {  
        $totalCustomer = Customer::count();  
        $totalUser      = User::count();  
        $totalService   = TypeOfService::count();  
  
        return view('admin.dashboard', compact('totalCustomer', 'totalUser',  
        ↪ 'totalService'));  
    }  
}
```

app/Http/Controllers/Operator/DashboardController.php:

```
<?php  
  
namespace App\Http\Controllers\Operator;  
  
use App\Http\Controllers\Controller;  
use App\Models\TransOrder;  
  
class DashboardController extends Controller  
{  
    public function index()  
    {  
        $totalHariIni = TransOrder::whereDate('order_date', today())->count();  
        $totalMenunggu = TransOrder::where('order_status', 0)->count();  
        $totalSelesai  = TransOrder::where('order_status', 1)->count();  
  
        return view('operator.dashboard', compact('totalHariIni',  
        ↪ 'totalMenunggu', 'totalSelesai'));  
    }  
}
```

app/Http/Controllers/Pimpinan/DashboardController.php:

```

<?php

namespace App\Http\Controllers\Pimpinan;

use App\Http\Controllers\Controller;
use App\Models\TransOrder;

class DashboardController extends Controller
{
    public function index()
    {
        $totalOmzet      = TransOrder::sum('total');
        $totalTransaksi = TransOrder::count();
        $totalBulanIni   = TransOrder::whereMonth('order_date', now()->month)
            ->whereYear('order_date', now()->year)
            ->count();

        return view('pimpinan.dashboard', compact('totalOmzet',
            ↪ 'totalTransaksi', 'totalBulanIni'));
    }
}

```

5.6 Routing Dasar Autentikasi

```

<?php

use App\Http\Controllers\AuthController;
use App\Http\Controllers\Admin\DashboardController as AdminDashboard;
use App\Http\Controllers\Operator\DashboardController as OperatorDashboard;
use App\Http\Controllers\Pimpinan\DashboardController as PimpinanDashboard;
use Illuminate\Support\Facades\Route;

Route::get('/', function () {
    return redirect()->route('login');
});

Route::get('/login', [AuthController::class, 'showLoginForm'])->name('login');
Route::post('/login', [AuthController::class, 'login'])->name('login.submit');
Route::post('/logout', [AuthController::class, 'logout'])->name('logout');

Route::middleware(['role:Administrator',
    ↪ 'prevent-back-history'])->prefix('admin')->name('admin.')->group(function
    ↪ () {
        Route::get('/dashboard', [AdminDashboard::class,
            ↪ 'index'])->name('dashboard');
    });

Route::middleware(['role:Operator', 'prevent-back-history'])->prefix(
    ↪ 'operator')->name('operator.')->group(function ()
    ↪ {
        Route::get('/dashboard', [OperatorDashboard::class,
            ↪ 'index'])->name('dashboard');
    });

```

```
});  
Route::middleware(['role:Pimpinan', 'prevent-back-history'])->prefix('pimpinan')->name('pimpinan.')->group(function ()  
    ↪ 'pimpinan')->name('pimpinan.')->group(function ()  
    ↪ {  
        Route::get('/dashboard', [PimpinanDashboard::class,  
            ↪ 'index'])->name('dashboard');  
    });  
});
```

Bab 6 — Master Data Administrator

Modul CRUD untuk Customer, User, dan Jenis Service.

6.1 Membuat Controller

```
php artisan make:controller Admin/CustomerController --resource
php artisan make:controller Admin/UserController --resource
php artisan make:controller Admin/TypeOfServiceController --resource
```

6.2 CRUD Customer

app/Http/Controllers/Admin/CustomerController.php:

```
<?php

namespace App\Http\Controllers\Admin;

use App\Http\Controllers\Controller;
use App\Models\Customer;
use Illuminate\Http\Request;

class CustomerController extends Controller
{
    public function index()
    {
        $customers = Customer::latest()->paginate(10);
        return view('admin.customer.index', compact('customers'));
    }

    public function create()
    {
        return view('admin.customer.create');
    }

    public function store(Request $request)
    {
        $request->validate([
            'customer_name' => 'required|string|max:50',
        ]);
    }
}
```

```

        'phone'          => 'required|string|max:13',
        'address'        => 'required|string',
    ]);

    Customer::create($request->only('customer_name', 'phone', 'address'));

    return redirect()->route('admin.customer.index')->with('success',
        ↳ 'Customer berhasil ditambahkan.');
```

```

}

public function edit(Customer $customer)
{
    return view('admin.customer.edit', compact('customer'));
}

public function update(Request $request, Customer $customer)
{
    $request->validate([
        'customer_name' => 'required|string|max:50',
        'phone'         => 'required|string|max:13',
        'address'        => 'required|string',
    ]);

    $customer->update($request->only('customer_name', 'phone', 'address'));

    return redirect()->route('admin.customer.index')->with('success',
        ↳ 'Customer berhasil diperbarui.');
```

```

}

public function destroy(Customer $customer)
{
    $customer->delete();

    return redirect()->route('admin.customer.index')->with('success',
        ↳ 'Customer berhasil dihapus.');
```

```

}
}

```

View resources/views/admin/customer/index.blade.php:

```

<x-layout-app :title="'Data Customer'">

    <div class="flex items-center justify-between mb-6">
        <div>
            <h2 class="font-display text-2xl font-bold text-ink">Data
                ↳ Customer</h2>
            <p class="text-ink/50 text-sm mt-1">Kelola data pelanggan
                ↳ laundry.</p>
        </div>
        <a href="{ route('admin.customer.create') }"
            class="inline-flex items-center gap-2 bg-gradient-to-r from-suds
                ↳ to-teal text-white font-semibold px-5 py-2.5 rounded-xl shadow-lg
                ↳ shadow-suds/20 hover:opacity-90 transition">
            <span>+</span> Tambah Customer

```

```

</a>
</div>

<div class="bg-white rounded-2xl shadow-sm border border-ink/5
  ↪ overflow-hidden">
  <table class="w-full text-sm">
    <thead>
      <tr class="bg-cloud text-ink/60 text-left">
        <th class="px-6 py-4 font-semibold">No</th>
        <th class="px-6 py-4 font-semibold">Nama Customer</th>
        <th class="px-6 py-4 font-semibold">Telepon</th>
        <th class="px-6 py-4 font-semibold">Alamat</th>
        <th class="px-6 py-4 font-semibold text-right">Aksi</th>
      </tr>
    </thead>
    <tbody class="divide-y divide-ink/5">
      @forelse ($customers as $customer)
        <tr class="hover:bg-cloud/60 transition">
          <td class="px-6 py-4 text-ink/50">{{ $loop->iteration
            ↪ }}</td>
          <td class="px-6 py-4 font-medium text-ink">{{
            ↪ $customer->customer_name }}</td>
          <td class="px-6 py-4 font-mono text-ink/70">{{
            ↪ $customer->phone }}</td>
          <td class="px-6 py-4 text-ink/70">{{ $customer->address
            ↪ }}</td>
          <td class="px-6 py-4">
            <div class="flex items-center justify-end gap-2">
              <a href="{{ route('admin.customer.edit',
                ↪ $customer->id) }}"
                  class="px-3 py-1.5 rounded-lg bg-suds/10
                    ↪ text-suds text-xs font-semibold hover:bg-suds hover:text-white
                    ↪ transition">
                Edit
              </a>
              <form action="{{ route('admin.customer.destroy',
                ↪ $customer->id) }}" method="POST"
                  onsubmit="return confirm('Yakin hapus data
                    ↪ ini?');">
                @csrf
                @method('DELETE')
                <button type="submit"
                  class="px-3 py-1.5 rounded-lg
                    ↪ bg-bubblegum/10 text-bubblegum text-xs font-semibold hover:bg-bubblegum
                    ↪ hover:text-white transition">
                Hapus
              </button>
            </form>
          </td>
        </tr>
      @empty
        <tr>

```

```

        <td colspan="5" class="px-6 py-12 text-center
        ↪ text-ink/40">
            Belum ada data customer.
        </td>
    </tr>
</tbody>
</table>
</div>

<div class="mt-6">
    {{ $customers->links() }}
</div>

</x-layout-app>

```

View resources/views/admin/customer/create.blade.php:

```

<x-layout-app :title="'Tambah Customer'">

    <div class="mb-6">
        <a href="{{ route('admin.customer.index') }}" class="text-sm
        ↪ text-ink/50 hover:text-suds transition">&larr; Kembali ke Data
        ↪ Customer</a>
        <h2 class="font-display text-2xl font-bold text-ink mt-2">Tambah
        ↪ Customer</h2>
    </div>

    @if ($errors->any())
        <div class="mb-6 rounded-xl bg-bubblegum/10 border border-bubblegum/30
        ↪ text-bubblegum text-sm px-4 py-3">
            <ul class="list-disc list-inside space-y-1">
                @foreach ($errors->all() as $error)
                    <li>{{ $error }}</li>
                @endforeach
            </ul>
        </div>
    @endif

    <div class="bg-white rounded-2xl shadow-sm border border-ink/5 p-6
    ↪ max-w-xl">
        <form method="POST" action="{{ route('admin.customer.store') }}"
        ↪ class="space-y-4">
            @csrf

            <div>
                <label class="block text-sm font-medium text-ink mb-1">Nama
                ↪ Customer</label>
                <input type="text" name="customer_name" value="{{
                ↪ old('customer_name') }}"
                ↪ class="w-full rounded-xl border border-ink/15 px-4 py-2.5
                ↪ text-ink focus:outline-none focus:ring-2 focus:ring-suds focus:border-suds
                ↪ transition">
            </div>

```

```

<div>
  <label class="block text-sm font-medium text-ink
    ↳ mb-1">Telepon</label>
  <input type="text" name="phone" value="{{ old('phone') }}"
    ↳ maxlength="13"
    ↳ class="w-full rounded-xl border border-ink/15 px-4 py-2.5
    ↳ text-ink focus:outline-none focus:ring-2 focus:ring-suds focus:border-suds
    ↳ transition">
</div>

<div>
  <label class="block text-sm font-medium text-ink
    ↳ mb-1">Alamat</label>
  <textarea name="address" rows="3"
    ↳ class="w-full rounded-xl border border-ink/15 px-4 py-2.5
    ↳ text-ink focus:outline-none focus:ring-2 focus:ring-suds focus:border-suds
    ↳ transition">{{ old('address') }}</textarea>
</div>

<div class="flex items-center gap-3 pt-2">
  <button type="submit"
    ↳ class="bg-gradient-to-r from-suds to-teal text-white
    ↳ font-semibold px-6 py-2.5 rounded-xl shadow-lg shadow-suds/20
    ↳ hover:opacity-90 transition">
    Simpan
  </button>
  <a href="{{ route('admin.customer.index') }}" class="text-ink/50
    ↳ hover:text-ink text-sm font-medium transition">Batal</a>
</div>
</form>
</div>

</x-layout-app>

```

View resources/views/admin/customer/edit.blade.php mengikuti pola yang sama seperti create.blade.php, dengan method PUT dan nilai awal input diisi dari data \$customer yang sudah ada.

6.3 CRUD Jenis Service

app/Http/Controllers/Admin/TypeOfServiceController.php:

```

<?php

namespace App\Http\Controllers\Admin;

use App\Http\Controllers\Controller;
use App\Models\TypeOfService;
use Illuminate\Http\Request;

class TypeOfServiceController extends Controller
{

```



```

public function index()
{
    $services = TypeOfService::latest()->paginate(10);
    return view('admin.service.index', compact('services'));
}

public function create()
{
    return view('admin.service.create');
}

public function store(Request $request)
{
    $request->validate([
        'service_name' => 'required|string|max:50',
        'price'         => 'required|integer|min:0',
        'description'   => 'nullable|string',
    ]);

    TypeOfService::create($request->only('service_name', 'price',
        ⇨ 'description'));

    return redirect()->route('admin.service.index')->with('success',
        ⇨ 'Jenis service berhasil ditambahkan.');
```

```

}

public function edit(TypeOfService $service)
{
    return view('admin.service.edit', compact('service'));
}

public function update(Request $request, TypeOfService $service)
{
    $request->validate([
        'service_name' => 'required|string|max:50',
        'price'         => 'required|integer|min:0',
        'description'   => 'nullable|string',
    ]);

    $service->update($request->only('service_name', 'price',
        ⇨ 'description'));

    return redirect()->route('admin.service.index')->with('success',
        ⇨ 'Jenis service berhasil diperbarui.');
```

```

}

public function destroy(TypeOfService $service)
{
    $service->delete();

    return redirect()->route('admin.service.index')->with('success',
        ⇨ 'Jenis service berhasil dihapus.');
```

```

}

```

```
}
```

View resources/views/admin/service/index.blade.php:

```
<x-layout-app :title="'Data Jenis Service'">

    <div class="flex items-center justify-between mb-6">
        <div>
            <h2 class="font-display text-2xl font-bold text-ink">Data Jenis
                ↪ Service</h2>
            <p class="text-ink/50 text-sm mt-1">Kelola jenis jasa laundry
                ↪ beserta harga per kg.</p>
        </div>
        <a href="{ { route('admin.service.create') } }"
            class="inline-flex items-center gap-2 bg-gradient-to-r from-suds
            ↪ to-teal text-white font-semibold px-5 py-2.5 rounded-xl shadow-lg
            ↪ shadow-suds/20 hover:opacity-90 transition">
            <span>+</span> Tambah Jenis Service
        </a>
    </div>

    <div class="bg-white rounded-2xl shadow-sm border border-ink/5
    ↪ overflow-hidden">
        <table class="w-full text-sm">
            <thead>
                <tr class="bg-cloud text-ink/60 text-left">
                    <th class="px-6 py-4 font-semibold">No</th>
                    <th class="px-6 py-4 font-semibold">Nama Jasa</th>
                    <th class="px-6 py-4 font-semibold">Harga / Kg</th>
                    <th class="px-6 py-4 font-semibold">Deskripsi</th>
                    <th class="px-6 py-4 font-semibold text-right">Aksi</th>
                </tr>
            </thead>
            <tbody class="divide-y divide-ink/5">
                @forelse ($services as $service)
                    <tr class="hover:bg-cloud/60 transition">
                        <td class="px-6 py-4 text-ink/50">{{ $loop->iteration
                            ↪ }}</td>
                        <td class="px-6 py-4 font-medium text-ink">{{
                            ↪ $service->service_name }}</td>
                        <td class="px-6 py-4 font-mono font-semibold
                            ↪ text-teal">Rp {{ number_format($service->price, 0,
                            ↪ ',', '.')} }}</td>
                        <td class="px-6 py-4 text-ink/70">{{
                            ↪ $service->description ?? '-' }}</td>
                        <td class="px-6 py-4">
                            <div class="flex items-center justify-end gap-2">
                                <a href="{ { route('admin.service.edit',
                                    ↪ $service->id) } }"
                                    class="px-3 py-1.5 rounded-lg bg-suds/10
                                    ↪ text-suds text-xs font-semibold hover:bg-suds hover:text-white
                                    ↪ transition">
                                    Edit
                                </a>
                            </div>
                        </td>
                    </tr>
                @endforelse
            </tbody>
        </table>
    </div>

</x-layout-app>
```

```

        <form action="{{ route('admin.service.destroy',
        ↪ $service->id) }}" method="POST"
            onsubmit="return confirm('Yakin hapus
jenis service ini?');">
            @csrf
            @method('DELETE')
            <button type="submit"
                class="px-3 py-1.5 rounded-lg
        ↪ bg-bubblegum/10 text-bubblegum text-xs font-semibold hover:bg-bubblegum
        ↪ hover:text-white transition">
                Hapus
            </button>
        </form>
    </div>
</td>
</tr>
@empty
<tr>
    <td colspan="5" class="px-6 py-12 text-center
        ↪ text-ink/40">
        ↪ Belum ada data jenis service.
    </td>
</tr>
@endforelse
</tbody>
</table>
</div>

<div class="mt-6">
    {{ $services->links() }}
</div>
</x-layout-app>

```

Form create dan edit untuk Jenis Service mengikuti pola sama seperti Customer, dengan tambahan input harga berformat angka dan prefix “Rp”.

6.4 CRUD User

app/Http/Controllers/Admin/UserController.php:

```

<?php

namespace App\Http\Controllers\Admin;

use App\Http\Controllers\Controller;
use App\Models\Level;
use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Hash;

class UserController extends Controller
{

```

```

public function index()
{
    $users = User::with('level')->latest()->paginate(10);
    return view('admin.user.index', compact('users'));
}

public function create()
{
    $levels = Level::all();
    return view('admin.user.create', compact('levels'));
}

public function store(Request $request)
{
    $request->validate([
        'id_level' => 'required|exists:level,id',
        'name'     => 'required|string|max:50',
        'email'    => 'required|email|max:50|unique:users,email',
        'password' => 'required|string|min:6',
    ]);

    User::create([
        'id_level' => $request->id_level,
        'name'     => $request->name,
        'email'    => $request->email,
        'password' => Hash::make($request->password),
    ]);

    return redirect()->route('admin.user.index')->with('success', 'User
        ↳ berhasil ditambahkan.');
```

```

}

public function edit(User $user)
{
    $levels = Level::all();
    return view('admin.user.edit', compact('user', 'levels'));
}

public function update(Request $request, User $user)
{
    $request->validate([
        'id_level' => 'required|exists:level,id',
        'name'     => 'required|string|max:50',
        'email'    => 'required|email|max:50|unique:users,email,' .
        ↳ $user->id,
        'password' => 'nullable|string|min:6',
    ]);

    $data = [
        'id_level' => $request->id_level,
        'name'     => $request->name,
        'email'    => $request->email,
    ];

```

```

if ($request->filled('password')) {
    $data['password'] = Hash::make($request->password);
}

$user->update($data);

return redirect()->route('admin.user.index')->with('success', 'User
    ↪ berhasil diperbarui.');
```

```

}

public function destroy(User $user)
{
    $user->delete();

    return redirect()->route('admin.user.index')->with('success', 'User
        ↪ berhasil dihapus.');
```

```

}
}

```

View resources/views/admin/user/index.blade.php (dengan badge warna berbeda tiap level):

```

<x-layout-app :title="'Data User'">

    <div class="flex items-center justify-between mb-6">
        <div>
            <h2 class="font-display text-2xl font-bold text-ink">Data User</h2>
            <p class="text-ink/50 text-sm mt-1">Kelola akun Administrator,
                ↪ Operator, dan Pimpinan.</p>
        </div>
        <a href="{ route('admin.user.create') }"
            class="inline-flex items-center gap-2 bg-gradient-to-r from-suds
                ↪ to-teal text-white font-semibold px-5 py-2.5 rounded-xl shadow-lg
                ↪ shadow-suds/20 hover:opacity-90 transition">
            <span>+</span> <span>Tambah User</span>
        </a>
    </div>

    <div class="bg-white rounded-2xl shadow-sm border border-ink/5
        ↪ overflow-hidden">
        <table class="w-full text-sm">
            <thead>
                <tr class="bg-cloud text-ink/60 text-left">
                    <th class="px-6 py-4 font-semibold">No</th>
                    <th class="px-6 py-4 font-semibold">>Nama</th>
                    <th class="px-6 py-4 font-semibold">Email</th>
                    <th class="px-6 py-4 font-semibold">Level</th>
                    <th class="px-6 py-4 font-semibold text-right">Aksi</th>
                </tr>
            </thead>
            <tbody class="divide-y divide-ink/5">
                @forelse ($users as $user)
                    <tr class="hover:bg-cloud/60 transition">

```

```

<td class="px-6 py-4 text-ink/50">{{ $loop->iteration
↪ }}</td>
<td class="px-6 py-4 font-medium text-ink">{{
↪ $user->name }}</td>
<td class="px-6 py-4 text-ink/70">{{ $user->email }}</td>
<td class="px-6 py-4">
    @php
        $badgeColor = match ($user->level->level_name) {
            'Administrator' => 'bg-suds/10 text-suds',
            'Operator'      => 'bg-teal/10 text-teal',
            'Pimpinan'      => 'bg-bubblegum/10
↪ text-bubblegum',
                                default      => 'bg-ink/10 text-ink',
        };
    @endphp
    <span class="px-3 py-1 rounded-full text-xs
↪ font-semibold {{ $badgeColor }}">
        {{ $user->level->level_name }}
    </span>
</td>
<td class="px-6 py-4">
    <div class="flex items-center justify-end gap-2">
        <a href="{{ route('admin.user.edit', $user->id)
↪ }}"
            class="px-3 py-1.5 rounded-lg bg-suds/10
↪ text-suds text-xs font-semibold hover:bg-suds hover:text-white
↪ transition">
            Edit
        </a>
        <form action="{{ route('admin.user.destroy',
↪ $user->id) }}" method="POST"
            onsubmit="return confirm('Yakin hapus user
↪ ini?');">
            @csrf
            @method('DELETE')
            <button type="submit"
↪ class="px-3 py-1.5 rounded-lg
↪ bg-bubblegum/10 text-bubblegum text-xs font-semibold hover:bg-bubblegum
↪ hover:text-white transition">
                Hapus
            </button>
        </form>
    </div>
</td>
</tr>
@empty
<tr>
    <td colspan="5" class="px-6 py-12 text-center
↪ text-ink/40">Belum ada data user.</td>
</tr>
@endforelse
</tbody>
</table>

```

```

</div>

<div class="mt-6">
    {{ $users->links() }}
</div>

</x-layout-app>

```

Form create dan edit User berisi input nama, email, password, dan dropdown pilihan level, mengikuti pola input sama seperti modul Customer/Jenis Service.

6.5 Routing Master Data

```

use App\Http\Controllers\Admin\CustomerController;
use App\Http\Controllers\Admin\UserController;
use App\Http\Controllers\Admin\TypeOfServiceController;

Route::middleware(['role:Administrator',
    ↪ 'prevent-back-history'])->prefix('admin')->name('admin.')->group(function
    ↪ () {
    Route::get('/dashboard', [AdminDashboard::class,
        ↪ 'index'])->name('dashboard');

    Route::resource('customer', CustomerController::class)->except('show');
    Route::resource('user', UserController::class)->except('show');
    Route::resource('service',
        ↪ TypeOfServiceController::class)->except('show');
});

```

Bab 7 — Transaksi Laundry (Operator)

Modul inti sistem: input transaksi dengan perhitungan subtotal otomatis, mendukung lebih dari satu jenis jasa dalam satu transaksi.

7.1 Controller TransOrderController

```
php artisan make:controller Operator/TransOrderController --resource
```

```
<?php

namespace App\Http\Controllers\Operator;

use App\Http\Controllers\Controller;
use App\Models\Customer;
use App\Models\TransOrder;
use App\Models\TransOrderDetail;
use App\Models\TypeOfService;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;

class TransOrderController extends Controller
{
    public function index()
    {
        $orders = TransOrder::with('customer')->latest()->paginate(10);
        return view('operator.order.index', compact('orders'));
    }

    public function create()
    {
        $customers = Customer::orderBy('customer_name')->get();
        $services = TypeOfService::orderBy('service_name')->get();
        return view('operator.order.create', compact('customers', 'services'));
    }

    public function store(Request $request)
    {
        $request->validate([
            'id_customer' => 'required|exists:customer,id',
        ]);
    }
}
```



```

        'services'      => 'required|array|min:1',
        'services.*'    => 'required|exists:type_of_service,id',
        'qty'           => 'required|array|min:1',
        'qty.*'         => 'required|numeric|min:0.1',
        'notes'         => 'nullable|array',
    ];

    DB::transaction(function () use ($request) {

        $orderCode = 'TRX-' . now()->format('Ymd') . '-' .
            str_pad(TransOrder::whereDate('created_at', now())->count() +
                ↪ 1, 4, '0', STR_PAD_LEFT);

        $order = TransOrder::create([
            'id_customer' => $request->id_customer,
            'order_code'  => $orderCode,
            'order_date'  => now()->toDateString(),
            'order_end_date' => null,
            'order_status' => 0, // 0 = baru
            'order_pay'    => 0,
            'order_change' => 0,
            'total'        => 0,
        ]);

        $grandTotal = 0;

        foreach ($request->services as $index => $serviceId) {
            $service = TypeOfService::findOrFail($serviceId);
            $qty      = $request->qty[$index];
            $subtotal = $service->price * $qty; // Subtotal = harga * qty

            TransOrderDetail::create([
                'id_order'    => $order->id,
                'id_service' => $service->id,
                'qty'         => $qty,
                'subtotal'    => $subtotal,
                'notes'       => $request->notes[$index] ?? null,
            ]);

            $grandTotal += $subtotal;
        }

        $order->update(['total' => $grandTotal]);
    });

    return redirect()->route('operator.order.index')->with('success',
        ↪ 'Transaksi laundry berhasil dibuat.');
```

```

}

public function show(TransOrder $order)
{
    $order->load('customer', 'details.service');
    return view('operator.order.show', compact('order'));
}

```

```
}
}
```

7.2 View Daftar Transaksi

resources/views/operator/order/index.blade.php:

```
<x-layout-app :title="'Transaksi Laundry'">

    <div class="flex items-center justify-between mb-6">
        <div>
            <h2 class="font-display text-2xl font-bold text-ink">Transaksi
                Laundry</h2>
            <p class="text-ink/50 text-sm mt-1">Daftar seluruh transaksi
                laundry yang pernah dibuat.</p>
        </div>
        <a href="{{ route('operator.order.create') }}"
            class="inline-flex items-center gap-2 bg-gradient-to-r from-suds
                to-teal text-white font-semibold px-5 py-2.5 rounded-xl shadow-lg
                shadow-suds/20 hover:opacity-90 transition">
            <span>+</span> Buat Transaksi Baru
        </a>
    </div>

    <div class="bg-white rounded-2xl shadow-sm border border-ink/5
        overflow-hidden">
        <table class="w-full text-sm">
            <thead>
                <tr class="bg-cloud text-ink/60 text-left">
                    <th class="px-6 py-4 font-semibold">No</th>
                    <th class="px-6 py-4 font-semibold">Kode Order</th>
                    <th class="px-6 py-4 font-semibold">Customer</th>
                    <th class="px-6 py-4 font-semibold">Tanggal</th>
                    <th class="px-6 py-4 font-semibold">Total</th>
                    <th class="px-6 py-4 font-semibold">Status</th>
                    <th class="px-6 py-4 font-semibold text-right">Aksi</th>
                </tr>
            </thead>
            <tbody class="divide-y divide-ink/5">
                @forelse ($orders as $order)
                    <tr class="hover:bg-cloud/60 transition">
                        <td class="px-6 py-4 text-ink/50">{{ $loop->iteration
                            }}</td>
                        <td class="px-6 py-4 font-mono text-ink font-medium">{{
                            $order->order_code }}</td>
                        <td class="px-6 py-4 text-ink">{{
                            $order->customer->customer_name }}</td>
                        <td class="px-6 py-4 text-ink/70">{{
                            \Carbon\Carbon::parse($order->order_date)-
                            >translatedFormat('d M Y')
                            }}</td>
                        <td class="px-6 py-4 font-mono font-semibold
                            text-teal">Rp {{ number_format($order->total, 0,
                            ',', ' ') }}</td>
                    </tr>
                @endforelse
            </tbody>
        </table>
    </div>
</x-layout-app>
```

```

<td class="px-6 py-4">
    @if ($order->order_status == 0)
        <span class="px-3 py-1 rounded-full text-xs
            ↳ font-semibold bg-sunbeam/20
            ↳ text-[#8A6300]">Baru</span>
        @else
            <span class="px-3 py-1 rounded-full text-xs
                ↳ font-semibold bg-teal/10 text-teal">Sudah
                ↳ Diambil</span>
        @endif
    </td>
    <td class="px-6 py-4 text-right">
        <a href="{{ route('operator.order.show', $order->id)
            ↳ }}"
            class="px-3 py-1.5 rounded-lg bg-suds/10 text-suds
            ↳ text-xs font-semibold hover:bg-suds hover:text-white transition">
            Detail
        </a>
    </td>
</tr>
@empty
<tr>
    <td colspan="7" class="px-6 py-12 text-center
        ↳ text-ink/40">Belum ada transaksi.</td>
</tr>
@endforelse
</tbody>
</table>
</div>

<div class="mt-6">
    {{ $orders->links() }}
</div>

</x-layout-app>

```

7.3 View Form Transaksi Baru (Dinamis)

resources/views/operator/order/create.blade.php — mendukung penambahan/penghapusan baris jasa secara dinamis, dengan kalkulasi subtotal langsung (live) di sisi klien:

```

<x-layout-app :title="'Buat Transaksi Laundry'">

    <div class="mb-6">
        <a href="{{ route('operator.order.index') }}" class="text-sm
            ↳ text-ink/50 hover:text-suds transition">&larr; Kembali ke
            ↳ Transaksi Laundry</a>
        <h2 class="font-display text-2xl font-bold text-ink mt-2">Buat
            ↳ Transaksi Baru</h2>
    </div>

    @if ($errors->any())

```

```

<div class="mb-6 rounded-xl bg-bubblegum/10 border border-bubblegum/30
  ↳ text-bubblegum text-sm px-4 py-3">
  <ul class="list-disc list-inside space-y-1">
    @foreach ($errors->all() as $error)
      <li>{{ $error }}</li>
    @endforeach
  </ul>
</div>
@endif

<form method="POST" action="{{ route('operator.order.store') }}"
  ↳ class="space-y-6">
  @csrf

  <div class="bg-white rounded-2xl shadow-sm border border-ink/5 p-6">
    <label class="block text-sm font-medium text-ink
      ↳ mb-1">Customer</label>
    <select name="id_customer" required
      class="w-full rounded-xl border border-ink/15 px-4 py-2.5
      ↳ text-ink focus:outline-none focus:ring-2 focus:ring-suds focus:border-suds
      ↳ transition">
      <option value="">-- Pilih Customer --</option>
      @foreach ($customers as $customer)
        <option value="{{ $customer->id }}">{{
          ↳ $customer->customer_name }} - {{ $customer->phone
          ↳ }}</option>
      @endforeach
    </select>
  </div>

  <div class="bg-white rounded-2xl shadow-sm border border-ink/5 p-6">
    <div class="flex items-center justify-between mb-4">
      <h3 class="font-display font-semibold text-ink">Detail Jasa</h3>
      <p class="text-sm text-ink/50">Total: <span id="grand-total"
        ↳ class="font-mono font-semibold text-teal">Rp 0</span></p>
    </div>

    <div id="service-rows" class="space-y-3">
      <div class="service-row grid grid-cols-1
        ↳ sm:grid-cols-[2fr_1fr_2fr_auto] gap-3 items-start
        ↳ bg-cloud/60 rounded-xl p-4">
        <div>
          <select name="services[]" required
            ↳ onchange="calculateRow(this)"
            class="service-select w-full rounded-lg border
            ↳ border-ink/15 px-3 py-2 text-sm text-ink focus:outline-none focus:ring-2
            ↳ focus:ring-suds transition">
            <option value="">-- Pilih Jasa --</option>
            @foreach ($services as $service)
              <option value="{{ $service->id }}"
                ↳ data-price="{{ $service->price }}"
                ↳ {{ $service->service_name }} (Rp {{
                ↳ number_format($service->price, 0, ',', '.') }}>kg)

```

```

        </option>
      @endforeach
    </select>
  </div>
  <div>
    <input type="number" name="qty[]" step="0.1" min="0.1"
      ↳ placeholder="Qty (kg)" required
      ↳ oninput="calculateRow(this)"
      class="qty-input w-full rounded-lg border
↳ border-ink/15 px-3 py-2 text-sm text-ink focus:outline-none focus:ring-2
↳ focus:ring-suds transition">
    </div>
    <div>
      <input type="text" name="notes[]" placeholder="Catatan
      ↳ (opsional)"
      class="w-full rounded-lg border border-ink/15 px-3
↳ py-2 text-sm text-ink focus:outline-none focus:ring-2 focus:ring-suds
↳ transition">
    </div>
    <div class="flex items-center h-full pt-2">
      <span class="row-subtotal font-mono text-sm font-semibold
      ↳ text-ink whitespace-nowrap">Rp 0</span>
      <button type="button" onclick="removeRow(this)"
      ↳ class="ml-3 text-bubblegum hover:text-bubblegum/70
      ↳ text-lg leading-none" title="Hapus
      ↳ baris">x</button>
    </div>
  </div>
</div>

  <button type="button" onclick="addServiceRow()"
    class="mt-4 inline-flex items-center gap-2 text-suds
↳ font-semibold text-sm hover:text-suds/70 transition">
    + Tambah Jasa Lain
  </button>
</div>

  <div class="flex items-center gap-3">
    <button type="submit"
      class="bg-gradient-to-r from-suds to-teal text-white
↳ font-semibold px-6 py-2.5 rounded-xl shadow-lg shadow-suds/20
↳ hover:opacity-90 transition">
      Simpan Transaksi
    </button>
    <a href="{ route('operator.order.index') }" class="text-ink/50
    ↳ hover:text-ink text-sm font-medium transition">Batal</a>
  </div>
</form>

<script>
  // Hitung ulang subtotal 1 baris, lalu update grand total keseluruhan.
  // Perhitungan final tetap dihitung ulang di server (Controller) demi
  ↳ keamanan data.

```

```

function calculateRow(el) {
  const row = el.closest('.service-row');
  const select = row.querySelector('.service-select');
  const qtyInput = row.querySelector('.qty-input');
  const subtotalEl = row.querySelector('.row-subtotal');

  const price = parseFloat(select.selectedOptions[0]?.dataset.price
    ↪ || 0);
  const qty = parseFloat(qtyInput.value || 0);
  const subtotal = price * qty;

  subtotalEl.textContent = 'Rp ' + subtotal.toLocaleString('id-ID');
  updateGrandTotal();
}

function updateGrandTotal() {
  let total = 0;
  document.querySelectorAll('.service-row').forEach(row => {
    const select = row.querySelector('.service-select');
    const qtyInput = row.querySelector('.qty-input');
    const price =
      ↪ parseFloat(select.selectedOptions[0]?.dataset.price || 0);
    const qty = parseFloat(qtyInput.value || 0);
    total += price * qty;
  });
  document.getElementById('grand-total').textContent = 'Rp ' +
    ↪ total.toLocaleString('id-ID');
}

function addServiceRow() {
  const container = document.getElementById('service-rows');
  const newRow = container.children[0].cloneNode(true);
  ↪ newRow.querySelectorAll('select, input').forEach(el => el.value =
    ↪ '');
  newRow.querySelector('.row-subtotal').textContent = 'Rp 0';
  container.appendChild(newRow);
}

function removeRow(btn) {
  const container = document.getElementById('service-rows');
  if (container.children.length > 1) {
    btn.closest('.service-row').remove();
    updateGrandTotal();
  } else {
    alert('Minimal harus ada 1 jasa dalam transaksi.');
```

```

  }
</script>

```

```

</x-layout-app>

```

7.4 View Detail Transaksi

resources/views/operator/order/show.blade.php:

```
<x-layout-app :title="'Detail Transaksi'">

    <div class="mb-6">
        <a href="{{ route('operator.order.index') }}" class="text-sm
        ↳ text-ink/50 hover:text-suds transition">&larr; Kembali ke
        ↳ Transaksi Laundry</a>
        <div class="flex items-center gap-3 mt-2">
            <h2 class="font-display text-2xl font-bold text-ink">{{
            ↳ $order->order_code }}</h2>
            @if ($order->order_status == 0)
                <span class="px-3 py-1 rounded-full text-xs font-semibold
                ↳ bg-sunbeam/20 text-[#8A6300]">Baru</span>
            @else
                <span class="px-3 py-1 rounded-full text-xs font-semibold
                ↳ bg-teal/10 text-teal">Sudah Diambil</span>
            @endif
        </div>
    </div>

    <div class="bg-white rounded-2xl shadow-sm border border-ink/5 p-6 mb-6">
        <h3 class="font-display font-semibold text-ink mb-3">Info Customer</h3>
        <div class="grid grid-cols-1 sm:grid-cols-3 gap-4 text-sm">
            <div>
                <p class="text-ink/50">Nama</p>
                <p class="font-medium text-ink">{{
                ↳ $order->customer->customer_name }}</p>
            </div>
            <div>
                <p class="text-ink/50">Telepon</p>
                <p class="font-medium text-ink">{{ $order->customer->phone
                ↳ }}</p>
            </div>
            <div>
                <p class="text-ink/50">Tanggal Masuk</p>
                <p class="font-medium text-ink">{{ \Carbon\Carbon::parse($order-
                ↳ >order_date)->translatedFormat('d F Y')
                ↳ }}</p>
            </div>
        </div>
    </div>

    <div class="bg-white rounded-2xl shadow-sm border border-ink/5
    ↳ overflow-hidden">
        <table class="w-full text-sm">
            <thead>
                <tr class="bg-cloud text-ink/60 text-left">
                    <th class="px-6 py-4 font-semibold">Jasa</th>
                    <th class="px-6 py-4 font-semibold">Qty (kg)</th>
                    <th class="px-6 py-4 font-semibold">Harga/kg</th>
                    <th class="px-6 py-4 font-semibold">Subtotal</th>
```

```

        <th class="px-6 py-4 font-semibold">Catatan</th>
      </tr>
    </thead>
    <tbody class="divide-y divide-ink/5">
      @foreach ($order->details as $detail)
        <tr>
          <td class="px-6 py-4 font-medium text-ink">{{
            ↳ $detail->service->service_name }}</td>
          <td class="px-6 py-4 text-ink/70">{{ $detail->qty }}</td>
          <td class="px-6 py-4 text-ink/70 font-mono">Rp {{
            ↳ number_format($detail->service->price, 0, ',',
            ↳ '.') }}</td>
          <td class="px-6 py-4 font-mono font-semibold
            ↳ text-teal">Rp {{ number_format($detail->subtotal,
            ↳ 0, ',', '.') }}</td>
          <td class="px-6 py-4 text-ink/50">{{ $detail->notes ??
            ↳ '-' }}</td>
        </tr>
      @endforeach
    </tbody>
  </table>
</div>

<div class="ticket-edge bg-gradient-to-r from-suds to-teal rounded-2xl p-6
↳ pb-8 mt-6 text-white flex items-center justify-between max-w-sm
↳ ml-auto shadow-lg shadow-suds/20">
  <span class="font-medium">Total Bayar</span>
  <span class="font-mono text-2xl font-bold">Rp {{
    ↳ number_format($order->total, 0, ',', '.') }}</span>
</div>

</x-layout-app>

```

7.5 Routing Transaksi

```

use App\Http\Controllers\Operator\TransOrderController;

Route::middleware(['role:Operator', 'prevent-back-history'])->prefix('
↳ 'operator')->name('operator.')->group(function ()
↳ {
  Route::get('/dashboard', [OperatorDashboard::class,
    ↳ 'index'])->name('dashboard');

  Route::resource('order', TransOrderController::class)->only(['index',
    ↳ 'create', 'store', 'show']);
});

```


Bab 8 — Transaksi Pengambilan Laundry (Operator)

8.1 Controller TransLaundryPickupController

```
php artisan make:controller Operator/TransLaundryPickupController
```

```
<?php

namespace App\Http\Controllers\Operator;

use App\Http\Controllers\Controller;
use App\Models\TransLaundryPickup;
use App\Models\TransOrder;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\DB;

class TransLaundryPickupController extends Controller
{
    public function index()
    {
        $orders = TransOrder::with('customer')
            ->where('order_status', 0)
            ->latest()
            ->paginate(10);

        return view('operator.pickup.index', compact('orders'));
    }

    public function create(TransOrder $order)
    {
        if ($order->order_status == 1) {
            return redirect()->route('operator.pickup.index')->with('error',
                'Transaksi ini sudah diambil sebelumnya.');
```

```

{
    $request->validate([
        'notes' => 'nullable|string',
    ]);

    if ($order->order_status == 1) {
        return redirect()->route('operator.pickup.index')->with('error',
            ↪ 'Transaksi ini sudah diambil sebelumnya.');
```

```

    }

    DB::transaction(function () use ($request, $order) {

```

```

        TransLaundryPickup::create([
            'id_order'    => $order->id,
            'id_customer' => $order->id_customer,
            'pickup_date' => now(),
            'notes'       => $request->notes,
        ]);

```

```

        $order->update([
            'order_status'    => 1,
            'order_end_date' => now()->toDateString(),
        ]);
    });

```

```

    return redirect()->route('operator.pickup.index')->with('success',
        ↪ 'Pengambilan laundry berhasil dicatat.');
```

```

    }
}

```

8.2 View Daftar Siap Diambil

resources/views/operator/pickup/index.blade.php:

```

<x-layout-app :title="'Pengambilan Laundry'">

```

```

    <div class="mb-6">
        <h2 class="font-display text-2xl font-bold text-ink">Daftar Laundry
            ↪ Siap Diambil</h2>
        <p class="text-ink/50 text-sm mt-1">Transaksi dengan status "Baru" yang
            ↪ menunggu diambil customer.</p>
    </div>

```

```

    <div class="bg-white rounded-2xl shadow-sm border border-ink/5
        ↪ overflow-hidden">
        <table class="w-full text-sm">
            <thead>
                <tr class="bg-cloud text-ink/60 text-left">
                    <th class="px-6 py-4 font-semibold">No</th>
                    <th class="px-6 py-4 font-semibold">Kode Order</th>
                    <th class="px-6 py-4 font-semibold">Customer</th>
                    <th class="px-6 py-4 font-semibold">Tanggal Masuk</th>

```

```

        <th class="px-6 py-4 font-semibold">Total</th>
        <th class="px-6 py-4 font-semibold text-right">Aksi</th>
    </tr>
</thead>
<tbody class="divide-y divide-ink/5">
    @forelse ($orders as $order)
        <tr class="hover:bg-cloud/60 transition">
            <td class="px-6 py-4 text-ink/50">{{ $loop->iteration
                ↳ }}</td>
            <td class="px-6 py-4 font-mono text-ink font-medium">{{
                ↳ $order->order_code }}</td>
            <td class="px-6 py-4 text-ink">{{
                ↳ $order->customer->customer_name }}</td>
            <td class="px-6 py-4 text-ink/70">{{
                ↳ \Carbon\Carbon::parse($order->order_date)-
                ↳ >translatedFormat('d M Y')
                ↳ }}</td>
            <td class="px-6 py-4 font-mono font-semibold
                ↳ text-teal">Rp {{ number_format($order->total, 0,
                ↳ ',', '.')} }}</td>
            <td class="px-6 py-4 text-right">
                <a href="{{ route('operator.pickup.create',
                    ↳ $order->id) }}"
                    class="inline-flex items-center gap-1.5 px-4 py-2
↳ rounded-lg bg-gradient-to-r from-suds to-teal text-white text-xs
↳ font-semibold hover:opacity-90 transition">
                    Proses Pengambilan
                </a>
            </td>
        </tr>
    @empty
        <tr>
            <td colspan="6" class="px-6 py-12 text-center
                ↳ text-ink/40">
                Tidak ada laundry yang menunggu diambil. Semua sudah
↳ selesai.
            </td>
        </tr>
    @endforelse
</tbody>
</table>
</div>

<div class="mt-6">
    {{ $orders->links() }}
</div>
</x-layout-app>

```

8.3 View Proses Pengambilan

resources/views/operator/pickup/create.blade.php:

```

<x-layout-app :title="'Proses Pengambilan'">

  <div class="mb-6">
    <a href="{ route('operator.pickup.index') }}" class="text-sm
      ↳ text-ink/50 hover:text-suds transition">&larr; Kembali ke
      ↳ Pengambilan Laundry</a>
    <h2 class="font-display text-2xl font-bold text-ink mt-2">Proses
      ↳ Pengambilan – {{ $order->order_code }}</h2>
  </div>

  <div class="bg-white rounded-2xl shadow-sm border border-ink/5 p-6 mb-6">
    <h3 class="font-display font-semibold text-ink mb-3">Info Customer</h3>
    <div class="grid grid-cols-1 sm:grid-cols-2 gap-4 text-sm">
      <div>
        <p class="text-ink/50">Nama</p>
        <p class="font-medium text-ink">{{
          ↳ $order->customer->customer_name }}</p>
      </div>
      <div>
        <p class="text-ink/50">Telepon</p>
        <p class="font-medium text-ink">{{ $order->customer->phone
          ↳ }}</p>
      </div>
    </div>
  </div>

  <div class="bg-white rounded-2xl shadow-sm border border-ink/5
    ↳ overflow-hidden mb-6">
    <table class="w-full text-sm">
      <thead>
        <tr class="bg-cloud text-ink/60 text-left">
          <th class="px-6 py-4 font-semibold">Jasa</th>
          <th class="px-6 py-4 font-semibold">Qty (kg)</th>
          <th class="px-6 py-4 font-semibold">Subtotal</th>
        </tr>
      </thead>
      <tbody class="divide-y divide-ink/5">
        @foreach ($order->details as $detail)
          <tr>
            <td class="px-6 py-4 font-medium text-ink">{{
              ↳ $detail->service->service_name }}</td>
            <td class="px-6 py-4 text-ink/70">{{ $detail->qty }}</td>
            <td class="px-6 py-4 font-mono font-semibold
              ↳ text-teal">Rp {{ number_format($detail->subtotal,
              ↳ 0, ',', '.') }}</td>
          </tr>
        @endforeach
      </tbody>
    </table>
  </div>

  <div class="ticket-edge bg-gradient-to-r from-suds to-teal rounded-2xl p-6
    ↳ pb-8 mb-6 text-white flex items-center justify-between max-w-sm
    ↳ shadow-lg shadow-suds/20">

```

```

<span class="font-medium">Total Bayar</span>
<span class="font-mono text-2xl font-bold">Rp {{
  ↳ number_format($order->total, 0, ',', '.') }}</span>
</div>

<div class="bg-white rounded-2xl shadow-sm border border-ink/5 p-6
  ↳ max-w-xl">
  <form method="POST" action="{ route('operator.pickup.store',
    ↳ $order->id) }}"
    ↳ onsubmit="return confirm('Konfirmasi: pakaian sudah diambil
  ↳ customer?');" class="space-y-4">
    @csrf

    <div>
      <label class="block text-sm font-medium text-ink mb-1">Catatan
        ↳ Pengambilan (opsional)</label>
      <textarea name="notes" rows="3"
        ↳ class="w-full rounded-xl border border-ink/15 px-4 py-2.5
        ↳ text-ink focus:outline-none focus:ring-2 focus:ring-suds focus:border-suds
        ↳ transition"
        ↳ placeholder="Contoh: diambil oleh keluarga
        ↳ customer"></textarea>
    </div>

    <button type="submit"
      ↳ class="inline-flex items-center gap-2 bg-gradient-to-r
      ↳ from-teal to-suds text-white font-semibold px-6 py-2.5 rounded-xl
      ↳ shadow-lg shadow-teal/20 hover:opacity-90 transition">
      ↳ Konfirmasi Pakaian Sudah Diambil
    </button>
  </form>
</div>

</x-layout-app>

```

8.4 Routing Pengambilan

```

use App\Http\Controllers\Operator\TransLaundryPickupController;

Route::middleware(['role:Operator', 'prevent-back-history'])->prefix('
  ↳ operator')->name('operator.')->group(function ()
  ↳ {
    Route::get('/dashboard', [OperatorDashboard::class,
      ↳ 'index'])->name('dashboard');

    Route::resource('order', TransOrderController::class)->only(['index',
      ↳ 'create', 'store', 'show']);

    Route::get('/pickup', [TransLaundryPickupController::class,
      ↳ 'index'])->name('pickup.index');
    Route::get('/pickup/{order}/create', [TransLaundryPickupController::class,
      ↳ 'create'])->name('pickup.create');
  }
);

```

```
Route::post('/pickup/{order}/store', [TransLaundryPickupController::class,  
    ↪ 'store'])->name('pickup.store');  
});
```

Bab 9 — Laporan Penjualan (Pimpinan)

Modul read-only untuk melihat ringkasan omzet dan riwayat seluruh transaksi, dengan filter rentang tanggal.

9.1 Controller LaporanController

php artisan make:controller Pimpinan/LaporanController

```
<?php

namespace App\Http\Controllers\Pimpinan;

use App\Http\Controllers\Controller;
use App\Models\TransOrder;
use Illuminate\Http\Request;

class LaporanController extends Controller
{
    public function index(Request $request)
    {
        $query = TransOrder::with('customer');

        if ($request->filled('start_date') && $request->filled('end_date')) {
            $query->whereBetween('order_date', [$request->start_date,
                ↪ $request->end_date]);
        }

        $orders = $query->latest()->paginate(10)->withQueryString();

        $totalOmzet      = (clone $query)->sum('total');
        $totalBaru       = (clone $query)->where('order_status', 0)->count();
        $totalSudahDiambil = (clone $query)->where('order_status', 1)->count();

        return view('pimpinan.laporan.index', compact(
            'orders', 'totalOmzet', 'totalBaru', 'totalSudahDiambil'
        ));
    }

    public function show(TransOrder $order)
```

```

{
    $order->load('customer', 'details.service');
    return view('pimpinan.laporan.show', compact('order'));
}

```

9.2 View Daftar Laporan

resources/views/pimpinan/laporan/index.blade.php:

```

<x-layout-app :title="'Laporan Penjualan'">

    <div class="mb-6">
        <h2 class="font-display text-2xl font-bold text-ink">Laporan
        ↪ Penjualan</h2>
        <p class="text-ink/50 text-sm mt-1">Ringkasan dan detail seluruh
        ↪ transaksi laundry.</p>
    </div>

    <div class="bg-white rounded-2xl shadow-sm border border-ink/5 p-5 mb-6">
        <form method="GET" action="{{ route('pimpinan.laporan.index') }}"
        ↪ class="flex flex-wrap items-end gap-4">
            <div>
                <label class="block text-xs font-medium text-ink/60 mb-1">Dari
                ↪ Tanggal</label>
                <input type="date" name="start_date" value="{{
                ↪ request('start_date') }}"
                class="rounded-xl border border-ink/15 px-4 py-2 text-sm
        ↪ text-ink focus:outline-none focus:ring-2 focus:ring-suds focus:border-suds
        ↪ transition">
            </div>
            <div>
                <label class="block text-xs font-medium text-ink/60
                ↪ mb-1">Sampai Tanggal</label>
                <input type="date" name="end_date" value="{{
                ↪ request('end_date') }}"
                class="rounded-xl border border-ink/15 px-4 py-2 text-sm
        ↪ text-ink focus:outline-none focus:ring-2 focus:ring-suds focus:border-suds
        ↪ transition">
            </div>
            <button type="submit"
                class="bg-gradient-to-r from-suds to-teal text-white
        ↪ font-semibold px-5 py-2 rounded-xl shadow-lg shadow-suds/20
        ↪ hover:opacity-90 transition text-sm">
                Filter
            </button>
            <a href="{{ route('pimpinan.laporan.index') }}" class="text-ink/50
            ↪ hover:text-ink text-sm font-medium transition">Reset</a>
        </form>
    </div>

    <div class="grid grid-cols-1 sm:grid-cols-3 gap-6 mb-6">

```



```

<div class="ticket-edge bg-gradient-to-br from-teal to-teal/80
  ↳ rounded-2xl p-6 pb-8 text-white shadow-lg shadow-teal/20">
  <p class="text-white/70 text-sm font-medium">Total Omzet</p>
  <p class="font-mono text-2xl font-bold mt-2">Rp {{
    ↳ number_format($totalOmzet, 0, ',', '.') }}</p>
</div>
<div class="ticket-edge bg-gradient-to-br from-sunbeam to-sunbeam/80
  ↳ rounded-2xl p-6 pb-8 text-ink shadow-lg shadow-sunbeam/20">
  <p class="text-ink/60 text-sm font-medium">Transaksi Baru</p>
  <p class="font-mono text-4xl font-bold mt-2">{{ $totalBaru }}</p>
</div>
<div class="ticket-edge bg-gradient-to-br from-suds to-suds/80
  ↳ rounded-2xl p-6 pb-8 text-white shadow-lg shadow-suds/20">
  <p class="text-white/70 text-sm font-medium">Sudah Diambil</p>
  <p class="font-mono text-4xl font-bold mt-2">{{ $totalSudahDiambil
    ↳ }}</p>
</div>
</div>

<div class="bg-white rounded-2xl shadow-sm border border-ink/5
  ↳ overflow-hidden">
  <table class="w-full text-sm">
    <thead>
      <tr class="bg-cloud text-ink/60 text-left">
        <th class="px-6 py-4 font-semibold">No</th>
        <th class="px-6 py-4 font-semibold">Kode Order</th>
        <th class="px-6 py-4 font-semibold">Customer</th>
        <th class="px-6 py-4 font-semibold">Tanggal</th>
        <th class="px-6 py-4 font-semibold">Total</th>
        <th class="px-6 py-4 font-semibold">Status</th>
        <th class="px-6 py-4 font-semibold text-right">Aksi</th>
      </tr>
    </thead>
    <tbody class="divide-y divide-ink/5">
      @forelse ($orders as $order)
        <tr class="hover:bg-cloud/60 transition">
          <td class="px-6 py-4 text-ink/50">{{ $loop->iteration
            ↳ }}</td>
          <td class="px-6 py-4 font-mono text-ink font-medium">{{
            ↳ $order->order_code }}</td>
          <td class="px-6 py-4 text-ink">{{
            ↳ $order->customer->customer_name }}</td>
          <td class="px-6 py-4 text-ink/70">{{
            ↳ \Carbon\Carbon::parse($order->order_date) -
            ↳ >translatedFormat('d M Y')
            ↳ }}</td>
          <td class="px-6 py-4 font-mono font-semibold
            ↳ text-teal">Rp {{ number_format($order->total, 0,
            ↳ ',', '.') }}</td>
          <td class="px-6 py-4">
            @if ($order->order_status == 0)
              <span class="px-3 py-1 rounded-full text-xs
                ↳ font-semibold bg-sunbeam/20
                ↳ text-[#8A6300]">Baru</span>

```

```

        @else
            <span class="px-3 py-1 rounded-full text-xs
                ↳ font-semibold bg-teal/10 text-teal">Sudah
                ↳ Diambil</span>
        @endif
    </td>
    <td class="px-6 py-4 text-right">
        <a href="{ route('pimpinan.laporan.show',
            ↳ $order->id) }}"
            class="px-3 py-1.5 rounded-lg bg-suds/10 text-suds
                ↳ text-xs font-semibold hover:bg-suds hover:text-white transition">
                Detail
        </a>
    </td>
</tr>
@empty
<tr>
    <td colspan="7" class="px-6 py-12 text-center
        ↳ text-ink/40">
        Tidak ada data transaksi pada rentang tanggal ini.
    </td>
</tr>
@endforelse
</tbody>
</table>
</div>

<div class="mt-6">
    {{ $orders->links() }}
</div>
</x-layout-app>

```

9.3 View Detail Laporan

resources/views/pimpinan/laporan/show.blade.php mengikuti struktur yang sama seperti detail transaksi pada modul Operator (Bab 7.4), dengan tambahan informasi alamat customer dan tanggal selesai.

9.4 Routing Laporan

```

use App\Http\Controllers\Pimpinan\LaporanController;

Route::middleware(['role:Pimpinan', 'prevent-back-history'])->prefix('
    ↳ pimpinan')->name('pimpinan.')->group(function ()
    ↳ {
        Route::get('/dashboard', [PimpinanDashboard::class,
            ↳ 'index'])->name('dashboard');

        Route::get('/laporan', [LaporanController::class,
            ↳ 'index'])->name('laporan.index');
    }

```

```
Route::get('/laporan/{order}', [LaporanController::class,  
    ↪ 'show'])->name('laporan.show');  
});
```

Bab 10 — Styling UI dengan Tailwind CSS v4

10.1 Instalasi Tailwind CSS v4 via Vite

```
npm install tailwindcss @tailwindcss/vite
```

vite.config.js:

```
import { defineConfig } from 'vite';
import laravel from 'laravel-vite-plugin';
import tailwindcss from '@tailwindcss/vite';

export default defineConfig({
  plugins: [
    laravel({
      input: ['resources/css/app.css', 'resources/js/app.js'],
      refresh: true,
    }),
    tailwindcss(),
  ],
});
```

10.2 Design Token — resources/css/app.css

```
@import "tailwindcss";

@theme {
  --color-ink: #10192E;
  --color-suds: #2D8CFF;
  --color-teal: #17B8A6;
  --color-bubblegum: #FF5D8F;
  --color-sunbeam: #FFC94A;
  --color-cloud: #F4F8FC;

  --font-display: "Baloo 2", sans-serif;
  --font-sans: "Plus Jakarta Sans", sans-serif;
  --font-mono: "IBM Plex Mono", monospace;
}
```

```

/* Signature element: efek sobekan tiket laundry di tepi bawah kartu statistik
↪ */
.ticket-edge {
  position: relative;
}
.ticket-edge::after {
  content: "";
  position: absolute;
  left: 0;
  right: 0;
  bottom: -1px;
  height: 10px;
  background-image: radial-gradient(circle 5px, var(--color-cloud) 5px,
↪ transparent 6px);
  background-size: 20px 20px;
  background-position: 0 0;
  background-repeat: repeat-x;
}

@keyframes float {
  0%, 100% { transform: translateY(0); }
  50% { transform: translateY(-20px); }
}
.animate-float {
  animation: float 6s ease-in-out infinite;
}

```

10.3 Layout Guest — resources/views/components/layout-guest.blade.php

```

<!DOCTYPE html>
<html lang="id">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>{{ $title ?? 'Sistem Informasi Laundry' }}</title>

  <link rel="preconnect" href="https://fonts.googleapis.com">
  <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
  <link href=
↪ "https://fonts.googleapis.com/css2?family=Baloo+2:wght@500;600;700;800
↪ &family=Plus+Jakarta+Sans:wght@400;500;600;700&
↪ family=IBM+Plex+Mono:wght@400;500&display=swap"
↪ rel="stylesheet">

  @vite(['resources/css/app.css', 'resources/js/app.js'])
</head>
<body class="font-sans antialiased">
  {{ $slot }}
</body>
</html>

```

10.4 Halaman Login (dengan Realtime Clock)

resources/views/auth/login.blade.php:

```
<x-layout-guest :title="'Login - Sistem Informasi Laundry'">

    <div class="min-h-screen relative overflow-hidden bg-gradient-to-br
        ↳ from-suds via-teal to-bubblegum flex items-center justify-center p-6">

        <div class="absolute -top-10 -left-10 w-40 h-40 rounded-full
            ↳ bg-white/20 animate-float"></div>
        <div class="absolute top-1/3 right-10 w-24 h-24 rounded-full
            ↳ bg-white/10 animate-float" style="animation-delay: 1.5s;"></div>
        <div class="absolute bottom-10 left-1/4 w-32 h-32 rounded-full
            ↳ bg-white/15 animate-float" style="animation-delay: 3s;"></div>

        <div class="relative z-10 w-full max-w-md">

            <div class="text-center mb-6">
                <div class="inline-flex items-center justify-center w-16 h-16
                    ↳ rounded-2xl bg-white/20 backdrop-blur-sm mb-3"></div>
                <h1 class="font-display text-3xl font-bold text-white">Fresh
                    ↳ Laundry</h1>
                <p class="text-white/80 text-sm mt-1">Sistem Informasi
                    ↳ Laundry</p>
            </div>

            <div class="bg-white/95 backdrop-blur rounded-3xl shadow-2xl p-8">

                <div class="text-center mb-6 pb-6 border-b border-dashed
                    ↳ border-ink/10">
                    <p id="live-clock" class="font-mono text-3xl font-semibold
                        ↳ text-ink tracking-wide">---:---:---</p>
                    <p id="live-date" class="text-sm text-ink/60 mt-1">Memuat
                        ↳ tanggal...</p>
                </div>

                <h2 class="font-display text-xl font-semibold text-ink
                    ↳ mb-4">Masuk ke akun kamu</h2>

                @if ($errors->any())
                    <div class="mb-4 rounded-xl bg-bubblegum/10 border
                        ↳ border-bubblegum/30 text-bubblegum text-sm px-4 py-3">
                        {{ $errors->first() }}
                    </div>
                @endif

                <form method="POST" action="{{ route('login.submit') }}"
                    ↳ class="space-y-4">
                    @csrf
```

```

        <div>
            <label class="block text-sm font-medium text-ink
                ↳ mb-1">Email</label>
            <input type="email" name="email" value="{{ old('email')
                ↳ }}" required
                    class="w-full rounded-xl border border-ink/15 px-4
↳ py-3 text-ink focus:outline-none focus:ring-2 focus:ring-suds
↳ focus:border-suds transition"
                    placeholder="nama@laundry.com">
        </div>

        <div>
            <label class="block text-sm font-medium text-ink
                ↳ mb-1">Password</label>
            <input type="password" name="password" required
                    class="w-full rounded-xl border border-ink/15 px-4
↳ py-3 text-ink focus:outline-none focus:ring-2 focus:ring-suds
↳ focus:border-suds transition"
                    placeholder="*****">
        </div>

        <button type="submit"
            class="w-full rounded-xl bg-gradient-to-r from-suds
↳ to-teal text-white font-semibold py-3 hover:opacity-90 active:scale-[0.98]
↳ transition">
            Masuk
        </button>
    </form>
</div>
</div>
</div>

<script>
    // Update jam & tanggal secara realtime setiap detik, format Indonesia
    function updateClock() {
        const now = new Date();
        const time = now.toLocaleTimeString('id-ID', { hour: '2-digit',
            ↳ minute: '2-digit', second: '2-digit' });
        const date = now.toLocaleDateString('id-ID', { weekday: 'long',
            ↳ day: 'numeric', month: 'long', year: 'numeric' });

        document.getElementById('live-clock').textContent = time;
        document.getElementById('live-date').textContent = date;
    }

    updateClock();
    setInterval(updateClock, 1000);
</script>
</x-layout-guest>

```

10.5 Layout App — resources/views/components/layout-app.blade.php

```
<!DOCTYPE html>
<html lang="id">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>{{ $title ?? 'Sistem Informasi Laundry' }}</title>

  <link rel="preconnect" href="https://fonts.googleapis.com">
  <link rel="preconnect" href="https://fonts.gstatic.com" crossorigin>
  <link href=
    ↪ "https://fonts.googleapis.com/css2?family=Baloo+2:wght@500;600;700;800
    ↪ &family=Plus+Jakarta+Sans:wght@400;500;600;700&
    ↪ family=IBM+Plex+Mono:wght@400;500&display=swap"
    ↪ rel="stylesheet">

  @vite(['resources/css/app.css', 'resources/js/app.js'])
</head>
<body class="font-sans antialiased bg-cloud text-ink">

  <div class="flex min-h-screen">

    @include('layouts.partials.sidebar')

    <div class="flex-1 flex flex-col min-w-0">

      @include('layouts.partials.topbar')

      <main class="flex-1 p-6 md:p-8">
        @if (session('success'))
          <div class="mb-6 rounded-xl bg-teal/10 border border-teal/30
            ↪ text-teal px-4 py-3 text-sm font-medium">
              {{ session('success') }}
            </div>
        @endif
        @if (session('error'))
          <div class="mb-6 rounded-xl bg-bubblegum/10 border
            ↪ border-bubblegum/30 text-bubblegum px-4 py-3 text-sm
            ↪ font-medium">
              {{ session('error') }}
            </div>
        @endif

        {{ $slot }}
      </main>
    </div>
  </div>
</body>
</html>
```


10.6 Sidebar — resources/views/layouts/partials/sidebar.blade.php

```
@php
    $level = auth()->user()->level->level_name;
@endphp

<aside class="w-64 shrink-0 bg-gradient-to-b from-ink to-[#1B2A4A] text-white
    ↪ flex flex-col">

    <div class="px-6 py-6 flex items-center gap-3 border-b border-white/10">
        <div class="w-10 h-10 rounded-xl bg-gradient-to-br from-suds to-teal
            ↪ flex items-center justify-center text-lg"></div>
        <div>
            <p class="font-display font-bold text-lg leading-tight">Fresh
                ↪ Laundry</p>
            <p class="text-xs text-white/50">{{ $level }} Panel</p>
        </div>
    </div>

    <nav class="flex-1 px-4 py-6 space-y-1">

        @if ($level === 'Administrator')
            <a href="{{ route('admin.dashboard') }}"
                class="flex items-center gap-3 px-4 py-3 rounded-xl transition
            ↪ {{ request()->routeIs('admin.dashboard') ? 'bg-suds text-white shadow-lg
            ↪ shadow-suds/30' : 'text-white/70 hover:bg-white/10 hover:text-white' }}">
                <span class="font-medium text-sm">Dashboard</span>
            </a>
            <a href="{{ route('admin.customer.index') }}"
                class="flex items-center gap-3 px-4 py-3 rounded-xl transition
            ↪ {{ request()->routeIs('admin.customer.*') ? 'bg-suds text-white shadow-lg
            ↪ shadow-suds/30' : 'text-white/70 hover:bg-white/10 hover:text-white' }}">
                <span class="font-medium text-sm">Customer</span>
            </a>
            <a href="{{ route('admin.user.index') }}"
                class="flex items-center gap-3 px-4 py-3 rounded-xl transition
            ↪ {{ request()->routeIs('admin.user.*') ? 'bg-suds text-white shadow-lg
            ↪ shadow-suds/30' : 'text-white/70 hover:bg-white/10 hover:text-white' }}">
                <span class="font-medium text-sm">User</span>
            </a>
            <a href="{{ route('admin.service.index') }}"
                class="flex items-center gap-3 px-4 py-3 rounded-xl transition
            ↪ {{ request()->routeIs('admin.service.*') ? 'bg-suds text-white shadow-lg
            ↪ shadow-suds/30' : 'text-white/70 hover:bg-white/10 hover:text-white' }}">
                <span class="font-medium text-sm">Jenis Service</span>
            </a>
        @endif

        @if ($level === 'Operator')
            <a href="{{ route('operator.dashboard') }}"
                class="flex items-center gap-3 px-4 py-3 rounded-xl transition {{
            ↪ request()->routeIs('operator.dashboard') ? 'bg-suds text-white shadow-lg
            ↪ shadow-suds/30' : 'text-white/70 hover:bg-white/10 hover:text-white' }}">
```

```

        <span class="font-medium text-sm">Dashboard</span>
    </a>
    <a href="{{ route('operator.order.index') }}"
        class="flex items-center gap-3 px-4 py-3 rounded-xl transition
    ↪ {{ request()->routeIs('operator.order.*') ? 'bg-suds text-white shadow-lg
    ↪ shadow-suds/30' : 'text-white/70 hover:bg-white/10 hover:text-white' }}">
        <span class="font-medium text-sm">Transaksi Laundry</span>
    </a>
    <a href="{{ route('operator.pickup.index') }}"
        class="flex items-center gap-3 px-4 py-3 rounded-xl transition
    ↪ {{ request()->routeIs('operator.pickup.*') ? 'bg-suds text-white shadow-lg
    ↪ shadow-suds/30' : 'text-white/70 hover:bg-white/10 hover:text-white' }}">
        <span class="font-medium text-sm">Pengambilan Laundry</span>
    </a>
@endif

@if ($level === 'Pimpinan')
    <a href="{{ route('pimpinan.dashboard') }}"
        class="flex items-center gap-3 px-4 py-3 rounded-xl transition {{
    ↪ request()->routeIs('pimpinan.dashboard') ? 'bg-suds text-white shadow-lg
    ↪ shadow-suds/30' : 'text-white/70 hover:bg-white/10 hover:text-white' }}">
        <span class="font-medium text-sm">Dashboard</span>
    </a>
    <a href="{{ route('pimpinan.laporan.index') }}"
        class="flex items-center gap-3 px-4 py-3 rounded-xl transition {{
    ↪ request()->routeIs('pimpinan.laporan.*') ? 'bg-suds text-white shadow-lg
    ↪ shadow-suds/30' : 'text-white/70 hover:bg-white/10 hover:text-white' }}">
        <span class="font-medium text-sm">Laporan Penjualan</span>
    </a>
@endif
</nav>

<div class="px-4 py-6 border-t border-white/10">
    <form method="POST" action="{{ route('logout') }}">
        @csrf
        <button type="submit" class="w-full flex items-center gap-3 px-4
    ↪ py-3 rounded-xl text-white/70 hover:bg-bubblegum/20
    ↪ hover:text-bubblegum transition text-sm font-medium">
            Logout
        </button>
    </form>
</div>
</aside>

```

10.7 Topbar — resources/views/layouts/partials/topbar.blade.php

```

<header class="bg-white border-b border-ink/5 px-6 md:px-8 py-4 flex
    ↪ items-center justify-between">

    <div>
        <h1 class="font-display text-xl font-semibold text-ink">{{ $title ??
    ↪ 'Dashboard' }}</h1>
    
```

```

        <p id="topbar-clock" class="text-xs text-ink/50 font-mono
        ↪ mt-0.5">Memuat waktu...</p>
    </div>

    <div class="flex items-center gap-3">
        <div class="relative">
            <div class="w-10 h-10 rounded-full bg-gradient-to-br from-bubblegum
            ↪ to-sunbeam flex items-center justify-center text-white
            ↪ font-semibold text-sm">
                {{ strtoupper(substr(auth()->user()->name, 0, 1)) }}
            </div>
            <span class="absolute bottom-0 right-0 w-3 h-3 bg-teal rounded-full
            ↪ ring-2 ring-white"></span>
        </div>
        <div class="hidden sm:block">
            <p class="text-sm font-semibold text-ink leading-tight">{{
            ↪ auth()->user()->name }}</p>
            <p class="text-xs text-ink/50">{{ auth()->user()->level->level_name
            ↪ }}</p>
        </div>
    </div>
</header>

<script>
    function updateTopbarClock() {
        const now = new Date();
        const formatted = now.toLocaleDateString('id-ID', {
            weekday: 'long', day: 'numeric', month: 'long', year: 'numeric'
        }) + ' - ' + now.toLocaleTimeString('id-ID');

        const el = document.getElementById('topbar-clock');
        if (el) el.textContent = formatted;
    }

    updateTopbarClock();
    setInterval(updateTopbarClock, 1000);
</script>

```

10.8 Dashboard 3 Role

resources/views/admin/dashboard.blade.php:

```

<x-layout-app :title="'Dashboard Administrator'">

    <div class="mb-8">
        <h2 class="font-display text-2xl font-bold text-ink">Halo, {{
        ↪ auth()->user()->name }}</h2>
        <p class="text-ink/50 text-sm mt-1">Berikut ringkasan master data
        ↪ laundry kamu hari ini.</p>
    </div>

    <div class="grid grid-cols-1 sm:grid-cols-3 gap-6 mb-8">

```

```

<div class="ticket-edge bg-gradient-to-br from-suds to-suds/80
  ↳ rounded-2xl p-6 pb-8 text-white shadow-lg shadow-suds/20">
  <p class="text-white/70 text-sm font-medium">Total Customer</p>
  <p class="font-mono text-4xl font-bold mt-2">{{ $totalCustomer
    ↳ }}</p>
  <p class="text-white/60 text-xs mt-1">pelanggan terdaftar</p>
</div>

<div class="ticket-edge bg-gradient-to-br from-teal to-teal/80
  ↳ rounded-2xl p-6 pb-8 text-white shadow-lg shadow-teal/20">
  <p class="text-white/70 text-sm font-medium">Total User</p>
  <p class="font-mono text-4xl font-bold mt-2">{{ $totalUser }}</p>
  <p class="text-white/60 text-xs mt-1">akun aktif (semua level)</p>
</div>

<div class="ticket-edge bg-gradient-to-br from-bubblegum
  ↳ to-bubblegum/80 rounded-2xl p-6 pb-8 text-white shadow-lg
  ↳ shadow-bubblegum/20">
  <p class="text-white/70 text-sm font-medium">Jenis Service</p>
  <p class="font-mono text-4xl font-bold mt-2">{{ $totalService }}</p>
  <p class="text-white/60 text-xs mt-1">jasa laundry tersedia</p>
</div>
</div>

<div class="bg-white rounded-2xl p-6 shadow-sm border border-ink/5">
  <h3 class="font-display font-semibold text-ink mb-4">Master Data</h3>
  <div class="grid grid-cols-1 sm:grid-cols-3 gap-4">

    <a href="{{ route('admin.customer.index') }}" class="group flex
      ↳ items-center gap-4 p-4 rounded-xl border border-ink/10
      ↳ hover:border-suds hover:bg-suds/5 transition">
      <div class="w-11 h-11 rounded-xl bg-suds/10 flex items-center
        ↳ justify-center text-xl group-hover:bg-suds
        ↳ group-hover:text-white transition"></div>
      <div>
        <p class="font-semibold text-ink text-sm">Customer</p>
        <p class="text-xs text-ink/50">Kelola data pelanggan</p>
      </div>
    </a>

    <a href="{{ route('admin.user.index') }}" class="group flex
      ↳ items-center gap-4 p-4 rounded-xl border border-ink/10
      ↳ hover:border-teal hover:bg-teal/5 transition">
      <div class="w-11 h-11 rounded-xl bg-teal/10 flex items-center
        ↳ justify-center text-xl group-hover:bg-teal
        ↳ group-hover:text-white transition"></div>
      <div>
        <p class="font-semibold text-ink text-sm">User</p>
        <p class="text-xs text-ink/50">Kelola akun operator</p>
      </div>
    </a>
  </div>

```

```

<a href="{{ route('admin.service.index') }}" class="group flex
↳ items-center gap-4 p-4 rounded-xl border border-ink/10
↳ hover:border-bubblegum hover:bg-bubblegum/5 transition">
  <div class="w-11 h-11 rounded-xl bg-bubblegum/10 flex
  ↳ items-center justify-center text-xl
  ↳ group-hover:bg-bubblegum group-hover:text-white
  ↳ transition"></div>
  <div>
    <p class="font-semibold text-ink text-sm">Jenis Service</p>
    <p class="text-xs text-ink/50">Kelola jasa & harga</p>
  </div>
</a>
</div>
</div>
</x-layout-app>

```

Dashboard Operator dan Pimpinan mengikuti struktur kartu statistik yang sama (grid 3 kolom dengan ticket-edge), menampilkan data ringkasan sesuai controller masing-masing yang telah dijelaskan pada Bab 5.5.

Bab 11 — Testing & Checklist Akhir

11.1 Perintah Build & Jalankan Server

```
php artisan migrate:fresh --seed
npm run build
php artisan view:clear
php artisan config:clear
php artisan serve
```

11.2 Checklist Fungsional

- ☐ Login berhasil untuk ketiga role dan diarahkan ke dashboard masing-masing
- ☐ Akses silang antar role menghasilkan 403 Forbidden
- ☐ CRUD Customer (tambah, edit, hapus) berjalan
- ☐ CRUD Jenis Service berjalan, harga tampil format rupiah
- ☐ CRUD User berjalan, badge level tampil sesuai
- ☐ Transaksi laundry: subtotal & total terhitung otomatis, mendukung banyak jasa dalam satu order
- ☐ Kalkulasi live di form transaksi berjalan sebelum submit
- ☐ Proses pengambilan mengubah status order dari 0 ke 1
- ☐ Laporan penjualan menampilkan data akurat dan filter tanggal berfungsi
- ☐ Logout lalu menekan tombol back browser tidak menampilkan halaman lama

11.3 Akun Default

Role	Email	Password
Administrator	admin@laundry.com	password
Operator	operator@laundry.com	password
Pimpinan	pimpinan@laundry.com	password

11.4 Penutup

Seluruh modul dalam buku ini disusun mengikuti ERD dan alur bisnis yang telah ditentukan tanpa perubahan struktur database. Urutan pengerjaan — setup, migration, model, seeder,

autentikasi, master data, transaksi, pengambilan, laporan, hingga styling — dirancang agar setiap tahap dapat diuji secara bertahap sebelum melangkah ke tahap berikutnya, sesuai kebutuhan pengerjaan Ujikom dalam batas waktu 8 jam.

Selamat mengerjakan Ujikom Junior Web Programming.