

ECS TASK

1. Setup a highly available ecs cluster with load balancer and dynamic port mapping.

NOTE:

Your cluster should maintain atleast 6 tasks at any point of time and should be highly availble across multiple AZ's.

Use the below image from deployment:

sabair0509/hiring-app:works

Create a role:

The image shows two screenshots of the AWS IAM console during the 'Create role' process.

First Screenshot: Select trusted entity

- Step 1: Select trusted entity (selected)
- Step 2: Add permissions
- Step 3: Name, review, and create

Select trusted entity Info

Trusted entity type

- ☒ **AWS service**
Allow AWS services like EC2, Lambda, or others to perform actions in this account.
- ☐ **AWS account**
Allow entities in other AWS accounts belonging to you or a 3rd party to perform actions in this account.
- ☐ **Web identity**
Allows users federated by the specified external web identity provider to assume this role to perform actions in this account.
- ☐ **SAML 2.0 federation**
Allow users federated with SAML 2.0 from a corporate directory to perform actions in this account.
- ☐ **Custom trust policy**
Create a custom trust policy to enable others to perform actions in this account.

Use case
Allow an AWS service like EC2, Lambda, or others to perform actions in this account.

Service or use case
EC2

Choose a use case for the specified service.
Use case
☒ **EC2**
Allow EC2 instances to call AWS services on your behalf.

Second Screenshot: Add permissions

Step 1: Select trusted entity

Step 2: Add permissions (selected)

Step 3: Name, review, and create

Add permissions Info

Permissions policies (1/1158) Info

Choose one or more policies to attach to your new role.

Search: containerserv X Filter by Type: All types 4 matches

Policy name	Type	Description
☐ AmazonEC2ContainerServiceAutoscaleRole	AWS managed	Policy to enable Task Autoscaling for Am...
☐ AmazonEC2ContainerServiceEventsRole	AWS managed	Policy to enable CloudWatch Events for E...
☒ AmazonEC2ContainerServiceforEC2Role	AWS managed	Default policy for the Amazon EC2 Role f...
☐ AmazonEC2ContainerServiceRole	AWS managed	Default policy for Amazon ECS service role.

► Set permissions boundary - optional

Cancel Previous Next

IAM > Roles > Create role

Step 3
Name, review, and create

Role details

Role name
Enter a meaningful name to identify this role.

Maximum 64 characters. Use alphanumeric and '+', '@', '-' characters.

Description
Add a short explanation for this role.

Maximum 1000 characters. Use letters (A-Z and a-z), numbers (0-9), tabs, new lines, or any of the following characters: '_', '@', '/', '[]', '!', '\$', '%', '^', '&', '~', '., @-/\[\]\!\\$\%^&~'.

Step 1: Select trusted entities [Edit](#)

Trust policy

```
1 - {  
2   "Version": "2012-10-17",  
3   "Statement": [  
4     {  
5       "Effect": "Allow",  
6       "Action": [  
7         "sts:AssumeRole"  
8       ],  
9       "Principal": {  
10        "Service": [  
11          "ec2.amazonaws.com"  
12        ]  
13      }  
14    ]  
15  }
```

AWS Console → ECS → Clusters → Create Cluster

Select:

👉 Cluster template: “EC2 Linux + Networking”

Configure:

- **Cluster name:** hiring-app-cluster
- **EC2 instance type:** c7 large (recommended)
- **Number of instances:** 2 (important for HA)
- **Key pair:** optional (for SSH)
- **VPC:** choose default or your VPC
- **Subnets:** select at least 2–3 AZ subnets

Enable:

✓ Auto Scaling Group (recommended)

👉 Click **Create**

aws

Search

[Alt+S]

Asia Pacific (Mumbai)

Bradhar (922345236105)

Bradhar

Amazon Elastic Container Service

Create cluster

Amazon Elastic Container Service

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Documentation

Discover products

Subscriptions

Create cluster

An Amazon ECS cluster groups together tasks and services, and allows for shared capacity and common configurations. All of your tasks, services and capacity must belong to a cluster.

Cluster configuration

Cluster name

hiring-app-cluster

Cluster name must be 1 to 255 characters. Valid characters are a-z, A-Z, 0-9, hyphens (-), and underscores (_).

Service Connect defaults – optional

Infrastructure - advanced

Configure the manner of obtaining compute resources that will be used to host your application.

Select a method of obtaining compute capacity

Your cluster is automatically configured for AWS Fargate (serverless), but you may choose to add Amazon EC2 instances (servers).

Fargate only

Serverless – you don't think about creating or managing servers. Great for most common workloads.

Fargate and managed instances

Managed instances - Amazon ECS will manage patching and scaling on your behalf while giving you configurability about the types of instances. Great for more advanced workloads.

Fargate and Self-managed instances

Self-managed instances - you must ensure the instances are patched and scaled properly, and you have full control over the instances.

On-demand

With on-demand instances, you pay for compute capacity by the hour, with no long-term commitments or upfront payments.

Spot

Amazon EC2 Spot instances let you take advantage of unused EC2 capacity in the AWS cloud. [Find out more](#)

Container instance Amazon Machine Image (AMI)

Choose the Amazon ECS-optimised AMI for your instance.

Amazon Linux 2023

EC2 instance type

Choose based on the workloads you plan to run on this cluster.

c7i-flex.large

x86_64

2 vCPU 4 GiB memory

EC2 instance role

An instance role is used by Amazon EC2 instances to make AWS API requests. If you don't already have an instance IAM role created, we can create one for you.

ecsInstanceRole

arn:aws:iam::922345236105:instance-profile/ecsInstanceRole

Create new instance profile

Desired capacity

Specify the number of instances to launch in your cluster.

Minimum

2

Maximum

6

SSH Key pair

If you do not specify a key pair, you can't connect to the instances via SSH unless you choose an AMI that is configured to allow users another way to log in.

mumbai

Create a new key pair

Amazon Elastic Container Service

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Documentation

Discover products

Subscriptions

Create cluster

VPC

Select a VPC to use for your Amazon ECS resources.

vpc-0a8ab810f0b1433db

default

Create a new VPC

Subnets

Select the subnets where your instances are launched and your tasks run. We recommend that you use three subnets for production.

Choose subnets

Clear current selection

subnet-00e4b2cd9dda9856d

ap-south-1b 172.31.0.0/20

subnet-01114db269c57e367

ap-south-1a 172.31.32.0/20

subnet-0e0e38026022ee763

ap-south-1c 172.31.16.0/20

Security group

Info

Choose an existing security group or create a new security group.

Use an existing security group

Create a new security group

Security group name

Choose an existing security group.

Choose security groups

sg-0a62f2666a2413423

default

Auto-assign public IP

Info

Choose whether to auto-assign a public IP to the Amazon EC2 instances

Turn on

Amazon Elastic Container Service

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Clusters

Cluster hiring-app-cluster has been created successfully.

View cluster

Clusters (1)

Info

Search clusters

By default, we only load up to 1,000 clusters at a time.

Cluster

Services

Tasks

Container instances

CloudWatch monitoring

Capacity provider

hiring-app-cluster

0

No tasks running

2 EC2

Default

ASG

AWS

Search

[Alt+S] Ask Amazon Q

Asia Pacific (Mumbai)

Bradhar (922345236105)

Bradhar

EC2 > Instances

EC2

Dashboard

AWS Global View

Events

Instances

Instances

Instance Types

Launch Templates

Spot Requests

Savings Plans

Reserved Instances

Dedicated Hosts

Capacity Reservations

Capacity Manager

Images

AMI

Instances (2)

Last updated less than a minute ago

Connect

Instance state

Actions

Launch instances

Saved filter sets

Running

Find Instance by attribute or tag (case-sensitive)

Instance state = running

Clear filters

	Name	Instance ID	Instance state	Instance type	Status check	Availability Zone	Public IPv4 DNS	F
☐	ECS Instance - ...	i-0d2fb64a55d7cc589	Running	c7i-flex.large	2/2 checks passed	ap-south-1c	ec2-3-110-125-38.ap-s...	3
☐	ECS Instance - ...	i-0cebfb5bbc3cda8bb	Running	c7i-flex.large	3/3 checks passed	ap-south-1a	ec2-3-109-144-30.ap-s...	3

Select an instance

EC2 Console → Load Balancers → Create Load Balancer

Configure:

- Name: `hiring-app-alb`
- Scheme: `Internet-facing`
- IP type: IPv4

Network:

- VPC: same as ECS cluster
- Subnets: select **at least 2 AZs**

Security Group:


- Allow HTTP (80) from `0.0.0.0/0`

👉 Create ALB

EC2 > Load balancers > Compare and select load balancer type


Load balancer types

Application Load Balancer [Info](#)



Choose an Application Load Balancer when you need a flexible feature set for your applications with HTTP and HTTPS traffic. Operating at the request level, Application Load Balancers provide advanced routing and visibility features targeted at application

Network Load Balancer [Info](#)



Choose a Network Load Balancer when you need ultra-high performance, TLS offloading at scale, centralized certificate deployment, support for UDP, and static IP addresses for your applications. Operating at the connection level, Network Load Balancers are

Gateway Load Balancer [Info](#)



Choose a Gateway Load Balancer when you need to deploy and manage a fleet of third-party virtual appliances that support GENEVE. These appliances enable you to improve security, compliance, and policy controls.

[Create](#)

© 2016 Amazon Web Services, Inc. or its affiliates. Privacy | Terms | Contact us

Network mapping Info

The load balancer routes traffic to targets in the selected subnets, and in accordance with your IP address settings.

VPC Info

The load balancer will exist and scale within the selected VPC. The selected VPC is also where the load balancer targets must be hosted unless routing to Lambda or on-premises targets, or if using VPC peering. To confirm the VPC for your targets, view [target groups](#).

vpc-0a8ab810f0b1433db
172.31.0.0/16

(default)  [Create VPC](#)

IP pools Info

You can optionally choose to configure an IPAM pool as the preferred source for your load balancers IP addresses. Create or view [Pools](#) in the [Amazon VPC IP Address Manager console](#).

☐ Use IPAM pool for public IPv4 addresses
The IPAM pool you choose will be the preferred source of public IPv4 addresses. If the pool is depleted IPv4 addresses will be assigned by AWS.

Availability Zones and subnets Info

Select at least two Availability Zones and a subnet for each zone. A load balancer node will be placed in each selected zone and will automatically scale in response to traffic. The load balancer routes traffic to targets in the selected Availability Zones only.

☒ **ap-south-1a (aps1-az1)**
Subnet
Only CIDR blocks corresponding to the load balancer IP address type are used. At least 8 available IP addresses are required for your load balancer to scale efficiently. Selected subnets must have Network ACL inbound and outbound ALLOW rules, and internet gateway (IGW) routes configured to allow traffic.

subnet-01114db269c57e367
172.31.32.0/20
Network ACL ALLOW rules: Inbound (1) Outbound (1) | Route table: IGW (✓)

☒ **ap-south-1b (aps1-az3)**
Subnet
Only CIDR blocks corresponding to the load balancer IP address type are used. At least 8 available IP addresses are required for your load balancer to scale efficiently. Selected subnets must have Network ACL inbound and outbound ALLOW rules, and internet gateway (IGW) routes configured to allow traffic.

Network ACL ALLOW rules: Inbound (1) Outbound (1) | Route table: IGW (✓)

Security groups Info

A security group is a set of firewall rules that control the traffic to your load balancer. Listed security groups are in the same VPC as you selected above. Selected security groups must include at least 1 inbound rule and 1 outbound rule to allow traffic to your load balancer.

Security groups

Select up to 5 security groups

default (sg-0a62f266a2413423) X
Inbound rule (1) Outbound rule (1)

[Create security group](#)

Listeners and routing Info

A listener is a process that checks for connection requests using the port and protocol you configure. The rules that you define for a listener determine how the load balancer routes requests to its registered targets.

▼ Listener HTTP:80

Remove

Protocol

HTTP

Port

80

1-65535

Default action Info

The default action is used if no other rules apply. Choose the default action for traffic on this listener.

Go to:

EC2 → Target Groups → Create Target Group

Configure:

- Target type: ☒ Instance
- Name: hiring-app-tg
- Protocol: HTTP
- Port: 0 (ignored in dynamic port mapping)

Health check:

- Path: /
- Port: traffic port
- Healthy threshold: 2
- Unhealthy threshold: 3

👉 Create target group

aws [Search] [Alt+S] Asia Pacific (Mumbai) Bradhar

EC2 > Target groups > Create target group

Step 1 **Create target group**
 Step 2 - recommended Register targets
 Step 3 Review and create

Create target group

A target group can be made up of one or more targets. Your load balancer routes requests to the targets in a target group and performs health checks on the targets.

Settings - immutable
 Choose a target type and the load balancer and listener will route traffic to your target. These settings can't be modified after target group creation.

Target type
 Indicate what resource type you want to target. Only the selected resource type can be registered to this target group.

☒ **Instances**
 Supports load balancing to instances in a VPC. Integrate with Auto Scaling Groups or ECS services for automatic management.
 Suitable for: ALB NLB GWLB

☐ **IP addresses**
 Supports load balancing to VPC and on-premises resources. Facilitates routing to IP addresses and network interfaces on the same instance. Supports IPv6 targets.
 Suitable for: ALB NLB GWLB

☐ **Lambda function**
 Supports load balancing to a single Lambda function. ALB required as traffic source.
 Suitable for: ALB

☐ **Application Load Balancer**
 Allows use of static IP addresses and PrivateLink with an Application Load Balancer. NLB required as traffic source.
 Suitable for: NLB

Target group name
 Name must be unique per Region per AWS account.

 Accepts: a-z, A-Z, 0-9, and hyphen (-). Can't begin or end with hyphen. 1-32 total characters; Count: 13/32

Protocol Port

EC2 > Target groups > Create target group

Step 1 Create target group
 Step 2 - recommended **Register targets**
 Step 3 Review and create

Register targets - recommended

This is an optional step to create a target group. However, to ensure that your load balancer routes traffic to this target group you must register your targets.

Available instances (2/2)

Filter instances

☒	Instance ID	Name	State	Security groups	Zone
☒	i-0d2fb64a55d7cc589	ECS Instance - hiring-app-cluster	Running	default	ap-south-1c
☒	i-0cebfb5bbc3cda8bb	ECS Instance - hiring-app-cluster	Running	default	ap-south-1a

2 selected

Ports for the selected instances
 Ports for routing traffic to the selected instances.

 1-65535 (separate multiple ports with commas)

[Include as pending below](#)

aws

Search

[Alt+S]

Asia Pacific (Mumbai)

Bradhar (922345236105)

Bradhar

EC2

Target groups

Create target group

hiring-app-tg

Instance

HTTP: 80

HTTP1

VPC

IP address type

vpc-0a8ab810f0b1433db

IPv4

Health check details

Health check protocol

Health check path

Health check port

Interval

Timeout

Healthy threshold

Unhealthy threshold

Success codes

HTTP

/

traffic-port

30 seconds

5 seconds

5

2

200

Step 2: Register targets

Edit

Targets (2)

Instance ID

Name

Port

Zone

i-Od2fb64a55d7cc589

ECS Instance - hiring-app-cluster

80

ap-south-1c

i-0cebf5b5bc3cda8bb

ECS Instance - hiring-app-cluster

80

ap-south-1a

Cancel

Previous

Create target group

aws

Search

[Alt+S]

Asia Pacific (Mumbai)

Bradhar (922345236105)

Bradhar

EC2

Load balancers

Create Application Load Balancer

Choose a target group and specify routing weight or [create target group](#).

Target group

hiring-app-tg

Target type: Instance, IPv4 | Target stickiness: Off

HTTP

Weight

1

Percent

100%

0-999

+ Add target group

You can add up to 4 more target groups.

Target group stickiness

Info

Enables the load balancer to bind a user's session to a specific target group. To use stickiness the client must support cookies. If you want to bind a user's session to a specific target, turn on the Target Group attribute Stickiness.

☐ Turn on target group stickiness

Listener tags - optional

Consider adding tags to your listener. Tags enable you to categorize your AWS resources so you can more easily manage them.

Add listener tag

You can add up to 50 more tags.

Add listener

You can add up to 49 more listeners.

Load balancer tags - optional

Consider adding tags to your load balancer. Tags enable you to categorize your AWS resources so you can more easily manage them. The 'Key' is required, but 'Value' is optional. For example, you can have Key = production-

Create role:

IAM > Roles > Create role

Step 1: Add permissions
Step 2: Name, review, and create

Trusted entity type

☒ AWS service
Allow AWS services like EC2, Lambda, or others to perform actions in this account.

☐ AWS account
Allow entities in other AWS accounts belonging to you or a 3rd party to perform actions in this account.

☐ Web identity
Allows users federated by the specified external web identity provider to assume this role to perform actions in this account.

☐ SAML 2.0 federation
Allow users federated with SAML 2.0 from a corporate directory to perform actions in this account.

☐ Custom trust policy
Create a custom trust policy to enable others to perform actions in this account.

Use case

Allow an AWS service like EC2, Lambda, or others to perform actions in this account.

Service or use case

Elastic Container Service

Choose a use case for the specified service.

Use case

☐ Elastic Container Service
Allows ECS to create and manage AWS resources on your behalf.

☐ Elastic Container Service Autoscale
Allows Auto Scaling to access and update ECS services.

☒ Elastic Container Service Task
Allows ECS tasks to call AWS services on your behalf.

IAM > Roles > Create role

Step 1: Select trusted entity
Step 2: Add permissions
Step 3: Name, review, and create

Add permissions [Info](#)

Permissions policies (1/1158) [Info](#)

Choose one or more policies to attach to your new role.

task

Filter by Type

All types

1 match

☒ Policy name

Type

Description

☒ AmazonECSTaskExecutionRolePolicy

AWS managed

Provides access to other AWS service res...

Set permissions boundary - optional

Cancel

Previous

Next

IAM > Roles > Create role

Step 1: Select trusted entity
Step 2: Add permissions
Step 3: Name, review, and create

Name, review, and create

Role details

Role name

Enter a meaningful name to identify this role.

ecs-task-execution

Maximum 64 characters. Use alphanumeric and '+', '@', '-', '_' characters.

Description

Add a short explanation for this role.

Allows ECS tasks to call AWS services on your behalf.

Maximum 1000 characters. Use letters (A-Z and a-z), numbers (0-9), tabs, new lines, or any of the following characters: _+@-/\[\]\#\%\^*\{\}\=\>

Step 1: Select trusted entities

Trust policy

1

4. Create ECS Task Definition (EC2 Launch Type)

Go to:

ECS → Task Definitions → Create new task definition

Select:

👉 EC2

Container settings:

- Container name: hiring-app
- Image:

sabair0509/hiring-app:works

- Memory: 1GB
- CPU: 0.5GB

Port mapping:

- Container port: 80
- Host port: 0 (THIS enables dynamic port mapping)

👉 Save container

👉 Create task definition

Amazon Elastic Container Service

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Documentation

Discover products

Subscriptions

Successfully created role: ECS-role-156ba6fd

Create new task definition

Task definition configuration

Task definition family

Specify a unique task definition family name.

hiring-app

Up to 255 letters (uppercase and lowercase), numbers, hyphens, and underscores are allowed.

Infrastructure requirements

Specify the infrastructure requirements for the task definition.

Launch type

Selection of the launch type will change task definition parameters.

☐ AWS Fargate

Serverless compute for containers.

☐ Managed instances

Use if you have specific hardware constraints, such as GPU accelerators, CPU instruction sets, or network-optimized hardware (offloads scaling, patching, and instance management to AWS).

☒ Amazon EC2 instances

Self-managed infrastructure using Amazon EC2 instances.

Create role

Define the role and role permissions you want to create for your ECS task. For fully custom role creation [create role in IAM](#).

Role details

Role name

ECS-role-156ba6fd

Maximum 64 characters. Use alphanumeric and +,=, @, _ characters.

Use cases

This role will allow your ECS task to call AWS services on your behalf. [View trust policy](#).

Select existing policy (1/1158)

Choose an existing IAM policy to use as the template for the new role

amazonecstas

Filter by Type

All types

1 match

☒ Policy name

☒ AmazonECSTaskExecutionRolePolicy

AWS managed

Not used

Provides access to other AWS service r...

Advanced

Cancel Create role

Amazon Elastic Container Service

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Documentation

Discover products

Create new task definition

Task size

Info

Specify the amount of CPU and memory to reserve for your task.

CPU

1 vCPU

Memory

1 GB

▼ Task roles - conditional

Task role

Info

A task IAM role allows containers in the task to make API requests to AWS services.

ECS-role-156ba6fd

Create new role

Task execution role

Info

A task execution IAM role is used by the container agent to make AWS API requests on your behalf. If you don't already have a task execution IAM role created, we can create one for you.

ECS-role-156ba6fd

Create new role

▼ Task placement - optional

Constraint

Info

Task placement constraints allow you to filter the container instances used for the placement of your tasks using built-in or custom attributes. The service scheduler first filters the container instances that match the constraints and then applies the placement strategy to place the task.

Add placement constraint

You can add 10 more placement constraints.

aws

load balancers

Ask Amazon Q

Asia Pacific (Mumbai)

Bradhar (922345236105)

Bradhar

Amazon Elastic Container Service

Create new task definition

Container Service

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer

AWS Batch

Amazon ECR

Repositories

Online learning workshop

Documentation

Discover products

Subscriptions

Tell us what you think

▼ Container - 1

Info

Essential container

Remove

Container details

Specify a name, container image and whether the container should be marked as essential. Each task definition must have at least one essential container.

Name

Essential container

hiring-app

Yes

Up to 255 letters (uppercase and lowercase), numbers, hyphens, and underscores are allowed.

Image URI

sabair0509/hiring-app:works

Browse ECR images

Up to 255 letters (uppercase and lowercase), numbers, hyphens, underscores, colons, periods, forward slashes, and number signs are allowed.

Private registry

Info

Store credentials in Secrets Manager, and then use the credentials to reference images in private registries.

Private registry authentication

Port mappings

Info

Add port mappings to allow the container to access ports on the host to send or receive traffic. For port name, a default will be assigned if left blank.

Host port

Container port

Protocol

Port name

App protocol

0

80

TCP

container-port-proto

HTTP

Remove

Add port mapping

The bridge network mode is selected. By default, dynamic host port mappings are used for each container. To configure a static host port mapping, specify a host port for each container port.

5. Create ECS Service (6 Tasks + HA)

Go to:

ECS → Cluster → hiring-app-cluster → Services → Create

Configure:

- Launch type: **EC2**
- Task definition: **hiring-app**
- Service name: **hiring-app-service**

Desired tasks:

👉 6

 **Networking section:**

- VPC: same VPC
- Subnets: select **multiple AZs**
- Security group:
 - Allow inbound from ALB security group



Load Balancer setup:

- Type: Application Load Balancer
- Select existing ALB: **hiring-app-alb**
- Listener: HTTP : 80
- Target group: **hiring-app-tg**

Existing cluster

hiring-app-cluster

▼ Compute configuration - *advanced*

Compute options [Info](#)

To ensure task distribution across your compute types, use appropriate compute options.

☐ Capacity provider strategy

Specify a launch strategy to distribute your tasks across one or more capacity providers.

☒ Launch type

Launch tasks directly without the use of a capacity provider strategy.

Launch type [Info](#)

Select either managed capacity (Fargate), or custom capacity (EC2 or user-managed, External instances). External instances are registered to your cluster using the ECS Anywhere capability.

EC2

► Troubleshooting configuration - *recommended*

Deployment configuration

Scheduling strategy [Info](#)

☒ Replica

Place and maintain a desired number of tasks across your cluster.

☐ Daemon

Place and maintain one copy of your task on each container instance.

Desired tasks

Amazon Elastic Container Service

Express Mode

Clusters

Namespaces

Task definitions

Daemon task definitions

Account settings

AWS Resource Explorer [↗](#)

AWS Batch [↗](#)

Amazon ECR [↗](#)

Repositories [↗](#)

Online learning workshop [↗](#)

Documentation [↗](#)

Discover products [↗](#)

Subscriptions [↗](#)

▼ Load balancing - *optional*

Configure load balancing using Amazon Elastic Load Balancing to distribute traffic evenly across the healthy tasks in your service.

☒ Use load balancing

VPC

Select the VPC for your load balancing resources.

vpc-0a8ab810f0b1433db

default



Create a new VPC [↗](#)

Load balancer type [Info](#)

Specify the load balancer type to distribute incoming traffic across the tasks running in your service.

☒ Application Load Balancer

An Application Load Balancer makes routing decisions at the application layer (HTTP/HTTPS), supports path-based routing, and can route requests to one or more ports.

☐ Network Load Balancer

A Network Load Balancer makes routing decisions at the transport layer (TCP/UDP).

Container

The container and port to load balance the incoming traffic to

hiring-app 80:80

Host port:Container port

Application Load Balancer

Specify whether to create a new load balancer or choose an existing one.

☐ Create a new load balancer

☒ Use an existing load balancer

Application Load Balancer

Specify whether to create a new load balancer or choose an existing one.

☐ Create a new load balancer

☒ Use an existing load balancer

Load balancer

Choose an existing load balancer to distribute traffic. View existing load balancers and create new one in [EC2 Console](#) [↗](#).

hiring-app-alb

hiring-app-alb-1248609123.ap-south-1.elb.amazonaws.com

internet-facing



Listener [Info](#)

Specify the port and protocol that the load balancer will listen for connection requests on.

☐ Create new listener

☒ Use an existing listener

Listener

HTTP:80



Listener rules for 80:HTTP [↗](#) (1)

Traffic received by the listener is routed according to its rules. Rules are evaluated in priority order, from the lowest value to the highest value. The default rule is evaluated last.

< 1 >

Priority



Rule path



Target group



default

/

[hiring-app-tg](#) [↗](#)

Amazon Elastic Container Service

Clusters > hiring-app-cluster > Create service

Priority: default

Rule path: /

Target group: hiring-app-tg

Target group

Specify whether to create a new target group or choose an existing one that the load balancer will use to route requests to the tasks in your service.

Create new target group

Use an existing target group

Target group name

hiring-app-tg

Health check path

/

Health check protocol

HTTP

Amazon Elastic Container Service

Clusters > hiring-app-cluster > Services > hiring-app-task-definition-service > Health

hiring-app-task-definition-service has been deployed successfully.

View service

Notifications

0 0 2 0 0 0

hiring-app-task-definition-service

Info

Delete service

Update service

Service overview

Info

Status: Active

Tasks (6 Desired): 0 pending | 6 running

Task definition: revision hiring-app-task-definition:1

Deployment status: Success

Health and metrics

Tasks

Logs

Deployments

Events

Configuration and networking

Service auto scaling

Event history

Status

Info

Service name: hiring-app-task-definition-service

Service ARN: arn:aws:ecs:ap-south-1:92234...

Deployments current state: 6 Completed tasks

Created at: 9 June 2026, 07:42 (UTC+5:30)

Health check grace period

0 seconds

Load balancer target health

Container name:port	Target group	Resource type	Target health	Load balancer	Load balancer type
---------------------	--------------	---------------	---------------	---------------	--------------------

aws

Search

Asia Pacific (Mumbai)

Bradhar (922345236105)

EC2 > Target groups > hiring-app-tg

EC2

Dashboard

AWS Global View

Events

Instances

Instances

Instance Types

Launch Templates

Spot Requests

Savings Plans

Reserved Instances

Dedicated Hosts

Capacity Reservations

Capacity Manager

Images

AMIs

AMI Catalog

Elastic Block Store

Volumes

Snapshots

hiring-app-tg

Actions

Details

arn:aws:elasticloadbalancing:ap-south-1:922345236105:targetgroup/hiring-app-tg/f92a72dcc5599c56

Target type: Instance

Protocol : Port: HTTP: 8080

Protocol version: HTTP1

VPC: vpc-0a8ab810f0b1433db

IP address type: IPv4

Load balancer: hiring-app-alb

8 Total targets

6 Healthy

2 Unhealthy

0 Unused

0 Initial

0 Draining

Distribution of targets by Availability Zone (AZ)

Select values in this table to see corresponding filters applied to the Registered targets table below.

Targets

Monitoring

Health checks

Attributes

Tags

Registered targets (8)

Info

Anomaly mitigation: Not applicable

Deregister

Register targets

Target groups route requests to individual registered targets using the protocol and port number specified. Health checks are performed on all registered targets according to the target group's health check settings. Anomaly detection is automatically applied to HTTP/HTTPS target groups with at least 3 healthy targets.

Verify: load balancer DNS/hiring

