

Program 3:

Develop an external style sheet named as “style.css” and provide different styles for h2, h3, hr, p, div, span, time, img & a tags. Apply different CSS selectors for tags and demonstrate the significance of each.

Index.html

```
<!DOCTYPE html>
```

```
<head>
```

```
  <title>Styled HTML Page | vtucode</title>
```

```
  <link rel="stylesheet" href="style.css">
```

```
</head>
```

```
<body>
```

```
  <h2>Main Heading</h2>
```

```
  <h3>Subheading</h3>
```

```
  <hr>
```

```
  <p>This is a paragraph demonstrating the basic text styling applied by CSS.</p>
```

```
  <div>
```

```
    This is a styled <strong>div</strong> element with padding and a light border. Inside the div, we can also use
```

```
    <span>span elements</span> that have their own styles, like this bold and orange text.
```

```
  </div>
```

<p>Current time: <time>10:30 AM</time></p>

<p>Visit vtuocode.in to learn more about our services.</p>

<p class="highlight">This paragraph is highlighted with a yellow background.</p>

<p class="center">This text is centered using a class selector.</p>

<p id="special-paragraph">This is a special paragraph with unique styles applied through an ID selector.</p>

</body>

</html>

Style.css

```
* {  
  margin: 0;  
  padding: 0;  
  box-sizing: border-box;  
}
```

```
h2 {  
  color: #2c3e50;  
  font-size: 2em;  
  margin-bottom: 10px;  
}
```

```
h3 {  
  color: #34495e;  
  font-size: 1.5em;  
  margin-bottom: 8px;  
}
```

```
hr {  
  border: 0;
```

```
height: 2px;
background-color: #e74c3c;
margin: 20px 0;
}
```

```
p {
  font-family: 'Arial', sans-serif;
  line-height: 1.6;
  margin: 10px 0;
}
```

```
div {
  padding: 15px;
  border: 1px solid #bdc3c7;
  background-color: #ecf0f1;
}
```

```
span {
  color: #e67e22;
  font-weight: bold;
}
```

```
time::before {
```

```
content: '🐱';  
color: #16a085;  
}
```

```
img {  
  margin-left: 15px;  
  height: 300px;  
  width: 400px;  
  border-radius: 8px;  
  box-shadow: 0 4px 8px rgba(0, 0, 0, 0.2);  
  max-width: 100%;  
}
```

```
a {  
  text-decoration: none;  
  color: #ea0e4c;  
}
```

```
a:hover {  
  color: #6200ee;  
  text-decoration: underline;  
}
```

```
.highlight {  
    background-color: yellow;  
    padding: 3px;  
}
```

```
.center {  
    text-align: center;  
}
```

```
#special-paragraph {  
    font-size: 1.2em;  
    color: #8e44ad;  
    background-color: #f5f5f5;  
    padding: 10px;  
    border-left: 5px solid #8e44ad;  
}
```

```
h2,  
h3,  
p {  
    margin-left: 20px;  
}
```