Grokking Under a Fixed Budget

Vihaan Jinesh Jain
25BYB0130

Kaashvi Goel
25BYB0129

Gaurav Kansal
25BYB0157

1. The task and dataset

Modulo keeps the remainder

961 pairs. Three fixed splits. Independent starting seeds.

2. How the code works



Checkpoint saves: weights, optimizer and random state.

3. Grokking: practice improves before new-question accuracy



S1 calibration (n=30): mean 5,347; median 4,375; SD 4,610 updates.

4. Two success rules

Every check: practice >=99% and held-out >=95%.

First: 3 checks ● ● ● 50-update span

Window: 21 checks ● 500-update span

Spans start at the first good check. Count the last check inside B/k.

U=min(T,C): capped time; eventual unfinished T stays unknown.

Chance of >=1 success: 1 - [1 - F(B/k)]^k F(t): one-run completion chance.

Results and the decision

Binary attempts. Exact intervals. Twelve Fisher tests with Holm correction.

5. Same total budget: B = 8,000 updates



Each segment is a fresh start. All allocated updates execute.

6. Fresh successes at the 8,000-update budget



Each bar: successes out of 30 independent attempts.

All three 4-versus-1 differences survive Holm correction.

7. Results at 12,000 updates (out of 30)

Split	1 run	2 runs	4 runs
S1	30	30	24
S2	30	30	20
S3	30	29	23

12k: only S2 detects a 4-vs-1 difference. Two-run results are inconclusive.

Example uncertainty: 28/30 = 93.3%; exact 95% interval 77.9%-99.2%.

8. Brief confirmation versus a longer window

S1, 8k, four starts

Decision: one long run was more reliable at 8k.

Scope: one task, one model, three splits. Later accuracy can still fall.

Next: other tasks, more splits and longer accuracy windows.

Sources: Power et al. (2022); Streeter et al. (2007). Full references: Assessment 9.