Grokking Under a Fixed Budget: An Empirical Study of Learning Time and Independent Restarts

Vihaan Jinesh Jain
25BYB0130

Kaashvi Goel
25BYB0129

Gaurav Kansal
25BYB0157

***Abstract*—Grokking is delayed improvement on held-out examples after strong training performance. We study completion-time variation in a fixed small transformer learning addition modulo 31, then compare one long run with two or four independent starts at total budgets of 8,000 or 12,000 updates. There are 90 calibration observations across three fixed dataset splits, including 20 reused runs, and 540 fresh policy attempts. Primary success requires three accuracy checks; a secondary endpoint requires a 500-update window. At 8,000 updates, one run succeeds 28/30 times on every split; four starts succeed 12/30, 9/30 and 11/30. All three contrasts survive Holm correction. At 12,000, only the second-split four-versus-one contrast is detected. No two-run contrast is detected. Four of twelve planned tests are significant. We report uncertainty and keep unfinished event times unknown. The proposed empirical contribution links completion curves, equal-budget allocation and finite stability, conditional on this task and model.**

***Index Terms*—grokking, random variables, independent restarts, fixed training budget, generalization, statistical inference**

I. Introduction and objectives

Grokking is delayed improvement on held-out examples after strong training performance [1]. We study its timing across random initializations and ask how to allocate a fixed training budget. The objectives are:

- characterize completion-time variability;
- estimate success before a training limit;
- compare one long run with independent shorter starts.

II. Related work and contribution

Power et al. established the grokking phenomenon [1]. Truong et al. study prediction of the delay as a first-passage problem [2], while restart schedules have an established randomized-algorithm literature [3]. Ootani emphasizes repeated seeds and a controlled numerical environment [4]. Our contribution is the measured connection between completion-time variability, equal-update allocation and a finite stability check. We do not introduce the restart identity or establish worldwide novelty.

III. Experimental design

All 961 ordered pairs $a, b \in \{0, \ldots, 30\}$ have label $(a + b) \bmod 31$; for example, $(30 + 4) \bmod 31 = 3$. The baseline has 576 practice and 385 held-out pairs. A fixed causal transformer [5] has 36,992 parameters: one attention block, width 64, four heads and a 128-unit ReLU layer, without biases, dropout or layer normalization. Full-batch AdamW [6] uses learning rate 0.003, betas (0.9,0.98) and weight decay 1.




Fig. 1. Recorded experimental workflow. Python trains and saves evaluation histories; R analyzes run and policy outcomes. Checkpoints support resumption. Numerical records remain separate from the reports.

Split seeds 20261013–20261015 each have 30 calibration runs capped at $C = 30,000$. Validation uses 30 fresh independent attempts in each split/budget/policy cell. For $k = 1, 2, 4$, each constituent receives B/k updates and all allocated updates execute. An attempt succeeds if any constituent qualifies. Seeds are disjoint between calibration and validation; model predictions are not averaged.

A. Outcomes and prospective controls

Each update uses all practice pairs. Evaluate every 25 updates, with update zero excluded from qualifying streaks. Both thresholds must hold: practice accuracy $\geq 99\%$ and held-out accuracy $\geq 95\%$. Memorization time requires three practice-only checks. Primary T uses three joint checks; secondary T_{500} uses 21, spanning 500 updates. Both record the final check and neither guarantees permanent generalization.

Let Q_j be one when both accuracy thresholds hold at update $25j$, and zero otherwise. The two recorded endpoints are

$$T = 25 \min\{j \geq 3 : Q_{j-2} = Q_{j-1} = Q_j = 1\}, \quad (1)$$

$$T_{500} = 25 \min\{j \geq 21 : Q_{j-20} = \cdots = Q_j = 1\}. \quad (2)$$

If no qualifying streak finishes by C, its event time remains unknown. The fully observed capped outcome is $U = \min(T, C)$.

The 8,000- and 12,000-update budgets were chosen from the original 20 baseline traces after every old policy succeeded

TABLE I
EXPERIMENTAL COHORTS AND OBSERVATION UNITS.

Cohort	Purpose	Sample
Original main study	Exploratory setting comparisons	120 runs; 20 per six cells
Follow-up calibration	Completion curves for three fixed splits	90 runs; 20 reused + 70 new
Follow-up validation	Fresh equal-budget comparisons	540 attempts; 1,260 runs

10/10 at 30,000. This data-informed choice is disclosed. Protocol and full seeds were committed before new training; calibration predictions were frozen before validation. Budgets, settings and sample sizes were not retuned after viewing outcomes.

B. Execution

Training uses CPU, four threads per run, float32, deterministic algorithms and disabled TF32, with no more than three independent processes. CUDA was unavailable in the recorded environment. Checkpoint recovery may repeat unsaved physical work; elapsed time excludes downtime and is affected by scheduling contention. Equality refers to logical optimizer updates within the same setting, not wall-clock speed or physical recovery overhead.

Recorded per-run elapsed times sum to 4.24 run-hours for new calibration and 8.60 for validation. Parallel jobs overlap, so these sums are not wall-clock duration. Unsaved work before interruption is not fully measured.

IV. LEARNING-TIME VARIABILITY

Across the 90 calibration observations, 90 first confirmations and 90 500-update confirmations occur by C. On the original split, mean capped first-confirmation time U is 5,347 updates, median 4,375 and sample SD 4,610. The means describe U=min(T,C); an unfinished T remains unknown. Calibration extends only the baseline setting, not all six original experimental cells.

Each curve is the fraction of its 30 runs confirmed by time t. Unfinished runs remain in the denominator. Differences are conditional on these fixed partitions, not all possible tasks.

V. BUDGET RELIABILITY: PREDICTION AND VALIDATION

For a fixed split, let $F(t) = P(T \leq t)$. With $n = 30$ calibration runs, estimate it by

$$\widehat{F}(t) = \frac{1}{n} \sum_{i=1}^{n} \mathbf{1}\{T_i \leq t\}. \tag{3}$$

Unfinished runs contribute no event before the cap and remain in the denominator. Conditional on the same task and numerical settings, independent initializations give

$$P(\text{at least one success}) = 1 - [1 - F(B/k)]^k. \tag{4}$$

Each validation attempt has a Bernoulli success indicator; its cell total follows a binomial sampling model. We estimate F from calibration and test frozen predictions with fresh seeds. Exact binomial intervals accompany observed proportions. Independent bootstrap resampling of calibration runs and policy attempts captures both uncertainty sources when comparing prediction with observation.

Three splits are fixed replications, not three new tasks. We interpret each panel separately. Point estimates near one can still have substantial uncertainty at n=30. Agreement with a prediction is not proof of the full timing model, and a nonsignificant contrast is not evidence that policies are equivalent.

A. Pre-specified policy comparisons

Twelve two-sided Fisher exact tests compare k=2 or k=4 with k=1 within each budget and split. Each null hypothesis states that the success probabilities are equal. Holm correction is applied jointly across all twelve; 4 adjusted p-values are below 0.05. The risk difference is restart probability minus the one-run probability. Negative values favour the one-run policy; positive values favour the specified restart policy. Fig. 4 uses conservative pointwise intervals from exact binomial margins. Planned bootstrap intervals remain in the numerical output as sensitivity summaries. Table differences are in percentage points (pp).

VI. FIRST CONFIRMATION VERSUS 500-UPDATE STABILITY

The primary rule confirms three checks separated by 25 updates. It does not require later accuracy to remain high. In the original 120-run study, 62 of 83 generalized runs later fell below 95% held-out accuracy. The follow-up therefore derives a distinct endpoint requiring 21 qualifying checks, spanning 500 updates, from exactly the same traces.

A stability event must finish before the constituent cap; no extra follow-up is granted to a short run. The stability event implies the primary event, so its probability cannot exceed primary success in the same sample. These secondary comparisons are descriptive. They distinguish a brief confirmation from a longer accuracy window, while allowing further deterioration after either event. Neither endpoint establishes permanent generalization or human-like rule understanding.

VII. SUPPORTING SETTING COMPARISONS AND TIMING MODELS

The original study retains 20 runs in each of six data-fraction/weight-decay cells. Its results provide exploratory context rather than additional validation attempts. The all-unfinished cell has U=C in every sample; zero sample SD of U does not imply zero variability in unrestricted T. Mean comparisons, regression and ANOVA describe capped outcomes only.




Fig. 2. Top: an original-split calibration run selected closest to median T, with first confirmation at 4,375 updates. The early window is illustrative; the full trace is retained. Bottom: empirical first-confirmation curves for all three splits, each with 30 calibration observations through 30,000 updates and unfinished outcomes retained in its denominator. Split 1 includes 20 reused runs; the other 70 calibration observations are new.

TABLE II
CALIBRATION OUTCOMES AT THE 30,000-UPDATE CAP.

Split	First events	500-window events	Mean U	Median U
S1	30/30	30/30	5,347	4,375
S2	30/30	30/30	4,251	3,988
S3	30/30	30/30	4,378	4,188

TABLE III
FRESH SUCCESSES OUT OF 30, PROBABILITY DIFFERENCES IN PERCENTAGE POINTS, AND HOLM-ADJUSTED P-VALUES.

Split / B	1 run	2 runs	4 runs	2 minus 1	4 minus 1	Holm p: 2 / 4
S1 / 8k	28/30	23/30	12/30	-16.7 pp	-53.3 pp	0.873 / 0.000187
S1 / 12k	30/30	30/30	24/30	+0.0 pp	-20.0 pp	1 / 0.166
S2 / 8k	28/30	24/30	9/30	-13.3 pp	-63.3 pp	1 / 6.57e-06
S2 / 12k	30/30	30/30	20/30	+0.0 pp	-33.3 pp	1 / 0.00717
S3 / 8k	28/30	25/30	11/30	-10.0 pp	-56.7 pp	1 / 6.8e-05
S3 / 12k	30/30	29/30	23/30	-3.3 pp	-23.3 pp	1 / 0.0843




Fig. 3. Filled points show observed first-confirmation proportions with exact 95% binomial intervals (30 fresh attempts per policy). Open points show frozen predictions with the transformed exact calibration intervals (30 separate calibration runs per split). All intervals are pointwise. S1 includes 20 reused calibration runs; its prediction intervals do not adjust for the earlier budget choice. All six conditions are reported, including unfavourable or inconclusive outcomes.

TABLE IV
ORIGINAL 120-RUN EXPLORATORY SETTING STUDY.

Data fraction	Decay	Events / n	Mean U	SD U
0.4	0.3	0/20	30,000	0
0.6	0.3	19/20	15,235	7,786
0.4	1	14/20	19,822	8,562
0.6	1	20/20	5,481	5,548
0.4	3	10/20	20,282	11,447
0.6	3	20/20	1,430	1,164

At 60% data, Pearson correlation of U with log decay is -0.715 and Spearman correlation is -0.866. The original two-factor residual Shapiro-Wilk p=0.000199 cautions against normal-error ANOVA claims. Permutation sensitivity also assumes exchangeable errors. The additive regression R-squared=0.630 describes sample variation, not held-out prediction accuracy. These syllabus analyses remain exploratory.

A. *Candidate distributions*

The expanded original-split calibration sample fits Exponential, Gamma and Weibull timing families. The recording-grid likelihood assigns event mass G(t-50)-G(t-75) to T=t and survival 1-G(C-50) to an unfinished run. AIC balances fit and parameter count; among converged fits, Gamma ranks lowest here (AIC 372.13). This is candidate ranking, not proof of a true timing law. Fitted curves are supplied separately; policy predictions use empirical F, not these timing fits.

The project applies random variables, capped expectation and variability, Bernoulli/binomial outcomes, intervals, hypothesis comparisons, regression and ANOVA where justified by the supplied syllabus [7]. It does not force a variance test




Fig. 4. First-confirmation probability differences. S1-S3 identify the fixed splits. Bounds combine two exact 97.5% marginal intervals to give conservative pointwise 95% coverage for a difference; they are not simultaneous across all contrasts. This avoids a collapsed bootstrap interval in constant-outcome groups. The zero line denotes equal probabilities.

TABLE V
TIMING-FAMILY COMPARISON ON THE EXPANDED ORIGINAL-SPLIT CALIBRATION SAMPLE.

Candidate	Events / n	AIC	Converged
Exponential	30/30	383.22	TRUE
Gamma	30/30	372.13	TRUE
Weibull	30/30	378.13	TRUE

or goodness-of-fit test onto unsuitable capped samples.

VIII. Discussion and Limitations

At 8,000 updates, one long run succeeds in 28/30 attempts on every split; four restarts succeed in 12/30, 9/30 and 11/30. All three contrasts survive Holm correction. At 12,000 updates, one run succeeds in 30/30 on every split, versus 24/30, 20/30 and 23/30 for four restarts; only the second-split contrast survives correction. No two-run contrast is detected. Dividing the budget too finely leaves less time for each learning delay. This interpretation is conditional on the measured curves, rather than a general argument against restarts. The earlier 30,000-update ceiling result remains consistent with these smaller-budget differences.

Evidence is conditional on one arithmetic task, one small architecture, selected decay and three fixed splits. Thirty attempts per condition are useful for substantial differences but cannot reliably resolve tiny gaps or establish equivalence. Held-out pairs are excluded from gradient updates but monitored for the endpoint; no additional untouched test set is claimed. Calibration predictions across budgets are correlated, and S1 intervals do not adjust for budget selection using reused traces. Bootstrap intervals are pointwise; normal-error assumptions fail in the exploratory setting models. Three split replications do not establish transfer to larger networks, natural-language tasks or different numerical environments.

IX. Conclusion

For this model and these three splits, four short runs are less reliable than one long run at 8,000 total updates. The 12,000-update results leave several comparisons unresolved; nonsignificance does not establish equality. Completion curves make budget allocation testable, while the 500-update endpoint shows why brief confirmation needs a separate stability description. Future work can test other tasks, additional splits and longer windows. No universal restart rule or new timing theorem is established.




Fig. 5. Both endpoints use the same attempt and must finish within its constituent cap B/k; panels use total B=8,000 or 12,000. Circles denote first confirmation and triangles the 500-update window. Bars are exact 95% intervals. The two endpoints are correlated, not independent samples.

X. Data availability and contribution

The versioned project repository retains source, fixed configuration, complete seed manifest, raw evaluation traces, R tables and graph sources, plus reproduction and audit commands. Repository access is controlled by its owner. Local checkpoints and dependency runtimes are excluded from Git. New training records, figures and manuscripts are separate from the archived original delivery. Established grokking and restart ideas are attributed; worldwide novelty and institutional similarity clearance are not claimed.

References

[1] A. Power, Y. Burda, H. Edwards, I. Babuschkin, and V. Misra, "Grokking: Generalization Beyond Overfitting on Small Algorithmic Datasets," Preprint, 2022. [Online]. Available: https://arxiv.org/abs/2201.02177

[2] X. K. Truong, Q. H. Truong, D. T. Luu, and T. D. Phan, "First-Passage Prediction of Grokking Delay: A Calibrated Law under AdamW with Causal Validation," Preprint, 2026. [Online]. Available: https://arxiv.org/abs/2605.18845

[3] M. Streeter, D. Golovin, and S. F. Smith, "Restart Schedules for Ensembles of Problem Instances," Research paper, 2007. [Online]. Available: https://www.cs.cmu.edu/~dgolovin/papers/aaai07b.pdf

[4] Y. Ootani, "Grokking Is Conditional and Fragile: A Fully-Tractable, Multi-Seed Study at 12K Parameters," Preprint, 2026. [Online]. Available: https://arxiv.org/abs/2607.05104

[5] A. Vaswani et al., "Attention Is All You Need," NeurIPS 2017. [Online]. Available: https://arxiv.org/abs/1706.03762

[6] I. Loshchilov and F. Hutter, "Decoupled Weight Decay Regularization," ICLR 2019. [Online]. Available: https://arxiv.org/abs/1711.05101

[7] BAMAT207 course specification, "Probability and Statistics: theory and embedded laboratory," Course specification. Official supplied syllabus, version 1, archived with the project.