

# Introduction to Database Systems

Radim Bača

Department of Computer Science, FEECS

radim.baca@vsb.cz

dbedu.cs.vsb.cz

# Content

- Data types
- SQL DDL
  - Create Table
  - Alter Table
  - Create Index
- SQL DML

# Data types

- Database systems implement several categories of data types:
  - Integers
  - Floats
  - Strings
  - Date and time
  - Binary strings & BLOBs (large objects)
- Different database systems often implement some data types differently (data types' names)
- Therefore, in what follows, we will focus on SQL Server 2012/16

# Data types

- Database systems implement several categories of data types:
  - Integers
  - Floats
  - Strings
  - Date and time
  - Binary strings & BLOBs (large objects)
- Different database systems often implement some data types differently (data types' names)
- Therefore, in what follows, we will focus on SQL Server 2012/16

# Table creation

- The statement

```
CREATE TABLE table (  
    attr1 int,  
    attr2 date  
)
```

creates a table with an integer attribute `attr1` and an attribute `attr2` of the type `date`

- In the second part of this lecture, we will return to this statement, nevertheless, as for data types, the above awareness is sufficient

# Numbers

- `int` (4 byte) - integer number
- `bit` - can gain these values: 0, 1, or NULL
- `decimal(d,p)/numeric(d,p)` - numbers with specified number of digits (d) and precision after the decimal point (p)
- `float` (8 byte) - numbers with decimal point
- In the previous examples, we often worked with integer data types

# Float

- IEEE 754 standard
- $sign * mantisa * 2^{exponent}$
- There can be rounding issues:
  - `SELECT 1.0 / 3 * 3`

# Strings

- Strings can have
  - fixed length
  - variable length
- Moreover, a string can be coded by
  - 8-bit code
  - UNICODE

	fixed length	variable length
8-bit code	char[n]	varchar[n]
UNICODE	nchar[n]	nvarchar[n]



## Strings - Variable vs. Fixed

- Fixed length strings
  - Can occupy more space
  - + Fast value update
- Variable length strings needs to 'create' a space during a value update

## Overflow Pages

- Most DBMS don't allow a tuple to exceed a size of a page (4 - 16kB)
- SQL Server requires a fixed size attributes of a row to fit into a page
- However, variable length values can exceed the page size
- Such data are stored separately in a *overflow pages*:
  - PostgreSQL: TOAST
  - MySQL: Overflow
  - SQL Server: Overflow

## Strings and functions

- Many functions (often specific for particular database systems) **relate to strings**: <http://msdn.microsoft.com/en-us/library/ms181984.aspx>
- You can take a look at a description of basic functions as:
  - CONCAT - concatenation
  - LEN - length of a string
  - LOWER - switches all letters to lower cases
  - LTRIM/RTRIM - skips all left/right blanks of a string
  - STR - transfers a string to a number
  - SUBSTRING - returns a substring

## Strings and functions

- Many functions (often specific for particular database systems) relate to strings: `http://msdn.microsoft.com/en-us/library/ms181984.aspx`
- You can take a look at a description of basic functions as:
  - CONCAT - concatenation
  - LEN - length of a string
  - LOWER - switches all letters to lower cases
  - LTRIM/RTRIM - skips all left/right blanks of a string
  - STR - transfers a string to a number
  - SUBSTRING - returns a substring

## Data type change

- Some data type changes happen implicitly (usually numeric data types)

```
CREATE TABLE table (  
    attr1 int,  
    attr2 float  
)
```

```
INSERT INTO table VALUES (2, NULL)
```

```
UPDATE table SET attr2 = attr1
```

- The assignment runs automatically without any need to change `int` to `float` (and the other way around)

# CAST

- Sometimes, the implicit data type change is not defined or is unclear from context
- Then it is necessary to change explicitly the data type by using the CAST statement

CAST (expression AS data\_type)

- *Find an average birth year of students.*

```
SELECT AVG(CAST (birth_year as FLOAT))  
FROM Student
```

# CAST

- Sometimes, the implicit data type change is not defined or is unclear from context
- Then it is necessary to change explicitly the data type by using the CAST statement

```
CAST (expression AS data_type)
```

- *Find an average birth year of students.*

```
SELECT AVG(CAST (birth_year as FLOAT))  
FROM Student
```

## Date and time

- We distinguish the following time data types:
  - those complying with time zones (`datetimeoffset`)
  - those without any information about time zones (`date`, `time`, `datetime2`)
- We will be concerned only with data types without time zones
- Date and time data types are sometimes confusing even for experienced programmer



## Date and time

- `date` (3 byte) - stores a date in an implicit format YYYY-MM-DD
- `datetime2` (6-8 byte) - stores both date and time in an implicit format YYYY-MM-DD HH:MM:SS
- `time` (5 byte) - stores a time in an implicit format HH:MM:SS
- `datetime2` is an extension of `datetime`; `datetime` is implemented in SQL Server only to keep the backward compatibility

## Dates and functions

- There are many functions for dates and times: <http://msdn.microsoft.com/en-us/library/ms186724.aspx>
- Let us mention only some of them:
  - SYSDATETIME - returns current date and time
  - GETDATE - returns current date
  - DAY(attr) - returns day from the attribute attr
  - MONTH(attr) - returns month from the attribute attr
  - YEAR(attr) - returns year from the attribute attr

# BLOB

- Binary large object (BLOB)
- It is a reference to an external object (File in file system)
- Different data types in different database systems:
  - Oracle - BFILE
  - SQL Server - FILESTREAM
  - MySQL - BLOB
- Most of these database systems has several others data types for large objects (some deprecated, some with specific features)

## BLOB

- Database system cannot manipulate the content of an external file
  - NO durability protection
  - NO transaction protection
- Objects above 256KB should be stored as a BLOB <sup>1</sup>
- The major difference is file fragmentation

---

<sup>1</sup>Sears, Russell, Catharine Van Ingen, and Jim Gray. To BLOB or Not To BLOB: Large Object Storage in a Database or a Filesystem?

# Data Definition Language (DDL)

- We will be mainly concerned with these statements:
  - `CREATE TABLE` - creates a table
  - `ALTER TABLE` - modifies a table scheme
  - `DROP TABLE` - deletes a table

# The CREATE TABLE statement

- Creation of a table:

```
CREATE TABLE table (attr1 data_type  
[constraints, attr2 ..., attr3 ...])
```

- Example:

```
CREATE TABLE Person (  
    id int PRIMARY KEY,  
    name varchar(20),  
    born date  
)
```

# Constraints

- Constraints that can appear after data type:
  - NOT NULL – the attribute cannot gain the NULL value
  - DEFAULT value – an implicit value of the attribute
  - UNIQUE – values of the attribute have to be unique throughout the table
  - PRIMARY KEY – the attribute is a primary key of the table
  - REFERENCES tab(attr) – the attribute is a foreign key and it refers to the attribute attr of the tab table

## Constraints - Example 1

- The previous table `Person` with more constraints:

```
CREATE TABLE Person (  
    id int PRIMARY KEY,  
    name varchar(20) NOT NULL,  
    born date DEAFULT NULL,  
    cat int REFERENCES cathegory  
)
```

- We can see that `REFERENCES` does not have to specify any attribute - and in this case, a primary key of the referred table (the `cathegory` table in the above example) is considered



## Constraints - Example 1

- The previous table `Person` with more constraints:

```
CREATE TABLE Person (  
    id int PRIMARY KEY,  
    name varchar(20) NOT NULL,  
    born date DEAFULT NULL,  
    cat int REFERENCES cathegory  
)
```

- We can see that `REFERENCES` does not have to specify any attribute - and in this case, a primary key of the referred table (the `cathegory` table in the above example) is considered

## Constraints - Example 2

- The previous table `Person` (an alternative notation):

```
CREATE TABLE Person (  
    id int,  
    name varchar(20) NOT NULL,  
    born date DEAFULT NULL,  
    cat int,  
    PRIMARY KEY (id),  
    FOREIGN KEY (cat) REFERENCES cathegory  
)
```

- Constraints concerning the primary and foreign keys are written in separate lines

## Constraints - Example 2

- The previous table `Person` (an alternative notation):

```
CREATE TABLE Person (  
    id int,  
    name varchar(20) NOT NULL,  
    born date DEAFULT NULL,  
    cat int,  
    PRIMARY KEY (id),  
    FOREIGN KEY (cat) REFERENCES cathegory  
)
```

- Constraints concerning the primary and foreign keys are written in separate lines

## Constraints - CHECK

- A constraint can be defined by a logical expression which has to be satisfied for the given attribute
- *Let us demand that any birth year cannot be under 1950.*

```
CREATE TABLE Person (  
    ...,  
    born date CHECK (YEAR(born) >= 1950),  
    ...  
)
```

## Constraints - CHECK

- A constraint can be defined by a logical expression which has to be satisfied for the given attribute
- *Let us demand that any birth year cannot be under 1950.*

```
CREATE TABLE Person (  
    ... ,  
    born date CHECK (YEAR(born) >= 1950) ,  
    ...  
)
```

## Table types

- Two major types of tables:
  - Heap
  - Sorted table (primary index)
- Primary key
  - SQL Server – table sorted according to the primary key
  - Oracle, MySQL, PostgreSQL – heap table + secondary index

# The ALTER TABLE Statement

- modifies a table scheme
- This modification can have many forms; let us mention at least basic ones:
  - addition of a column (`ALTER TABLE tab ADD ...`)
  - deletion of a column (`ALTER TABLE tab DROP COLUMN ...`)
  - modification of a column (`ALTER TABLE tab ALTER COLUMN ...`)
- This is a syntax used by SQL Server
- Oracle and MySQL use `MODIFY` instead of `ALTER COLUMN`

## The ALTER TABLE Statement

- modifies a table scheme
- This modification can have many forms; let us mention at least basic ones:
  - addition of a column (`ALTER TABLE tab ADD ...`)
  - deletion of a column (`ALTER TABLE tab DROP COLUMN ...`)
  - modification of a column (`ALTER TABLE tab ALTER COLUMN ...`)
- This is a syntax used by SQL Server
- Oracle and MySQL use `MODIFY` instead of `ALTER COLUMN`



## The ALTER TABLE Statement - examples

- *Let us add a column of the type `numeric(6,2)` for a salary to the table `Person`.*

```
ALTER TABLE Person  
ADD salary numeric(6,2)
```

- *However, the `salary` column is not enough now and we need to extend the range by 2 digits.*

```
ALTER TABLE Person  
ALTER COLUMN salary numeric(8,2)
```

- *But finally, we decide to delete the `salary` column for some reason.*

```
ALTER TABLE Person  
DROP COLUMN salary
```

## The ALTER TABLE Statement - examples

- *Let us add a column of the type `numeric(6,2)` for a salary to the table `Person`.*

```
ALTER TABLE Person  
ADD salary numeric(6,2)
```

- *However, the `salary` column is not enough now and we need to extend the range by 2 digits.*

```
ALTER TABLE Person  
ALTER COLUMN salary numeric(8,2)
```

- *But finally, we decide to delete the `salary` column for some reason.*

```
ALTER TABLE Person  
DROP COLUMN salary
```

## The ALTER TABLE Statement - examples

- *Let us add a column of the type `numeric(6,2)` for a salary to the table `Person`.*

```
ALTER TABLE Person  
ADD salary numeric(6,2)
```

- *However, the `salary` column is not enough now and we need to extend the range by 2 digits.*

```
ALTER TABLE Person  
ALTER COLUMN salary numeric(8,2)
```

- *But finally, we decide to delete the `salary` column for some reason.*

```
ALTER TABLE Person  
DROP COLUMN salary
```

# The DROP TABLE Statement

- Deletion of a table including its definition:

```
DROP TABLE table
```

- Deletion of a table is not allowed when some foreign key refers to it

# The DROP TABLE Statement

- Deletion of a table including its definition:

```
DROP TABLE table
```

- Deletion of a table is not allowed when some foreign key refers to it

## Renaming of a Table or a Column

- How to rename a table:

```
RENAME TABLE original_table TO new_table
```

- How to rename a column:

```
RENAME COLUMN original_column TO new_column
```

- However, these SQL commands are not supported by SQL Server and they are replaced by `sp_rename`:

- `sp_rename 'puvodni_tabulka', 'nova_tabulka'`
- `sp_rename 'tab.puvodni_sloupec', 'nova_sloupec'`

## Renaming of a Table or a Column

- How to rename a table:

```
RENAME TABLE original_table TO new_table
```

- How to rename a column:

```
RENAME COLUMN original_column TO new_column
```


- However, these SQL commands are not supported by SQL Server and they are replaced by `sp_rename`:

- `sp_rename 'puvodni_tabulka', 'nova_tabulka'`
- `sp_rename 'tab.puvodni_sloupec', 'nova_sloupec'`

# CREATE INDEX

```
CREATE INDEX index_name ON table(attributes)
```

- It creates a B+tree having `attributes` are the key
- B+tree helps fast seek of a row according to the key
- It is used automatically






# CREATE INDEX

```
CREATE INDEX index_name ON table(attributes)
```

- It creates a B+tree having `attributes` are the key
- B+tree helps fast seek of a row according to the key
- It is used automatically
- ```
CREATE INDEX ix_student  
ON Student (name)
```

```
SELECT * FROM Student  
WHERE name = 'Tonda'
```



# Indexes

- There are many types of indexes:
  - B+tree
  - Hash table
  - Bitmap
  - R-tree and much more
- + Speed up queries
- Slow down insert/updates/deletes

# INSERT - adds records

- Adding one record:

```
INSERT INTO table  
VALUES (value1, ..., valuem)
```

where the *table* has *m* attributes

- Adding records from an existing relation:

```
INSERT INTO table  
SELECT ... FROM ...
```

where the result of the query has to have the same number of attributes as the *table* and also the data types have to mutually correspond

## INSERT - adds records

- Adding one record:

```
INSERT INTO table  
VALUES (value1, ..., valuem)
```

where the *table* has *m* attributes

- Adding records from an existing relation:

```
INSERT INTO table  
SELECT ... FROM ...
```

where the result of the query has to have the same number of attributes as the *table* and also the data types have to mutually correspond


# DELETE - removes records

- **DELETE FROM** *table*  
**WHERE** *condition*
- The condition can be relatively complicated
- The condition can contain subqueries, aggregate functions, etc.

## UPDATE - changes records


- **UPDATE** *table*  
**SET**  $A_1 = expr_1, \dots, A_n = expr_n$   
**WHERE** *condition*
- Similarly to DELETE, the condition can be relatively complicated

## Example 1: Simple adding



- *Insert into the database a student called Alex.*
  - `INSERT INTO Student`  
`VALUES (9, 'Alex', NULL)`
  - The `sID` of the student is chosen as the first available (unused) `sID` in the `Student` table
  - When running this statement repeatedly, we get an error reporting a conflict with the primary key constraint


## Example 1: Simple adding



- *Insert into the database a student called Alex.*
  - `INSERT INTO Student`  
`VALUES (9, 'Alex', NULL)`
  - The `sID` of the student is chosen as the first available (unused) `sID` in the `Student` table
  - When running this statement repeatedly, we get an error reporting a conflict with the primary key constraint




## Example 2: INSERT and SELECT




- *Add all students to a subject with suID 4 for the year 2012.*
  - `INSERT INTO Studies`  
`SELECT sid, 4, 2012, NULL FROM Student`
  - We can see that the scheme of the result of the SELECT query has to correspond to the scheme of the Studies table
  - Therefore, four attributes of the integer data type have to be in the result

## Example 2: INSERT and SELECT




- *Add all students to a subject with sulD 4 for the year 2012.*
  - `INSERT INTO Studies`  
`SELECT sID, 4, 2012, NULL FROM Student`
  - We can see that the scheme of the result of the `SELECT` query has to correspond to the scheme of the `Studies` table
  - Therefore, four attributes of the integer data type have to be in the result

## Example 2: INSERT and SELECT



- *Add all students to a subject with suID 4 for the year 2012.*
  - `INSERT INTO Studies`  
`SELECT sid, 4, 2012, NULL FROM Student`
  - We can see that the scheme of the result of the `SELECT` query has to correspond to the scheme of the `Studies` table
  - Therefore, four attributes of the integer data type have to be in the result

## Example 3: INSERT and SELECT




- *To the UDBS subject and for the year 2012, add all students who gained less than 51 points in 2011.*

```

INSERT INTO Studies
SELECT S.sID, S.suID, 2012, NULL
FROM Studies S, Subject Su
WHERE S.suID = Su.suID and Su.name = 'UDBS'
      and S.year = 2011
      and S.gained_points < 51
  
```

## Example 3: INSERT and SELECT




- *To the UDBS subject and for the year 2012, add all students who gained less than 51 points in 2011.*

```


INSERT INTO Studies
SELECT S.sID, S.suID, 2012, NULL
FROM Studies S, Subject Su
WHERE S.suID = Su.suID and Su.name = 'UDBS'
      and S.year = 2011
      and S.gained_points < 51
  
```

## Example 4: Simple delete




- *Remove a student with the sID 1 from the database.*
  - `DELETE FROM Studies WHERE sID = 1`
  - `DELETE FROM Student WHERE sID = 1`
  - First we have to delete the corresponding records from the `Studies` table and only then we can remove the student from the `Student` table

## Example 4: Simple delete



- *Remove a student with the sID 1 from the database.*
  - `DELETE FROM Studies WHERE sID = 1`
  - `DELETE FROM Student WHERE sID = 1`
  - First we have to delete the corresponding records from the `Studies` table and only then we can remove the student from the `Student` table


## Example 4: Simple delete



- *Remove a student with the sID 1 from the database.*
  - `DELETE FROM Studies WHERE sID = 1`
  - `DELETE FROM Student WHERE sID = 1`
  - First we have to delete the corresponding records from the **Studies** table and only then we can remove the student from the **Student** table



## Example 5: DELETE and SELECT




- Remove all students who gained twice less than 51 points in some subject.

```

DELETE FROM Studies WHERE sID in
    (SELECT Ss.sID FROM Student S, Studies Ss
    WHERE S.sID = Ss.sID and
        Ss.gained_points < 51
    GROUP BY Ss.sID, suID
    HAVING COUNT(*) >= 2)
  
```

## Example 5: DELETE and SELECT




- Remove all students who gained twice less than 51 points in some subject.

```

DELETE FROM Studies WHERE sID in
  (SELECT Ss.sID FROM Student S, Studies Ss
   WHERE S.sID = Ss.sID and
        Ss.gained_points < 51
   GROUP BY Ss.sID, suID
   HAVING COUNT(*) >= 2)
  
```


## Example 6: Simple update



- *Set all students' gained\_points to 90 for all subjects they studied in 2011.*

```
UPDATE Studies
SET gained_points = 90
WHERE year = 2011
```


## Example 6: Simple update



- *Set all students' gained\_points to 90 for all subjects they studied in 2011.*

```
UPDATE Studies
SET gained_points = 90
WHERE year = 2011
```

## Example 7: UPDATE and SET with SELECT




- For all subjects studied in 2011 and all students, set `gained_points` to the minimum of points gained (among all students) in 2010.

```

UPDATE Studies
SET gained_points =
    (SELECT MIN(gained_points) FROM Studies
     WHERE year = 2010)
WHERE year = 2011
  
```


- Note that the second condition corresponds to the `UPDATE` statement, while the first one is a part of `SELECT`

## Example 7: UPDATE and SET with SELECT



- For all subjects studied in 2011 and all students, set *gained\_points* to the minimum of points gained (among all students) in 2010.
  - UPDATE Studies  
 SET *gained\_points* =  
     (SELECT MIN(*gained\_points*) FROM Studies  
       WHERE *year* = 2010)  
 WHERE *year* = 2011
  - Note that the second condition corresponds to the UPDATE statement, while the first one is a part of SELECT

## Example 8: UPDATE and SET with alias




- For all subjects studied in 2011 and all students, set `gained_points` to the minimum of points gained by the corresponding student in 2010.

```

UPDATE s1
SET s1.gained_points =
    (SELECT MIN(gained_points) FROM Studies
     WHERE year = 2010 and sID = s1.sID)
FROM Studies s1
WHERE s1.year = 2011
  
```

## Example 8: UPDATE and SET with alias



- For all subjects studied in 2011 and all students, set `gained_points` to the minimum of points gained by the corresponding student in 2010.

```

UPDATE s1
SET s1.gained_points =
    (SELECT MIN(gained_points) FROM Studies
     WHERE year = 2010 and sID = s1.sID)
FROM Studies s1
WHERE s1.year = 2011
  
```



## DELETE, UPDATE, and foreign keys

- In some cases, removing or changing records can be forbidden by the database system
- For example, if we run the statement

```
DELETE FROM Studies
```

we get the following error report in the SQL Server:

**The DELETE statement conflicted with the REFERENCE constraint ...**

- We cannot remove students if there are records about their study in the `Studies` table which refer to them
- So first it is necessary to remove the corresponding records from the `Studies` table
- The above holds analogously also for UPDATE

## References

- W3C Schools, SQL Tutorial.  
<http://www.w3schools.com/sql/default.asp>
- Jennifer Widom. Introduction to Databases.  
<https://www.coursera.org/course/db>
- Course home pages <http://dbedu.cs.vsb.cz>