

## Input

- The **possible** commands are:
  - "Done"
  - "Change {char} {replacement}"
  - "Includes {substring}"
  - "End {substring}"
  - "Uppercase"
  - "FindIndex {char}"
  - "Cut {startIndex} {count}"

## Output

- The **possible** outputs are:
  - "True"
  - "False"

## Examples

Input	Output
//Th1s 1s my string!// Change 1 i Includes string End my Uppercase FindIndex I Cut 5 5 Done	//This is my string!// True False //THIS IS MY STRING!// 4 S IS
*S0ftUni is the B3St Plac3** Change 2 o Includes best End is Uppercase FindIndex P Cut 3 7 Done	*S0ftUni is the B3St Plac3** False False *S0FTUNI IS THE B3ST PLAC3** 21 FTUNI I

## JS Examples

The input will be provided as an array of strings.

Input	Output
-------	--------

<pre>(["//Th1s 1s my str1ng!//", "Change 1 i", "Includes string", "End my", "Uppercase", "FindIndex I", "Cut 5 5", "Done"])</pre>	<pre>//This is my string// True False //THIS IS MY STRING// 4 S IS</pre>
<pre>(["*S0ftUni is the B3St Plac3**", "Change 2 o", "Includes best", "End is", "Uppercase", "FindIndex P", "Cut 3 7", "Done"])</pre>	<pre>*S0ftUni is the B3St Plac3** False False *S0FTUNI IS THE B3ST PLAC3** 21 FTUNI I</pre>