

## Problem 3 - P!rates

Problem for exam preparation for the [Programming Fundamentals Course @SoftUni](#).  
Submit your solutions in the SoftUni judge system at <https://judge.softuni.org/Contests/Practice/Index/2302#2>.

*Anno 1681. The Caribbean. The golden age of piracy. You are a well-known pirate captain by the name of Jack Daniels. Together with your comrades Jim (Beam) and Johnny (Walker), you have been roaming the seas, looking for gold and treasure... and the occasional killing, of course. Go ahead, target some wealthy settlements and show them the pirate's way!*

Until the **"Sail"** command is given, you will be receiving:

- You and your crew have targeted **cities**, with their **population** and **gold**, separated by **" | "**.
- If you receive a city that has already been received, you have to increase the population and gold with the given values.

After the **"Sail"** command, you will start receiving lines of text representing events until the **"End"** command is given.

Events will be in the following format:

- **"Plunder=>{town}=>{people}=>{gold}"**
  - You have successfully attacked and plundered the town, killing the given number of people and stealing the respective amount of gold.
  - For every town you attack print this message: **"{town} plundered! {gold} gold stolen, {people} citizens killed."**
  - If any of those two values (population or gold) **reaches zero**, the town is disbanded.
    - You need to **remove it** from your collection of targeted cities and print the following message: **"{town} has been wiped off the map!"**
  - There will be no case of receiving more people or gold than there is in the city.
- **"Prosper=>{town}=>{gold}"**
  - There has been dramatic economic growth in the given city, **increasing its treasury** by the given amount of gold.
  - The gold amount **can be a negative number, so be careful**. If a negative amount of gold is given, print: **"Gold added cannot be a negative number!"** and ignore the command.
  - If the given gold is a valid amount, increase the town's gold reserves by the respective amount and print the following message:

**"{gold added} gold added to the city treasury. {town} now has {total gold} gold."**

### Input

- On the first lines, until the **"Sail"** command, you will be receiving strings representing the cities with their gold and population, separated by **" | "**
- On the following lines, until the **"End"** command, you will be receiving strings representing the actions described above, separated by **"=>"**

## Output

- After receiving the "End" command, if there are any existing settlements on your list of targets, you need to print all of them, in the following format:

"Ahoy, Captain! There are {count} wealthy settlements to go to:

{town1} -> Population: {people} citizens, Gold: {gold} kg

{town2} -> Population: {people} citizens, Gold: {gold} kg

...

{town...n} -> Population: {people} citizens, Gold: {gold} kg"

- If there are no settlements left to plunder, print:

"Ahoy, Captain! All targets have been plundered and destroyed!"

## Constraints

- The initial population and gold of the settlements will be valid 32-bit integers, never negative, or exceed the respective limits.
- The town names in the events will always be valid towns that should be on your list.

## Examples

Input	Output
Tortuga 345000 1250 Santo Domingo 240000 630 Havana 410000 1100 Sail Plunder=>Tortuga=>75000=>380 Prosper=>Santo Domingo=>180 End	Tortuga plundered! 380 gold stolen, 75000 citizens killed.  180 gold added to the city treasury. Santo Domingo now has 810 gold.  Ahoy, Captain! There are 3 wealthy settlements to go to:  Tortuga -> Population: 270000 citizens, Gold: 870 kg Santo Domingo -> Population: 240000 citizens, Gold: 810 kg  Havana -> Population: 410000 citizens, Gold: 1100 kg
Input	Output

Nassau  95000  1000	Gold added cannot be a negative number!
San Juan  930000  1250	Nassau plundered! 750 gold stolen, 94000 citizens killed.
Campeche  270000  690	Nassau plundered! 150 gold stolen, 1000 citizens killed.
Port Royal  320000  1000	Nassau has been wiped off the map!
Port Royal  100000  2000	Campeche plundered! 690 gold stolen, 150000 citizens killed.
Sail	Campeche has been wiped off the map!
Prosper=>Port Royal=>-200	Ahoy, Captain! There are 2 wealthy settlements to go to:
Plunder=>Nassau=>94000=>750	San Juan -> Population: 930000 citizens, Gold: 1250 kg
Plunder=>Nassau=>1000=>150	Port Royal -> Population: 420000 citizens, Gold: 3000 kg
Plunder=>Campeche=>150000=>690	
End	

## JS Examples

Input	Output
(["Tortuga  345000  1250", "Santo Domingo  240000  630", "Havana  410000  1100", "Sail", "Plunder=>Tortuga=>75000=>380", "Prosper=>Santo Domingo=>180", "End"])	Tortuga plundered! 380 gold stolen, 75000 citizens killed.  180 gold added to the city treasury. Santo Domingo now has 810 gold.  Ahoy, Captain! There are 3 wealthy settlements to go to:  Tortuga -> Population: 270000 citizens, Gold: 870 kg  Santo Domingo -> Population: 240000 citizens, Gold: 810 kg  Havana -> Population: 410000 citizens, Gold: 1100 kg
Input	Output

<pre>(["Nassau  95000  1000", "San Juan  930000  1250", "Campeche  270000  690", "Port Royal  320000  1000", "Port Royal  100000  2000", "Sail", "Prosper=&gt;Port Royal=&gt;-200", "Plunder=&gt;Nassau=&gt;94000=&gt;750", "Plunder=&gt;Nassau=&gt;1000=&gt;150", "Plunder=&gt;Campeche=&gt;150000=&gt;690", "End"])</pre>	<p>Gold added cannot be a negative number!</p> <p>Nassau plundered! 750 gold stolen, 94000 citizens killed.</p> <p>Nassau plundered! 150 gold stolen, 1000 citizens killed.</p> <p>Nassau has been wiped off the map!</p> <p>Campeche plundered! 690 gold stolen, 150000 citizens killed.</p> <p>Campeche has been wiped off the map!</p> <p>Ahoy, Captain! There are 2 wealthy settlements to go to:</p> <p>San Juan -&gt; Population: 930000 citizens, Gold: 1250 kg</p> <p>Port Royal -&gt; Population: 420000 citizens, Gold: 3000 kg</p>
---	---