

Inputs

- The possible commands are:
 - "Add - {phone}"
 - "Remove - {phone}"
 - "Bonus phone - {oldPhone}:{newPhone}"
 - "Last - {phone}"
 - "End"

Examples

Input	Output
SamsungA50, MotorolaG5, IphoneSE Add - Iphone10 Remove - IphoneSE End	SamsungA50, MotorolaG5, Iphone10
HuaweiP20, XiaomiNote Remove - Samsung Bonus phone - XiaomiNote:Iphone5 End	HuaweiP20, XiaomiNote, Iphone5
SamsungA50, MotorolaG5, HuaweiP10 Last - SamsungA50 Add - MotorolaG5 End	MotorolaG5, HuaweiP10, SamsungA50

JS Examples

The input will be an array of strings.

Input	Output
(["SamsungA50, MotorolaG5, IphoneSE", "Add - Iphone10", "Remove - IphoneSE", "End"])	SamsungA50, MotorolaG5, Iphone10
(["HuaweiP20, XiaomiNote", "Remove - Samsung", "Bonus phone - XiaomiNote:Iphone5", "End"])	HuaweiP20, XiaomiNote, Iphone5
(["SamsungA50, MotorolaG5, HuaweiP10", "Last - SamsungA50", "Add - MotorolaG5", "End"])	MotorolaG5, HuaweiP10, SamsungA50

