AXSOS ACADEMY

Problem-Solving Patterns Find the Missing Numbers





Outline

- Introduce the topic to the academy team including Idea, Problem statement, and solution. (15 Minutes)
- Practice a challenge with the team. (15 Minutes)
- Take feedback from the team and update later the slides and confluence accordingly. (10 Minutes)
- Team to evaluate the session. (5 Minutes)

Total time: 45 Minutes



What is a Cyclic sort pattern?

- Cyclic sort is used for coding problems that involve arrays of numbers with a given range (from 1 to n).
- What do we mean by arrays with a given range??
- Include only the element from the given range.



What is a Cyclic sort pattern?

- Example: An array with a given range from 1 to 6.
- Unsorted array within a given range from 1 to 6.

4 2 6 3 5 1



What is a Cyclic sort pattern?

Sorted array within a given range from 1 to 6.

1 2 3 4 5 6

• Unsorted array without a given range from 1 to 6.

3 59 6 11 4 2



Problem Statement

Given an unsorted array containing numbers taken from the range 1 to 'n'.
 The array can have duplicates, which means some numbers will be missing. Find all those missing numbers.



Solution

Brute-Force solution indicates iterating two for loops.

• B-F Time complexity: $O(N^2)$ Not accepted!

Do we have a better solution??




Solution

- Let's check the below-recommended solution.
- What if we apply the cyclic sort that we started with in the previous session?
- After that we iterate the array and check if the value equal index + 1 (because it started from 1 to n)



Solution

• Example: [4, 3, 2, 7, 8, 2, 3, 1]





Solution code

```
function cyclic_sort(arr){
        let i = 0
 4
        var count = 0;
        while ( i < arr.length){
            var newspot = arr[i] - 1;
            if ( arr[i] !== arr[newspot]){
 8
                var newvalue = arr[i];
 9
                arr[i] = arr[newspot]
10
                arr[newspot] = newvalue;
11
                count++;
                console.log(count)
12
13
            }else{
                i++;
14
15
                count++;
16
                console.log(count)
            }
17
18
19
        missingNumbers = []
20
        for ( i = 0; i < arr.length; i++){
21
22
            if ( arr[i] !== i+1){
23
                missingNumbers.push(i+1);
24
            }
25
        }
26
        console.log("Final "+count)
27
28
        return missingNumbers;
29 }
```



Time & Space complexity

• Time complexity: O(N)

• Space complexity: O(1)



Team Practice

- Let's go to the below link:
- https://leetcode.com/problems/find-all-numbers-disappeared-in-anarray/description/

Time to solve is 15 minutes.

Feedback









- Let us evaluate this session by filling out the survey.
- https://forms.office.com/e/nYjZHFtsPV

The aim of the evaluation is to enhance the content.





Zettachring 6 · 70567 Stuttgart Fon +49 711.901196 0 Fax +49 711.901196 111

Ougarit Bld. 1st floor · Al Irsal Street · Al Masayef · Ramallah Fon +970 2 2988350 Fax +970 2 2988364 Daimlerstraße 17/1 · 72581 Dettingen an der Erms Fon +49 711.901196 0 Fax +49 711.901196 111

19 Hartom Street · Har Hotzvim · Jerusalem Fon +970 2 2988350 Fax +970 2 2988364

Neuenhofer Str. 11 · 42657 Solingen Fon +49 212.2245505 0 Fax +49 212.2245505 110

Karatasou 7 · 54627 Thessaloniki Fon +49 711.901196 0 Fax +49 711.901196 111