



EXECUTIVE PILOT PROPOSAL

90-Day BreatheAtrium Pilot

A concise pilot path for facility managers and building owners with overheated atriums, using solar-assisted natural ventilation as a mixed-mode comfort and cooling-burden retrofit.

TARGET CUSTOMER

Facility teams responsible for hot atriums

Facility managers and building owners operating malls, universities, government offices, hotels, office towers, or transport hubs with glass atriums that overheat during occupied periods.

PROBLEM

Heat build-up becomes an operating burden

Hot upper layers, occupant discomfort, weak air movement, and higher cooling burden can make atriums expensive to operate and difficult to keep comfortable.

PROPOSED INTERVENTION

Passive-first retrofit, measured before claims

Audit, sensor mapping, solar-assisted ventilation design, low-level intake, high-level exhaust, optional water-wall or evaporative assist, and BMS integration for mixed-mode operation.

Audit

Sensor mapping

Solar-assisted design

Low-level intake

High-level exhaust

Optional water wall

BMS integration

Dashboard

Verification report

PILOT SCOPE

Twelve weeks from baseline to scale decision

WEEK 1-2

Audit and baseline measurement

Site walk-through, heat-risk mapping, sensor placement plan, and pre-install temperature, humidity, CO₂, airflow, and cooling-energy proxy baseline.

WEEK 3-6

Prototype or retrofit installation

Low-level intake path, high-level exhaust path, solar-assisted ventilation design, optional water-wall assessment, and BMS coordination.

WEEK 7-10

Monitored operation

Operate the passive-first mode, watch comfort indicators, tune control assumptions, and keep a facilities log of operational observations.

WEEK 11-12

Verification and scale decision

Compare baseline and operating periods, summarize findings, document constraints, and decide whether to scale, redesign, or stop.

Pilot decision pack

KPIS

What will be measured

- Temperature stratification reduction
- Occupied-zone comfort improvement
- Airflow improvement
- CO2 / ventilation trend
- Cooling energy proxy
- User feedback

COMMERCIAL MODEL

Clear buyer path

- Paid feasibility audit
- Pilot fee
- Full retrofit package
- Monitoring subscription

THE ASK

Access and approval

- Pilot atrium access
- Researcher support
- Facility manager contact
- Permission to install sensors

DISCLAIMER

Measured evidence before scale

Results depend on site conditions and require measurement. Savings and comfort improvements should only be claimed after site audit, sensor measurement, and post-install verification.

SCALE DECISION

Approve, redesign, or stop

The pilot closes with a concise verification report: what improved, what did not, what site constraints matter, and whether the atrium is ready for a full retrofit package.

FACILITY APPROVAL

Decision gate

**FACILITY
MANAGER**

PILOT SPONSOR