	FUNCIONAR	IOS	H_FUNCIONARIOS		
Р	* fun_id	NUMBER (6)	P * hfun_id	NUMBER (6)	
	<ul><li>fun_matricula</li></ul>	VARCHAR2 (255)	hfun_matricula	VARCHAR2 (255)	
	* fun_primeiro_nome	VARCHAR2 (15)	hfun_primeiro_nome	VARCHAR2 (255)	
	fun_nome_meio	VARCHAR2 (30)	hfun_nome_meio	VARCHAR2 (255)	
	* fun_ultimo_nome	VARCHAR2 (15)	hfun_ultimo_nome	VARCHAR2 (255)	
	* fun_data_nascimento	DATE	hfun_data_nascimento	DATE	
	* fun_sexo	CHAR (1)	hfun_sexo	CHAR (1)	
	* fun_telefone_residencial	VARCHAR2 (255)	hfun_telefone_residencial	VARCHAR2 (255)	
	* fun_telefone_movel	VARCHAR2 (255)	hfun_telefone_movel	VARCHAR2 (255)	
	* fun_data_contratacao	DATE	hfun_data_contratacao	DATE	
	* fun_car_id	NUMBER (6)	hfun_car_id	NUMBER (6)	
	* fun_salario	NUMBER (8,2)	hfun_salario	VARCHAR2 (255)	
	* fun_dep_id	NUMBER (6)	hfun_dep_id	NUMBER (6)	
	<pre>* fun_tur_id</pre>	NUMBER (6)	hfun_tur_id	NUMBER (6)	
	* fun_end_cep	VARCHAR2 (255)	hfun_end_cep	VARCHAR2 (255)	
	* fun_end_logradouro	VARCHAR2 (255)	hfun_end_logradouro	VARCHAR2 (255)	
	* fun_end_numero	VARCHAR2 (255)	hfun_end_numero	VARCHAR2 (255)	
	* fun_end_complemento	VARCHAR2 (255)	hfun_end_complemento	VARCHAR2 (255)	
	* fun_end_bairro	VARCHAR2 (255)	hfun_end_bairro	VARCHAR2 (255)	
	* fun_cid_id	NUMBER (6)	hfun_cid_id	NUMBER (6)	
( <u>G</u> )	⇒ PK FUN (fun id)		P * hfun_dt_entrada	TIMESTAMP	
	PK_HFUN (hfun_id, hfun_dt_entrada)				