

# Elementary Operations on Quasi-Toeplitz Matrices

PCCA6

Ali Arda BARUT  
Rafael LLAMAS

May 20, 2026

## Contents

|          |                                                                 |          |
|----------|-----------------------------------------------------------------|----------|
| <b>1</b> | <b>Introduction</b>                                             | <b>2</b> |
| 1.1      | Foundations of Toeplitz and Quasi-Toeplitz Structures . . . . . | 2        |
| 1.1.1    | Toeplitz Matrices . . . . .                                     | 2        |
| 1.1.2    | Quasi-Toeplitz Matrices . . . . .                               | 2        |
| 1.1.3    | Displacement Matrices . . . . .                                 | 2        |
| 1.1.4    | Mathematical Approach . . . . .                                 | 3        |
| 1.1.5    | Computational Approach . . . . .                                | 3        |
| 1.1.6    | Generator Matrices and Reconstruction . . . . .                 | 3        |
| 1.1.7    | Displacement Operators . . . . .                                | 4        |
| <b>2</b> | <b>Operation</b>                                                | <b>4</b> |
| 2.1      | Addition . . . . .                                              | 4        |
| 2.1.1    | Introduction . . . . .                                          | 4        |
| 2.1.2    | Exemple . . . . .                                               | 4        |
| 2.1.3    | Benchmark . . . . .                                             | 5        |
| 2.2      | Multiplication . . . . .                                        | 5        |
| 2.2.1    | Introduction . . . . .                                          | 5        |
| 2.2.2    | Multiplication Vecteur . . . . .                                | 6        |
| 2.2.3    | Exemple . . . . .                                               | 7        |
| 2.2.4    | Benchmark . . . . .                                             | 8        |
| <b>3</b> | <b>Generator Compression</b>                                    | <b>8</b> |
| <b>4</b> | <b>Inversion</b>                                                | <b>9</b> |
| 4.1      | Introduction . . . . .                                          | 9        |
| 4.1.1    | Split and Pack quadrants from displacement generators . . . . . | 11       |
| 4.1.2    | Conclusion . . . . .                                            | 15       |

# 1 Introduction

In computational numerical linear algebra, dense matrices often present a computational bottleneck, scaling quadratically in terms of memory usage ( $O(nm)$ ) on a matrix with  $n$  rows and  $m$  columns and cubically in terms of time complexity ( $O(n^3)$ ) for standard operations. However, these structured matrices are utilised by a wide class of systems such as signal processing[3][6] applications and classical quantum simulation[7]. In these systems, the elements are arranged in repeating, deterministic patterns. Designing algorithms that take advantage of this pattern can bypass the fundamental limitations of dense linear algebra.

## 1.1 Foundations of Toeplitz and Quasi-Toeplitz Structures

### 1.1.1 Toeplitz Matrices

A Toeplitz matrix is characterized by the property that all elements along any given diagonal are identical. For a matrix  $A \in \mathbb{K}^{n \times m}$ , it satisfies the condition  $A_{i,j} = A_{i+1,j+1}$ . In other words, a Toeplitz matrix is one in which each element in the first row and first column descends diagonally. It can be represented by a sequence of elements  $\{a_k\}$  such that:

$$A = \begin{pmatrix} a_{0,0} & a_{0,1} & a_{0,2} & \cdots & \cdots & a_{0,(m-3)} & a_{0,(m-2)} & a_{0,(m-1)} \\ a_{1,0} & a_{0,0} & a_{0,1} & \ddots & & \cdots & a_{0,(m-3)} & a_{0,(m-2)} \\ a_{2,0} & a_{1,0} & a_{0,0} & \ddots & \ddots & & \cdots & a_{0,(m-3)} \\ \vdots & \vdots & \vdots & \ddots & \ddots & \ddots & & \vdots \\ a_{(n-1),0} & a_{(n-2),0} & a_{(n-3),0} & \cdots & a_{0,0} & a_{0,1} & a_{0,2} & \cdots & a_{0,m-(n-1)} \end{pmatrix}$$

$$A_{i,j} = a_{i-j}, \quad 0 \leq i < n, \quad 0 \leq j < m$$

### 1.1.2 Quasi-Toeplitz Matrices

A Quasi-Toeplitz matrix generalizes the Toeplitz structure by allowing a correction term of finite rank. Formally, a matrix  $A$  is Quasi-Toeplitz if it can be written as  $A = T + E$ , where  $T$  is a Toeplitz matrix and  $E$  is a correction matrix with  $\text{rank}(E) < \infty$  [1].

### 1.1.3 Displacement Matrices

For a matrix  $A \in \mathbb{K}^{n \times m}$ , we define the displacement matrix  $\nabla A$  using:

$$\nabla A = A - ZAZ^T \tag{1}$$

where  $Z$  represents the lower shift matrix and  $Z^T$  represents the upper shift matrix. Essentially,  $Z$  is a matrix with ones on the first sub-diagonal and zeros everywhere else:

$$Z = \begin{pmatrix} 0 & 0 & 0 & \cdots & \cdots & 0 \\ 1 & 0 & 0 & \cdots & \cdots & 0 \\ 0 & 1 & 0 & \cdots & \cdots & 0 \\ \vdots & \vdots & \ddots & \ddots & & \vdots \\ \vdots & \vdots & & \ddots & \ddots & \vdots \\ 0 & 0 & \cdots & \cdots & 1 & 0 \end{pmatrix} \in \mathbb{K}^{n \times n}, \quad Z^T = \begin{pmatrix} 0 & 1 & 0 & \cdots & \cdots & 0 \\ 0 & 0 & 1 & \cdots & \cdots & 0 \\ 0 & 0 & 0 & \ddots & & \vdots \\ \vdots & \vdots & \vdots & & \ddots & \vdots \\ 0 & 0 & 0 & \cdots & \cdots & 1 \\ 0 & 0 & 0 & \cdots & \cdots & 0 \end{pmatrix} \in \mathbb{K}^{m \times m}$$

### 1.1.4 Mathematical Approach

For a generic Toeplitz matrix of size  $n \times m$ , this subtraction results in zeros everywhere except for the first row and the first column.

$$\nabla A = \begin{pmatrix} y_0 & x_1 & x_2 & \cdots & x_{m-1} \\ y_1 & 0 & 0 & \cdots & 0 \\ y_2 & 0 & 0 & \cdots & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots \\ y_{n-1} & 0 & 0 & \cdots & 0 \end{pmatrix} \in \mathbb{K}^{n \times m}$$

This allows us to represent the  $n \times m$  matrix using only  $O(n + m)$  elements rather than storing the full  $O(nm)$  dense matrix.

### 1.1.5 Computational Approach

While the definition in Equation (1) suggests a matrix on matrix subtraction with overhead, the structured nature of  $A$  allows for a more efficient computation. By leveraging the Toeplitz structure, displacement  $\nabla A$  can be computed via a loop:

$$(\nabla A)_{i,j} = \begin{cases} A_{i,j} & \text{if } i = 0 \text{ or } j = 0 \\ A_{i,j} - A_{i-1,j-1} & \text{otherwise} \end{cases} \quad (2)$$

In practice, we enable optimization through pointer arithmetics. By iterating from the bottom-right index  $(n, m)$  toward the origin  $(0, 0)$ , the displacement can be calculated in-place, resulting a complexity bound of  $O(nm)$ .

### 1.1.6 Generator Matrices and Reconstruction

While the displacement matrix  $\nabla A$  physically occupies an  $n \times m$  dense layout with the 0s, its low displacement rank ( $\alpha \leq 2$ ) allows  $A$  to be compressed and stored via a pair of smaller matrices known as generators, denoted as  $G \in \mathbb{K}^{n \times \alpha}$  and  $H \in \mathbb{K}^{m \times \alpha}$ , which satisfy:

$$\nabla A = GH^T \quad (3)$$

To reconstruct the uncompressed operator  $A$  directly from its generator columns  $g_k$  and  $h_k$  (for  $k = 1, \dots, \alpha$ ), we formalize the families of lower and upper triangular Toeplitz operators.

For a column vector  $v = [v_0, v_1, \dots, v_{n-1}]^T \in \mathbb{K}^n$ , we define the lower triangular Toeplitz operator  $L_n(v) \in \mathbb{K}^{n \times n}$  as the square matrix. Let  $U_{n,m}(w) \in \mathbb{K}^{n \times m}$  be the rectangular upper triangular Toeplitz operator generated by a vector  $w = [w_0, w_1, \dots, w_{m-1}]^T \in \mathbb{K}^m$ . This operator is formed by taking the first  $n$  rows of the fully square  $m \times m$  upper triangular matrix  $L_m(w)^T$ :

$$L_n(v) = \begin{pmatrix} v_0 & 0 & 0 & \cdots & 0 \\ v_1 & v_0 & 0 & \cdots & 0 \\ v_2 & v_1 & v_0 & \cdots & 0 \\ \vdots & \vdots & \ddots & \ddots & \vdots \\ v_{n-1} & v_{n-2} & \cdots & v_1 & v_0 \end{pmatrix} \quad U_{n,m}(w) = \begin{pmatrix} w_0 & w_1 & w_2 & \cdots & \cdots & w_{m-1} \\ 0 & w_0 & w_1 & \cdots & \cdots & w_{m-2} \\ 0 & 0 & w_0 & \cdots & \cdots & w_{m-3} \\ \vdots & \vdots & \ddots & \ddots & & \vdots \\ 0 & 0 & \cdots & 0 & w_0 & \cdots \end{pmatrix}$$

By denoting the individual columns of the generators as  $G = [g_1, \dots, g_\alpha]$  and  $H = [h_1, \dots, h_\alpha]$ , the displacement inversion theorem [2] establishes that the full matrix  $A$  can be synthesized as a sum of products of these triangular structures:

$$GH^T = \nabla A \quad \Longleftrightarrow \quad A = \sum_{k=1}^{\alpha} L_n(g_k) U_{n,m}(h_k) \quad (4)$$

### 1.1.7 Displacement Operators

We define two displacements operators:

$$\begin{aligned}\phi_+(A) &= A - ZAZ^T = \nabla A \\ \phi_-(A) &= A - Z^T AZ\end{aligned}$$

where  $Z$  is the downshift matrix defined in the previous section. The two operators differ in the direction of the operation:  $\phi_+$  operates by  $Z$  (a downshift), while  $\phi_-$  operates by  $Z^T$  (an upshift). For a Toeplitz matrix  $A$ , both operators gives a low-rank result, with  $\text{rank}(\phi_{\pm}(A)) \leq 2$ . Computationally, it follows the same path as the calculation of  $\nabla A$ . Main difference being we can run this time in increasing order:

$$\phi_-(A)_{i,j} = \begin{cases} A_{i,j} & \text{if } i = n - 1 \text{ or } j = m - 1 \\ A_{i,j} - A_{i+1,j+1} & \text{otherwise} \end{cases} \quad (5)$$

Where  $n$  and  $m$  are respectfully the number of rows and columns of matrix  $A$ .

## 2 Operation

### 2.1 Addition

#### 2.1.1 Introduction

With the displacement generators, we can simplify the addition of 2 matrices and thus reduce its cost by concatenating the generators of the 2 matrices. From the property 10.7 and 10.8, we can pass from  $O(n^2)$  for the naive algorithm to  $O(\alpha \times M(n))$  for the version that we implement. We need  $A=(T,U)$  and  $B=(G,H)$

---

#### Algorithm 1 Generator Addition

---

```

1: function GR_MAT_MUL_GENERATOR( $T, U, G, H$ )
2:    $G_C \leftarrow \text{GR\_MAT\_CONCAT\_HORIZONTAL}(T, G)$ 
3:    $H_C \leftarrow \text{GR\_MAT\_CONCAT\_HORIZONTAL}(U, H)$ 
4:   return  $G_C, H_C$ 
5: end function
```

---

#### 2.1.2 Exemple

We takes  $A$  and  $B$ , two randoms matrices,  $C$  the result we need to get of  $A$  and  $B$ . Every matrices are in  $Z/_{13}Z$ .

$$A = \begin{pmatrix} 0 & 7 & 10 \\ 5 & 0 & 7 \\ 0 & 5 & 0 \end{pmatrix}, B = \begin{pmatrix} 9 & 12 & 4 \\ 0 & 9 & 12 \\ 3 & 0 & 9 \end{pmatrix}, C = \begin{pmatrix} 9 & 6 & 1 \\ 5 & 9 & 6 \\ 3 & 5 & 9 \end{pmatrix} \quad (6)$$

If we takes displacement generator of  $A = (T,U)$  and  $B = (G,H)$

$$T = \begin{pmatrix} 0 & 1 \\ 1 & 0 \\ 0 & 0 \end{pmatrix}, U = \begin{pmatrix} 5 & 0 \\ 0 & 7 \\ 0 & 10 \end{pmatrix}, G = \begin{pmatrix} 1 & 0 \\ 0 & 0 \\ 9 & 1 \end{pmatrix}, H = \begin{pmatrix} 9 & 0 \\ 12 & 9 \\ 4 & 3 \end{pmatrix} \quad (7)$$

and we do the concatenation of T,G and U,H to obtain  $RES_G$  and  $RES_H$  (we have to do the concatenation in the order that I cited the elements).

$$RES_G = \begin{pmatrix} 0 & 1 & 1 & 0 \\ 1 & 0 & 0 & 0 \\ 0 & 0 & 9 & 1 \end{pmatrix}, RES_H = \begin{pmatrix} 5 & 0 & 9 & 0 \\ 0 & 7 & 12 & 9 \\ 0 & 10 & 4 & 3 \end{pmatrix} \quad (8)$$

The matrix that we get D :

$$D = \begin{pmatrix} 9 & 6 & 1 \\ 5 & 9 & 6 \\ 3 & 5 & 9 \end{pmatrix} \quad (9)$$

We can see that the matrix D is equal to C so our way to add the 2 matrices is correct in this case.

### 2.1.3 Benchmark

The benchmark obtained highlights the following results:

| $n$  | Generators (ms) | Flint Dense (ms) |
|------|-----------------|------------------|
| 128  | 3.577e-03       | 1.373e-02        |
| 1024 | 3.205e-02       | 2.52             |
| 4096 | 1.148e-01       | 29.18            |

Table 1: Median runtimes over 5 runs

(ici courbe des temps) blablabla...explication complexité...blablabla

## 2.2 Multiplication

### 2.2.1 Introduction

With displacement generators we also can simplify the multiplication of 2 matrices and thus reduce its cost by concatenating the generators of the 2 matrices. - The displacement generators  $A=(T,U)$  and  $B=(G,H)$

-  $W = Z \times A \times Z^t \times G$

-  $V = B^t \times U$

- a (resp. b) a vector which is the last column of  $Z \times A$  (resp.  $Z \times B^t$ )

This allows us to pass from  $O(n^3)$  for the naive algorithm to  $O(\alpha^2 \times M(n))$  for the version we implement.

**Algorithm 2** Generator Multiplication

---

```

1: function GR_MAT_MUL_GENERATOR( $T, U, G, H$ )
2:    $W_{Temp} \leftarrow \text{GR\_MAT\_APPLY\_ZT}(G)$ 
3:    $W \leftarrow \text{GR\_MAT\_MUL\_VECTOR}(T, U, W_{Temp})$ 
4:    $W \leftarrow \text{GR\_MAT\_APPLY\_Z}(W)$ 
5:    $V \leftarrow \text{GR\_MAT\_MUL\_VECTOR}(H, G, U)$ 
6:    $a \leftarrow \text{GR\_MAT\_MUL\_VECTOR}(T, U, LastCol)$ 
7:    $a \leftarrow \text{GR\_MAT\_APPLY\_Z}(a)$ 
8:    $b \leftarrow \text{GR\_MAT\_MUL\_VECTOR}(H, G, LastCol)$ 
9:    $b \leftarrow \text{GR\_MAT\_APPLY\_Z}(b)$ 
10:   $b \leftarrow \text{GR\_MAT\_NEG}(b)$ 
11:   $G_C \leftarrow \text{GR\_MAT\_CONCAT\_HORIZONTAL}(T, W, a)$ 
12:   $H_C \leftarrow \text{GR\_MAT\_CONCAT\_HORIZONTAL}(V, H, b)$ 
13:  return  $G_C, H_C$ 
14: end function

```

---

We use the vector

$$LastCol = \begin{pmatrix} 0 \\ 0 \\ \cdot \\ \cdot \\ \cdot \\ 0 \\ 1 \end{pmatrix} \quad (10)$$

in order to retrieve the last column of the matrix, this vector is composed of 0 except for the last element of the column which is fixed to 1.

### 2.2.2 Multiplication Vecteur

Perform the matrix multiplication with their displacement generators needs a function that multiplies a vector with displacement generators to avoid recomposing the matrices.

$$C = \sum_{k=1}^{\alpha} L(g_k) U(h_k) V \quad (11)$$

To do that, we takes the formula for the reconstruction and we transform our displacement generators into polynomials and make every operation into them.

**Algorithm 3** Multiplication de Matrice Structurée par un Vecteur/Matrice

---

```

1: function GR_MAT_MUL_VECTOR( $G, H, V$ )
2:    $n \leftarrow nbRows(G)$ 
3:    $m \leftarrow nbRows(H)$ 
4:   for  $j \leftarrow 0$  to  $nbCols(V)$  do
5:      $P_v \leftarrow \sum_{r=0}^{m-1} V[r, j]x^r$ 
6:     for  $k \leftarrow 0$  to  $nbCols(G)$  do
7:        $P_g \leftarrow \sum_{r=0}^{n-1} G[r, k]x^r$ 
8:        $P_h \leftarrow \sum_{r=0}^{m-1} H[r, k]x^r$ 
9:        $P_{h\_rev} \leftarrow \text{Reverse}(P_h, m)$ 
10:       $P_{tmp} \leftarrow P_{h\_rev}P_v$ 
11:       $P_{tmp\_shift} \leftarrow P_{tmp} \gg (m-1)$ 
12:       $P_{res} \leftarrow P_g P_{tmp\_shift}$ 
13:      for  $i \leftarrow 0$  to  $\text{Length}(P_{tmp2}) - 1$  do
14:         $C[i, j] \leftarrow C[i, j] + \text{Coefficient}(P_{res}, i)$ 
15:      end for
16:    end for
17:  end for
18:  return  $Res$ 
19: end function

```

---

**2.2.3 Exemple**

We takes A and B, two randoms matrices, C the result we need to get of A and B. Every matrices are in  $Z/_{13}Z$ .

$$A = \begin{pmatrix} 10 & 5 & 8 \\ 5 & 10 & 5 \\ 3 & 5 & 10 \end{pmatrix}, B = \begin{pmatrix} 0 & 3 & 0 \\ 3 & 0 & 3 \\ 0 & 3 & 0 \end{pmatrix}, C = \begin{pmatrix} 2 & 2 & 2 \\ 4 & 4 & 4 \\ 2 & 0 & 2 \end{pmatrix} \quad (12)$$

If we takes displacement generator of A = (T,U) and B = (G,H)

$$T = \begin{pmatrix} 1 & 0 \\ 7 & 1 \\ 12 & 11 \end{pmatrix}, U = \begin{pmatrix} 10 & 0 \\ 5 & 4 \\ 8 & 9 \end{pmatrix}, G = \begin{pmatrix} 0 & 1 \\ 1 & 0 \\ 0 & 0 \end{pmatrix}, H = \begin{pmatrix} 3 & 0 \\ 0 & 3 \\ 0 & 0 \end{pmatrix} \quad (13)$$

We need to calculate W and V before concatenating the generators of A and B to obtain the displacement generator of D.

$$W = \begin{pmatrix} 0 & 0 \\ 10 & 0 \\ 5 & 0 \end{pmatrix}, V = \begin{pmatrix} 2 & 12 \\ 2 & 1 \\ 2 & 12 \end{pmatrix} \quad (14)$$

Puis faire la concatenation de T,W et  $\alpha$  pour obtenir  $RES_G$  et la concatenation de V,H et  $\beta$  pour obtenir  $RES_H$  (il faut faire la concatenation dans l'ordre que j'ai cité les éléments).

$$RES_G = \begin{pmatrix} 1 & 0 & 0 & 0 & 0 \\ 7 & 1 & 10 & 0 & 8 \\ 12 & 11 & 5 & 0 & 5 \end{pmatrix}, RES_H = \begin{pmatrix} 2 & 12 & 3 & 0 & 0 \\ 2 & 1 & 0 & 3 & 0 \\ 2 & 12 & 0 & 0 & 10 \end{pmatrix} \quad (15)$$

La matrice que l'on a obtenue D :

$$D = \begin{pmatrix} 2 & 2 & 2 \\ 4 & 4 & 4 \\ 2 & 0 & 2 \end{pmatrix} \quad (16)$$



We can see that the matrix D is equal to C so our way to multiply the 2 matrices is correct in this case.

### 2.2.4 Benchmark

The benchmark obtained highlights the following results: (ici courbe des temps) blablabla...explication

| $n$  | Generators (ms) | Flint Dense (ms) | Vector (ms) | Vector Flint (ms) |
|------|-----------------|------------------|-------------|-------------------|
| 128  | 6.289e-01       | 3.032            | 1.221e-01   | 3.217e-02         |
| 1024 | 3.736           | 984.2            | 6.383e-01   | 1.554             |
| 4096 | 12.42           | 39810            | 2.063       | 17.63             |

Table 2: Median runtimes over 5 runs

complexité...blablabla

## 3 Generator Compression

Matrices  $G \in \mathbb{R}^{n \times \alpha}$  and  $H \in \mathbb{R}^{n \times \alpha}$  representing a displacement matrix  $\nabla A = GH^T$ , where the actual rank of  $\nabla A$  is  $r < \alpha$ .

**Goal:** Find generators  $G' \in \mathbb{R}^{n \times r}$  and  $H' \in \mathbb{R}^{n \times r}$  s.t. the product is the same:

$$G'H'^T = GH^T$$

We will achieve this by independently compression both matrices and applying the inverse of the operations done to the other.

---

#### Algorithm 4 Generator Compression

---

```

1: function GR_MAT_GENERATOR_COMPRESS( $G_A, H_A$ )
2:    $G_1, H_1 \leftarrow$  GR_MAT_GENERATOR_COMPRESS_AUX( $G_A, H_A$ )
3:    $H_D, G_D \leftarrow$  GR_MAT_GENERATOR_COMPRESS_AUX( $H_1, G_1$ )
4:   return  $G_D, H_D$ 
5: end function

```

---



---

#### Algorithm 5 Generator Compression Auxiliary

---

```

1: function GR_MAT_GENERATOR_COMPRESS_AUX( $G, H$ )
2:    $P, L, U \leftarrow$  LU_Decomposition( $G^T$ )  $\triangleright PG^T = LU$ 
3:    $r \leftarrow$  Number of non-zero rows in  $U$   $\triangleright$  rank
4:   if  $r < 1$  then
5:     return Generators of a 0 matrix
6:   end if
7:    $G_D \leftarrow (U_{[0:r-1],*})^T$ 
8:    $H_D \leftarrow HP^T \times L_{*,[0:r-1]}$ 
9:   return  $G_D, H_D$ 
10: end function

```

---

Note that calling GR\_MAT\_GENERATOR\_COMPRESS\_AUX twice with swapped arguments (and variables) is valid because each call preserves the product  $GH^T$ , as can be verified from the LU factorization.

*Proof.* We show that the second call to the auxiliary function preserves the generator product, meaning  $H_D G_D^T = H_1 G_1^T$ .

First argument is  $H_1$ , the LU decomposition is performed on  $H_1^T$  giving  $PH_1^T = LU$ . Since  $U$  has rank  $r$ , the product only depends on the first  $r$  columns and rows:  $LU = L_{*,[0:r-1]} U_{[0:r-1],*}$ . Starting from  $PH_1^T = LU$  and multiplying both sides on the left by  $P^T$ :

$$\begin{aligned} H_1^T &= P^T L_{*,[0:r-1]} U_{[0:r-1],*} \\ H_1 &= (U_{[0:r-1],*})^T L_{*,[0:r-1]}^T P \end{aligned}$$

Based on the swapped inputs to the auxiliary function, returned generators are assigned as  $H_D = (U_{[0:r-1],*})^T$  and  $G_D = G_1 P^T L_{*,[0:r-1]}$ . Taking the transpose of  $G_D$ :

$$G_D^T = (G_1 P^T L_{*,[0:r-1]})^T = L_{*,[0:r-1]}^T P G_1^T$$

For  $H_D G_D^T$ , we see  $H_1$  form:

$$\begin{aligned} H_D G_D^T &= (U_{[0:r-1],*})^T (L_{*,[0:r-1]}^T P G_1^T) \\ &= ((U_{[0:r-1],*})^T L_{*,[0:r-1]}^T P) G_1^T \\ &= H_1 G_1^T. \end{aligned}$$

Since  $H_D G_D^T = H_1 G_1^T$ , transposing gives us  $G_D H_D^T = G_1 H_1^T$ .  $\square$

Computing the LU factorization of the transposed generator  $G^T \in \mathbb{K}^{r \times n}$  requires  $\mathcal{O}(r^2 n)$  operations. Extracting  $U$  and applying the permutation matrix  $P^T$  to  $H$  is in  $\mathcal{O}(rn)$ . Computing the new right factor  $H_D = H P^T \times L_{*,[0:r-1]}$  involves multiplying an  $n \times k$  matrix by a  $k \times r$  matrix. Using standard matrix multiplication, this takes  $\mathcal{O}(r^2 n)$  operations. Our implementation is using loops to get the selected amount of rows and columns but their complexities are bounded by  $\mathcal{O}(r^2 n)$ .

We can generalize the complexity by revising for any matrix in  $\mathbb{K}^{m \times n}$  the overall time complexity for the generator compression is  $\mathcal{O}(rmn)$ .

Our implementation can be found in 4.1.2.

## 4 Inversion

### 4.1 Introduction

In this section we will study how we implemented Strassen's inversion method on displacement generators. Algorithm follows:

**Algorithm 7** Strassen-type Inversion for Displacement Generators (adapted from [2])

---

```

1: procedure STRASSENINVERSEGENERATORS( $G_A, H_A$ )
2:   if  $n = 1$  then ▷ Step 1: Base Case
3:     return  $G_D, H_D$  representing the inverse of the scalar value of  $A$  from  $G_A, H_A$ 
4:   end if

5:    $G_a, H_a, \dots, G_d, H_d \leftarrow \text{SPLITQUADRANTS}(G_A, H_A)$  ▷ Step 2: Split into Quadrants

6:    $G_e, H_e \leftarrow \text{STRASSENINVERSEGENERATORS}(G_a, H_a)$  ▷  $e := a^{-1}$  ▷ Step 3: Recursion
   #1

7:    $G_{ce}, H_{ce} \leftarrow \text{COMPRESS}(\text{MUL}(G_c, H_c, G_e, H_e))$  ▷ Step 4: Schur Complement
8:    $G_{eb}, H_{eb} \leftarrow \text{COMPRESS}(\text{MUL}(G_e, H_e, G_b, H_b))$ 
9:    $G_{ceb}, H_{ceb} \leftarrow \text{COMPRESS}(\text{MUL}(G_c, H_c, G_{eb}, H_{eb}) \times -1)$ 
10:   $G_S, H_S \leftarrow \text{COMPRESS}(\text{ADD}(G_d, H_d, G_{ceb}, H_{ceb}))$  ▷  $S := d - ceb$ 

11:   $G_t, H_t \leftarrow \text{STRASSENINVERSEGENERATORS}(G_S, H_S)$  ▷  $t := S^{-1}$  ▷ Step 5: Recursion
   #2

12:   $G_{ebt}, H_{ebt} \leftarrow \text{COMPRESS}(\text{MUL}(G_{eb}, H_{eb}, G_t, H_t))$  ▷ Step 6: Strassen Assembly
13:   $G_{tce}, H_{tce} \leftarrow \text{COMPRESS}(\text{MUL}(G_t, H_t, G_{ce}, H_{ce}))$ 
14:   $G_{ebtce}, H_{ebtce} \leftarrow \text{COMPRESS}(\text{MUL}(G_{ebt}, H_{ebt}, G_{ce}, H_{ce}))$ 

15:   $G_x, H_x \leftarrow \text{COMPRESS}(\text{ADD}(G_e, H_e, G_{ebtce}, H_{ebtce}))$  ▷  $x := e + ebtce$ 
16:   $G_y, H_y \leftarrow \text{NEGATE}(G_{ebt}, H_{ebt})$  ▷  $y := -ebt$ 
17:   $G_z, H_z \leftarrow \text{NEGATE}(G_{tce}, H_{tce})$  ▷  $z := -tce$ 

18:   $G_{Inv}, H_{Inv} \leftarrow \text{PACKQUADRANTS}(G_x, H_x, G_y, H_y, G_z, H_z, G_t, H_t)$  ▷ Step 7: Pack
19:  return  $\text{COMPRESS}(G_{Inv}, H_{Inv})$ 
20: end procedure

```

---

This algorithm is based on Algorithm 10.1 from [2, Algorithm 10.1]. Notice that we strictly operate on  $\Phi_+$  displacement and bypassing  $\Phi_-$  generators.

*Proof.* We proceed by induction on the size of the matrix  $n = 2k$ . Let  $\Phi_+(X) = X - ZXZ^T$  be the displacement operator.

**Base Case ( $n = 1$ ):** For a scalar matrix  $A = [a]$ , the operator  $Z$  is a  $1 \times 1$  zero matrix. The displacement of  $A$  is  $\Phi_+(A) = A - 0 \cdot A \cdot 0 = A$ .

**Inductive Step:** Consider a matrix  $A$  of size  $2k \times 2k$  represented by  $\Phi_+$  generators. The Strassen-type inversion relies on splitting the sub-blocks  $a, b, c, d$  which are represented by  $\Phi_+$  displacements, recursive calls to invert top-left block  $a$  ( $e = a^{-1}$ ) and another for the Schur complement  $t = S^{-1}$  and each outputs a  $\Phi_+$  generator. Lastly, multiplication and addition algorithms are taking a generator of  $\Phi_+$  displacement and returns a generator of  $\Phi_+$  displacement. Each computation and the final assembly remain in  $\Phi_+$  displacement.

**Conclusion:** Because the base case returns the inverse to  $\Phi_+$  generators, and the arithmetics are on  $\Phi_+$  generator operations, by induction, we maintain  $\Phi_+$  displacement during the entire

execution. □

#### 4.1.1 Split and Pack quadrants from displacement generators

Any Strassen-type divide and conquer algorithm will divide the problem to create sub-problems to economise in complexity. This type of approach on displacement generators require arithmetic operations to ensure the data stability during execution.

Main concern regarding this approach for our implementation of Toeplitz matrices in this project is that the algorithm doesn't have direct access to the dense matrix  $A$ . Any splitting and packing operation done will be on the generators  $G_A$  and  $H_A$  which represent the matrix entirely by default. Challenge of applying this split and pack comes from the displacement operator  $\Phi_+$  affecting the dense matrix entirely.

Let a dense matrix  $A$  be split into four quadrants:

$$A = \begin{pmatrix} a & b \\ c & d \end{pmatrix}$$

The shift operator  $Z$  acts on the entire matrix resulting elements from blocks to cross its boundaries. Precisely the last column of  $a$  shifted down into  $b$ . Last row of  $a$  shifted down into  $c$ . Last row of  $b$ , last column of  $c$  and the bottom-right element of  $a$  shifted down into  $d$ .

When we attempt to evaluate the local displacement of a sub-block (for example,  $\Phi_+(d)$ ), we cannot simply extract the rows from the global generators  $G_A$  and  $H_A$ . The global generators are corrupted by the boundary elements of  $a$  that shifted into  $b$  and  $c$ .

To correctly split or pack the generators without having access to the dense matrix  $A$ , we must mathematically isolate and correct these boundary crossings which we call bleeding.

**Splitting:** During the Split, our goal is to extract the generators for the sub-blocks  $a, b, c, d$  using only the global generators  $G_A$  and  $H_A$ .

We start by splitting literally the generators  $G_A$  and  $H_A$ :

$$G = \begin{pmatrix} G_{TOP} \\ G_{BOTTOM} \end{pmatrix}, \quad H = \begin{pmatrix} H_{TOP} \\ H_{BOTTOM} \end{pmatrix}$$

We define  $n_1 = \text{ceil}(n/2)$  and  $n_2 = \text{floor}(n/2)$ . Let  $G_{TOP}$  and  $H_{TOP}$  be a matrix of size  $n_1 \times \text{rank}$  and  $G_{BOTTOM}$  and  $H_{BOTTOM}$  be a matrix of size  $n_2 \times \text{rank}$ . This allows us to create a split dimension which handles odd and even numbers.

---

For  $a$ , there are no bleed corrections. This block is the one that bleeds to all other blocks, in other words, there are no external shifts into it. Thus, its generators are simply the truncated top halves of the global generators:

$$G_a = G_{TOP}, \quad H_a = H_{TOP}$$


---

For  $b$ , block  $a$  bleeds into it from the left. Specifically the last column of block  $a$  shifts rightwards across the boundary into the first column of block  $b$ . To correct this bleed, we need to define the vector  $e^{(m)}$  that has the dimensions of  $m \times 1$ : Let  $e_0^{(m)}$  be a column vector with a 1 at

the top, and  $e_{m-1}^{(m)}$  be a column vector with a 1 at the bottom:

$$e_0^{(m)} = \begin{pmatrix} 1 \\ 0 \\ \vdots \\ 0 \end{pmatrix}, \quad e_{m-1}^{(m)} = \begin{pmatrix} 0 \\ \vdots \\ 0 \\ 1 \end{pmatrix}$$

We calculate  $v_a$ , the last column of  $a$ . This column must contain the data for the bleed values, meaning that we are forced to partially calculate that part of the dense matrix. We rely on  $\Phi_+$  displacement reconstruction formula.

For any cell at row  $i$  and column  $j$ , the value of the dense matrix  $A$  is given by the sum of the shifted generator products, bounded by the diagonal limit  $\min(i, j)$ :

$$A_{i,j} = \sum_{k=0}^{r-1} \sum_{x=0}^{\min(i,j)} G_A[i-x, k] H_A[j-x, k]$$

where  $r$  is the displacement rank. The first sum of  $k$  is to run the columns of the displacement generators to retrieve the base values. The second sum over  $x$  essentially climbs up diagonally through the displacement matrix since  $\Phi_+$  displacement subtracts diagonally the shifted matrix, we must add these shifted generator products back together to reconstruct the true value and stop when we hit the matrix boundary at  $\min(i, j)$ .

Since  $a$  is an  $n_1 \times n_1$  matrix, the global column index for  $v_a$  is  $j = n_1 - 1$  (the left end of the block  $a$ ). For any row index  $i$  within this block ( $0 \leq i < n_1$ ), we are guaranteed that  $i \leq n_1 - 1$ . So the boundary condition simplifies to  $\min(i, n_1 - 1) = i$ . We can write the  $i$ -th element of the vector  $v_a$  as:

$$(v_a)_i = \sum_{k=0}^{r-1} \sum_{x=0}^i G_A[i-x, k] H_A[n_1-1-x, k]$$

By doing this, we evade the total reconstruction of a matrix and do a vector extraction which has the complexity  $\mathcal{O}(n_1 \cdot r)$ .

We shift  $v_a$  down using  $Z_{n_1}$  and append it to  $G_{TOP}$ . The corresponding  $H$  generator receives the vector  $e_0^{(n_2)}$  to activate this correction exclusively on the first column of  $b$  when multiplied:

$$G_b = (G_{TOP} \quad Z_{n_1} v_a), \quad H_b = (H_{BOTTOM} \quad e_0^{(n_2)})$$

For block  $c$ , data bleeds into it from above. The last row of block  $a$  shifts downwards across the boundary. Just like to block  $b$ , we calculate  $r_a$ , the last row of  $a$ .

$$(r_a)_j = \sum_{k=0}^{r-1} \sum_{x=0}^j G_A[n_1-1-x, k] H_A[j-x, k]$$

Because  $H$  matrices represent the transposed components of the displacement (in this case row instead of column), we apply the shift  $Z_{n_1}$  to  $r_a$  and append it to  $H_{TOP}$ :

$$G_c = (G_{BOTTOM} \quad e_0^{(n_2)}), \quad H_c = (H_{TOP} \quad Z_{n_1} r_a)$$

Block  $d$  has the most bleeding, as it receives shifts from the last column of  $c$  ( $v_c$ ) shifting right, the last row of  $b$  ( $r_b$ ) shifting down, and the bottom-right scalar of  $a$  ( $s_a$ ) shifting diagonally into

the top-left cell of  $d$ . We extract  $v_c$ ,  $r_b$ , and  $s_a$  from the global generators continuing the logic we have applied to block  $a$ :

$$(v_c)_l = \sum_{k=0}^{r-1} \sum_{x=0}^{n_1-1} G_A[n_1 + l - x, k] H_A[n_1 - 1 - x, k]$$

$$(r_b)_m = \sum_{k=0}^{r-1} \sum_{x=0}^{n_1-1} G_A[n_1 - 1 - x, k] H_A[n_1 + m - x, k]$$

$s_a$  is a single scalar value located at the exact bottom-right corner of block  $a$ . Its global row and column indices are both exactly  $n_1 - 1$ , the boundary limit is  $\min(n_1 - 1, n_1 - 1) = n_1 - 1$ .

$$s_a = \sum_{k=0}^{r-1} \sum_{x=0}^{n_1-1} G_A[n_1 - 1 - x, k] H_A[n_1 - 1 - x, k]$$

We scale the basis vector  $e_0^{(n_2)}$  by  $s_a$  and add it to the shifted column vector  $Z_{n_2} v_c$ . We create a double correction structure appended to the original truncated generators:

$$G_d = \begin{pmatrix} G_{BOTTOM} & s_a e_0^{(n_2)} + Z_{n_2} v_c & e_0^{(n_2)} \end{pmatrix}, \quad H_d = \begin{pmatrix} H_{BOTTOM} & e_0^{(n_2)} & Z_{n_2} r_b \end{pmatrix}$$

### Packing

Pack performs the exact inverse of the splitting operation. After computing the inverse sub-blocks (we note as  $x, y, z, t$ ), our goal is to get the global generators  $G_{Inv}$  and  $H_{Inv}$  for the full inverse matrix  $A^{-1}$ .

If we were to concatenate the local generators, the result would assume that the boundaries between the blocks are filled with zeros. Because the operator  $\Phi_+$  shifts data across these boundaries, just like during split, we must re-inject the bleeding corrections to restore the data integrity.

Just as we calculated boundaries, we partially reconstruct the boundary vectors of the local inverse blocks using again the formula. Because we are now operating on isolated blocks' generators (rather than the single global array), the coordinates for each reconstruction does not need an offset (like  $+n_1$  we did for split). So the diagonal shift boundaries must be bounded by local dimensions.

Let  $r_x, r_y$ , and  $r_z$  be the respective displacement ranks of these blocks, and let  $w$  represent the diagonal shift index. Block  $x$  is an  $n_1 \times n_1$  matrix. Because it is a square block, its boundaries mirror the exact logic we used for block  $a$ . The last column ( $v_x$ ), last row ( $r_x$ ), and bottom-right scalar ( $s_x$ ) are computed strictly from  $G_x$  and  $H_x$ :

$$(v_x)_i = \sum_{k=0}^{r_x-1} \sum_{w=0}^i G_x[i - w, k] H_x[n_1 - 1 - w, k] \quad \text{for } 0 \leq i < n_1$$

$$(r_x)_j = \sum_{k=0}^{r_x-1} \sum_{w=0}^j G_x[n_1 - 1 - w, k] H_x[j - w, k] \quad \text{for } 0 \leq j < n_1$$

$$s_x = \sum_{k=0}^{r_x-1} \sum_{w=0}^{n_1-1} G_x[n_1 - 1 - w, k] H_x[n_1 - 1 - w, k]$$

Block  $z$  has dimensions  $n_2 \times n_1$ . The last column is fixed at local index  $j = n_1 - 1$ , while the row index  $l$  varies up to  $n_2 - 1$ . Unlike split,  $l$  is no longer offset by a global position. Therefore, we must do the diagonal shift using  $\min(l, n_1 - 1)$  to ensure the reconstruction does not exceed the dimensions of  $z$ :

$$(v_z)_l = \sum_{k=0}^{r_z-1} \sum_{w=0}^{\min(l, n_1-1)} G_z[l-w, k] H_z[n_1-1-w, k] \quad \text{for } 0 \leq l < n_2$$

Same for the block  $y$  which has the dimensions  $n_1 \times n_2$ . The last row is fixed at index  $i = n_1 - 1$ , and the column index  $m$  varies up to  $n_2 - 1$ . Again, because we are operating within local coordinates, the diagonal shift is bounded by  $\min(n_1 - 1, m)$ :

$$(r_y)_m = \sum_{k=0}^{r_y-1} \sum_{w=0}^{\min(n_1-1, m)} G_y[n_1-1-w, k] H_y[m-w, k] \quad \text{for } 0 \leq m < n_2$$

To apply these corrections, we construct a large set of global generators. We horizontally concatenate the local generators of  $x, y, z, t$  into their respective quadrants. To correct the displacement boundaries, we append four specific correction columns ( $c_1, c_2, c_3, c_4$ ).

We define these giant global generators as block matrices:

$$G_{RES} = \begin{pmatrix} G_x & G_y & 0 & 0 & -Z_{n_1} v_x & 0 & 0 & 0 \\ 0 & 0 & G_z & G_t & 0 & -e_0^{(n_2)} & -(s_x e_0^{(n_2)} + Z_{n_2} v_z) & -e_0^{(n_2)} \end{pmatrix}$$

$$H_{RES} = \begin{pmatrix} H_x & 0 & H_z & 0 & 0 & Z_{n_1} r_x & 0 & 0 \\ 0 & H_y & 0 & H_t & e_0^{(n_2)} & 0 & e_0^{(n_2)} & Z_{n_2} r_y \end{pmatrix}$$

Notice that the boundary correction columns in  $G_{RES}$  has negative signs. The displacement operation subtracts the diagonally shifted matrix:  $\Phi_+(A^{-1}) = A^{-1} - ZA^{-1}Z^T$ . When the local inverse blocks  $(x, y, z, t)$  are computed, their local displacements (ex.  $G_y H_y^T$ ) are evaluated as if the blocks exist alone, assuming that any data shifted outside their local boundaries is replaced by zeros.

Within the global structure of  $A^{-1}$ , these blocks are next to eachother. The global shift operator  $Z$  pushes data across these block boundaries. Any data that bleeds from block  $x$  into block  $y$  must physically enter the local equation of  $y$  as a subtracted value. By negating bleeds on the appended correction columns in  $G_{RES}$ , the generator multiplication  $G_{RES} H_{RES}^T$  produces these required negative terms.

To prove the mathematical correctness of these correction columns, we can compute the global displacement reconstruction by multiplying the uncompressed generators:  $\Phi_+(A^{-1}) = G_{RES} H_{RES}^T$ .

$$G_{RES} H_{RES}^T = \begin{pmatrix} G_x H_x^T & G_y H_y^T - Z_{n_1} v_x (e_0^{(n_2)})^T \\ G_z H_z^T - e_0^{(n_2)} (Z_{n_1} r_x)^T & G_t H_t^T - Z_{n_2} v_z (e_0^{(n_2)})^T - e_0^{(n_2)} (Z_{n_2} r_y)^T - s_x e_0^{(n_2)} (e_0^{(n_2)})^T \end{pmatrix}$$

The terms  $(G_x H_x^T, G_y H_y^T, \text{etc.})$  represent the isolated local displacements of the sub-matrices. The subtracted terms are the bleeds. For example the term  $-Z_{n_1} v_x (e_0^{(n_2)})^T$  subtracts the shifted last column of block  $x$  into the first column of block  $y$ .

This implementation exposes a vulnerability: Let  $r_x, r_y, r_z, r_t$  be the displacement ranks of the quadrants. The rank of our assembled matrix is:

$$\text{Rank}_{RES} = r_x + r_y + r_z + r_t + 4$$

Passing this uncompressed matrix up to the next recursion level would cause the rank to explode. Therefore, immediately after constructing  $G_{RES}$  and  $H_{RES}$ , we compress them.

#### 4.1.2 Conclusion

The advantage of this inversion lies on displacement generators rather than dense matrix representations like any other algorithm mentioned in this report.

By operating on generators of size  $n \times r$  (where the displacement rank  $r \ll n$ ), the complexity in memory is reduced from the standard  $\mathcal{O}(n^2)$  down to  $\mathcal{O}(r \cdot n)$ . Assuming optimal generator multiplication, the complexity of the recursive Strassen-type assembly falls significantly below the  $\mathcal{O}(n^3)$  or  $\mathcal{O}(n^{2.81})$  operations required by classical dense matrix inversion.

Despite these gains, the structured approach introduces overhead due to strict displacement boundary management. The split and pack require continuous  $\mathcal{O}(r \cdot n)$  diagonal vector extractions to mathematically correct the  $\Phi_+$  bleeding. More critically, the structural reassembly during the pack and each multiplication and addition increases the rank, requiring more computation for compressions at every recursive return.

While this implementation is great for large matrices with a strictly bounded rank, the overhead makes the algorithm computationally disadvantageous for smaller matrices compared to standard dense inversion.

**[TODO: ARDA: THRESHOLD ???] [TODO: ARDA: BENCHMARKS for both n for any nxn and for displacement rank]**

| $n$  | Generators (ms) | Flint Dense (ms) |
|------|-----------------|------------------|
| 128  | 7.78            | 2.71             |
| 256  | 12.47           | 11.91            |
| 512  | 30.62           | 78.60            |
| 1024 | 77.38           | 547.4            |
| 2048 | 200.5           | 3850             |
| 4096 | 545.8           | 26940            |

Table 3: Median runtimes over 5 runs

As detailed by Victor Y. Pan in *Structured Matrices and Polynomials* [5, Chapter 5], an alternative is the Morf-Bitmead-Anderson (MBA) algorithm. Originally proposed by Morf (1980) and Bitmead and Anderson (1980), it achieves  $\mathcal{O}(n \log^2 n)$  complexity for Toeplitz-like matrices. Because it is also a divide-and-conquer method, this approach still requires calculations of sub-quadrants and continuous generator compression.

To bypass the need to split the matrix, one should prefer to implement the Newton iterative version. Pan dedicates analysis to this approach in [5, Chapters 6 and 7], which is based on the Schulz iteration:  $X_{k+1} = X_k(2I - AX_k)$ .

While the implementation here computes  $A^{-1}$  explicitly, it is worth noting that in practice, solving a linear system  $Ax = b$  does not require forming the inverse directly. Recent work by Khichane and Neiger [4] proposes a deterministic algebraic approach that reformulates the system in terms of polynomial arithmetic, solving it with  $\tilde{\mathcal{O}}(r^{\omega-1}n)$  complexity while bypassing explicit inversion altogether.

**[TODO: THINGS TO IMPROVE]**



## References

- [1] D. A. Bini, S. Massey, and B. Meini. On functions of quasi-toeplitz matrices. *Sbornik: Mathematics*, 208(11):1628–1645, November 2017. URL: <http://dx.doi.org/10.1070/SM8864>, doi:10.1070/sm8864.
- [2] Alin Bostan, Frédéric Chyzak, Marc Giusti, Romain Lebreton, Grégoire Lecerf, Bruno Salvy, and Éric Schost. *Algorithmes efficaces en calcul formel*, August 2017. 686 pages. Édition 1.0. URL: <https://hal.archives-ouvertes.fr/AECF/>.
- [3] Ignat Domanov and Lieven De Lathauwer. Generic uniqueness of a structured matrix factorization and applications in blind source separation. *IEEE Journal of Selected Topics in Signal Processing*, 10(4):701–711, 2016. doi:10.1109/JSTSP.2016.2526971.
- [4] Sara Khichane and Vincent Neiger. Matrices with displacement structure: a deterministic approach for linear systems and nullspace bases, 2026. URL: <https://arxiv.org/abs/2603.02425>, arXiv:2603.02425.
- [5] Victor Y. Pan. *Structured Matrices and Polynomials: Unified Superfast Algorithms*. Birkhäuser & Springer, 2001. URL: <https://doi.org/10.1007/978-1-4612-0129-8>.
- [6] Janusz P. Papliński, Aleksandr Cariow, Paweł Strzelec, and Marta Makowska. Digital signal processing (dsp)-oriented reduced-complexity algorithms for calculating matrix–vector products with small-order toeplitz matrices. *Signals*, 5(3):417–437, 2024. URL: <https://www.mdpi.com/2624-6120/5/3/21>, doi:10.3390/signals5030021.
- [7] S. S. Zhou and J. B. Wang. Efficient quantum circuits for dense circulant and circulant like operators. *Royal Society Open Science*, 4(5):160906, 05 2017. arXiv:<https://royalsocietypublishing.org/rsos/article-pdf/doi/10.1098/rsos.160906/509313/rsos.160906.pdf>, doi:10.1098/rsos.160906.

## Annexe

### Implementations

#### Displacement

```
Project
\  src
|  \  displacement_matrices
|  |  |  displacement_matrices.c
|  |  |  displacement_matrices.h
```

`gr_mat_displacement(gr_mat_t D, gr_mat_t A, disp_type_t type, gr_ctx_t ctx)` Is the function taking as parameter the matrix  $A$  and returns into the matrix  $D$ , indicating destination, the displacement matrix of  $A$ . According to the type of displacement we pass via the parameter `type`, it calculates the implementations (2) or (5).

`int gr_mat_G_H(gr_mat_t G, gr_mat_t H, gr_mat_t A, disp_type_t type, gr_ctx_t ctx)` Is the function that computes the generator matrices  $G$  and  $H^T$  for an input matrix  $A$ . Based on the displacement equations discussed previously, the equation (4), the function first calculates the displacement matrix according to the specified type of displacement. Since the displacement of a structured matrix (like a Toeplitz matrix) inherently results in a matrix with a low rank ( $\alpha$ ),  $D$  can be factored into two smaller matrices such that  $D = GH^T$ . The function achieves this by performing an LU decomposition on the displacement matrix  $D$ . It then extracts the independent columns to form  $G$  and the corresponding rows to form  $H^T$ . This is where the storage economy for structured matrices come from.

`int gr_mat_reconstruct_A(gr_mat_t A, gr_mat_t G, gr_mat_t H, disp_type_t type, gr_ctx_t ctx)` [\[TODO: RAFAEL -> V2 VERSION\]](#)

#### Compression

```
Project
\  src
|  \  compression
|  |  |  compression.c
|  |  |  compression.h
```

`int gr_mat_generator_compress(gr_mat_t G_d, gr_mat_t H_d, gr_ctx_t ctx);`  
Is our function that implements the algorithms talked in chapter 3.