

Topic 3 (Part III: Overloading and Polymorphism)

C++ advanced features review: *when can/should I use them?*

資料結構與程式設計
Data Structure and Programming

Sep, 2011

Sharing in the code...

◆Remember:

Many constructs (in C++) are to promote **sharing** in the code.

1. Pointer: share the same data location
(as different variables)
2. Reference: an alias to an existing variable
3. Function: share the common codes
4. Class: data with the same attributes and
definition (as data type)

Sharing in the code...

◆ And we will learn...

5. Inherited class: different but similar classes sharing the common data members or member functions
6. Function overloading: same function name, diff arguments
7. Operator overloading: redefine the C++ operators for user-defined data type (class)
8. Template class: same storage method, diff data types
9. Template function: same algorithm flow, diff data types
10. Functional object: same algorithm flow, diff argument types

Key Concept #1: “Has a” vs. “Is a”

◆ class Car {

Engine _eng;

};

→ Class Car “has a” data member of type “Engine”

◆ class Dog : public Animal {

...

};

→ Class Dog “is a” inherited type of “Animal”

Key Concept #2: Inheritance to share common data and methods

```
◆ class Base {  
    public:  
        <common data or methods>  
    protected: // public to Derived classes  
                // private to others  
        <shared data or methods>  
    private:    // Base's private only  
        <private data or methods>  
};  
class Derived : public Base {  
    public:  
        <specific data or methods>  
    private:  
        <specific data or methods>  
};
```

“protected” vs. “private” access specifiers

◆ protected:

- To allow member functions of the derived classes to directly access the base class' data members and member functions

◆ private:

- Member functions of the derived classes cannot directly access the base class' private components
- However, derived classes still inherit the private data members (Remember: “is a”)
 - To access them, create protected or public functions in base class

◆ Note: “friend” specification is NOT inherited

Key Concept #3: Inheritance to specialize distinct methods with the same function

```
◆ class Shape {  
    public:        virtual void draw() = 0;  
    protected:    double _centerCoord;  
};  
class Square : public Shape {  
    public:        void draw();  
    private:       double _edgeLength;  
};  
class Circle: public Shape {  
    public:        void draw();  
    private:       double _radiusLength;  
};
```

➔ In C style, people use “switch” ➔ NOT GOOD

Virtual Functions

```
class Base {  
    public:  
        virtual void f();  
        void g();  
};  
class Derived: public Base  
{  
    public:  
        void f();  
        void g();  
};  
int main()  
{  
    Base b; b.f(); b.g();  
    Derived d; d.f(); d.g();  
}
```

➔ Which f() and g() are called?

Base::f()

Base::g()

Derived::f()

Derived::g()

➔ What does “virtual” keyword do in this case? What if we DO NOT declare “virtual” for f()?

➔ What’s the difference if we DO NOT declare Derived as a derived class of Base?

Key Concept #4: Virtual function is useful only with polymorphism


- ◆ Polymorphism occurs when a derived object invokes a virtual function through a base-class pointer or reference
 - C++ dynamically chooses the correct function for the class from which the object was instantiated
- ◆ Common usage:
 - `Base *p = new Derived;`
`p->virtualFunction();`
 - `Derived d;`
`Base &r = d;`
`r.virtualFunction();`

Key Concept #5: Polymorphism for dynamic type specification

- ◆ Analogy:
 - The size of a dynamic array is undefined.
It is determined during execution.
 - `int *arr = 0;`
... `// size is determined`
`arr = new int[size];`
- ◆ When the type of a variable is not determined before execution, but its category is clearly defined...
 - Category: base class; type: inherited class
 - `Category *p;`
...
`p = new MyType;`

[NOTE] We can use “pointer” when the type of the derived class is not determined in the beginning

```
◆ class Node {
    Array<Node*> _children;
public:
    void addChild(Node* c){_children.push_back(c); }
};
class BinaryNode : public Node {...};
class NNaryNode : public Node {...};
-----
Node*    o1, o2; // type is not yet
...      // determined
o1 = new Circle;
o2 = new Square;
n->addChild(o1);
n->addChild(o2);
```



Key Concept #6: Virtual function makes polymorphism meaningful

◆ Use base class pointer or reference as the interface. Pass inherited class pointer or object for different application scenarios.

◆ [Example] HW #3

```
bool CmdParser::regCmd(..., CmdExec* e) {
    ...
    return (_cmdMap.insert
        (CmdRegPair(mandCmd, e)).second;
}

CmdExecStatus CmdParser::execOneCmd() {
    ...
    CmdExec* e = parseCmd(option);
    if (e != 0) return e->exec(option);
    ...
}
```

More on HW #3

- ◆ For each inherited class:

```
#define CmdClass(T) \
class T: public CmdExec { \
public: \
    T() {} \
    ~T() {} \
    CmdExecStatus exec(const string& option); \
    void usage(ostream& os) const; \
    void help() const; \
}
```

- ◆ Implement “exec()”, “usage()” and “help()” functions independently in each package/directory
→ Easy to extend the set of commands


In the previous “Node” example...

- ◆

```
class Node { virtual void draw() const=0; }
class Circle: public Node { void draw() const; }
class Square: public Node { void draw() const; }
```
- ◆

```
void Graph::dfsTraverse() {
    Graph::setGlobalRef();
    dfsTraverse(_root);
}

void Graph::dfsTraverse(Node *n) {
    if (n->isGlobalRef()) return;
    n->setGlobalRef();
    for_each_child(c, n)
        dfsTraverse(c);
    n->draw();
}
```



Key Concept #7: Function prototype of virtual function

- ◆ Be sure to make the function prototype of the inherited class exactly the same as that of the base class, including “const”, etc.
- ◆ Once a function is declared `virtual`, it remains `virtual` all the way down the inheritance hierarchy from that point, even if that function is not explicitly declared `virtual` when a class overrides it.
 - But explicitly declare `virtual` will make the program more readable

Virtual Functions

```
class Animal {
    // no "bark" is defined
};
class Dog: public Animal {
public:
    virtual void bark();
};
class KDog: public Dog {
public:
    void bark();
};
class GDog: public KDog {
public:
    void bark();
};
```

```
int main() {
    Animal *a = new KDog;
    a->bark();

    Dog *b = new KDog;
    b->bark();

    Dog *c = new GDog;
    c->bark();

    Kdog *d = new Gdog;
    d->bark();
}
→ Any compilation error?
→ Which bark() is called?
```


Virtual Functions

```
class Base {
public:
    virtual void f();
    void g();
    virtual void h();
};
class Derived: public Base
{
public:
    void f();
    void g();
};
int main()
{
    Base* p = new Derived;
    p->f(); p->g(); p->h();
}
```

```
Base* q = new Base;
q->f(); q->g(); q->h();

Derived* r = new Derived;
r->f(); r->g(); q->h();
}
```

→ Any compilation error?
→ Which f(), g(), h() are called?

```
== p ==
Derived::f()
Base::g()
Base::h()
== q ==
Base::f()
Base::g()
Base::h()
== r ==
Derived::f()
Derived::g()
Base::h()
```

Key Concept #8: Abstract class and pure virtual function

- ◆ A class is said “abstract” if we have no intention to create any object out of it.
 - e.g. “Node” in the previous example
- ◆ A “pure virtual function” is a function defined as “= 0”.
 - We cannot omit the function definition of any pure virtual function in the derived class.
- ◆ If a class has a pure virtual function, this class becomes “abstract”.
 - We cannot create any object for an abstract class (e.g. Node n; Node *p = new Node;)
 - But polymorphism is OK (e.g. Node *n = new Circle)

Summary #1: Keyword “virtual”

- ◆ Explicitly add the keyword “virtual” whenever applicable
 - Only if this function will NOT be made virtual in the future
- ◆ The function definition in the inherited class can be omitted if the intention is to call the base-class function
 - But NOT applicable if the function in the base class is pure virtual.

Key Concept #9: Constructors

- ◆ As its name suggests, the constructor of the “base” class will be called before that of the inherited class.
 - Both will/must be called.
- ◆ Constructor cannot be virtual
 - Doesn’t make sense to be virtual.
- ◆ What about destructor? Which one will be called first?

Key Concept #10: Virtual Destructor

```
class Base
{
    A _a;
public:
    Base(){}
    ~Base(){}
};

class Derived:public Base
{
    B _b;
public:
    Derived(){}
    ~Derived(){}
};
```

```
int
main()
{
    Base* p = new Derived;
    Base* q = new Base;
    Derived* r = new Derived;
    ...
    delete p; delete q;
    delete r
}
```

→ Which constructors / destructors are called?

→ What happens if the derived class' destructor is not called?

Declaring Virtual Destructor

```
class Base
{
    A _a;
public:
    Base(){}
    virtual ~Base(){}
};

class Derived:public Base
{
    B _b;
public:
    Derived(){}
    ~Derived(){}
};
```

```
int
main()
{
    Base* p = new Derived;
    Base* q = new Base;
    Derived* r = new Derived;
    ...
    delete p; delete q;
    delete r
}
```

→ Which constructors / destructors are called?

What's the difference?

```
class Base
{
    public:
        Base(int){}
        virtual ~Base(){}
};

class Derived:public
    Base
{
    public:
        Derived(int){}
        ~Derived(){}
};
```

```
int
main()
{
    Base *p
        = new Derived(10);
    Base *q = new Base(20);
    ...
    delete p;
    delete q;
}
→Compilation error. Why?
```

Why compilation error?

◆By default, “Base()” will be called by any “Derived(…)”

```
[Sol #1]
class Base {
    public:
        Base() {}
        Base(int){}
        virtual ~Base(){}
};

class Derived: public
    Base {
    public:
        Derived(int){}
        ~Derived(){}
};
→ But “Base(int)” won't be called
```

```
[Sol #2]
class Base {
    public:
        Base(int){}
        virtual ~Base(){}
};

class Derived: public Base {
    public:
        // Explicitly call Base(i)
        Derived(int i):Base(i){}
        ~Derived(){}
};
→ Recommended
```

Summary #2: Constructor & Destructor

In short, when calling constructor / destructor of the derived class, make sure the data members in the base class are well taken care of



1. Explicitly calling Base constructor
2. Define “virtual” Base destructor

Key Concept #11: Casting a base class pointer to the derived class

- ◆

```
class Base { };  
class Derived: public Base {  
public: void f() {}  
};  
=====
```

```
Base *p = new Derived();  
p->f();
```

 - ➔ Any problem?
 - ➔ Compile error if “f()” is not defined in Base
- ◆ When we declare a member function in a derived class, and we use polymorphism to define the variable as a base class pointer
 - How can we call the derived class' member function?
 - Create a (pure) virtual function that does nothing
 - If so, what about the other derived classes?
 - ➔ Leave the member function in derived class only; use “type casting” to cast the pointer from base class to derived class

dynamic_cast<Type>(variable)

- ◆ [Note] Use “dynamic_cast” to cast between “base” and “derived” classes

```
class Child : public Parent {
    void childOnlyMethod();
    // no virtual childOnlyMethod() in Parent
    ...
};
// Better make sure, "Parent* p = new Child;"
void f(Parent *p) {
    dynamic_cast<Child *>(p)
        ->childOnlyMethod();
};
```

- ◆ [Note] If the underlying object is NOT of the derived type, 0 is assigned; → Used with caution!!

static_cast<Type>(variable)

- ◆ [Note] Use “static_cast” to cast between “base” and “derived” classes

```
class Child : public Parent {
    void childOnlyMethod();
    // no virtual childOnlyMethod() in Parent
    ...
};
// Better make sure, "Parent* p = new Child;"
void f(Parent *p) {
    static_cast<Child *>(p)
        ->childOnlyMethod();
};
```

- ◆ [Note] No checking between sizes of objects; also use with caution

Key Concept #12: Access specifier in derived classes


- ◆ `class Derived : [accessSpecifier] Base { ... };`
 - private/protected/public
- ◆ Data accessibility in derived classes

access specifier \ data in Base	private	protected	public
private	N/A	private	private
protected	N/A	protected	protected
public	N/A	protected	public


- ◆ Note: “accessSpecifier” is optional
 - `class Derived: Base;` → `class Derived: private Base;`
 - `struct Derived: Base;` → `struct Derived: public Base;`

Key Concept #13: Multiple Inheritance

- ◆ `class Operator {};`
- `class BooleanOp : public Operator {};`
- `class BinaryOp : public Operator {};`
- `class AndOp : public BooleanOp, public BinaryOp {};`




duplicated “Operator” sub-objects



Multiple Inheritance

```
◆ class Operator {};  
  class BooleanOp : virtual public Operator {};  
  class BinaryOp : virtual public Operator {};  
  class AndOp : public BooleanOp, public BinaryOp {};
```



Sharing in the code...

- ◆ And we will learn...
- 5. Inherited class: different but similar classes sharing the common data members or member functions
- 6. Function overloading: same function name, diff arguments
- 7. Operator overloading: redefine the C++ operators for user-defined data type (class)
- 8. Template class: same storage method, diff data types
- 9. Template function: same algorithm flow, diff data types
- 10. Functional object: same algorithm flow, diff argument types

Key Concept #14: Function Overloading

- ◆ Sometimes we want to call the same function with different types/number of parameters, and we don't want to create different function names for them...
 - e.g. // kind of awkward...
void computeScoreByInt(int);
void computeScoreByStudent(const Student&);
- ◆ Function overloading
 - Same function name, different function arguments

Key Concept #15: Can't overload a function with different return types

- ◆ "Return type" is NOT part of a function signature.
 - e.g.
bool f() { ... }
int f() { ... }
int main() { int i = f(); }
➔ Which one is called?

Key Concept #16: Default argument

- ◆ You cannot overload a function with and without default argument
 - e.g.
void f(int i = 0);
void f(int i);
→ Compile error!! “f(int)” is redefined...
But this is OK:
void f(); // overload “void f(int i = 0)”
- ◆ Default argument can ONLY appear once in the entire program. And it should be declared in the first encounter.
 - Usually the function prototype or inside the class definition
 - Compile error if multiply declared, even with the same value!!

Key Concept #17: Why operator overloading?

- ◆ Operator overloads are very useful in making the code more concise (c.f. Function overload)
- ◆ Basic concept:

```
MyNumber n1, n2;  
n1 = "32hf908abc0";  
n2 = f(...);  
...  
MyNumber n3 = n1 + n2;
```

 1. n1 calls “MyNumber::operator +” with parameter n2
→ return a temporary object, say n4
 2. n3 calls “MyNumber::operator =” with parameter n4
→ returned result is stored in n3 itself

Key Concept #18: Pay attention to the function prototypes for operator overloading

```
1. T& operator = (const T& v);
2. T& operator [] (size_type i);
3. const T& operator [] (size_type i) const;
4. T operator ~ () const;    // also for -, &, |, etc
5. T& operator ++();        // ++v
6. T operator ++(int);       // v++
7. T operator + (const T& v) const;
   // also for -, *, &, etc
8. T& operator += (const T& v);
   // also for -=, *=, &=, etc
9. bool operator == (const T& v) const;
   //also for !=, etc
10. friend ostream& operator << (ostream&, const T&);
```

- ◆ The operator '()' can also be overloaded and used as "generator"

Notes about operator overloading

- ◆ Explicit calling overloaded operator functions
 - e.g. "a.operator +(b)" is equivalent to "a + b"
- ◆ Member or global function?
 - e.g. "a + b" can be treated as
 1. Member function : "a.operator +(b)"
 2. Global function : "::operator +(a, b)"

→ Compile error will arise if both are defined.
- ◆ Why "friend" for "friend ostream& operator << (ostream&, const T&);"
 - Who calls "cout << t"?
 - Can we overload "ostream::operator <<"?

Notes about operator overloading

- ◆ There is no restriction on the semantics of the overloaded operators.
 - For example, you can overload an addition operator “+” and define it as performing “subtraction”.
 - No compile error/warning.
 - But since it is counter-intuitive, you may introduce some runtime error.
- ◆ The syntax of the operators is defined in language parser (compiler). You cannot change it.
 - For example, you cannot do “a ++ b”.
- ◆ The return type of operators can be arbitrary.
 - However, please make it intuitive.
- ◆ The arguments for “()” operator can be arbitrary.

Return-by-Object or Reference?

- ◆ To share the codes in operator overloading implementations, the “return-by-object” version of the operator overloading function usually reuses the “return-by-reference” one.
- ◆ e.g.

```
T operator ++(int) { // i++
    T ret = *this; ++(*this); return ret;
}
T operator + (const T& v) const {
    T ans = *this; ans += v; return ans;
}
```

Example: Random Number Generator

```
class RandomNumGen {
public:
    RandomNumGen() { srandom(getpid()); }
    RandomNumGen(unsigned seed) { srandom(seed); }
    int operator() (int range) const {
        return int(range * (double(random()) / INT_MAX));
    }
    int operator() (int min, int max) const { ... }
};

main()
{
    RandomNumGen rn;
    ...
    int a = rn(10); // random number in [0, 9]
    int b = rn(100); // random number in [0, 99]
    int c = rn(10, 100);
}
```

Key Concept #19: Template Class

- ◆ When the methods of a class can be applied to various data types

- Specify once, apply to all
- Container classes

e.g.

```
template <class T>
class vector {
    ....
};
```

```
vector<int>          arr;
vector<vector<int> > arr2D;
```

➔ [note] make sure a space between "> >"

➔ [note] "template <class T>" is a modifier, not a variable definition, to the class/function in concern. It can be repeated in the same file.

Key Concept #20: Template's Arguments

◆ Can also contain expression

- However, the 1st argument must be class name

e.g.

```
template<class T, int SIZE>
class Buffer
{
    T    _data[SIZE];
};
```

```
-----
Buffer<unsigned, 100>    uBuf;
Buffer<MyClass, 1024>    myBuf;
```

→ Why not use “#define” or declare it as a data member?

Key Concept #21: Template Function

◆ A common method/algorithm that can be applied to various data types

e.g.

```
template<class T>
void sort(vector<T>&)
{
    ...
}
```

```
-----
vector<int> arr;
...
sort<int>(arr);
```

Notes about template function

- ◆ Template arguments
 - Any of the template arguments can be class type or expression
 - ➔ `template <int S> void f() { ... while (i < S)... }`
 - The template type symbol(s) can be used in function prototype and/or function body
- ◆ When calling template functions, template type symbols can be omitted
 - `template <class T> void f (T a) { ... }`
`int main() { f(3); f(3.0); }`
- ◆ However, if there is(are) “non-type” symbol(s), or ambiguity arises, you need to explicitly specify the template symbol(s)
 - `template <class T> void f() { ... }`
`int main() { f(3); f(3.0); } // compile error`

Key Concept #22: Functional Object

- ◆ Remember:
 - You can overload the “()” operator for a class
 - e.g.

```
class A {
    bool operator() (int i) const {
        return (_data > i); }
};
```

 - ➔ Note: returned type and input parameters may vary
 - What if you pass in such kind of an object to a function?
 - e.g.

```
void f(const Compare& cmp,
      const T& a, const T& b) {
    if (cmp(a, b)) ...
}
```

 - ➔ Look like a function pointer?

Functional Object in Polymorphism

- ◆ A class/object whose main purpose is to perform a specific function
 - “()” is overloaded
 - Usually passed as reference or pointer to other functions
- ◆ Work with class inheritance

```
• class Compare {
    virtual bool operator() (int) const = 0; };
class Less : public Compare {
    bool operator() (int) const; };
class Greater : public Compare {
    bool operator() (int) const; };
=====
void f(const Compare& p);
int main() {
    Less a;  f(a);
    Greater b; f(b);
}
```

Example of Functional Object Applications

- ◆ Graph traversal
 - In a graph data structure, provide a generic traversal function (DFS or BFS).
 - Take a base class functional object as the parameter
 - class DoVertex {
 virtual void operator() (Vertex *) = 0;
};
 - Define derived classes for intended actions
 - e.g. PrintVertex, Simulate, SetMark, etc
- ➔ Same graph traversal code, different functionalities

(FYI) Functional Object and Algorithm Classes in STL

◆ Many algorithm and functional object classes in STL

- for_each, find, copy, sort, swap, search, random_shuffle, power, ...etc
- unary function, binary function, predicate
- arithmetic, logic, comparison operations
- ➔ For more information, please refer to:
<http://www.sgi.com/tech/stl/>
(See: Table of contents)

Summary #3: Template Class/Function vs. Function Overload vs. Functional Object

To maximize code reuse (less duplicated code)

◆ Template

- Class template
 - Same storage method, different data types
- Function template
 - Same algorithm flow, different data types

◆ Function overloading

- Same function name, different function arguments

◆ Functional object

- Same algorithm flow, different functional methods as "arguments"