

- Boxplot:

- $Q_1 = N \times 0.25$
- $Q_2 = N \times 0.5$
- $Q_3 = N \times 0.75$
- $IQR = Q_3 - Q_1$
- $Bounds = [Q_1 - 1.5 \times IQR, Q_3 + 1.5 \times IQR]$

- Pearson = $\frac{\Sigma(y_{1i} - \bar{y}_1)(y_{2i} - \bar{y}_2)}{\sqrt{\Sigma(y_{1i} - \bar{y}_1)^2 \times \Sigma(y_{2i} - \bar{y}_2)^2}}$

- Spearman: Assign ranks and apply Pearson formula.
Example: $[20, 10, 20, 30, 20] \rightarrow [3, 1, 3, 5, 3]$

- Normalization:

- MinMax: $\frac{y_i - \min}{\max - \min}$
- Standardization: $\frac{y_i - \mu}{\sigma}$

- Binarization:

- Range (equal width): Depends on variable range
Example: $y \in [-1, 1] : [0.2, -0.1, 0.6] \rightarrow [1, 0, 1]$
- Frequency (equal depth): Depends on variable mean
Example: $\bar{y} = 25 : [10, 40, 30, 20] \rightarrow [0, 1, 1, 0]$

- Confusion Matrix:

| | | True | | | B |
|------|---|------|----|----|----|
| | | A | B | C | |
| Pred | A | TA | FA | FA | TP |
| | B | FB | TB | FB | TN |
| | C | FC | FC | TC | FP |
| | | | | | FN |

- Metrics:

- Accuracy = $\frac{TP + TN}{total}$
- Error rate = $1 - Accuracy = \frac{FP + FN}{total}$
- Recall = $\frac{TP}{TP + FN}$ (Sensitivity)
- Fallout = $\frac{TN}{TN + FP}$ (Specificity)
- Precision = $\frac{TP}{TP + FP}$
- $F_1 = \frac{TP}{TP + \frac{1}{2}(FP + FN)}$

- Error:

- Sum of Squares Error: $SSE = \sum (Z - \hat{Z})^2$
- Maen Squared Error: $MSE = \frac{1}{n} SSE$
- Root Maen Squared Error: $RMSE = \sqrt{MSE}$
- Mean Absolute Error: $MAE = \frac{1}{n} \sum |Z - \hat{Z}|$

- Information Gain: $IG(y_{out}|y_i) = E(y_{out}) - E(y_{out}|y_i)$

- Entropy: $E(y) = - \sum P(x_i) \log(P(x_i))$

- Decision trees:

1. Choose feature with highest IG.
2. Split dataset by that feature, create leaves if necessary.
3. Repeat until unable to proceed.

Prune: (Given a twig)

1. Count it's leaves labels.
Example: $\#A = 5, \#B = 6$
2. Remove it's leaves.
3. Relabel twig as a leaf.
Example: $B(6/11), \#B > \#A$

- Vector Norm:

$$\|x\|_p = \sqrt[p]{\sum_{i=1}^n |x_i|^p} \quad \|x\|_\infty = \max |x_i|$$

- Matrix Multiplication:

$$\begin{bmatrix} \dots & \dots & n \\ \dots & \dots & \dots \\ m & \dots & \dots \end{bmatrix} \cdot \begin{bmatrix} \dots & \dots & l \\ \dots & \dots & \dots \\ n & \dots & \dots \end{bmatrix} = \begin{bmatrix} \dots & \dots & l \\ \dots & \dots & \dots \\ m & \dots & \dots \end{bmatrix}$$

- Gaussian Distribution:

- Variance: $var = \frac{\sum (y_i - \mu)^2}{n(-1)}$
- Standard Deviation: $\sigma = \sqrt{var}$
- $P(y|\mu, \sigma) = \frac{1}{\sqrt{2\pi} \cdot \sigma} \cdot \exp\left(-\frac{1}{2} \left(\frac{y - \mu}{\sigma}\right)^2\right)$

- Gaussian Mixture:

- Covariance: $cov(y_1, y_2) = \frac{\sum (y_{1i} - \mu_1)(y_{2i} - \mu_2)}{n(-1)}$
- Covariance Matrix: $\Sigma(y_1, y_2) = \begin{bmatrix} var(y_1) & cov(y_1, y_2) \\ cov(y_1, y_2) & var(y_2) \end{bmatrix}$
- $|\Sigma| = \begin{vmatrix} a & b \\ c & d \end{vmatrix} = ad - bc$
- $P(y|\mu, \Sigma) = \frac{1}{(2\pi)^{d/2} |\Sigma|^{1/2}} \cdot \exp\left(-\frac{1}{2} (y - \mu)^T \Sigma^{-1} (y - \mu)\right)$

- Naive Bayes:

- MAP: $P(C|x) = \frac{P(C)P(x|C)}{P(x)}$
- ML: $P(C|x) = P(x|C)$

1. Calculate probability for each class.
2. Calculate $P(x|C)$ for each attribute and each class.
3. TODO

- K-Nearest Neighbors:

1. Distances: (for n variables)
 - Manhattan: $\sum |y_{1i} - y_{2i}|$
 - Euclidean: $\sqrt{\sum (y_{1i} - y_{2i})^2}$
 - Cosine: $\frac{\sum y_{1i} y_{2i}}{\sqrt{\sum y_{1i}^2} \sqrt{\sum y_{2i}^2}}$
 - Hamming: #Differences
2. Choose K nearest neighbors.
3. Classify using mean if variable is numeric, or mode if it is categoric.
4. If weighted, divide by weight.

- Regressions:

- Linear: $W = (X^T X)^{-1} X^T Z$
- Ridge: $W = (X^T X + \lambda I)^{-1} X^T Z$

- Perceptron:

$\hat{Z} = a(W^T X)$, $a \leftarrow$ activation function
If $Z \neq \hat{Z} \rightarrow W' = W + \eta(Z - \hat{Z})X$

- Neural Networks (MLP):

- Forward: $x^{[0]} \rightarrow z^{[1]} = w^{[1]}x^{[0]} + b^{[1]} \rightarrow x^{[1]} = a(z^{[1]}) \rightarrow \dots \rightarrow z^{[i]} = w^{[i]}x^{[i-1]} + b^{[i]} \rightarrow x^{[i]} = a(z^{[i]}) \rightarrow E$
- Backward:

$$* \delta^{[last]} = \frac{\partial E}{\partial x^{[last]}} \circ \frac{\partial x^{[last]}}{\partial z^{[last]}}$$

$$* \delta^{[i]} = \left(w^{[i+1]}\right)^T \cdot \delta^{[i+1]} \circ \frac{\partial x^{[i]}}{\partial z^{[i]}}$$

$$* w^{[i]'} = w^{[i]} - \eta \frac{\partial E}{\partial w^{[i]}} \quad * \frac{\partial E}{\partial w^{[i]}} = \delta^{[i]} \cdot \left(x^{[i-1]}\right)^T$$

$$* b^{[i]'} = b^{[i]} - \eta \frac{\partial E}{\partial b^{[i]}} \quad * \frac{\partial E}{\partial b^{[i]}} = \delta^{[i]}$$

– Derivatives:

| Name | Error function | $\frac{\partial E}{\partial x^{[i]}}$ |
|------------------------|---|--|
| Squared Error | $\frac{1}{2} \left(x^{[i]} - t \right)^2$ | $x^{[i]} - t$ |
| Cross-entropy | $-\sum_{i=1}^n t_i \log \left(x_i^{[i]} \right)$ | $-\frac{t}{x^{[i]}} + \frac{1-t}{1-x^{[i]}}$ |
| Name | Activation function | $\frac{\partial x^{[i]}}{\partial z^{[i]}}$ |
| Sigmoid $\sigma(x)$ | $\frac{1}{1+e^{-x}}$ | $x^{[i]} (1-x^{[i]})$ |
| Hyper. tan. $\tanh(x)$ | $\frac{e^x - e^{-x}}{e^x + e^{-x}}$ | $1 - \left(x^{[i]} \right)^2$ |
| ReLU $R(x)$ | 0 if $x < 0$ x if $x \geq 0$ | 0 if $x < 0$ 1 if $x \geq 0$ |
| Softmax $S(x)$ | $\frac{e^{x_i}}{\sum_{j=1}^n e^{x_j}}$ | $x^{[i]} (1-x^{[i]})$ |
| Function | | Derivative |
| $e^{f(x)}$ | | $e^x \times f'(x)$ |

NOTE:

* When cross-entropy and softmax are combined:

$$\delta^{[last]} = \frac{\partial E}{\partial z^{[last]}} = x^{[last]} - t$$

• K-Means:

1. Assign each point to a cluster.
2. Update centroids: $\text{centroid}_{new} = \text{mean of cluster points}$
3. Repeat until centroids don't change.

• EM:

– Initializaion: Initial mixture parameters

– Expectation (E-step):

Calculate weights for each datapoint x_i for each cluster c_k :

$$\gamma_{ki} = \frac{\mathcal{N}(x_i | \mu_k, \Sigma_k) \cdot \pi_k}{\sum_{j=1}^k \mathcal{N}(x_i | \mu_j, \Sigma_j) \cdot \pi_j}$$

– Maximization (M-step):

Update parameters for each cluster: (for n observations)

$$\begin{aligned} * N_k &= \sum_{i=1}^n \gamma_{ki} \\ * \mu_k &= \frac{1}{N_k} \sum_{i=1}^n \gamma_{ki} \cdot x_i \\ * \Sigma_k &= \frac{1}{N_k} \sum_{i=1}^n \gamma_{ki} \cdot (x_i - \mu_k) \cdot (x_i - \mu_k)^T \\ * \pi_k &= \frac{N_k}{N} \end{aligned}$$

• Silhouette: $\in [-1,1]$ (the closer to 1 the better)

– For an observation x_i :

- * a = average distance of x_i to the points in it's cluster
- * b = average distance of x_i to points in closest cluster
- * $s_{observation} = \frac{b-a}{\max(a,b)}$

– For a cluster:

Average of the cluster's observations silhouettes

– For the solution:

Average of the clusters silhouettes