

HADROS3: Physics and Statistical Theory of the Implemented Pipeline

Rafael C. R. de Lima

Implemented theory through H3-W9b POWHEG real-smoke and real-free execution

2026-06-27

This document describes only the physics, statistics, numerical methods, and proxy models implemented in the current HADROS3 pipeline. It is not a user manual, dashboard guide, installation guide, or proposal for future stages. Where the implementation uses diagnostic renderers or physics proxies, that status is stated explicitly. This is a living theory document for HADROS3. It describes exclusively the physics currently implemented in the official HADROS3 pipeline. Future or planned models are not described here until they become part of the official implementation.

Official Physics Reference

This document is the official reference describing the physics currently implemented in HADROS3.

If any discrepancy is found between the implementation and this document, either:

- the implementation must be corrected; or
- this document must be updated.

Such discrepancies must never be ignored.

The scientific traceability chain for implemented physics is

$$\text{code} \rightarrow \text{provenance} \rightarrow \text{Theory PDF}. \quad (0.1)$$

Each simulation provenance record must identify the theory version that describes its physical and statistical assumptions.

Theory Version Information

Field	Value
Software Version	0.9.0
Physics Version	1.2
Theory Version	1.2
Compatible HADROS3 commit	f14befe
Document generation date	2026-06-27
Pipeline version	H3-W9b
Current implementation status	implemented through H3-W9b POWHEG real-smoke and real-free execution

Stage	Theory status
H3-W5 UHE Source	implemented and documented
H3-W6 Forward Geodesics	implemented and documented
H3-W7 DIS Interaction Sampler	implemented and documented
H3-W8 Observer Bridge	implemented/proxy and documented
H3-W9a POWHEG Dry Run	implemented/dry run and documented
H3-W9b POWHEG Real Smoke/Free	implemented/smoke+free and documented
H3-W10 PYTHIA	planned, not documented as implemented
H3-W11 GEANT4	planned, not documented as implemented
H3-W12 Photon Transport	planned, not documented as implemented
H3-W13 Spectra	planned, not documented as implemented

Contents

Official Physics Reference	1
Theory Version Information	2
Scope and Notation	5
1 Camera / Kerr Ray Tracing	7
1.1 Implemented camera modes	7
1.2 Camera frame	7
1.3 Pinhole diagnostic projection	8
1.4 Inputs and outputs	8
2 Black Hole and Kerr Geometry	9
2.1 Metric functions	9
2.2 ZAMO quantities	10
2.3 Null invariant	10
3 Torus / Medium	11
3.1 Analytic density model	11
3.2 MediumRenderer	11
3.3 Inputs and outputs	12
4 UHE Source	13
4.1 Coordinate cone sampling	13
4.2 Energy and directions	13
4.3 Inputs and outputs	14
5 Forward Geodesics	15
5.1 Momentum construction	15
5.2 Hamiltonian system	15
5.3 Segment quantities	16
5.4 Inputs and outputs	16

6	DIS Interaction Sampler	17
6.1	Density and local energy	17
6.2	Cross-section interpolation	17
6.3	Optical depth and probability	17
6.4	Interaction sampling	18
6.5	Weights	18
6.6	Inputs and outputs	18
7	Observer Bridge	20
7.1	Purpose	20
7.2	Geometry proxies	20
7.3	Score definition	20
7.4	Proxy risk flags	21
7.5	Inputs and outputs	21
8	POWHEG Hard Process Preparation and Smoke Execution	22
8.1	Dry-run role	22
8.2	Candidate selection	22
8.3	Input-card mapping	23
8.4	Real-smoke and real-free LHE validation	23
8.5	Event requests	24
8.6	Inputs and outputs	24
9	Provenance and Statistical Weights	25
9.1	Stage provenance	25
9.2	Weight chain	25
9.3	Random seeds	26
10	Pipeline Summary	27
10.1	Implemented stage contract	27
10.2	Explicit non-goals of the implemented stages	27
A	Appendix: Symbols and Product Names	29

Scope and Notation

The implemented HADROS3 pipeline is organized as a staged calculation,

$$\text{inputs} \rightarrow \text{run}() \rightarrow \text{outputs} \rightarrow \text{diagnostics} \rightarrow \text{provenance}. \quad (0.2)$$

Each implemented stage consumes official products from earlier stages and writes to its own output directory. The stages covered here are the camera preview, Kerr geometry utilities, analytic medium, UHE source, forward null geodesics, DIS optical-depth sampler, Observer Bridge scoring, and POWHEG dry-run hard-process preparation.

This document is maintained as a required living reference for implemented physics. When a new HADROS3 stage changes or adds physical equations, statistical weights, physical approximations, or proxy models, this source file and the regenerated PDF must be updated with the implementation.

Table 3: Implemented-stage coverage in this theory document. Planned stages are listed only to mark that their physics is not yet documented as implemented.

HADROS3 stage	Implementation status	Theory documented
H3-W5 UHE Source	implemented	yes
H3-W6 Forward Geodesics	implemented	yes
H3-W7 DIS Interaction Sampler	implemented	yes
H3-W8 Observer Bridge	implemented/proxy	yes
H3-W9a POWHEG Dry Run	implemented/dry run	yes
H3-W9b POWHEG Real Smoke/Free	implemented/smoke+free	yes
H3-W10 PYTHIA	planned	no
H3-W11 GEANT4	planned	no
H3-W12 Photon Transport	planned	no
H3-W13 Spectra	planned	no

All radii in the dynamical Kerr calculation are expressed in gravitational radius units,

$$r_g = \frac{GM}{c^2}. \quad (0.3)$$

The implementation uses Boyer-Lindquist coordinates $x^\mu = (t, r, \theta, \phi)$ and the metric signature $(-, +, +, +)$. The dimensionless Kerr spin is denoted by a in units of r_g . The code clamps spin-dependent operations away from the extremal singular limit where needed.

Table 4: Primary symbols used in the implemented theory.

Symbol	Meaning
r, θ, ϕ	Boyer-Lindquist spherical coordinates in r_g units.
Σ, Δ, A	Standard Kerr metric functions.
p_μ	Covariant four-momentum components.
$E_{\nu, \text{local}}$	Neutrino energy measured in a local medium or ZAMO frame.
$\rho(r, \theta)$	Analytic torus rest-mass density.
n_b	Baryon number density, $n_b = \rho/m_b$.
$\sigma_{\nu N}(E)$	Tabulated charged-current neutrino-nucleon DIS cross section.
τ	Integrated DIS optical depth along one forward path.
S_{obs}	Observer Bridge final observation score.

Chapter 1

Camera / Kerr Ray Tracing

1.1 Implemented camera modes

The camera preview layer is a visual and diagnostic stage. It is separate from the DIS interaction physics and from the Observer Bridge scoring. Its main product is a rendered observer-view image, typically `CameraPreview/hadros3_camera_preview.png`. The implemented backend selection includes:

- **analytic_geometry_only**: always available; a schematic camera preview, not a physical Kerr ray-traced image.
- **kerr_like_cuda**: a self-contained HADROS3 CUDA preview executable using a Kerr-like camera model.
- **full_kerr**: a self-contained HADROS3 CUDA preview executable using the full-Kerr preview mode when available.
- **legacy_cpu_geodesic_preview**: detected for provenance but not used as the primary self-contained HADROS3 runtime path.

The camera preview can render a torus-like visual object and polar funnels. This visual object is not the DIS optical-depth calculation. The provenance marks camera-preview products separately from the shared `MediumRenderer`. In current provenance, the camera preview records `medium_renderer_used = false` because its purpose is visual camera preview, not the shared diagnostic density-map renderer.

1.2 Camera frame

Observer Bridge camera diagnostics use the same geometric convention for the camera direction that is also relevant when overlaying candidates on the camera preview. A camera position is built from

$$\mathbf{x}_{\text{obs}} = r_{\text{obs}} \begin{pmatrix} \sin i \cos \varphi_{\text{obs}} \\ \sin i \sin \varphi_{\text{obs}} \\ \cos i \end{pmatrix}, \quad (1.1)$$

where r_{obs} is `observer_distance_rg`, i is `observer_inclination_deg`, and φ_{obs} is `observer_azimuth_deg`. The forward axis points approximately toward the origin,

$$\hat{\mathbf{f}} = -\frac{\mathbf{x}_{\text{obs}}}{|\mathbf{x}_{\text{obs}}|}. \quad (1.2)$$

The right and up axes are built from a world z axis, with a fallback right axis if the camera is too close to the polar direction:

$$\hat{\mathbf{r}}_{\text{cam}} = \frac{\hat{\mathbf{f}} \times \hat{\mathbf{z}}}{|\hat{\mathbf{f}} \times \hat{\mathbf{z}}|}, \quad (1.3)$$

$$\hat{\mathbf{u}}_{\text{cam}} = \frac{\hat{\mathbf{r}}_{\text{cam}} \times \hat{\mathbf{f}}}{|\hat{\mathbf{r}}_{\text{cam}} \times \hat{\mathbf{f}}|}. \quad (1.4)$$

1.3 Pinhole diagnostic projection

For Observer Bridge candidate overlays, the implemented projection is a geometric pinhole proxy. It converts a candidate position $\mathbf{x}$ into a camera vector

$$\mathbf{d} = \mathbf{x} - \mathbf{x}_{\text{obs}} \quad (1.5)$$

and projects it as

$$z_{\text{cam}} = \mathbf{d} \cdot \hat{\mathbf{f}}, \quad (1.6)$$

$$x_{\text{ndc}} = \frac{\mathbf{d} \cdot \hat{\mathbf{r}}_{\text{cam}}}{z_{\text{cam}} \tan(\text{FOV}_x/2)}, \quad (1.7)$$

$$y_{\text{ndc}} = \frac{\mathbf{d} \cdot \hat{\mathbf{u}}_{\text{cam}}}{z_{\text{cam}} \tan(\text{FOV}_y/2)}. \quad (1.8)$$

The field-of-view flag is true when $z_{\text{cam}} > 0$ and $|x_{\text{ndc}}| \leq 1$, $|y_{\text{ndc}}| \leq 1$. The camera overlay records `candidate_overlay_projection_model = geometric_pinhole_proxy` and `candidate_overlay_not_rtraced = true`. Therefore the background image may be generated by the camera renderer, but the plotted Observer Bridge candidates are not ray-traced secondary particles.

1.4 Inputs and outputs

Role	Implemented item
Inputs	Black-hole spin, observer distance, inclination, azimuth, FOV, image resolution, torus and funnel visual parameters.
Outputs	<code>CameraPreview/hadros3_camera_preview.png</code> , <code>CameraPreview/hadros3_camera_preview_summary.json</code> .
Approximations	Analytic fallback is schematic. CUDA preview is visual camera rendering; candidate overlays remain pinhole proxies.
Provenance	Records backend used, fallback status, whether CUDA was used, and whether full-Kerr preview mode was requested.

Chapter 2

Black Hole and Kerr Geometry

2.1 Metric functions

HADROS3 uses the Kerr metric in Boyer-Lindquist coordinates and in r_g units. The standard metric functions are

$$\Sigma = r^2 + a^2 \cos^2 \theta, \quad (2.1)$$

$$\Delta = r^2 - 2r + a^2, \quad (2.2)$$

$$A = (r^2 + a^2)^2 - a^2 \Delta \sin^2 \theta. \quad (2.3)$$

The outer horizon radius is

$$r_+ = 1 + \sqrt{1 - a^2}. \quad (2.4)$$

The nonzero covariant metric components implemented for the dynamical calculation are

$$g_{tt} = - \left(1 - \frac{2r}{\Sigma} \right), \quad (2.5)$$

$$g_{t\phi} = - \frac{2ar \sin^2 \theta}{\Sigma}, \quad (2.6)$$

$$g_{rr} = \frac{\Sigma}{\Delta}, \quad (2.7)$$

$$g_{\theta\theta} = \Sigma, \quad (2.8)$$

$$g_{\phi\phi} = \left(r^2 + a^2 + \frac{2a^2 r \sin^2 \theta}{\Sigma} \right) \sin^2 \theta = \frac{A \sin^2 \theta}{\Sigma}. \quad (2.9)$$

The corresponding inverse components used by the Hamiltonian geodesic solver are

$$g^{tt} = - \frac{A}{\Sigma \Delta}, \quad (2.10)$$

$$g^{t\phi} = - \frac{2ar}{\Sigma \Delta}, \quad (2.11)$$

$$g^{rr} = \frac{\Delta}{\Sigma}, \quad (2.12)$$

$$g^{\theta\theta} = \frac{1}{\Sigma}, \quad (2.13)$$

$$g^{\phi\phi} = \frac{\Delta - a^2 \sin^2 \theta}{\Sigma \Delta \sin^2 \theta}. \quad (2.14)$$

2.2 ZAMO quantities

The implemented ZAMO lapse and frame-dragging angular velocity are

$$\alpha = \sqrt{\frac{\Sigma\Delta}{A}}, \quad (2.15)$$

$$\omega = \frac{2ar}{A}. \quad (2.16)$$

For a covariant momentum with components p_t and p_ϕ , the ZAMO energy proxy used in the C++ tetrad utilities is

$$E_{\text{ZAMO}} = -\frac{p_t + \omega p_\phi}{\alpha}. \quad (2.17)$$

The local tetrad initialization maps a normalized local spatial direction (n_r, n_θ, n_ϕ) into a contravariant null vector and then lowers the index with $g_{\mu\nu}$. The implementation checks that the resulting null norm is finite and that the ZAMO energy is positive.

2.3 Null invariant

The null condition is

$$g^{\mu\nu} p_\mu p_\nu = 0. \quad (2.18)$$

Both Python reference utilities and the C++ forward-geodesic backend monitor this invariant. The calculation also monitors the Killing quantities

$$E_\infty = -p_t, \quad (2.19)$$

$$L_z = p_\phi, \quad (2.20)$$

which are conserved because the metric is stationary and axisymmetric.

Chapter 3

Torus / Medium

3.1 Analytic density model

The implemented medium model is an analytic torus density field. It is not a hydrodynamical simulation. The density is evaluated as

$$\rho(r, \theta) = \rho_0 \exp \left[-\frac{1}{2} \left(\frac{r - r_{\text{peak}}}{\sigma_r} \right)^2 \right] \exp \left[-\frac{1}{2} \left(\frac{\theta - \pi/2}{\sigma_\theta} \right)^2 \right], \quad (3.1)$$

with the hard radial support

$$\rho(r, \theta) = 0 \quad \text{if} \quad r < r_{\text{inner}} \quad \text{or} \quad r > r_{\text{outer}}. \quad (3.2)$$

The implemented radial width is

$$\sigma_r = \frac{1}{2}(r_{\text{outer}} - r_{\text{inner}}), \quad (3.3)$$

and the angular width is

$$\sigma_\theta = \max(\theta_{\text{half}}, 10^{-6}). \quad (3.4)$$

The configuration parameter `half_opening_angle_deg` is therefore a Gaussian angular width, not a hard angular boundary. This interpretation is recorded in diagnostics as `half_opening_angle_interpretation = gaussian_width_not_boundary`.

Within the hard radial support, the code can apply a configured `density_floor_g_cm3` by taking the maximum of the analytic value and the floor. Outside the radial shell, the density remains exactly zero.

3.2 MediumRenderer

The shared `MediumRenderer` renders the same analytic density model used by the DIS sampler diagnostics. It records

$$\text{medium_renderer_used} = \text{true}, \quad (3.5)$$

$$\text{density_model_has_hard_radial_cut} = \text{true}, \quad (3.6)$$

$$\text{density_model_theta_profile} = \text{gaussian}, \quad (3.7)$$

$$\text{density_model_theta_is_hard_cut} = \text{false}. \quad (3.8)$$

The renderer draws the hard radial cuts and Gaussian angular density levels. Those angular levels are visual density contours, not physical walls.

3.3 Inputs and outputs

Role	Implemented item
Inputs	<code>rho0_g_cm3</code> , <code>r_inner_rg</code> , <code>r_peak_rg</code> , <code>r_outer_rg</code> , <code>half_opening_angle_deg</code> , optional density floor.
Used by	DIS density evaluation, DIS density diagnostics, forward geometry diagnostics, Observer Bridge diagnostic projections.
Approximation	Static analytic density field; no GRMHD evolution; no self-consistent thermal or composition model.
Output semantics	Positive density only inside the hard radial shell; Gaussian tail in θ .

Chapter 4

UHE Source

4.1 Coordinate cone sampling

The implemented UHE source is a coordinate-volume sampler in a polar cone. For a cone spanning $r_{\min} \leq r \leq r_{\max}$ and $\theta_{\min} \leq \theta \leq \theta_{\max}$, the coordinate volume used for sampling is

$$V_{\text{cone}} = \frac{2\pi}{3} (r_{\max}^3 - r_{\min}^3) (\cos \theta_{\min} - \cos \theta_{\max}). \quad (4.1)$$

Uniform coordinate-volume sampling is implemented by drawing $u_r, u_\theta, u_\phi \sim U(0, 1)$ and setting

$$r = [r_{\min}^3 + u_r(r_{\max}^3 - r_{\min}^3)]^{1/3}, \quad (4.2)$$

$$\cos \theta = \cos \theta_{\min} - u_\theta(\cos \theta_{\min} - \cos \theta_{\max}), \quad (4.3)$$

$$\phi = 2\pi u_\phi. \quad (4.4)$$

The source sampling and physical PDFs are both recorded as

$$p_{\text{source}} = \frac{1}{V_{\text{cone}}}, \quad (4.5)$$

so the implemented source weight is unity for the default model:

$$w_{\text{source}} = \frac{p_{\text{physical}}}{p_{\text{sampling}}} = 1. \quad (4.6)$$

4.2 Energy and directions

The implemented source energy model is monoenergetic:

$$E_{\nu, \text{emit}} = E_0. \quad (4.7)$$

For the isotropic local direction model, the code samples a unit vector in a ZAMO orthonormal frame:

$$\cos \alpha = 2u_\alpha - 1, \quad (4.8)$$

$$\beta = 2\pi u_\beta, \quad (4.9)$$

$$n_r = \cos \alpha, \quad (4.10)$$

$$n_\theta = \sin \alpha \cos \beta, \quad (4.11)$$

$$n_\phi = \sin \alpha \sin \beta. \quad (4.12)$$

The sampling PDF is

$$p_{\Omega} = \frac{1}{4\pi}, \quad (4.13)$$

and the default direction weight is unity.

The source stage does not itself produce the physical Kerr four-momentum for forward propagation. It records the source position, energy, and local direction. The forward-geodesic stage constructs the physical Kerr null momentum from those quantities.

4.3 Inputs and outputs

Role	Implemented item
Inputs	Cone geometry, sample count, random seed, monoenergetic neutrino energy, direction model.
Outputs	<code>UHEsource/uhe_neutrino_source_samples.jsonl</code> and source summary products.
Weights	<code>source_weight = 1</code> and <code>direction_weight = 1</code> for the implemented default uniform/properly matched sampling.
Approximation	Coordinate cone volume, not a GR invariant emissivity integral.

Chapter 5

Forward Geodesics

5.1 Momentum construction

The forward stage consumes UHE source samples and constructs a Kerr null covector. For a local isotropic direction, the ZAMO tetrad maps the local direction into a null four-vector and then into covariant momentum components. For legacy coordinate radial directions, the implementation constructs a covariant momentum with $p_t = -E$ and solves the null constraint for p_r .

The implementation records that the physical Kerr four-momentum is constructed in the forward stage, not in the source sampler.

5.2 Hamiltonian system

The Hamiltonian for null geodesics is

$$H(x, p) = \frac{1}{2} g^{\mu\nu}(x) p_\mu p_\nu. \quad (5.1)$$

The implemented equations of motion are

$$\frac{dx^\mu}{d\lambda} = g^{\mu\nu} p_\nu, \quad (5.2)$$

$$\frac{dp_i}{d\lambda} = -\frac{1}{2} \partial_i g^{\mu\nu} p_\mu p_\nu, \quad i \in \{r, \theta\}. \quad (5.3)$$

The cyclic momenta are conserved by construction in the differential system:

$$\frac{dp_t}{d\lambda} = 0, \quad \frac{dp_\phi}{d\lambda} = 0. \quad (5.4)$$

The current implementation uses an RK4 stepping procedure with substeps and invariant checks. Derivatives of inverse metric components are evaluated numerically. When needed, p_r can be renormalized to keep the null constraint within tolerance. The solver stops when it reaches the horizon neighborhood, the configured outer radius, maximum steps, or an invalid invariant condition.

5.3 Segment quantities

Each accepted forward path is written as a set of path segments. The segment length used downstream is a coordinate path-length proxy,

$$\Delta l_{\text{coord}} = [(\Delta r)^2 + (r_{\text{mid}} \Delta \theta)^2 + (r_{\text{mid}} \sin \theta_{\text{mid}} \Delta \phi)^2]^{1/2}. \quad (5.5)$$

This is then converted to cm in the DIS stage by multiplying by r_g in cm. This is an implemented optical-depth path-length approximation and should not be confused with a fully covariant matter-frame line element.

5.4 Inputs and outputs

Role	Implemented item
Inputs	<code>UHEsource/uhe_neutrino_source_samples.jsonl</code> , black-hole spin, step settings, tolerances, outer radius, requested number of samples.
Outputs	<code>ForwardGeodesics/uhe_neutrino_forward_paths.jsonl</code> , <code>ForwardGeodesics/uhe_neutrino_forward_path_segments.jsonl</code> , and summary diagnostics.
Invariants	Null norm, Killing energy, and L_z are monitored.
Approximation	Numerical RK4 Hamiltonian evolution with coordinate segment lengths for downstream optical depth.

Chapter 6

DIS Interaction Sampler

6.1 Density and local energy

The DIS sampler consumes forward path segments and evaluates the analytic torus density at segment midpoints. The baryon density is

$$n_b(r, \theta) = \frac{\rho(r, \theta)}{m_b}, \quad (6.1)$$

where m_b is the baryon mass in grams.

The local neutrino energy is computed from the covariant momentum. If the configured static medium model is valid at that position, the code uses the static observer expression

$$E_{\text{local}} = -p_t u^t, \quad u^t = \frac{1}{\sqrt{-g_{tt}}}. \quad (6.2)$$

If a static observer is not valid, or if the implementation needs the fallback, the ZAMO expression is used:

$$E_{\text{local}} = -\left(\frac{p_t}{\alpha} + \frac{\omega p_\phi}{\alpha}\right) = -\frac{p_t + \omega p_\phi}{\alpha}. \quad (6.3)$$

The static-to-ZAMO fallback is recorded as a physics-risk approximation.

6.2 Cross-section interpolation

The DIS charged-current cross sections are read from compact tabulated files for the implemented GBW and IIM models. If an energy lies inside the tabulated range, the interpolation is log-log:

$$\ln \sigma_{\nu N}(E) = \ln \sigma_0 + \frac{\ln E - \ln E_0}{\ln E_1 - \ln E_0} (\ln \sigma_1 - \ln \sigma_0). \quad (6.4)$$

Requests outside the tabulated range are rejected for that segment and the segment contribution is set to zero in the diagnostic recomputation.

6.3 Optical depth and probability

For each segment,

$$\Delta \tau_i = n_{b,i} \sigma_{\nu N}(E_{\text{local},i}) \Delta l_i, \quad (6.5)$$

where Δl_i is the coordinate path-length proxy converted from r_g to cm. The total optical depth along a path is

$$\tau = \sum_i \Delta \tau_i. \quad (6.6)$$

The interaction probability is

$$P_{\text{int}} = 1 - \exp(-\tau), \quad (6.7)$$

implemented numerically as

$$P_{\text{int}} = -\text{expm1}(-\tau) \quad (6.8)$$

with clipping to the interval $[0, 1]$.

6.4 Interaction sampling

If a path is accepted by the Bernoulli trial with probability P_{int} , the segment index is sampled by the inverse CDF

$$P(i) = \frac{\Delta \tau_i}{\sum_j \Delta \tau_j}. \quad (6.9)$$

After the segment is selected, the implemented accepted-point sampler requires the final recorded interaction point to have positive medium density. It performs rejection sampling inside the chosen segment and records

$$\text{interaction_point_density_checked} = \text{true}, \quad (6.10)$$

$$\text{interaction_point_inside_medium} = \text{true} \quad \text{when} \quad \rho(r_{\text{int}}, \theta_{\text{int}}) > 0, \quad (6.11)$$

$$\text{interaction_point_rho_g_cm3} = \rho(r_{\text{int}}, \theta_{\text{int}}). \quad (6.12)$$

The fallback policy is recorded in `interaction_point_sampling_method`. The present criterion for a valid accepted point is $\rho(r_{\text{int}}, \theta_{\text{int}}) > 0$.

6.5 Weights

The DIS products preserve source and direction weights from the UHE source. The pre-event weight used downstream is recorded as `final_pre_event_weight`. The DIS sampler also records optical-depth and expected-interaction quantities so that later stages can distinguish the sampling decision from pre-event observation scoring.

6.6 Inputs and outputs

Role	Implemented item
Inputs	Forward geodesic paths and segments, source samples, DIS cross-section tables, analytic medium parameters, random seed.
Outputs	DIS/dis_path_optical_depths.jsonl, DIS/dis_accepted_interactions.jsonl, optical-depth report, diagnostics, GBW/IIM comparison products.

Diagnostics	Tau distribution, interaction probability distribution, optical depth maps, medium density map, accepted interaction distributions, sigma and correlation plots.
Approximation	Static or ZAMO local energy model; coordinate path-length proxy; compact cross-section tables.

Chapter 7

Observer Bridge

7.1 Purpose

The Observer Bridge consumes accepted DIS interactions and assigns a non-destructive observation score. It does not generate secondary particles, does not call POWHEG, does not call PYTHIA, does not call GEANT4, and does not perform photon transport. All accepted DIS interactions become Observer Bridge candidates, even if they are outside the camera FOV or have small score.

7.2 Geometry proxies

The interaction position is converted to Cartesian coordinates through

$$(x, y, z) = (r \sin \theta \cos \phi, r \sin \theta \sin \phi, r \cos \theta). \quad (7.1)$$

The observer is placed at the configured camera position. The geometric direction from the interaction to the observer is

$$\hat{\mathbf{n}}_{\text{obs}} = \frac{\mathbf{x}_{\text{obs}} - \mathbf{x}_{\text{int}}}{|\mathbf{x}_{\text{obs}} - \mathbf{x}_{\text{int}}|}. \quad (7.2)$$

The implemented escape proxy compares this direction with the local radial direction,

$$w_{\text{esc}} = \max(0, \hat{\mathbf{x}}_{\text{int}} \cdot \hat{\mathbf{n}}_{\text{obs}}). \quad (7.3)$$

This is a proxy, not a particle-transport escape calculation.

The FOV weight is either a hard FOV flag or a soft Gaussian-like angular proxy, depending on configuration. The visibility, line-of-sight, and redshift models are explicitly recorded as proxies. The implemented default redshift and line-of-sight weights are unity proxies unless configured otherwise.

7.3 Score definition

The implemented physics weight in the C++ Observer Bridge is

$$w_{\text{physics}} = \text{final_pre_event_weight}, \quad (7.4)$$

with a fallback to source times direction weight when that field is absent. The observer weight is the product of the implemented proxy factors:

$$w_{\text{observer}} = w_{\text{esc}} w_{\text{visibility}} w_{\text{FOV}} w_{\text{distance}} w_{\text{redshift}} w_{\text{LOS}}. \quad (7.5)$$

The final observation score is

$$S_{\text{obs}} = w_{\text{physics}} w_{\text{observer}}. \quad (7.6)$$

All three quantities are recorded for each candidate: `physics_weight`, `observer_weight`, and `final_observation_score`. The implementation enforces non-negative proxy weights by clipping or construction.

7.4 Proxy risk flags

The reports record the proxy nature of the bridge:

$$\text{secondary_particle_proxy_model} \neq \text{full_transport}, \quad (7.7)$$

$$\text{escape_proxy_physics_risk} = \text{true}, \quad (7.8)$$

$$\text{visibility_proxy_physics_risk} = \text{true}, \quad (7.9)$$

$$\text{redshift_proxy_physics_risk} = \text{true}. \quad (7.10)$$

The stage status is scoring-only. It is intentionally non-destructive.

7.5 Inputs and outputs

Role	Implemented item
Inputs	DIS/dis_accepted_interactions.jsonl and runtime configuration. It may consult previous products for diagnostics.
Outputs	ObserverBridge/observer_bridge_candidates.jsonl, ObserverBridge/observer_bridge_ranked_events.jsonl, JSON/CSV summaries, camera-view and overlay diagnostics.
Invariant policy	Number of candidates scored equals number of accepted DIS interactions consumed. FOV is not used as a destructive filter.
Approximation	Geometric escape, visibility, FOV, redshift, and line-of-sight proxies. No secondary-particle generation.

Chapter 8

POWHEG Hard Process Preparation and Smoke Execution

8.1 Dry-run role

H3-W9a prepares local POWHEG DIS jobs but deliberately does not execute `pwhg_main`. It consumes ranked Observer Bridge events and writes its own products under `POWHEG/`. It does not modify `ObserverBridge/`, `DIS/`, `ForwardGeodesics/`, or `UHEsource/`.

The H3-W9a run mode is

$$\text{powheg_run_mode} = \text{dry_run}. \quad (8.1)$$

The reports record

$$\text{powheg_invoked} = \text{false}, \quad (8.2)$$

$$\text{pwhg_main_executed} = \text{false}, \quad (8.3)$$

$$\text{powheg_lhe_generated} = \text{false}. \quad (8.4)$$

H3-W9b adds a controlled real-smoke mode:

$$\text{powheg_run_mode} = \text{real_smoke}. \quad (8.5)$$

This mode selects only the top-ranked candidate, writes one input card, executes the self-contained local executable `external/powheg/build/DIS/pwhg_main`, and validates a minimal LHE file. It is a pipeline smoke execution, not the full production event-generation stage. PYTHIA, GEANT4, photon transport, and spectra remain disabled.

8.2 Candidate selection

The driver reads `ObserverBridge/observer_bridge_ranked_events.jsonl`, sorts candidates by decreasing final observation score, and uses the original input order as a tie-breaker. The implemented selection policies are:

- `top_score`: take highest-score candidates up to `max_powheg_events`.
- `score_threshold`: discard candidates below `min_final_observation_score`, then cap at `max_powheg_events`.
- `all_candidates`: represented by the same sorted traversal and cap.

8.3 Input-card mapping

Each selected candidate receives a request identifier of the form H3PWHG-000001. Each request has its own `powheg_input_cards/<request_id>/powheg.input`. The implemented mapping is

$$E_{\nu,\text{local}} \rightarrow \text{ebeam1}, \quad (8.6)$$

$$m_N = 0.938272 \text{ GeV} \rightarrow \text{ebeam2}, \quad (8.7)$$

$$\text{events_per_candidate} \rightarrow \text{numevts}, \quad (8.8)$$

$$\text{channel_type} = 3, \quad (8.9)$$

$$\text{vtype} = 2. \quad (8.10)$$

The dry-run card also records fixed PDF choices `lhans1 = 303400` and `lhans2 = 303400`. The implemented scale cap is

$$Q_{\text{max}} = \min \left(2\sqrt{0.938272 E_{\nu,\text{local}}}, 10^5 \right). \quad (8.11)$$

For the implemented seed mode, the seed is

$$\text{powheg_seed} = \text{random_seed} + \text{candidate_rank}. \quad (8.12)$$

8.4 Real-smoke and real-free LHE validation

In H3-W9b real-smoke mode, the prepared POWHEG card is copied into an isolated work directory and `pwheg_main` is executed with that directory as its working directory. The produced `pwgevents.lhe` must satisfy

$$\text{<LesHouchesEvents} \in \text{pwgevents.lhe}, \quad (8.13)$$

$$\text{</LesHouchesEvents>} \in \text{pwgevents.lhe}, \quad (8.14)$$

$$N_{\text{LHE events}} > 0. \quad (8.15)$$

The validated LHE and run log are copied to

$$\text{POWHEG/powheg_lhe/H3PWHG-000001/pwgevents.lhe}, \quad (8.16)$$

$$\text{POWHEG/powheg_run_logs/H3PWHG-000001/powheg.log}. \quad (8.17)$$

The validation report records `powheg_invoked=true`, `pwheg_main_executed=true`, `powheg_lhe_generated=true` and `n_lhe_events`. This smoke mode does not modify `ObserverBridge/`, `DIS/`, `ForwardGeodesics/`, or `UHEsource/`.

H3-W9b real-free mode uses the same local POWHEG execution and LHE validation rules, but it removes the real-smoke safety clamp. The number of interaction candidates is set by `max_powheg_events`, and the number of independent POWHEG hard-scattering realizations per selected interaction is set by `events_per_candidate`. Each selected candidate is executed in its own isolated POWHEG work directory. The produced LHE files are copied under `POWHEG/powheg_lhe/<powheg_request_id>/pwgevents.lhe`, and the parser aggregates all produced LHE files into the POWHEG particle and event summaries. The provenance records `powheg_real_free_invoked=true`, `real_free_mode=true`, `n_powheg_jobs_requested`, `n_powheg_jobs_run`, `events_per_candidate_requested`, and `n_lhe_events_total`. This mode still does not invoke PYTHIA, GEANT4, photon transport, or spectra.

8.5 Event requests

The event request file POWHEG/powheg_event_requests.jsonl records for each prepared job:

$$\mathcal{R}_{\text{POWHEG}} = \{\text{powheg_request_id}, \text{candidate_rank}, \text{interaction_id}, \text{event_id}, \text{source_sample_id}, E_{\nu, \text{local}}, w_{\text{physics}}, w_{\text{observer}}, S_{\text{obs}}, \text{powheg_input_path}, \text{powheg_seed}, \text{powheg_status}\}. \quad (8.18)$$

The dry-run status is `dry_run_ready`; `powheg_invoked` is false for every dry-run request. In real-smoke mode the initial status is `real_smoke_ready`; after successful validation the request records `real_smoke_lhe_generated`, `powheg_invoked=true`, `pwheg_main_executed=true`, the LHE path, the log path, and `n_lhe_events`. In real-free mode the analogous statuses are `real_free_ready` and `real_free_lhe_generated`; multiple validated LHE products may be recorded in a single POWHEG run.

8.6 Inputs and outputs

Role	Implemented item
Inputs	ObserverBridge/observer_bridge_ranked_events.jsonl and POWHEG configuration values.
Outputs	POWHEG/powheg_event_requests.jsonl, input cards, summary JSON/CSV, report JSON, validation report, diagnostic plots, and in real-smoke or real-free mode validated <code>pwgevents.lhe</code> products.
Still disabled	No PYTHIA; no GEANT4; no photon transport; no spectra.
Backend	C++17 executable <code>bin/hadros3_powheg_driver</code> . Python handles orchestration and plots.

Chapter 9

Provenance and Statistical Weights

9.1 Stage provenance

Each stage records the backend, products, validation flags, and disabled future stages relevant to its current implementation. A typical provenance record contains:

$$\{\text{parameters, products, validation, stage summaries, disabled stages}\}. \quad (9.1)$$

The implemented provenance explicitly marks future expensive stages as disabled until they are introduced:

$$\text{pythia_invoked} = \text{false}, \quad (9.2)$$

$$\text{geant4_invoked} = \text{false}, \quad (9.3)$$

$$\text{photon_transport_invoked} = \text{false}, \quad (9.4)$$

$$\text{expensive_event_generation_invoked} = \text{false}. \quad (9.5)$$

For H3-W9a, POWHEG is active only as dry-run preparation:

$$\text{status} = \text{powheg_jobs_prepared_no_lhe}. \quad (9.6)$$

For H3-W9b real-smoke execution:

$$\text{status} = \text{powheg_real_smoke_lhe_generated}. \quad (9.7)$$

The provenance also records the scientific theory reference for the run:

$$\text{theory_document} = \text{docs/Theory/HADROS3_Physics_Theory.pdf}, \quad (9.8)$$

$$\text{theory_version} = \backslash \text{TheoryVersion} , \quad (9.9)$$

$$\text{theory_commit} = \text{runtime git commit}, \quad (9.10)$$

$$\text{theory_generation_date} = \text{runtime provenance timestamp}. \quad (9.11)$$

These fields connect each generated result to the theory document that describes the implemented physical and statistical assumptions.

9.2 Weight chain

The implemented source and direction samplers are configured so that the default source and direction weights are unity:

$$w_{\text{source}} = 1, \quad (9.12)$$

$$w_{\text{direction}} = 1. \quad (9.13)$$

The DIS sampler records interaction and pre-event weights. The Observer Bridge then uses

$$w_{\text{physics}} = \text{final_pre_event_weight} \quad (9.14)$$

and computes

$$S_{\text{obs}} = w_{\text{physics}} w_{\text{observer}}. \quad (9.15)$$

The POWHEG dry-run and real-smoke modes carry those weights into each event request. They do not change the physics score. H3-W9a stops after card preparation; H3-W9b executes one local POWHEG smoke job and validates the resulting minimal LHE.

9.3 Random seeds

The implemented random stages record seeds:

- UHE source sampling records its source seed.
- DIS interaction sampling records its acceptance and point-sampling seed.
- POWHEG dry-run and real-smoke modes record `random_seed` and the per-candidate `powheg_seed`.

These seeds are part of the statistical contract of the pipeline.

Chapter 10

Pipeline Summary

10.1 Implemented stage contract

The current implemented pipeline can be summarized as

UHESource $\rightarrow$ ForwardGeodesics $\rightarrow$ DIS $\rightarrow$ ObserverBridge $\rightarrow$ POWHEG RealSmoke. (10.1)

The camera preview is an observer-view diagnostic that can be used by the dashboard and by Observer Bridge overlays, but it is not a physical secondary-particle propagation stage.

Table 10.1: Implemented pipeline products and semantic status.

Stage	Official inputs	Official outputs	Status
UHE Source	Configuration	UHEsource/ JSONL/JSON	Sampling proxy with monoenergetic source.
Forward Geodesics	UHEsource/	ForwardGeodesics/ paths and segments	Kerr null geodesic propagation.
DIS Sampler	ForwardGeodesics/, UHEsource/	DIS/ optical-depth and accepted interactions	Optical-depth DIS sampler.
Observer Bridge	DIS/dis_accepted_interactions	ObserverBridge/ candidates and ranked events	Non-destructive geo- metric scoring proxy.
POWHEG Real Smoke	ObserverBridge/observerBridge/observerBridge/ POWHEG/realSmoke	POWHEG/realSmoke/ put cards, validation report, and one smoke LHE	H3-W9a dry run plus H3-W9b local one- job LHE smoke.

10.2 Explicit non-goals of the implemented stages

The current pipeline does not yet implement:

- production-scale POWHEG event execution beyond the real-smoke mode;
- PYTHIA showering and hadronization;

- GEANT4 detector or material transport;
- photon transport from secondaries to the observer;
- full GRMHD torus evolution;
- full physical visibility, escape, redshift, or line-of-sight transport.

Those future stages must preserve the contract that each stage consumes official previous outputs, writes only to its own directory, records provenance, and marks expensive or proxy physics explicitly.

Appendix A

Appendix: Symbols and Product Names

Product or field	Meaning
uhe_neutrino_source_samples.json	UHE neutrino source positions, energies, directions, and sampling weights.
uhe_neutrino_forward_path_segments.json	Forward-going UHE neutrino path segments with midpoint coordinates, momenta, and segment lengths.
dis_path_optical_depths.json	Path-level DIS optical depths and interaction probabilities.
dis_accepted_interactions.json	Accepted DIS interactions and their density-checked interaction points.
observer_bridge_candidates.json	Accepted DIS interactions scored as observation candidates.
observer_bridge_ranked_event_candidates.json	Accepted DIS interaction candidate family ranked by final observation score.
powheg_event_requests.json	Dry-run POWHEG event requests and card paths.
final_pre_event_weight	Physics weight consumed by Observer Bridge as implemented.
final_observation_score	Product of implemented physics and observer weights.
powheg_invoked	False in H3-W9a dry run; true in H3-W9b real smoke.
pwhg_main_executed	False in H3-W9a dry run; true in H3-W9b real smoke.
powheg_lhe_generated	False in H3-W9a dry run; true in H3-W9b real smoke.