



# Modeling Data Relationships

---




# Topics

- Building Data Relationships
- Entity & Reference Identifiers
- Relationships
  - 1 to 1
  - 1 to Many
  - Many to Many
- Indexes
- Referential Integrity (Delete rule)
- Entity Diagrams

# Building Data Relationships

Data types are rarely isolated


- A rich data model establishes the relationships between data
- The Relationships can be as important as the data itself



# Entity Identifier

An Entity must have an  **Identifier** to allow relationships


- **Id** attribute is a long integer and automatically numbered by default
- Mandatory
- Possible types
  - Text
  - Integer / Long Integer
  - (Another) Entity Identifier














Represents the database table's Primary Key

- OutSystems support **simple primary keys**
- **NO** composite keys!

# Referencing Data

- Entities can be referenced by their identifier
  - Create an attribute of type  Entity Identifier
  - Can be mandatory or not
  - Static Entities can only reference other Static Entities
- Represents the database table's Foreign Key
- *NullIdentifier()* is the default value for reference attributes

Order
 Id
 Description
 DueDate
 CreatedOn
 ShippedOn
 Priority
 AssignedTo
 ReviewedBy
 Status
 RequestedBy

Priority Entity Attribute	
Name	Priority
Description	...
Label	Priority
Data Type	 Priority Identifier ▼
Is Mandatory	No ▼
Delete Rule	Protect ▼




# 1-to-1 Relationship

## 1-to-1

- Each Receipt belongs to **one** Order
- Each Order has at **most one** Receipt

OrderReceipt is an **extension** of Order


- OrderReceipt has an identifier of type ***Order Identifier***
- Is Mandatory is set to *Yes*
- OrderReceipt Identifier must be explicitly assigned with the *Order* identifier when creating the record



# Extension Entity

## Extension Entity

- Shares its identifier with the base Entity
- The two Entities could be merged
- Usually split apart due to:
  - Performance issues
  - Base Entity is read only (e.g. User)




# 1-to-many Relationship

## 1-to-many

- Each Customer may have **many** Orders
- An Order was requested by **one** Customer

## A Customer submits multiple Orders

- Order Entity has a reference attribute of type *Customer Identifier (RequestedBy)*
- Reference attribute may or may not be mandatory
  - If not mandatory, some Orders may not know which Customer requested the Order






# Master-Detail Entities

## Master-Detail

- Detail Entity references the Master Entity
- Detail Entity has a reference attribute of type *MasterEntity Identifier*
- An Entity can have multiple reference attributes




# Many-to-many Relationship

## Many-to-many

- Each Product may be part of **many** Orders
- Each Order may have **many** Products

An OrderProduct **Junction Entity** is required


- Reference attribute *OrderId* of type *Order Identifier*
- Reference attribute *ProductId* of type *Product Identifier*



# Junction Entity

## Junction Entity

- New Entity with its own unique **Id**
- One reference attribute per each Entity of the relationship
  - *MasterEntity1 Identifier*
  - *MasterEntity2 Identifier*
- Unique Index with both reference attributes may be useful



# Indexes

Speed up data retrieval over certain attributes

- Costs additional writes and storage space
- Reference attributes have automatically created indexes
- Custom indexes can be created

Avoid duplicates

- Define the Index as **Unique**
- Combine one or more attributes

The screenshot displays the configuration interface for the 'OrderProduct' entity. The 'Indexes' tab is active, showing a list of indexes on the left and a detailed view of the 'OrderProduct' index on the right. The index is configured with the name 'OrderProduct', a unique constraint, and two attributes: 'Orderid' and 'Productid'.

OrderProduct Entity	
Name	OrderProduct
Description	...
Public	Yes
Expose Read Only	No
Indexes	
More...	


OrderProduct	
Name	OrderProduct
Description	
More options	
Attributes   <b>Indexes</b>   Example Record   Advanced	
New Delete	
AutoIndex_Orderid	
AutoIndex_Productid	
OrderProduct	
Name	OrderProduct
Description	...
Unique	Yes
Attributes	
Attribute 1	Orderid
Attribute 2	Productid
(Add Attribute)	
Created by jnc	
Last modified by jnc at 11:17 AM	

# Referential Integrity

## Delete Rule property of the reference attribute

Applied when deleting a record from the referenced Entity (e.g. Customer)

- **Protect** - does not allow deleting the record
  - Ex: Customer with Orders is not deleted
- **Delete** - deletes the record and cascades delete all the records that reference it
  - Ex: Customer and all its Orders are deleted
- **Ignore** - does not guarantee referential integrity
  - Ex: Customer is deleted. Orders are kept




# Entity Diagram

Visual representation of the Data Model

Designed by the developer

The Entity Diagram represents:

- Entities
- Relationships
- Delete Rules
  - Protect
  - **Delete**
  - Ignore



# Summary

- Building Data Relationships
- Entity & Reference Identifiers
- Relationships
  - 1 to 1
  - 1 to Many
  - Many to Many
- Indexes
- Referential Integrity (Delete rule)
- Entity Diagrams



# **Modeling Data Relationships**

## **Thank You!**