

RT58x SDK Release Notes



Contents

RT:	58x SDK Release Notes	1
Cor	ntents	2
1	Revision History	3
2	RT58x_SDK_v1.8.0	8
3	RT58x_SDK_v1.7.0	9
4	RT58x_SDK_v1.6.0	10
5	RT58x_SDK_v1.5.0	11
6	RT58x_SDK_v1.4.0	12
7	RT58x_SDK_v1.3.0	13
8	RT58x_SDK_v1.2.3_BLE_Mesh	15
9	RT58x_SDK_v1.2.2_Zigbee	16
10	RT58x_SDK_v1.2.1	17
11	RT58x_SDK_v1.2.0	18
12	RT58x_SDK_v1.1.1	20
13	RT58x_SDK_v1.1.0	21
14	RT58x_SDK_v1.0.1	23
15	RT58x_SDK_v1.0.0_Mesh	24
16	RT58x_SDK_v1.0.0	25
17	RT58x_SDK_v0.3.1	28
18	RT58x_SDK_v0.2.0	30
19	RT58x_SDK_v0.1.0	31



1 Revision History

Date	Version	Description
2021/11/05	0.1.0 (alpha)	- Initial version
2022/01/11	0.2.0 (alpha)	- For SubG only
2022/02/16	0.3.1 (alpha)	- Added GCC project for all examples
		- Added Zigbee/BLE multi-protocol demo
		- Added more Zigbee examples
		- Added more tools and related documents
		- Unified application architecture of different protocols
		- Modified power saving example
2022/03/31	1.0.0	- Added more peripheral drivers and examples
		- Added BLE demos with low power mode mechanism
		- Added more tools and related documents
		- Integrated DTM function
		- Fixed bug in BLE multi-link demo
2022/04/08	1.0.0 (Mesh)	- Added BLE Mesh demo example
		- Added BLE Mesh App
		- Added BLE Mesh documents
2022/05/18	1.0.1	- Added software PMU calibration
		- Extend Zigbee maximum network nodes
		- Fixed low speed timer reload issue
2022/06/10	1.1.0	-Added examples: I2S digital microphone
		-Added Address protect in flash driver.
		-Modify PWM example
		-Added BLE UART_cmd demo
		-Added BLE Beacon demo
		-Added Zigbee Gateway command example
		-Added Zigbee User_specific cluster
		-Added Thermostat cluster
		-Fixed Zigbee two end-point bug
		-Fixed Zigbee OTA buffer issue
2022/07/09	1 1 1	-RF_Lab_Test_Tool support SubG RF test
2022/07/08	1.1.1	- Modify PMU DCDC initial setting to enhance the
2022/07/10	120	stability under stress environment
2022/07/19	1.2.0	-BLE: add Privacy and connect CTE API
		-Zigbee: now can pre-configure network parameter.



		7' 1 11 OTA C 1
		-Zigbee: add OTA function in new gateway demo
		-Zigbee: AES by HW accelerator.
		-Add multi-protocol demo: Zigbee Easy Gateway
		-Add multi-protocol demo: utilize BLE to reset Zigbee
		device
		-Add Android app for multi-protocol demos.
2022/09/05	1.2.1	-Tools: MP_Tool add Tx power 0/4 dBm target
		-Zigbee: optimize RX current consumption
		-Zigbee: device send leave command to gateway after
		factory reset
2022/09/30	1.2.2	Zigbee Gateway module:
		- Revise binding command
		- Add read attribute, write attribute, configure report
		command
		Zigbee Light:
		- Add OTA client cluster
		- Add finding & binding process
		Zigbee Switch:
		- Remove endpoint 1&3
		- Add OTA client cluster
		- Add finding & binding process
		Zigbee OTA Server:
		- Removed (gateway module replace)
		Zigbee OTA Client:
		- Removed (light/switch replace)
2022/10/13	1.2.3	BLE Mesh:
		-Implement Model and Lighting Demo.
		-BLE Mesh Performance Tuning
		-BLE Mesh Document
2023/01/17	1.3.0	Platform & Peripheral:
		- Update ADC setting to improve accuracy of chip
		variation
		- Bootloader support FOTA image decompression.
		Zigbee:
		- Power on/off 5 times to reset light device
		- Add sensor related clusters
		- New flash update algorithm
		- Add library version



		N. 110 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
		- Modify private cluster ID
		- Improve interoperability with other Zigbee device
		- Fix under multi-PAN environment, device may accept
		packet from different PAN_ID.
		BLE:
		- Use 2 bytes to indicate LL TX data sequence
		- FOTA flow update. Support image compression
		BLE Mesh:
		- Fixed transparent transmission bug: now different packet
		size are all right
		Sub-G:
		- Add OQPSK 6.25k data rate
		- Add field test demo code
		Tool:
		- Android app: support BLE Mesh demo
		- Android app: support Zigbee smart home
		- MP_tool: separate BLE/Zigbee Tx power target
		- FOTA tool: support OTA image compression
		- RF_lab_test_tool: modify SubG test option
2023/03/07	1.4.0	Platform:
2023/03/07	1.4.0	- Add 2MB Flash FLM
2023/03/07	1.4.0	- Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity
2023/03/07	1.4.0	Add 2MB Flash FLMUpdate flash driving setting to improve RX sensitivityFix Deep Sleep issue
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW.
2023/03/07	1.4.0	Add 2MB Flash FLMUpdate flash driving setting to improve RX sensitivityFix Deep Sleep issue
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW.
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW. Tool:
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW. Tool: - MP_tool support 2MB flash
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW. Tool: - MP_tool support 2MB flash Multi-Protocol:
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW. Tool: - MP_tool support 2MB flash Multi-Protocol: - Modify Zigbee/BLE application document
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW. Tool: - MP_tool support 2MB flash Multi-Protocol: - Modify Zigbee/BLE application document Other:
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW. Tool: - MP_tool support 2MB flash Multi-Protocol: - Modify Zigbee/BLE application document Other: - 2MB flash OTA add secure upgrade
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW. Tool: - MP_tool support 2MB flash Multi-Protocol: - Modify Zigbee/BLE application document Other: - 2MB flash OTA add secure upgrade FW:
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW. Tool: - MP_tool support 2MB flash Multi-Protocol: - Modify Zigbee/BLE application document Other: - 2MB flash OTA add secure upgrade FW: - Fixed getting wrong RSSI value when TX power is very
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW. Tool: - MP_tool support 2MB flash Multi-Protocol: - Modify Zigbee/BLE application document Other: - 2MB flash OTA add secure upgrade FW: - Fixed getting wrong RSSI value when TX power is very low on Sub-G - Enable MAC features for multi-protocol
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW. Tool: - MP_tool support 2MB flash Multi-Protocol: - Modify Zigbee/BLE application document Other: - 2MB flash OTA add secure upgrade FW: - Fixed getting wrong RSSI value when TX power is very low on Sub-G - Enable MAC features for multi-protocol - Support up to 32 sets of source match address
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW. Tool: - MP_tool support 2MB flash Multi-Protocol: - Modify Zigbee/BLE application document Other: - 2MB flash OTA add secure upgrade FW: - Fixed getting wrong RSSI value when TX power is very low on Sub-G - Enable MAC features for multi-protocol - Support up to 32 sets of source match address - Security key setup failed when BLE is enabled on
2023/03/07	1.4.0	 - Add 2MB Flash FLM - Update flash driving setting to improve RX sensitivity - Fix Deep Sleep issue - Turn off LDO Enable when not loading 80251 FW. Tool: - MP_tool support 2MB flash Multi-Protocol: - Modify Zigbee/BLE application document Other: - 2MB flash OTA add secure upgrade FW: - Fixed getting wrong RSSI value when TX power is very low on Sub-G - Enable MAC features for multi-protocol - Support up to 32 sets of source match address



2023/06/29	1.5.0	 [Platform]: Modify VS Code and SDK Getting Start document. Add SDK Quick Start document [Tool]: MP Tool v1.4.0 support Sub-G power trim, matter production with certificates, and 1 to 16 parallel test BLE Mesh Android app support Scenes, Rafael TRSP Server, and Rafael TRSP Client modes [BLE Mesh]: Add gateway project and document Restructure the file and folder for client model Fixed provisioning fail issue
2023/08/23	1.6.0	[Platform]: - Add SRAM power enable at initial function Modify WDT setting to let WDT can reset all blocks - Modify WDT example - Fix Bootloader OTA decoder error at some image length [SubG]: - Support 433MHz [BLE]: - Add Privacy for Direct ADV, Scan [BLE Mesh]: - Gateway support BLE Transparent Transmission [Tool]: - MP Tool apply RF Trim calibration value - RF Lab Test Tool add SubG Tx power selection for band0 915Mhz to band2 433Mhz.
2024/01/08	1.7.0	 [BLE]: - Add privacy demo example - Support LE Secure Connection [BLE Mesh]: - Server library support BLE TRSP service [Thread]: - Add Thread example and document [Zigbee]: - Modify gateway command document [Tool]:



		- Mobile App add LE commission for SubG device to
		join SubG network
2024/03/21	1.8.0	[Platform]:
		- Add examples projects: Flash_RW, GPIO_Interrupt,
		Gpio_Input, GPIO_Output, SADC_Polling,
		Timer_Periodic, Timer_Freerun, WDT_Interrupt
		[SubG]:
		- Support 470~510MHz
		- Keep Tx constant power (15dBm) regardless Vbat
		voltage
		[Thread]:
		-Add SubG frequency band setting (915M, 868M, 433M)
		[Tool]:
		-RF lab test tool: add SubG 470~510MHz



2 RT58x_SDK_v1.8.0

New Features

- -Platform
 - ➤ Add examples project:
 Flash_RW/GPIO_Interrupt/GPIO_Input/GPIO_Output
 SADC Polling/Timer Periodic/Timer Freerun/WDT Interrupt
- -SubG
 - > Add 470~510MHz band
 - ➤ Keep Tx constant power (15dBm) regardless Vbat voltage (Frequency: 433~510MHz)
- -Thread
 - ➤ Add SubG frequency band setting (915M, 868M, 433M)

• Feature Changes

- -Tool
 - > RF lab test tool: add SubG 470~510MHz

Bug Fixes



3 RT58x_SDK_v1.7.0

New Features

- -BLE
 - ➤ Add privacy demo example
 - > Support LE secure connection
- -BLE Mesh
 - ➤ Server library support BLE TRSP service
- -Thread
 - ➤ Add Thread example and document

• Feature Changes

- -Zigbee
 - ➤ Modify gateway command document
- -Tool
 - ➤ Mobile App add BLE commission for Sub_G device to join Sub_G network

Bug Fixes



4 RT58x_SDK_v1.6.0

New Features

- -SubG
 - ➤ Support 433MHz
- -BLE
 - ➤ Add Privacy for Direct ADV, Scan
- -BLE Mesh
 - ➤ Gateway supports BLE Transparent Transmission

Feature Changes

- -Platform
 - > SRAM power enable at the start of system initial function. To avoid operation abnormal after wakeup from Deep Sleep
- -Tool
 - ➤ ISP tool add SubG Tx power selection band0 [915Mhz] and band2 [433Mhz].
 - ➤ RF Lab Test Tool add SubG Tx power selection band0[915Mhz] to band2 [433Mhz].

Bug Fixes

- -Tool
 - > MP Tool apply RF Trim calibration value to solve random RX fail issue
- Platform
 - ➤ Modify WDT setting to let WDT can reset all blocks
 - > Fix Bootloader OTA decoder error at some image length



5 RT58x_SDK_v1.5.0

New Features

• Feature Changes

- -Platform
 - ➤ Modify VS Code and SDK Getting Start document.
 - > Add SDK Quick Start document

-Tool

- ➤ BLE Mesh app: Android app support Scenes, Rafael TRSP Server, and Rafael TRSP Client modes
- ➤ MP Tool v1.4.0: support Sub-G power trim, matter production with certificates, and 1 to 16 parallel test

-BLE Mesh

- > Implement gateway project and document
- Restructure the file and folder for client model

Bug Fixes

- -BLE Mesh
 - > Fixed provisioning fail issue

Known Issues

-None



6 RT58x_SDK_v1.4.0

New Features

- -Platform
 - ➤ Add 2MB Flash FLM
 - > Update flash driving setting to improve RX sensitivity

Feature Changes

- -Tool
 - ➤ MP tool support 2MB flash
- -Multi Protocol
 - ➤ Modify Zigbee/BLE application document for first time join Zigbee network
- -Other
 - > 2MB flash OTA support secure upgrade
- -FW
 - ➤ Enable MAC features for multi-mode
 - ➤ Support Up to 32 Sets of Source Match Address
 - > Security key setup failed when BLE is enabled on multi-mode FW

Bug Fixes

- -Platform
 - Fix Deep Sleep issue
 - > Turn off LDO Enable when not loading 80251 FW.

Known Issues

-None



7 RT58x_SDK_v1.3.0

New Features

-Zigbee:

- ➤ New flash update algorithm
- > Add library version

-Tool:

➤ Android app: add Zigbee smart home

Feature Changes

-Zigbee:

- ➤ Power on/off 5 times to reset light device
- ➤ Gateway for Home Automation
 - Add sensor related clusters
- ➤ Modify private cluster ID

-BLE:

- > Use 2 bytes to indicate LL TX data sequence
- > FOTA flow update to support image compression

-BLE Mesh:

➤ Change ADV_enable complete event response timing from "TX complete" to "constant delay"

-SubG:

➤ Add SubG_Field_Test demo



-Platform:

- ➤ Bootloader Support LZMA decompression for FOTA
- ➤ Add "volatile" to avoid optimization in Sleep mode

-Tool:

- ➤ Android app: modify BLE Mesh demo
- ➤ MP tool
 - Separate BLE/Zigbee Tx power target
 - Manual set X'tal cap
- > ISP tool
 - Support SubG
 - FOTA with image compression

Bug Fixes

-Peripheral:

> Update ADC setting to overcome chip variation issue.

-Zigbee:

- ➤ Solve one interoperability issue with Legacy Zigbee gateway
- Fix under multi-PAN environment, device may accept packet from different PAN ID.

-BLE Mesh:

- ➤ Fixed bug: in transparent transmission, different packet size stress test assert
- Fixed bug: sometimes Provision fail

-Sub G:

- ➤ Fixed GCC project
- > Fixed received data sequence in SubG TRX demo example

Known Issues

-Platform:

➤ Cortex M3 can't enter deep sleep mode if communication subsystem still working. Will fix it in SDK v1.3.1



8 RT58x_SDK_v1.2.3_BLE_Mesh

- New Features
- None.

• Feature Changes

- -BLE Mesh:
 - ➤ Implement Model and Lighting Demo.
 - > BLE Mesh Performance Tuning.
 - > BLE Mesh Document.
- Bug Fixes
- None.
- Known Issues
- None.



9 RT58x_SDK_v1.2.2_Zigbee

New Features

- None.

• Feature Changes

-Zigbee:

- > Gateway module:
- Revise binding command
- Add read attribute, write attribute, configure report command
- Light:
- Add OTA client cluster
- Add finding & binding process
- > Switch:
- Remove endpoint 1&3
- Add OTA client cluster
- Add finding & binding process
- > OTA Server:
- Removed (gateway module replace)
- > OTA Client:
- Removed (light/switch replace)

Bug Fixes

- None.

Known Issues



10 RT58x_SDK_v1.2.1

New Features

- Tools:
 - ➤ MP_Tool add Tx power 0/4 dBm target

• Feature Changes

- -Zigbee:
 - ➤ Optimize RX current consumption
 - > Device send leave command to gateway after factory reset
- Bug Fixes
- None.
- Known Issues
 - None.



11 RT58x_SDK_v1.2.0

New Features

-BLE:

➤ Add Privacy and connect CTE API.

-Zigbee:

- ➤ Now can pre-configure the network parameters.
- ➤ Add OTA function in new gateway demo.

-Multi-protocol:

- ➤ Zigbee Easy Gateway: implement Zigbee gateway by one RT582 chip. Running BLE/Zigbee multi-protocol on RT582 to replace traditional Zigbee gateway.
- ➤ Utilize BLE to reset Zigbee Device when Gateway is broken or offline.

-Tools:

- ➤ Android app: Easy Gateway app
- > Android app: utilize BLE to reset Zigbee Device

Feature Changes

- Zigbee AES by HW accelerator.



Bug Fixes

- Zigbee address generation form MAC address in flash OTP

Known Issues



12 RT58x_SDK_v1.1.1

New Features

- None.

Feature Changes

- Modify PMU DCDC initial setting to enhance the stability under stress environment.

Bug Fixes

- None.

Known Issues



13 RT58x_SDK_v1.1.0

New Features

- -Added examples: I2S digital microphone
- -Modify PWM example
- -BLE:
 - ➤ Added UART cmd demo
 - ➤ Added Beacon demo

-Zigbee:

- ➤ Gateway example support more commands
- ➤ Added User_specific_cluster
- ➤ Added Scene in light demo
- ➤ Added Thermostat cluster

-Multi-protocol:

➤ Added Zigbee ZED with BLE OTA demo

-Tools:

- > RF_Lab_Test_Tool: supports SubG RF test. On the GUI, remove WiSun mode and change to SubG mode
- ➤ ISP_Tool: (1) remove MP_sector Download and Erase button



- (2) Judge If IC had been MP_calibrated or not? If not, UI show warning message.
- Android App: add BLE Mesh On/Off demo

Feature Changes

- Projects include TX_power compensation. Default is disable

Bug Fixes

- Fixed Zigbee two end-point bug.
- Fixed Zigbee OTA buffer issue.

Known Issues



14 RT58x_SDK_v1.0.1

New Features

- Added software PMU calibration.

Feature Changes

- Extend Zigbee maximum network nodes to 200.

Bug Fixes

- Fixed low speed timer reload abnormal issue under low temperature.

Known Issues



15 RT58x_SDK_v1.0.0_Mesh

New Features

- Added BLE Mesh demo example.
 - > \Project\Application\BLE Mesh\GenericOnOff\.
- Added BLE Mesh App.
 - ➤ \Tools\Android App\.
- Added BLE Mesh documents.
 - ➤ \Tools\Android App\User guide\

Android APP BLE Mesh user guide V1.2.pdf.

- ➤ \Docs\RT58x_BLE_Mesh_User_Guide_V1.0.pdf.
- ➤ \Docs\RT58x_SDK_for_BLE_Mesh_Demo_Guide_V1.0.pdf.

Feature Changes

- None.

Bug Fixes

- None.

Known Issues



16 RT58x_SDK_v1.0.0

New Features

- Added peripheral drivers and examples for I2S, Timer, Watchdog, and SADC.
- Added BLE demo example with low power mode mechanism.
- Added BLE UART_TRSP demo with low power mode mechanism and wakeup by URAT break in "Rafael UART Break tool".
- Added more tools.
 - ➤ Upgraded xcode from v5.5 to v5.6 in iOS App.
 - ➤ Added Zigbee/BLE multi-standard demo in iOS App.
 - ➤ Added UART_Break_Tool to send break signal to wakeup BLE before sending characters for BLE UART TRSP demo.
 - ➤ Added Tx Power trim, ADC trim, and Comparator trim to MP Tool.
- Added related documents.
 - ➤ [SW_15]RT58x_Zigbee_Gateway_Light_Switch_Operation_Guide_V1.0.
 - > RT58x SDK Reference Guide in Doxygen format.



Feature Changes

- Removed Direct_Test_Mode demo and integrated DTM function into "RF Lab Test Tool FW".

Bug Fixes

- Fixed bug in BLE multi-link demo.

Known Issues

- None.

Notes

- SDK includes MCU peripheral examples, BLE examples, and Zigbee examples. All examples support Keil and GCC projects.
 - ➤ Peripheral: \Project\Examples\.
 - ➤ BLE: \Project\Application\BLE_Demo\.
 - ➤ Zigbee: \Project\Application\Zigbee_Demo\.
 - ➤ Zigbee & BLE: \Project\Application\Multi_Protocol_Demo\.
- For all examples to work properly, the bootloader needs to be downloaded first. Please refer to the documentation for details.
 - ➤ \Docs\[SW_02]RT58x_SDK_IOT_Application_Overview_V1
 .0.
- Measure sleep power consumption project.



- ➤ \Project\Examples\Sleep.
- Tool and test image to measure RF performance.
 - ➤ \Tools\IOT_Evaluation_Tool.
 - ➤ \Tools\IOT_Evaluation_Tool\RF_Lab_Test_Tool_FW.



17 RT58x_SDK_v0.3.1

New Features

- Added GCC project for all examples.
- Added Zigbee/BLE multi-protocol demo.
- Added more Zigbee examples, eg: Gateway, OTA, etc.
- Added more tools.
 - ➤ ISP Tool
 - > RF Lab Test Tool
 - Security_Boot_Tool
 - ➤ Mass_Production_Tool
 - ➤ Android_App
 - ➤ iOS_App
- Added related documents.
 - ➤ [SW_01]RT58x_SOC_Platform_Getting_Started_V1.1
 - ➤ [SW_02]RT58x_SDK_IOT_Application_Overview_V1.0
 - > [SW 03]RT58x Zigbee SDK User Guide V1.0
 - ➤ [SW_04]RT58x_Zigbee_Application_Guide_V1.0
 - > [SW 06]RT58x BLE SDK User Guide V1.0
 - ➤ [SW 07]RT58x BLE SDK Application Guide v1.0



- > [SW_08]RT58x_BLE_SDK_OTA_Guide_V1.0
- > [SW_09]RT58x_BLE_SDK_Service_Profile_Guide_V1.0
- > [SW_13]RT58x_Multi_Protocol_Application_Guide_V1.0

Feature Changes

- Unified application architecture of different protocols.
- Modified power saving example.

Bug Fixes

- None.

Known Issues



18 RT58x_SDK_v0.2.0

New Features

- For SubG only.

Feature Changes

- None.

Bug Fixes

- None.

Known Issues



19 RT58x_SDK_v0.1.0

New Features

- Initial version.
- Added peripheral drivers and examples.
- Added BLE stack and BLE applications.

Feature Changes

- None.

Bug Fixes

- None.

Known Issues