

INSTITUTO TECNOLÓGICO DE AERONÁUTICA



Rafael Studart Mattos Di Piero

**MULTI-AGENT GRAPH EXPLORATION WITHOUT
COMMUNICATION**

Bachelor's Thesis
2024

Course of Computer Engineering

Rafael Studart Mattos Di Piero

**MULTI-AGENT GRAPH EXPLORATION WITHOUT
COMMUNICATION**

Advisor

Prof. Dr. Luiz Gustavo Bizarro Mirisola (ITA)

Co-advisor

Prof. Dr. Vitor Venceslau Curtis (ITA)

COMPUTER ENGINEERING

SÃO JOSÉ DOS CAMPOS
INSTITUTO TECNOLÓGICO DE AERONÁUTICA

Cataloging-in Publication Data
Documentation and Information Division

Studart Mattos Di Piero, Rafael
Multi-Agent Graph Exploration Without Communication / Rafael Studart Mattos Di Piero.
São José dos Campos, 2024.
19f.

Bachelor's Thesis – Course of Computer Engineering– Instituto Tecnológico de Aeronáutica,
2024. Advisor: Prof. Dr. Luiz Gustavo Bizarro Mirisola. Co-advisor: Prof. Dr. Vitor Venceslau
Curtis.

1. Graph. 2. Search. 3. Multi-agent. 4. Mixed Radix. I. Instituto Tecnológico de Aeronáutica.
II. Title.

BIBLIOGRAPHIC REFERENCE

STUDART MATTOS DI PIERO, Rafael. **Multi-Agent Graph Exploration Without Communication**. 2024. 19f. Bachelor's Thesis – Instituto Tecnológico de Aeronáutica, São José dos Campos.

CESSION OF RIGHTS

AUTHOR'S NAME: Rafael Studart Mattos Di Piero

PUBLICATION TITLE: Multi-Agent Graph Exploration Without Communication.

PUBLICATION KIND/YEAR: Bachelor's Thesis (Undergraduation study) / 2024

It is granted to Instituto Tecnológico de Aeronáutica permission to reproduce copies of this final paper and to only loan or to sell copies for academic and scientific purposes. The author reserves other publication rights and no part of this final paper can be reproduced without the authorization of the author.

Rafael Studart Mattos Di Piero
Rua do H8A, Ap. 125
12.228-460 – São José dos Campos–SP

MULTI-AGENT GRAPH EXPLORATION WITHOUT COMMUNICATION

Bachelor's Thesis approved in its final version by the signatories below:

Rafael Studart Mattos Di Piero

Author

Luiz Gustavo Bizarro Mirisola (ITA)

Advisor

Vitor Venceslau Curtis (ITA)

Co-advisor

Prof. Dr. Marcos Ricardo Omena de Albuquerque Máximo

Course Coordinator of Computer Engineering

São José dos Campos: Jun 20, 2024.

To my family, for their love and constant support. To my friends, for standing by me through all moments.

Acknowledgments

TO BE WRITTEN

"The journey of a thousand miles begins with one step."

— LAO TZU

Resumo

Teste

Abstract

TO BE WRITTEN

List of Abbreviations and Acronyms

DFS Depth First Search

BFS Breath First Search

LCL Last Common Location

List of Symbols

G Graph

v_n Vertex

v_nv_m Edge

Contents

1	INTRODUCTION	12
1.1	Motivation	12
1.2	Objective	13
1.3	Definitions	13
1.3.1	Graph	13
1.3.2	Agent	14
1.3.3	Mixed Radix	15
2	METHODOLOGY	16
2.1	Modeling	16
2.1.1	Simulation	16
2.1.2	Graph	16
2.1.3	Agent	16
2.2	Mixed Radix Representation	16
2.3	Graph Exploration Algorithm	16
3	RESULTS AND DISCUSSION	17
3.1	Performance Evaluation Methodology	17
3.2	Baseline Algorithm Performance	17
3.3	Incremental Algorithm Performance	17
3.4	Comparison with Tarry's Algorithm	17
4	CONCLUSIONS AND FUTURE WORKS	18
	BIBLIOGRAPHY	19

1 Introduction

1.1 Motivation

Graph theory is a fundamental field of mathematics with significant relevance in computer science due to its ability to model relationships between objects. One of the key challenges in computer science is graph traversal and exploration, which involves systematically navigating through the nodes of a graph with a specific purpose. This topic has practical applications across diverse fields, such as network routing, robotics, procedural generation, electronics design, and more.

When considering the complexities and time constraints imposed by real-world environments, graph exploration must be expanded to consider multi-agent systems. In such systems, multiple autonomous agents collaborate to explore graphs, aiming to distribute tasks to achieve optimal efficiency. However, one of the challenges in these type of system is communication, as strategies need to balance the trade-off between the amount of information shared among agents and the cost of sharing it.

Various versions of this problem have been explored in research. One such approach, discussed by Kivelevitch and Cohen (2010), proposed a generalization of Tarry’s Algorithm with significant emphasis on minimizing data transfer. Nevertheless, this solution is limited to mazes and does not extend to general graphs.

Despite the previously mentioned research, the concept of zero-communication exploration has not been concretely established in the literature. We believe this gap is significant, as practical situations might involve scenarios where communication is limited or impossible due to bandwidth limitations or energy consumption, such as deep-sea exploration, search with energy-limited agents, or high-efficiency state space search.

This work aims to address this gap by presenting a continuation and expansion of a method initially developed for perfect maze exploration (NAEEM, 2021) as discussed by Rodrigues (2024). Building upon this groundwork, the research extends the method to accommodate diverse graph structures by removing dependencies on specific projects. General improvements, such as structuring the exploration into well-defined and extensible

classes and incorporating built-in testing, strive to make the development process more versatile and robust, paving the way for broader applications in multi-agent systems.

1.2 Objective

This study aims to propose a viable algorithm for graph exploration by multi-agents, specifically targeting the identification of a goal node. A previous paper by Rodrigues (2024) discussed an approach for perfect maze exploration, which can be modeled as a tree, a connected acyclic undirected graph. Expanding the proposed algorithm to connected cyclic graphs could allow further discussion and contribute to research in real-world applications such as robotics, as well as in the theoretical analysis of parallelism and communication between agents.

1.3 Definitions

This section aims to define key concepts in graph theory and multi-agent exploration that are essential for understanding the context and methodology of our research, ensuring clarity and consistency in the subsequent discussions.

1.3.1 Graph

Graphs are structures in mathematics and computer science used to represent relationships between pairs of objects. According to Manber (1989), a graph $G = (V, E)$ is defined as a set V of vertices (or nodes) and a set E of edges, that connect pairs of vertices.

1.3.1.1 Common Nomenclature

In graph theory, the basic terminology includes the following components:

- Vertex (Node): The fundamental unit of a graph, representing an object or a point.
- Edge: A connection between a pair of vertices, representing a relationship between them.
- Adjacency: Two vertices v and w of a graph G are adjacent if there is an edge vw joining them, and the vertices v and w are then incident with such an edge. (WILSON, 1996)

- Degree: Degree of a vertex v of G is the number of edges incident with v . (WILSON, 1996)
- Path: A path in a graph G , as defined by Wilson (1996), is a finite sequence of edges of the form v_0v_1, v_1v_2, \dots in which any two consecutive edges are adjacent, all edges are distinct and all vertices v_0, v_1, \dots, v_m are distinct (except, possibly, $v_0 = v_m$).
- Cycle: A path where $v_0 = v_m$ and with at least one edge. (WILSON, 1996)

1.3.1.2 Key Properties

A few key properties of graphs that interest us are:

- Connectivity: A graph is connected if and only if there is a path between each pair of vertices. (WILSON, 1996)
- Acyclicity: A graph is acyclic if it has no cycles. A tree is a special case of an acyclic connected graph.

1.3.1.3 Traversal

Graph traversal is the process of visiting all the vertices in a graph in a systematic manner. Two fundamental algorithms for graph traversal are:

- Breadth-first search (BFS): Expands the frontier between discovered and undiscovered vertices uniformly across the breadth of the frontier. (MANBER, 1989)
- Depth-first search (DFS): Explores edges out of the most recently discovered vertex v that still has unexplored edges leaving it. (MANBER, 1989)

1.3.2 Agent

An agent in maze exploration, as defined by Kivelevitch and Cohen (2010), is an entity able to move within the maze in any direction as long as it does not encounter obstacles.

In the context of graph exploration, this concept extends to an agent's ability to traverse edges between vertices within the graph structure. Each agent acts independently, making decisions based on its individual memory and the local information available at its current vertex and its adjacent edges.

1.3.3 Mixed Radix

A mixed radix system is a positional numerical system in which the numerical base for each digit varies. This allows for more flexible representation of numbers, accommodating various scales within the same numerical framework.

One mathematical approach for representing mixed radix numbers can be found in Arndt (2011), which establishes a comprehensive arithmetical method for manipulating them. However, for the specific subset of real numbers within the interval $[0, 1]$, a more specialized approach is utilized, as described by Rodrigues (2024).

In this context, the mixed radix representation $A = [a_0, a_1, a_2, \dots, a_{n-1}]$ of a number x with respect to a radix vector $M = [m_0, m_1, m_2, \dots, m_{n-1}]$, where $x \in [0, 1]$, is given by:

$$x = \sum_{k=0}^{n-1} a_k \prod_{j=0}^k \frac{1}{m_j} \quad (1.1)$$

where $0 \leq a_j < m_j$. (RODRIGUES, 2024)

For instance, if x is represented by $2_31_21_40_31_5$, and considering that a_i is on the left of a_{i+1} , x might be transformed to the decimal base by the following steps:

$$x = 2_31_21_40_31_5 \quad (1.2)$$

$$A = [2, 1, 1, 0, 1] \quad (1.3)$$

$$M = [3, 2, 4, 3, 5] \quad (1.4)$$

$$n = 5 \quad (1.5)$$

$$x = \sum_{k=0}^4 a_k \prod_{j=0}^k \frac{1}{m_j} \approx 0.8777778 \quad (1.6)$$

2 Methodology

2.1 Modeling

2.1.1 Simulation

2.1.2 Graph

2.1.3 Agent

2.2 Mixed Radix Representation

2.3 Graph Exploration Algorithm

3 Results and Discussion

3.1 Performance Evaluation Methodology

3.2 Baseline Algorithm Performance

3.3 Incremental Algorithm Performance

3.4 Comparison with Tarry's Algorithm

4 Conclusions and Future Works

Bibliography

ARNDT, J. Mixed radix numbers. In: **Matters Computational**. Berlin, Heidelberg: Springer, 2011. p. 183–209.

KIVELEVITCH, E.; COHEN, K. Multi-agent maze exploration. **Journal of Aerospace Computing, Information, and Communication**, v. 7, p. 391–405, 2010.

MANBER, U. **Introduction to Algorithms: A Creative Approach**. 1st. ed. New York: Addison-Wesley, 1989.

NAEEM, M. A. **pyamaze**. 2021. <https://www.github.com/MAN1986/pyamaze>. Accessed on: June, 2024.

RODRIGUES, A. J. D. S. **Multi-agent graph exploration without communication**. Bachelor's Thesis — Instituto Tecnológico de Aeronáutica,, São José dos Campos, 2024.

WILSON, R. J. **Introduction to Graph Theory**. 4th. ed. Boston, MA: Longman Group Ltd, 1996.

FOLHA DE REGISTRO DO DOCUMENTO			
1. CLASSIFICAÇÃO/TIPO TC	2. DATA 20 de Junho de 2024	3. DOCUMENTO Nº DCTA/ITA/?/2024	4. Nº DE PÁGINAS 19
5. TÍTULO E SUBTÍTULO: Multi-Agent Graph Exploration Without Communication			
6. AUTOR(ES): Rafael Studart Mattos Di Piero			
7. INSTITUIÇÃO(ÕES)/ÓRGÃO(S) INTERNO(S)/DIVISÃO(ÕES): Instituto Tecnológico de Aeronáutica – ITA			
8. PALAVRAS-CHAVE SUGERIDAS PELO AUTOR: Graph, Search, Multi-Agent, Mixed-Radix			
9. PALAVRAS-CHAVE RESULTANTES DE INDEXAÇÃO: ?			
10. APRESENTAÇÃO: (X) Nacional () Internacional ITA, São José dos Campos. Curso de Graduação em Engenharia de Computação. Orientador: Prof. Dr. Luiz Gustavo Bizarro Mirisola; coorientador: Prof. Dr. Vitor Venceslau Curtis. Publicado em 2024.			
11. RESUMO: TO BE WRITTEN			
12. GRAU DE SIGILO: (X) OSTENSIVO () RESERVADO () SECRETO			