This is Google's cache of https://moddingwiki.shikadi.net/wiki/OP2 Bank Format. It is a snapshot of the page as it appeared on 17 Feb 2022 01:23:39 GMT. The current page could have changed in the meantime. Learn more.

Full version Text-only version View source

Tip: To quickly find your search term on this page, press Ctrl+F or

F (Mac) and use the find bar.

OP2 Bank Format

From ModdingWiki Jump to navigation Jump to search

The OP2 Bank Format is an instrument bank format used by the DMX sound library developed by Paul Radek of Digital Expressions, Inc. The 128 melodic and 47 percussion instrument limit was most likely chosen so that a single OP2 file could store all the instruments for a General MIDI song. This bank has support for two-voice instruments to provide support for pseudo four-operator instruments. File of this format usually has GENMIDI name without extension as embedded WAD resource, but also can have .OP2 extension.

Contents

- 1 File format
 - 1.1 Instrument
 - 1.2 Instrument names
 - 1.3 Fine tune
 - 1.4 Percussion instruments
- 2 Tools

File format

Data type	Name	Description
<u>char</u> [8]	magic	#OPL_II# signature, doesn't null terminated
BYTE[175][36]	instrument	Set of 175 instrument entry
<u>char</u> [175][32]	names	Instrument names per every instrument entry, must be null terminated

Instrument

Each bank contains 128 melodic and 47 percussion instruments.

Data type	Name	OPL base register	Description
UINT16LE	E flags	N/A	Instrument flags: $0x01$ - fixed pitch, $0x02$ - delayed vibrato (unused), $0x04$ - Double-voice mode
<u>UINT8</u>	fineTune	N/A	Second voice detune level

OP2 Bank Format

Format type Musical Instrument Hardware OPL, MIDI **Number of instruments** 175 **Instruments named?** Yes, 31 char Chex Ouest Chex Quest 2 **Doom** Doom 2 Games **Heretic** Hexen

> Raptor Strife

2/27/22, 4:32 PM	1		OP2 Bank Format - ModdingWiki			
<u>UINT8</u>	noteNum	N/A	Percussion note number (between 0 and 128)			
			First voice			
<u>UINT8</u>	iModChar1	0x20	Modulator characteristic (Mult, KSR, EG, VIB and AM flags)			
<u>UINT8</u>	iModAttack1	0x60	Modulator attack/decay level			
<u>UINT8</u>	iModSustain1	0x80	Modulator sustain/release level			
<u>UINT8</u>	iModWaveSel1	0xE0	Modulator wave select			
<u>UINT8</u>	iModScale1	0x40	Modulator key scaling (first two bits)			
<u>UINT8</u>	iModLevel1	0x40	Modulator output level (last six bits)			
<u>UINT8</u>	iFeedback1	0xC0	Feedback/connection			
<u>UINT8</u>	iCarChar1	0x23	Carrier characteristic (Mult, KSR, EG, VIB and AM flags)			
<u>UINT8</u>	iCarAttack1	0x63	Carrier attack/decay level			
<u>UINT8</u>	iCarSustain1	0x83	Carrier sustain/release level			
<u>UINT8</u>	iCarWaveSel1	0xE3	Carrier wave select			
<u>UINT8</u>	iCarScale1	0x43	Carrier key scaling (first two bits)			
<u>UINT8</u>	iCarLevel1	0x43	Carrier output level (last six bits)			
<u>UINT8</u>	reserved1	N/A	Unused byte			
INT16LE	noteOffset1	N/A	MIDI note offset for a first voice			
Second voice						
<u>UINT8</u>	iModChar2	0x20	Modulator characteristic (Mult, KSR, EG, VIB and AM flags)			
<u>UINT8</u>	iModAttack2	0x60	Modulator attack/decay level			
<u>UINT8</u>	iModSustain2	0x80	Modulator sustain/release level			
<u>UINT8</u>	iModWaveSel2	0xE0	Modulator wave select			
<u>UINT8</u>	iModScale2	0x40	Modulator key scaling (first two bits)			
<u>UINT8</u>	iModLevel2	0x40	Modulator output level (last six bits)			
<u>UINT8</u>	iFeedback2	0xC0	Feedback/connection			
<u>UINT8</u>	iCarChar2	0x23	Carrier characteristic (Mult, KSR, EG, VIB and AM flags)			
<u>UINT8</u>	iCarAttack2	0x63	Carrier attack/decay level			
<u>UINT8</u>	iCarSustain2	0x83	Carrier sustain/release level			
<u>UINT8</u>	iCarWaveSel2	0xE3	Carrier wave select			
<u>UINT8</u>	iCarScale2	0x43	Carrier key scaling (first two bits)			
<u>UINT8</u>	iCarLevel2	0x43	Carrier output level (last six bits)			
<u>UINT8</u>	reserved2	N/A	Unused byte			
INT16LE	noteOffset2	N/A	MIDI note offset for a second voice			

Instrument names

After 175'th instrument is following an array of 32-byte null-terminated instrument names

Fine tune

Fine tune value is an index offset of frequencies table. 128 is a center, i.e. don't detune. Formula of index offset is: (fine_tune / 2) - 64. Each unit of fine tune field is approximately equal to 1/0.015625 of tone.

Percussion instruments

Percussion instruments are in range between 35 (Bass drum 1) and 81 (Open Triangle) MIDI indeces.

Tools

The following tools are able to work with files in this format.

Name	Platform	Play?	Create new?	Modify?	Convert/export to other?	Import from other?	Access hidden data?	Edit metadata?	Notes
IMF Creator	Windows	Yes	Yes	Yes	Yes; .op2	Yes; many	Yes; delayed vibrato	Yes	Utility by Adam Biser to create IMF music. Also includes OP2 bank editor.
OPL3 Bank Editor	Linux, Windows, macOS	Yes	Yes	Yes	Yes; many	Yes; many	No	Yes	

Retrieved from 'https://moddingwiki.shikadi.net/w/index.php?title=OP2 Bank Format&oldid=9138' **Categories**:

- All file formats
- All instrument formats
- OPL instruments
- MIDI instruments
- Chex Quest
- Chex Quest 2
- <u>Doom</u>
- <u>Doom 2</u>
- Heretic
- Hexen
- Raptor
- Strife

Navigation menu

Personal tools

- <u>Log in</u>
- Request account

Namespaces

- <u>Page</u>
- Discussion

Variants

Views

- Read
- View source
- <u>View history</u>

More

Search

Search ModdingWiki Search Go

Navigation

• Main Page

Games

- By title
- By company
- By genre
- Modded
- Cheats

Modding

- Programs
- Tutorials
- Community portal

Programming

• File formats

Help needed

- Known info to be added
- More info needed
- <u>Unmoddable games</u>
- Images needed
- Pages with TODOs

Wiki

- Editing guidelines
- Recent changes
- Random page
- <u>Help</u>

Tools

- What links here
- Related changes
- Special pages
- Printable version

- Permanent link
- Page information
- Browse properties
- This page was last modified on 16 August 2020, at 14:33.
- Privacy policy
- About ModdingWiki
- Disclaimers



