

PBQ Nmap Cheat Sheet

Correct answers, identification logic, and exam-friendly nmap commands (1 page).

Nmap commands to run

Quick discovery (PBQ console friendly):

```
nmap server1.lab.local
nmap server2.lab.local
nmap server3.lab.local
nmap server4.lab.local
nmap server5.lab.local
```

More realistic (service detection):

```
nmap -sV server1.lab.local
nmap -sV server2.lab.local
nmap -sV server3.lab.local
nmap -sV server4.lab.local
nmap -sV server5.lab.local
```

Answer key and how to identify the server type from scan output

Host	IP	Open ports seen	Role (why)	Non-compliant port (why)
server1.lab.local	192.168.1.10	22, 53, 3306	Database (3306 shows MySQL / MariaDB).	53/tcp (DNS exposed; not needed for host).
server2.lab.local	192.168.1.20	22, 23	Switch (management ports only; no app services).	23/tcp (Telnet is plaintext remote management).
server3.lab.local	192.168.1.30	22, 80, 443	Web server (80/443 indicate HTTP/HTTPS).	80/tcp (HTTP is plaintext; prefer 443)
server4.lab.local	192.168.1.40	21, 135, 139, 445	File server (139/445 indicate SMB/CIFS sharing).	21/tcp (FTP is plaintext; prefer SFTP/FTPS)
server5.lab.local	192.168.1.50	25, 993	Mail server (25 SMTP plus 993 IMAPS).	25/tcp (SMTP without TLS; prefer submission/STARTTLS).

Fast interpretation tips

- Use the service column in nmap output: 3306=mysql, 445=microsoft-ds (SMB), 25=smtp, 993=imaps, 80=http, 23=telnet.
- 'Only management ports' (22/23) with no app ports often indicates network gear rather than a server workload.
- Mark plaintext/legacy services as non-compliant: Telnet 23, FTP 21, HTTP 80, and unnecessary DNS 53.