

Contents

1	000	1
1.1	Remember [9 lines] - 575b8cdd	1
2	Data Structure	1
2.1	DSU [33 lines] - 35ae5d3b	1
2.2	Fenwick Tree [34 lines] - 75085855	2
2.3	Persistent Segment Tree [103 lines] - 0ec23046	2
2.4	SQRT Decomposition [66 lines] - b82550a8	2
2.5	Segment Tree Lazy [66 lines] - 1229c3a7	3
2.6	Segment Tree [32 lines] - 957994f6	3
2.7	Special Range Query Example Fixing Right Position [73 lines] - e834812e	3
2.8	Sqrt Tricks [8 lines] - 4f4d4f16	4
2.9	Trie Bit [38 lines] - 300d2d92	4
3	Dynamic Programming	4
3.1	All Possible Subarray Sum [6 lines] - 18ee4984	4
3.2	CHT [46 lines] - ea32a345	4
3.3	Digit DP [15 lines] - 6ec98828	5
3.4	Divide and Conquer DP [26 lines] - 91a711fa	5
3.5	LCIS o(n*m) [22 lines] - c8f9d47f	5
3.6	LCS [59 lines] - d1c8c325	5
3.7	LIS O(nlogn) with full path [39 lines] - 2cab3900	5
3.8	MCM [26 lines] - 2dd10507	6
3.9	Maximum Submatrix [33 lines] - c1178137	6
3.10	SOS DP [55 lines] - 509e6475	6
4	Game Theory	6
4.1	Points to be noted [14 lines] - f960ca72	6
5	Geometry	6
5.1	2D Convex Hull [65 lines] - aed084cc	6
5.2	Computational Geometry [70 lines] - 92134ce2	7
6	Graph	7
6.1	Articulation Bridges [40 lines] - f1f88788	7
6.2	Articulation Points [39 lines] - 50d23cbe	7
6.3	Bellmanford [22 lines] - 4ca51cfd	8
6.4	Block Cut Tree [75 lines] - 192484e1	8
6.5	Centroid Decomposition [30 lines] - 2fb8ca4f	8
6.6	Dijkstra [22 lines] - 4c1dbc1b	8
6.7	Eularian Circuit [16 lines] - 9da20d99	8
6.8	Floyed Warshall [13 lines] - 4ea8fd7d	8
6.9	Heavy Light Decomposition [100 lines] - 7b1a5885	9
6.10	K'th Shortest path [40 lines] - 726428ad	9
6.11	Kruskal [13 lines] - 22efc58b	9
6.12	LCA using Segment Tree [80 lines] - e99ed31c	9
6.13	LCA [40 lines] - bfc76c0	10
6.14	SCC [47 lines] - a8ab7ad2	10
6.15	SPFA O(V*E) [57 lines] - 68121e58	10

6.16	Topological Sort [33 lines] - 2725b3e1	11
6.17	Tree Rerooting [97 lines] - a06a53a6	11
7	Misc	11
7.1	Bit count in O(1) [5 lines] - c2d40607	11
7.2	Bit hacks [16 lines] - 96eab638	11
7.3	Bitset C++ [13 lines] - 096a3812	12
7.4	Knight Moves [2 lines] - 28da3d5e	12
7.5	Random Generator [6 lines] - 19e7d615	12
7.6	Special DS [22 lines] - 31b89845	12
7.7	Usefull Things [9 lines] - c67addfa	12
7.8	VScode setup [7 lines] - 3e225a41	12
7.9	stress [25 lines] - 4a84e7fd	12
7.10	vimrc [12 lines] - 1f47305c	12
8	Number Theory	12
8.1	10-ary to m-ary [22 lines] - e6c26ef1	12
8.2	Basis Vector [89 lines] - 409325f7	12
8.3	Binary Exponentiation [9 lines] - 57b21c36	13
8.4	CRT [21 lines] - 1d2ddbdc	13
8.5	Catalan Numbers [8 lines] - 1e8c9e0a	13
8.6	Count 1s 0 to n [9 lines] - 9292bf04	13
8.7	Divisors multiple info [35 lines] - 1866b9dd	13
8.8	Extended GCD [8 lines] - cdfca975	13
8.9	Find numbers in L to R divisible by all array elements [12 lines] - 833394ad	13
8.10	GaussElimination [39 lines] - fd4ae4aaf	13
8.11	Largest Power of n! [11 lines] - dc59263a	14
8.12	Leap Year [13 lines] - 8ff2b7cb	14
8.13	Logab [3 lines] - 1ababcb	14
8.14	Matrix [105 lines] - 57e4b34b	14
8.15	Miller-Rabin-Pollard-Rho [35 lines] - b1755b01	14
8.16	Mobius [11 lines] - b11a0bce	15
8.17	Mod Inverse [5 lines] - 5a017bdc	15
8.18	Modular Operations [12 lines] - f875804f	15
8.19	NOD of n! [13 lines] - 60fc48f	15
8.20	No of Digits in n! in base B [7 lines] - 888ae2de	15
8.21	Principle of Inclusion Exclusion [21 lines] - 7692d42f	15
8.22	Print Calander of Any Year [44 lines] - e4845a4b	15
8.23	SOD, NOD Upto N [30 lines] - ad992d27	15
8.24	SPF [10 lines] - 764405a0	15
8.25	Segmented Sieve [17 lines] - 034da99c	16
8.26	Sieve Phi Mobius [13 lines] - 88190466	16
8.27	Sieve upto 1e9 [71 lines] - a03ff5a3	16
8.28	Sieve [16 lines] - 8babdb35	16
8.29	String Mod [5 lines] - 15587fee	16
8.30	nCr [39 lines] - 8a93b828	16
9	Some Algorithms	16
9.1	2D Prefix Sum [2 lines] - fa2a0bef	16
9.2	Big Integer [89 lines] - 88146b73	17
9.3	Expression Parsing [85 lines] - 47499dbc	17
9.4	Infix to Postfix [94 lines] - 5c5d4f41	17
9.5	Kadanes [9 lines] - 6304cec2	18
9.6	Monotonic Stack (next greater) [7 lines] - 96018665	18
9.7	Spirally Traverse [25 lines] - 7ebd7ad5	18
9.8	Ternary Search [10 lines] - 20b1a65d	18

10	String	18
10.1	AhoCorasick [55 lines] - 53423257	18
10.2	Hashing [44 lines] - 856b95a5	19
10.3	KMP [22 lines] - e87ecc3e	19
10.4	Suffix Array [134 lines] - 595a0dc9	19
10.5	Suffix Automaton [156 lines] - 835183e3	20
10.6	Trie [43 lines] - d276b245	21
11	Random	21
11.1	Combinatorics	21
11.1.1	Catalan Number	21
11.1.2	Stirling Number of the First Kind	22
11.1.3	Stirling Numbers of the Second Kind	22
11.1.4	Bell Number	22
11.1.5	Lucas Theorem	22
11.1.6	Derangement	22
11.1.7	Burnside Lemma	22
11.1.8	Eulerian Number	22
11.2	Number Theory	22
11.2.1	Mobius Function and Inversion	22
11.2.2	GCD and LCM	23
11.2.3	Gauss Circle Theorem	23
11.2.4	Pick's Theorem	23
11.2.5	Formula Cheatsheet	23
11.2.6	Geometry and Formulas	23
11.2.7	Most Number of Divisors	24
11.2.8	Pascal's Triangle	24
11.2.9	Logarithm Rules	24
11.2.10	Miscellaneous	24
11.3	Probability and Expectation	25
1	000	
1.1	Remember [9 lines] - 575b8cdd	
# Don't stuck in one approach		
# Bruteforce is sometimes the best way to go		
# Reset global variables		
# Check for overflow		
# Read the problem carefully		
# Break the problem into smaller parts (go step by step)		
# Check for negative numbers, zero, one or small cases		
# For problems like making string A to B, try to work backwards from B to A or it may be easier to make both A and B to some C		
# L > R can occur		
2	Data Structure	
2.1	DSU [33 lines] - 35ae5d3b	
struct DSU { vector<int> par, sz, minElmt, maxElmt, cntElmt; int cc; public: DSU(int n) { par.resize(n + 1); sz.resize(n + 1, 1); minElmt.resize(n + 1); maxElmt.resize(n + 1); cntElmt.resize(n + 1, 1); }		

```

cc = n;
for (int i = 1; i <= n; i++) par[i] = minElmt[i] =
    maxElmt[i] = i;
}
int find(int u) {
    if (u == par[u]) return u;
    return par[u] = find(par[u]);
}
void unite(int u, int v) {
    int pU = find(u);
    int pV = find(v);
    if (pU == pV) return;
    if (sz[pU] < sz[pV]) swap(pU, pV);
    par[pV] = pU;
    sz[pU] += sz[pV];
    cc--;
    cntElmt[pU] += cntElmt[pV];
    minElmt[pU] = min(minElmt[pU], minElmt[pV]);
    maxElmt[pU] = max(maxElmt[pU], maxElmt[pV]);
}
int getMinElementIntheSet(int u) { return
    minElmt[find(u)]; }
int getMaxElementIntheSet(int u) { return
    maxElmt[find(u)]; }
int getNumofElementIntheSet(int u) { return
    cntElmt[find(u)]; }
};

```

2.2 Fenwick Tree [34 lines] - 75085855

```

int fenwick[N];
void update(int ind, int val) {
    while (ind < N) {
        fenwick[ind] += val;
        ind += ind & -ind;
    }
}
int query(int ind) {
    int sum = 0;
    while (ind > 0) {
        sum += fenwick[ind];
        ind -= ind & -ind;
    }
    return sum;
}
struct Fenwick2D {
    vector<vector<int>>> t;
    int n, m;
    Fenwick2D(int n, int m) : n(n), m(m), t(n + 1,
        vector<int>(m + 1, 0)) {}
    void update(int i, int j, int v) {
        for (int x = i; x <= n; x += x & -x)
            for (int y = j; y <= m; y += y & -y) t[x][y] += v;
    }
    int query(int i, int j) {
        int s = 0;
        for (int x = i; x > 0; x -= x & -x)
            for (int y = j; y > 0; y -= y & -y) s += t[x][y];
        return s;
    }
    int query(int r1, int c1, int r2, int c2) {
        return query(r2, c2) - query(r1 - 1, c2) -
            query(r2, c1 - 1) +
            query(r1 - 1, c1 - 1);
    }
};

```

2.3 Persistent Segment Tree [103 lines] - 0ec23046

```

#include <bits/stdc++.h>
using namespace std;
#define i64 long long
#ifdef ONPC
#include "mydebug.h"
#else
#define debug(...) 1
#endif
const int N = 30000 + 5;
int arr[N];
struct Node {
    int val;
    Node* lc;
    Node* rc;
    Node() {
        lc = NULL;
        rc = NULL;
    }
};
Node* versions[N];
Node* build(int l, int r) {
    Node* node = new Node();
    if (l == r) {
        node->val = 0;
        return node;
    }
    int mid = (l + r) / 2;
    node->lc = build(l, mid);
    node->rc = build(mid + 1, r);
    node->val = node->lc->val + node->rc->val;
    return node;
}
int query(Node* node, int l, int r, int ql, int qr) {
    if (l > qr || r < ql) return 0;
    if (ql <= l && r <= qr) {
        return node->val;
    }
    int mid = (l + r) / 2;
    int left = query(node->lc, l, mid, ql, qr);
    int right = query(node->rc, mid + 1, r, ql, qr);
    return left + right;
}
Node* update(Node* node, int l, int r, int ind, int val)
{
    Node* newnode = new Node();
    if (l == r) {
        newnode->val = node->val + val;
        return newnode;
    }
    int mid = (l + r) / 2;
    if (l <= ind && ind <= mid) {
        newnode->lc = update(node->lc, l, mid, ind, val);
        newnode->rc = node->rc;
    } else {
        newnode->lc = node->lc;
        newnode->rc = update(node->rc, mid + 1, r, ind,
            val);
    }
    newnode->val = newnode->lc->val + newnode->rc->val;
    return newnode;
}
void solve() {
    int n;
    cin >> n;
    vector<int> comp;

```

```

for (int i = 1; i <= n; i++) {
    cin >> arr[i];
    comp.push_back(arr[i]);
}
sort(comp.begin(), comp.end());
comp.erase(unique(comp.begin(), comp.end()),
    comp.end());
int sz = comp.size();
for (int i = 1; i <= n; i++) {
    arr[i] = lower_bound(comp.begin(), comp.end(),
        arr[i]) - comp.begin();
}
versions[0] = build(0, sz - 1);
for (int v = 1; v <= n; v++) {
    versions[v] = update(versions[v - 1], 0, sz - 1,
        arr[v], +1);
}
int q;
cin >> q;
vector<int> ans(q + 1);
for (int i = 1; i <= q; i++) {
    int a, b, c;
    cin >> a >> b >> c;
    int l = a ^ ans[i - 1];
    int r = b ^ ans[i - 1];
    int k = c ^ ans[i - 1];
    l = max(1, l);
    r = min(n, r);
    if (l > r) {
        ans[i] = 0;
        continue;
    }
    k = upper_bound(comp.begin(), comp.end(), k) -
        comp.begin();
    if (k >= sz) {
        ans[i] = 0;
        continue;
    }
    ans[i] = query(versions[r], 0, sz - 1, k, sz - 1) -
        query(versions[l - 1], 0, sz - 1, k, sz - 1);
}
for (int i = 1; i <= q; i++) {
    cout << ans[i] << '\n';
}
}

```

2.4 SQRT Decomposition [66 lines] - b82550a8

```

// https://www.spoj.com/problems/GIVEAWAY/
// 0 l r k : count of numbers >= k in [l,r]
// 1 idx val : update a[idx] = val
const int N = 5e5 + 5, BLK = 700;
vector<int> block[N / BLK + 5];
int get_block(int idx) { return idx / BLK; }
void solve() {
    int n;
    cin >> n;
    vector<int> a(n);
    for (int i = 0; i < n; i++) cin >> a[i];
    for (int i = 0; i < n; i++) {
        block[get_block(i)].push_back(a[i]);
    }
    int last_blk = get_block(n - 1);
    for (int i = 0; i <= last_blk; i++) {
        sort(block[i].begin(), block[i].end());
    }
    int q;

```

```

cin >> q;
while (q-- > 0) {
    int ty;
    cin >> ty;
    if (ty == 0) {
        // query
        // O(sqrt(n) log(sqrt(n)))
        int l, r, k;
        cin >> l >> r >> k;
        l--, r--;
        int bl = get_block(l);
        int br = get_block(r);
        int ans = 0;
        if (bl == br) {
            // just brute force
            for (int i = l; i <= r; i++) {
                if (a[i] >= k) ans++;
            }
        } else {
            for (int i = l; get_block(i) < (bl + 1); i++) {
                if (a[i] >= k) ans++;
            }
            for (int i = r; get_block(i) > (br - 1); i--) {
                if (a[i] >= k) ans++;
            }
            for (int b = bl + 1; b < br; b++) {
                // sorted vector, [1, 5, 10, 20], k = 6, ans += 2
                auto it = lower_bound(block[b].begin(), block[b].end(), k);
                ans += block[b].end() - it;
            }
        }
        cout << ans << '\n';
    } else {
        // update
        // O(sqrt(n) log(sqrt(n)))
        int idx, val;
        cin >> idx >> val;
        idx--;
        int old = a[idx];
        int b = get_block(idx);
        auto it = lower_bound(block[b].begin(), block[b].end(), old);
        *it = val;
        sort(block[b].begin(), block[b].end());
        a[idx] = val;
    }
}
}

```

2.5 Segment Tree Lazy [66 lines] - 1229c3a7

/* 1. TO ADAPT FOR ANY PROBLEM, ONLY EDIT THESE 4 THINGS:

- `Node` struct : Add your variables (sum, max, pref, suff). Ensure Node() is a neutral/identity element!
- `combine()` : How to merge the left and right children.
- `applySet()` : How setting a range to `v` changes a Node. (Updates lzSet, clears lzAdd).
- `applyAdd()` : How adding `v` to a range changes a Node. (Updates lzAdd).

2. NEVER TOUCH `push()`, `update()`, OR `query()`! They are mathematically bug-proof.
3. WHY applySet CLEARS lzAdd? Overwriting a range completely destroys its previous history (adds).
4. WHY push SET BEFORE ADD? "Set this to X, then add Y" implies Set happened first.
5. FOR TOGGLE/XOR/INVERSION: Change `lzAdd` to `lzXor`, delete `Set` logic, update `applyAdd`.
6. 1-BASED INDEXING: Use `seg.build(a)`, `seg.add(l, r, v)`, `seg.query(l, r)`.

*/

```

struct Node {
    ll sum;
    Node(ll _sum = 0) { sum = _sum; };
};

struct STLazy {
    int n; vector<Node> seg; vector<ll> lzAdd, lzSet;
    vector<bool> hasSet;
    STLazy(int _n) : n(_n), seg(4*_n+5), lzAdd(4*_n+5, 0), lzSet(4*_n+5, 0), hasSet(4*_n+5, 0) {}

    Node combine(Node l, Node r) {
        Node res; res.sum = l.sum + r.sum;
        return res;
    }

    void applySet(int node, int l, int r, ll v) {
        seg[node].sum = (ll)(r - l + 1) * v;
        lzSet[node] = v; hasSet[node] = 1; lzAdd[node] = 0;
    }

    void applyAdd(int node, int l, int r, ll v) {
        seg[node].sum += (ll)(r - l + 1) * v;
        lzAdd[node] += v;
    }

    void push(int node, int l, int r) {
        if (l == r) return;
        int mid = (l + r) >> 1, lc = node << 1, rc = node << 1 | 1;
        if (hasSet[node]) {
            applySet(lc, l, mid, lzSet[node]);
            applySet(rc, mid + 1, r, lzSet[node]);
            hasSet[node] = 0;
        }
        if (lzAdd[node] != 0) {
            applyAdd(lc, l, mid, lzAdd[node]);
            applyAdd(rc, mid + 1, r, lzAdd[node]);
            lzAdd[node] = 0;
        }
    }

    void build(int node, int l, int r, const vector<ll>& a) {
        if (l == r) { seg[node] = Node(a[l]); return; }
        int mid = (l + r) >> 1;
        build(node<<1, l, mid, a); build(node<<1|1, mid+1, r, a);
        seg[node] = combine(seg[node<<1], seg[node<<1|1]);
    }

    void update(int node, int l, int r, int ql, int qr, ll v, int type) {
        if (ql > r || qr < l) return;
        if (ql <= l && r <= qr) { type == 1 ? applySet(node, l, r, v); return; }
        push(node, l, r);
    }
}

```

```

    int mid = (l + r) >> 1;
    update(node<<1, l, mid, ql, qr, v, type);
    update(node<<1|1, mid+1, r, ql, qr, v, type);
    seg[node] = combine(seg[node<<1], seg[node<<1|1]);
}

Node query(int node, int l, int r, int ql, int qr) {
    if (ql > r || qr < l) return Node();
    if (ql <= l && r <= qr) return seg[node];
    push(node, l, r);
    int mid = (l + r) >> 1;
    return combine(query(node<<1, l, mid, ql, qr), query(node<<1|1, mid+1, r, ql, qr));
}
};

```

2.6 Segment Tree [32 lines] - 957994f6

```

struct Node {
    ll sum;
    Node() { sum = 0; };
};

struct ST {
    int n; vector<Node> seg;
    ST(int _n) : n(_n), seg(4*_n+5) {}

    Node combine(Node l, Node r) {
        Node res; res.sum = l.sum + r.sum;
        return res;
    }

    void build(int node, int l, int r, const vector<ll>& a) {
        if (l == r) { seg[node].sum = a[l]; return; }
        int mid = (l + r) >> 1;
        build(node<<1, l, mid, a); build(node<<1|1, mid+1, r, a);
        seg[node] = combine(seg[node<<1], seg[node<<1|1]);
    }

    void update(int node, int l, int r, int pos, ll v) {
        if (l == r) { seg[node].sum = v; return; }
        int mid = (l + r) >> 1;
        if (pos <= mid) update(node<<1, l, mid, pos, v);
        else update(node<<1|1, mid+1, r, pos, v);
        seg[node] = combine(seg[node<<1], seg[node<<1|1]);
    }

    Node query(int node, int l, int r, int ql, int qr) {
        if (ql > r || qr < l) return Node();
        if (ql <= l && r <= qr) return seg[node];
        int mid = (l + r) >> 1;
        return combine(query(node<<1, l, mid, ql, qr), query(node<<1|1, mid+1, r, ql, qr));
    }
};

```

2.7 Special Range Query Example Fixing Right Position

[73 lines] - e834812e

```

/*
https://codeforces.com/gym/106107/problem/B
We need to count "good subarrays" [l, r] where:
1. Length >= 2
2. a[l] exists somewhere in b[l...r]

```

```

3. a[r] does NOT exist in b[l...r]
*/
#include <bits/stdc++.h>
using namespace std;
#define i64 long long
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;

const int N = 5e5 + 5;
i64 fenwick[N];

void update(int ind, int val) {
    while (ind < N) {
        fenwick[ind] += val;
        ind += ind & -ind;
    }
}

i64 query(int ind) {
    i64 sum = 0;
    while (ind > 0) {
        sum += fenwick[ind];
        ind -= ind & -ind;
    }
    return sum;
}

void solve() {
    int n;
    cin >> n;
    vector<int> comp;
    vector<int> a(n + 1), b(n + 1);
    gp_hash_table<int, vector<int>> mp;
    for (int i = 1; i <= n; i++) cin >> a[i];
    for (int i = 1; i <= n; i++) {
        cin >> b[i];
        mp[b[i]].push_back(i);
    }
    vector<int> rend(n + 1, n + 1);
    for (int i = 1; i <= n; i++) {
        if (mp[a[i]].empty()) continue;
        auto it = lower_bound(mp[a[i]].begin(),
            mp[a[i]].end(), i);
        if (it == mp[a[i]].end()) continue;
        rend[i] = max(i + 1, *it); // length >= 2, l < r
    }
    vector<vector<int>> active(n + 2);
    for (int i = 1; i <= n; i++) {
        if (rend[i] <= n) {
            active[rend[i]].push_back(i); // i to rend[i] is a
            segment
        }
    }
    gp_hash_table<int, int> last;
    i64 seg_count = 0, ans = 0;
    for (int r = 1; r <= n; r++) {
        last[b[r]] = r;
        for (auto l : active[r]) {
            update(l, 1);
            seg_count++;
        }
        int last_pos = (last.find(a[r]) != last.end()) ?
            last[a[r]] : 0;
        i64 bad = query(last_pos);
        ans += seg_count - bad;
    }
    cout << ans << '\n';
}

```

```

// clear fenwick tree
for (int r = 1; r <= n; r++) {
    for (auto l : active[r]) update(l, -1);
}
}

2.8 Sqrt Tricks [8 lines] - 4f4df416
1. Size of the block is not always Sqrt, adjust it as
   necessary. if o(n/b+b) then take n/b = b and
   calculate b.
2. MO's Algorithm
   *it is possible to solve a Mo problem without any
   remove operation. For L in one block R only
   increases, for every range we can start L from
   the last of that block
3. Sqrt Decomposition by time of queries.
   *keep overall solution and sqrt(n) updates in a
   vector and for a query iterate over all of them,
   when the vector size exceeds sqrt(n) you can add
   these updates with overall solution using o(n)
4. If sum of N positive numbers are S, there are at most
   sqrt(S) distinct values.
5. Randomization
6. Baby step, gaint step

2.9 Trie Bit [38 lines] - 300d2d92
struct BitTrie {
    static const int BT = 62; // Use 30 for numbers <=
    10^9
    struct Node {
        int nxt[2]{}; // {} zero-initializes the array
        int cnt = 0;
    };
    vector<Node> t;
    BitTrie() : t(1) {} // Initializes with root at
    index 0
    //d = 1 for insert, d = -1 for remove
    void insert(long long x, int d = 1) {
        int u = 0;
        t[u].cnt += d; // Track total elements at root
        for (int i = BT - 1; i >= 0; i--) {
            int v = (x >> i) & 1;
            if (!t[u].nxt[v]) {
                t[u].nxt[v] = t.size();
                t.emplace_back();
            }
            u = t[u].nxt[v];
            t[u].cnt += d;
        }
    }
    long long query(long long x) {
        if (!t[0].cnt) return 0;
        int u = 0;
        long long mx = 0;
        for (int i = BT - 1; i >= 0; i--) {
            int r = (x >> i) & 1;
            if (t[u].nxt[r ^ 1] && t[t[u].nxt[r ^
                1]].cnt > 0) {
                mx |= (1LL << i);
                u = t[u].nxt[r ^ 1];
            } else {
                u = t[u].nxt[r];
            }
        }
        return mx;
    }
};
}

```

3 Dynamic Programming

3.1 All Possible Subarray Sum [6 lines] - 18ee4984

```

bitset<100005> bs = 1;
for (auto i : a) {
    bs |= (bs << i); // if previous 1 value pos is
    possible now ith bit or ith sm
    // is also possible
}
cout << bs.count() - 1 << endl;

```

3.2 CHT [46 lines] - ea32a345

```

#define x first
#define y second
// Warning: replace __int128 with long double if using
// floating point lines or if unsure about the
// compiler
// Queries maximum by default, pass false in constructor
// to query minimum
// Line = pair (m, c) for a line y = mx + c
// Make sure lines are inserted in non-decreasing order
// for maximum queries, and non-increasing order for
// minimum queries
template<typename T, class Line = pair<T, T>> // Make
    sure multiplications fit in T
class CHT {
private:
    vector<Line> lines;
    bool maximum;
public:
    CHT(bool maximum = true) { this->maximum = maximum; }
    void addLine(Line line) {
        if (!maximum) line.first = -line.first, line.second
            = -line.second;
        insert(line);
    }
    T query(const T &x) {
        assert(!lines.empty());
        int L = 0, R = lines.size() - 1;
        while (L != R) {
            int mid1 = L + (R - L) / 3;
            int mid2 = R - (R - L) / 3;
            if (lines[mid1].x * x + lines[mid1].y
                >= lines[mid2].x * x + lines[mid2].y
            ) R = mid2 - 1;
            else L = mid1 + 1;
        }
        T res = lines[L].x * x + lines[L].y;
        return maximum ? res : -res;
    }
private:
    bool bad(const Line &line1, const Line &line2, const
        Line &line3) {
        return __int128(line3.y - line1.y) *
            __int128(line1.x - line2.x)
            <= __int128(line2.y - line1.y) *
                __int128(line1.x - line3.x);
    }
    void insert(const Line &line) {
        while (lines.size() > 0 && lines.back().x == line.x)
            lines.pop_back();
        lines.push_back(line);
        int sz = lines.size();
    }
}

```

```

while (sz >= 3 && bad(lines[sz - 3], lines[sz - 2],
    lines[sz - 1])) {
    lines.erase(lines.end() - 2);
    sz--;
}
};

```

3.3 Digit DP [15 lines] - 6ec98828

```

int f(int pos, int up, int under, int nz) {
    if (pos == n) return 0;
    int& ans = dp[pos][under][up][nz];
    if (ans != -1) return ans;
    int ans = 0;
    int start = up ? 0 : s[pos] - '0';
    int end = under ? 9 : t[pos] - '0';
    for (int d = start; d <= end; d++) {
        int n_up = up || (d > s[pos] - '0');
        int n_under = under || (d < t[pos] - '0');
        int n_nz = nz || (d != 0);
        ans += f(pos + 1, n_under, n_up, n_nz);
    }
    return ans;
}

```

3.4 Divide and Conquer DP [26 lines] - 91a711fa

```

ll G,L;///total group,cell size
ll dp[8001][801],cum[8001];
ll C[8001];///value of each cell
inline ll cost(ll l,ll r){
    return (cum[r]-cum[l-1])*(r-l+1);
}
void fn(ll g,ll st,ll ed,ll r1,ll r2){
    if(st>ed)return;
    ll mid=(st+ed)/2,pos=-1;
    dp[mid][g]=inf;
    for(int i=r1;i<=r2;i++){
        ll tcost=cost(i,mid)+dp[i-1][g-1];
        if(tcost<dp[mid][g]){
            dp[mid][g]=tcost,pos=i;
        }
    }
    fn(g,st,mid-1,r1,pos);
    fn(g,mid+1,ed,pos,r2);
}
int main(){
    for(int i=1;i<=L;i++){
        cum[i]=cum[i-1]+C[i];
    }
    for(int i=1;i<=L;i++){
        dp[i][1]=cost(1,i);
    }
    for(int i=2;i<=G;i++)fn(i,1,L,1,L);
}

```

3.5 LCIS o(n*m) [22 lines] - c8f9d47f

```

int a[100] = {0}, b[100] = {0}, f[100] = {0};
int n = 0, m = 0;
int main(void) {
    cin >> n;
    for (int i = 1; i <= n; i++) cin >> a[i];
    cin >> m;
    for (int i = 1; i <= m; i++) cin >> b[i];
    for (int i = 1; i <= n; i++) {
        int k = 0;
        for (int j = 1; j <= m; j++) {
            if (a[i] > b[j] && f[j] > k)
                k = f[j];
            else if (a[i] == b[j] && k + 1 > f[j])

```

```

                f[j] = k + 1;
            }
        }
        int and = 0;
        for (int i = 1; i <= m; i++)
            if (f[i] > ans) ans = f[i];
        cout << and << endl;
        return 0;
    }
}

```

3.6 LCS [59 lines] - d1c8c325

```

// LCS DP Table and LCS Length
vector<vector<int>> dp(s.size() + 1,
    vector<int>(t.size() + 1));
for (int i = 1; i <= s.size(); i++) {
    for (int j = 1; j <= t.size(); j++) {
        if (s[i - 1] == t[j - 1])
            dp[i][j] = dp[i - 1][j - 1] + 1;
        else
            dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
    }
}
cout << dp[s.size()][t.size()] << "\n";
// Any LCS String
string a;
int i = s.size();
int j = t.size();
while (i > 0 && j > 0) {
    if (s[i - 1] == t[j - 1]) {
        a += s[i - 1];
        i--, j--;
    } else if (dp[i][j - 1] > dp[i - 1][j])
        j--;
    else
        i--;
}
reverse(a.begin(), a.end());
cout << a << "\n";
// Lexicographically smallest LCS
vector<vector<string>> dpp(s.size() + 1,
    vector<string>(t.size() + 1));
for (int i = 1; i <= s.size(); i++) {
    for (int j = 1; j <= t.size(); j++) {
        if (s[i - 1] == t[j - 1])
            dpp[i][j] = dpp[i - 1][j - 1] + s[i - 1];
        else if (dp[i][j - 1] < dp[i - 1][j])
            dpp[i][j] = dpp[i - 1][j];
        else if (dp[i][j - 1] > dp[i - 1][j])
            dpp[i][j] = dpp[i][j - 1];
        else
            dpp[i][j] = min(dpp[i][j - 1], dpp[i - 1][j]);
    }
}
cout << dpp[s.size()][t.size()] << "\n";
// number of distinct LCS sequences
int MOD = 1e9 + 7;
vector<vector<int>> cnt(s.size() + 1,
    vector<int>(t.size() + 1));
for (int i = 1; i <= s.size(); i++) {
    for (int j = 1; j <= t.size(); j++) {
        if (s[i - 1] == t[j - 1])
            cnt[i][j] = cnt[i - 1][j - 1];
        else if (dp[i][j - 1] < dp[i - 1][j])
            cnt[i][j] = cnt[i - 1][j];
        else if (dp[i][j - 1] > dp[i - 1][j])
            cnt[i][j] = cnt[i][j - 1];
        else
            cnt[i][j] = cnt[i][j - 1] + cnt[i - 1][j];
    }
}

```

```

    else {
        cnt[i][j] = cnt[i - 1][j] + cnt[i][j - 1];
        if (dp[i][j] == dp[i - 1][j - 1]) cnt[i][j] -=
            cnt[i - 1][j - 1];
        cnt[i][j] = (cnt[i][j] + MOD) % MOD;
    }
}
}

```

3.7 LIS O(nlogn) with full path [39 lines] - 2cab3900

```

//1. LIS Length(Change lower_bound to upper_bound to
    allow EQUAL elements)
int LIS(vector<int>& v) {
    vector<int> seq;
    for (int x:v) { auto it =
        lower_bound(seq.begin(),seq.end(),x);
        if(it==seq.end()) seq.push_back(x); else *it=x; }
    return seq.size();
}
//2. LIS with Reconstruction
vector<int> getLIS(vector<int>& v) {
    int n=v.size(); vector<int> seq, id, p(n,-1), ans;
    for(int i=0;i<n;i++) {
        int pos = lower_bound(seq.begin(),seq.end(),v[i])-
            seq.begin();
        if(pos>0) p[i]=id[pos-1]; // Link current element to
            previous best
        if(pos==seq.size()) {seq.push_back(v[i]);
            id.push_back(i);}
        else {seq[pos]=v[i]; id[pos]=i;}
    }
    // Backtrack using parent array `p`
    for(int c=id.empty()-1;id.back(); c!--1; c=p[c])
        ans.push_back(v[c]);
    reverse(ans.begin(),ans.end()); return ans;
}
//3. SEGTree LIS WRAPPER: For Weights, Counts, and
    Restrictions. O(N log N)
//Assumes you have a Point Update, Range Max Query
    SegTree ready.
ll getLIS_SegTree(vector<int>& a, vector<ll>& w) {
    vector<int> b=a; ll ans=0;
    // Coordinate Compression: SegTree leaves [1..M]
        represent the SORTED VALUES
    sort(b.begin(),b.end());
    b.erase(unique(b.begin(),b.end()),b.end());
    int M = b.size();
    //Call build(1, 1, M) here to initialize SegTree
        leaves to 0
    for(int i=0;i<a.size();i++) {
        // x is the 1-based compressed index of value a[i]
        int x = lower_bound(b.begin(),b.end(),a[i])-
            b.begin()+1;
        // 1. Strictly Increasing: query(1, 1, M, 1, x - 1)
        // 2. Non-Decreasing (equal allowed): query(1, 1, M,
            1, x)
        // 3. Condition (e.g. diff >= K): Find pos of
            (a[i]-K) in 'b' and query up to pos
        ll mx = (x==1) ? 0 : query(1, 1, M, 1, x-1);
        mx += w[i]; ans = max(ans, mx);
        // Update the max value ending exactly at compressed
            value 'x'
        update(1, 1, M, x, mx);
    } return ans;
}

```

3.8 MCM [26 lines] - 2dd10507

```
const int N = 1005;
vector<int> v;
int dp[N][N], mark[N][N];
int MCM(int i, int j) {
    if (i == j) return dp[i][j] = 0;
    if (dp[i][j] != -1) return dp[i][j];
    int mn = INT_MAX;
    for (int k = i; k < j; k++) {
        int x = mn;
        mn = min(mn, MCM(i, k) + MCM(k + 1, j) + v[i - 1] *
            v[k] * v[j]);
        if (x != mn) mark[i][j] = k;
    }
    return dp[i][j] = mn;
}
void print_order(int i, int j) {
    if (i == j)
        cout << "X" << i;
    else {
        cout << "(";
        print_order(i, mark[i][j]);
        print_order(mark[i][j] + 1, j);
        cout << ")";
    }
}
// memset(dp, -1, sizeof dp);
// print_order(1, n);
```

3.9 Maximum Submatrix [33 lines] - c1178137

```
int a[150][150] = {0};
int c[200] = {0};
int maxarray(int n) {
    int b = 0, sum = -100000000;
    for (int i = 1; i <= n; i++) {
        if (b > 0)
            b += c[i];
        else
            b = c[i];
        if (b > sum) sum = b;
    }
    return sum;
}
int maxmatrix(int n) {
    int sum = -100000000, max = 0;
    for (int i = 1; i <= n; i++) {
        for (int j = 1; j <= n; j++) c[j] = 0;
        for (int j = i; j <= n; j++) {
            for (int k = 1; k <= n; k++) c[k] += a[j][k];
            max = maxarray(n);
            if (max > sum) sum = max;
        }
    }
    return sum;
}
int main(void) {
    int n = 0;
    cin >> n;
    for (int i = 1; i <= n; i++)
        for (int j = 1; j <= n; j++) cin >> a[i][j];
    cout << maxmatrix(n);
    return 0;
}
```

3.10 SOS DP [55 lines] - 509e6475

```
// sum over subsets
// fact: need sum of submasks
```

```
void SOS(vector<int>& v) {
    const int BITS = log2(*max_element(v.begin(),
        v.end())) + 1;
    vector<int> freq(1 << BITS, 0);
    for (int mask : v) freq[mask]++;
    vector<vector<int>> dp(BITS + 1, vector<int>(1 <<
        BITS, 0));
    for (int mask = 0; mask < 1 << BITS; mask++) {
        dp[0][mask] = freq[mask];
    }
    for (int bits = 1; bits <= BITS; bits++) {
        for (int mask = 0; mask < 1 << BITS; mask++) {
            if ((mask & (1 << (bits - 1))) == 0) {
                dp[bits][mask] = dp[bits - 1][mask];
            } else {
                int other_mask = mask - (1 << (bits - 1));
                dp[bits][mask] = dp[bits - 1][mask] + dp[bits -
                    1][other_mask];
            }
        }
    }
    for (int mask : v) cout << dp[BITS][mask] << '\n';
}
// O(BITS * 2 ^ BITS)
// dp[bits][mask] means left most 'bits' of submasks can
// be differ (submask)
// for dp[1][11] 01, 00 are not allow because leftmost 1
// bit can be differ. 10
// and 11 are allowed. for travarsing all the submask of
// a mask we can use
// submask = mask
// do {
//     submask = (submask - 1) & mask
// } while (submask)
// O(3 ^ BITS)
const int MAXN = 1 << 20, MLOG = 20;
int dp[MAXN], freq[MAXN];
// Sum over subsets (SOS Down)
void forward1() {
    for (int bit = 0; bit < MLOG; bit++)
        for (int i = 0; i < MAXN; i++)
            if (i & (1 << bit)) dp[i] += dp[i ^ (1 << bit)];
}
void backward1() {
    for (int bit = 0; bit < MLOG; bit++)
        for (int i = MAXN - 1; i >= 0; i--)
            if (i & (1 << bit)) dp[i] -= dp[i ^ (1 << bit)];
}
// Sum over supersets (SOS Up)
void forward2() {
    for (int bit = 0; bit < MLOG; bit++)
        for (int i = MAXN - 1; i >= 0; i--)
            if (i & (1 << bit)) dp[i ^ (1 << bit)] += dp[i];
}
void backward2() {
    for (int bit = 0; bit < MLOG; bit++)
        for (int i = 0; i < MAXN; i++)
            if (i & (1 << bit)) dp[i ^ (1 << bit)] -= dp[i];
}
```

4 Game Theory**4.1 Points to be noted** [14 lines] - f960ca72

```
>[First Write a Brute Force solution]
>Nim = all xor
>Misere Nim = Nim + corner case: if all piles are 1,
reverse(nim)
```

```
>Bogus Nim = Nim
>Staircase Nim = Odd indexed pile Nim (Even indexed pile
doesnt matter, as one player can give bogus moves to
drop all even piles to ground)
>Sprague Grundy: [Every impartial game under the normal
play convention is equivalent to a one-heap game of
nim]
Every tree = one nim pile = tree root value; tree leaf
value = 0; tree node value = mex of all child nodes.
[Careful: one tree node can become multiple new tree
roots(multiple elements in one node), then the value
of that node = xor of all those root values]
>Hackenbush(Given a rooted tree; cut an edge in one
move; subtree under that edge gets removed; last
player to cut wins):
Colon:  $//G(u) = (G(v1) + 1) \oplus (G(v2) + 1) \oplus \dots [v1, v2, \dots$ 
are childs of  $u]$ 
For multiple trees ans is their xor
>Hackenbush on graph (instead of tree given an rooted
graph):
fusion: All edges in a cycle can be fused to get a tree
structure; build a super node, connect some single
nodes with that super node, number of single nodes
is the number of edges in the cycle.
Sol: [Bridge component tree] mark all bridges, a group
of edges that are not bridges, becomes one component
and contributes number of edges to the hackenbush.
(even number of edges contributes 0, odd number of
edges contributes 1)
```

5 Geometry**5.1 2D Convex Hull** [65 lines] - aed084cc

```
struct point {
    ll x, y;
    bool operator==(point const& t) const { return (x ==
        t.x && y == t.y); }
};
int orientation(point a, point b, point c) {
    ll d = (c.y - b.y) * (b.x - a.x) - (c.x - b.x) * (b.y
        - a.y);
    if (d < 0)
        return -1; // clockwise
    else if (d > 0)
        return 1; // anticlockwise
    return 0; // collinear
}
bool clockwise(point a, point b, point c, bool
    include_collinear) {
    int o = orientation(a, b, c);
    if (o < 0) return true;
    if (o > 0) return false;
    return include_collinear;
}
bool collinear(point a, point b, point c) { return
    orientation(a, b, c) == 0; }
bool cmp_points(point& p1, point& p2) {
    return make_pair(p1.x, p1.y) < make_pair(p2.x, p2.y);
}
ll distance_sq(point a, point b) {
    ll d = (a.x - b.x) * (a.x - b.x) + (a.y - b.y) * (a.y
        - b.y);
    return d;
}
void print(vector<point>& v) {
    for (auto it : v) {
```

```

    cout << "(" << it.x << ", " << it.y << ")" << "\n";
}
vector<point> convex_hull(vector<point>& points,
    bool include_collinear = false) {
    int sz = (int)points.size();
    point p0 = *min_element(points.begin(), points.end(),
        cmp_points);
    vector<point> convex_hull_vector = points;
    sort(convex_hull_vector.begin(),
        convex_hull_vector.end(),
        [&p0](const point& p1, const point& p2) {
            int o = orientation(p0, p1, p2);
            if (o == 0) {
                return distance_sq(p0, p1) < distance_sq(p0,
                    p2);
            }
            return o < 0;
        });
    if (include_collinear) {
        int idx = sz - 1;
        while (idx >= 0 &&
            collinear(p0, convex_hull_vector[idx],
                convex_hull_vector.back()))
            idx--;
        reverse(convex_hull_vector.begin() + idx + 1,
            convex_hull_vector.end());
    }
    vector<point> st;
    for (int i = 0; i < sz; i++) {
        while (st.size() >= 2 &&
            !clockwise(st[st.size() - 2], st.back(),
                convex_hull_vector[i],
                    include_collinear)) {
            st.pop_back();
        }
        st.push_back(convex_hull_vector[i]);
    }
    if (!include_collinear && st.size() == 2 && st[0] ==
        st[1]) {
        st.pop_back();
    }
    return st;
}

```

5.2 Computational Geometry [70 lines] - 92134ce2

```

typedef long long int T;
typedef double Tf;
Tf eps = 1e-10;
// int sgn(Tf x)
// {
//     if (fabs(x) < eps) return 0;
//     if (x > 0) return 1;
//     return -1;
// }
int sgn(T x) {
    if (x == 0) return 0;
    if (x > 0)
        return 1;
    else
        return -1;
}
struct point {
    T x, y;
    point(T x = 0, T y = 0) {

```

```

        this->x = x;
        this->y = y;
    }
    point operator+(point p) { return point(x + p.x, y +
        p.y); }
    point operator-(point p) { return point(x - p.x, y -
        p.y); }
    Tf len() { return sqrt(x * x + y * y); }
    T norm() { return x * x + y * y; }
    point operator*(T a) { return point(x * a, y * a); }
    point operator/(T a) { return point(x / a, y / a); }
    // integer
    bool operator==(point p) { return p.x == x && p.y ==
        y; }
    // float
    // bool operator==(point p) {
    //     return sgn(p.x - x) == 0 && sgn(p.y - y) == 0;
    // }
    bool operator<(point p) {
        if (x == p.x) return y < p.y;
        return x < p.x;
    }
    // float
    // bool operator<(point p) {
    //     if (sgn(p.x - x) == 0) return sgn(y - p.y) ==
    //         -1;
    //     return sgn(x - p.x) == -1;
    // }
};
T dot(point a, point b) { return a.x * b.x + a.y * b.y; }
T cross(point a, point b) { return a.x * b.y - b.x *
    a.y; }
T orien(point a, point b, point c) { return cross(a -
    b, a - c); }
Tf area(point a, point b, point c) { return
    abs(orien(a, b, c)) / (Tf)2; }
struct segment {
    point a, b;
    bool onSegment(point p) {
        if (sgn(orien(a, b, p)) != 0) return false;
        return sgn(dot(p - a, p - b)) <= 0;
    }
    bool intersection(segment s) {
        if (onSegment(s.a)) return true;
        if (onSegment(s.b)) return true;
        if (s.onSegment(a)) return true;
        if (s.onSegment(b)) return true;
        int s1 = sgn(orien(a, b, s.a));
        int s2 = sgn(orien(a, b, s.b));
        int s3 = sgn(orien(s.a, s.b, a));
        int s4 = sgn(orien(s.a, s.b, b));
        if (s1 * s2 < 0 && s3 * s4 < 0) return true;
        return false;
    }
};
ostream& operator<<(ostream& os, point p) {
    return os << "(" << p.x << ", " << p.y << ")";
}

```

6 Graph

6.1 Articulation Bridges [40 lines] - f1f88788

```

const int N = 2e5 + 5;
vector<pair<int, int>> g[N];
int vis[N], st[N], low[N];
int clk, n;

```

```

vector<pair<int, int>> bridges;
void dfs(int u, int p, int edg) {
    vis[u] = 1;
    ++clk;
    st[u] = clk;
    low[u] = clk;
    for (auto[v, id]: g[u]) {
        // handled parallel edges between u, v
        if (v == p && id == edg) continue;
        if (vis[v]) {
            low[u] = min(low[u], st[v]);
        } else {
            dfs(v, u, id);
            low[u] = min(low[u], low[v]);
            if (st[u] < low[v]) {
                // edge u, v has bridge
                bridges.push_back({
                    u,
                    v
                });
            }
        }
    }
}
void find_bridges() {
    clk = 0;
    for (int i = 1; i <= n; i++) {
        vis[i] = 0;
        st[i] = low[i] = -1;
    }
    for (int i = 1; i <= n; i++) {
        if (!vis[i]) {
            dfs(i, 0, -1);
        }
    }
}

```

6.2 Articulation Points [39 lines] - 50d23cbe

```

const int N = 2e5 + 5;
vector<int> g[N];
int vis[N], st[N], low[N], adjComp[N];
int clk, n;
void dfs(int u, int p) {
    vis[u] = 1;
    ++clk;
    st[u] = clk;
    low[u] = clk;
    int child = 0;
    for (int v: g[u]) {
        if (v == p) continue;
        if (vis[v]) {
            low[u] = min(low[u], st[v]);
        } else {
            dfs(v, u);
            low[u] = min(low[u], low[v]);
            if (low[v] >= st[u] && p != 0) {
                adjComp[u]++;
            }
            child++;
        }
    }
    if (p == 0 && child > 1) {
        adjComp[u] = child - 1;
    }
}

```

```
void find_vertices() {
    clk = 0;
    for (int i = 1; i <= n; i++) {
        vis[i] = 0;
        st[i] = low[i] = -1;
    }
    for (int i = 1; i <= n; i++) {
        if (!vis[i]) {
            dfs(i, 0);
        }
    }
}
```

6.3 Bellmanford [22 lines] - 4ca51cfd

```
void bellmanFord(int num_of_nd, int src) {
    dist[src] = 0;
    for (int step = 0; step < num_of_nd; step) {
        for (int i = 1; i <= num_of_nd; i++) {
            for (auto it : adj[i]) {
                int u = i;
                int v = it.first;
                int wt = it.second;
                if (dist[u] != inf && ((dist[u] + wt) <
                    dist[v])) {
                    if (step == num_of_nd - 1) {
                        cout << "Negative cycle found\n ";
                        return;
                    }
                    dist[v] = dist[u] + wt;
                    parent[v] = u;
                }
            }
        }
    }
    for (int i = 1; i <= num_of_nd; i++) cout << dist[i]
        << " ";
    cout << endl;
}
```

6.4 Block Cut Tree [75 lines] - 192484e1

```
const int N = 2e5 + 5;
vector<int> g[N], bct[2 * N];
int vis[N], low[N], disc[N], is_art[N];
stack<int> stk;
vector<int> block_of[N];
int clk, n, m, bct_nodes, root;
void dfs(int u, int p) {
    vis[u] = 1;
    disc[u] = low[u] = ++clk;
    stk.push(u);
    int child = 0;
    for (int v : g[u]) {
        if (v == p) continue;
        if (!vis[v]) {
            child++;
            dfs(v, u);
            low[u] = min(low[u], low[v]);
            if ((p == -1 && child > 1) || (p != -1 && low[v]
                >= disc[u])) {
                is_art[u] = 1;
                vector<int> block;
                while (stk.top() != v) {
                    block.push_back(stk.top());
                    stk.pop();
                }
                block.push_back(stk.top());
                stk.pop();
            }
        }
    }
    block.push_back(u);
    int block_id = ++bct_nodes;
    for (int x : block) {
        block_of[x].push_back(block_id);
        if (is_art[x]) {
            bct[x].push_back(block_id);
            bct[block_id].push_back(x);
        }
    }
}

}

}

root = n + 1;
for (int i = 1; i <= n; i++) {
    if (is_art[i]) {
        root = i;
        break;
    }
}
}
```

```
block.push_back(u);
int block_id = ++bct_nodes;
for (int x : block) {
    block_of[x].push_back(block_id);
    if (is_art[x]) {
        bct[x].push_back(block_id);
        bct[block_id].push_back(x);
    }
}
} else {
    low[u] = min(low[u], disc[v]);
}
}

}

void build_bct() {
    clk = 0;
    bct_nodes = n;
    for (int i = 1; i <= n; i++) {
        vis[i] = is_art[i] = 0;
        block_of[i].clear();
        bct[i].clear();
    }
    for (int i = n + 1; i <= 2 * n; i++) bct[i].clear();
    for (int i = 1; i <= n; i++) {
        if (!vis[i]) {
            dfs(i, -1);
            if (!stk.empty()) {
                int block_id = ++bct_nodes;
                while (!stk.empty()) {
                    int x = stk.top();
                    stk.pop();
                    block_of[x].push_back(block_id);
                    if (is_art[x]) {
                        bct[x].push_back(block_id);
                        bct[block_id].push_back(x);
                    }
                }
            }
        }
    }
}

}

}

root = n + 1;
for (int i = 1; i <= n; i++) {
    if (is_art[i]) {
        root = i;
        break;
    }
}
}
```

6.5 Centroid Decomposition [30 lines] - 2fb8ca4f

```
const int N = 1e5 + 5;
vector<int> g[N];
int sz[N], dead[N], cenpar[N];
void dfs_sz(int u, int p) {
    sz[u] = 1;
    for (int v : g[u]) {
        if (v == p || dead[v]) continue;
        dfs_sz(v, u);
        sz[u] += sz[v];
    }
}

int find_centroid(int num, int u, int p) {
    for (int v : g[u]) {
        if (v != p && !dead[v] && 2 * sz[v] > num) {
            return find_centroid(num, v, u);
        }
    }
}
```

```
}
}
return u;
}

void decompose(int u, int p) {
    dfs_sz(u, p);
    int cent = find_centroid(sz[u], u, p);
    dead[cent] = true;
    cenpar[cent] = p;
    for (int v : g[cent]) {
        if (!dead[v]) {
            decompose(v, cent);
        }
    }
}
```

6.6 Dijkstra [22 lines] - 4c1dbc1b

```
void Dijkstra(int start) {
    // vector<pair<int, int>> adj[N];
    priority_queue<pair<int, int>, vector<pair<int,
        int>>, greater<pair<int, int>>> pq;
    pq.push({0, start});
    while (!pq.empty()) {
        auto it = pq.top();
        pq.pop();
        int wt = it.first;
        int u = it.second;
        if (vis[u])
            continue;
        vis[u] = 1;
        for (pair<int, int> i : adj[u]) {
            int adjWt = i.second;
            int adjNode = i.first;
            if (dist[adjNode] > wt + adjWt) {
                dist[adjNode] = wt + adjWt;
                pq.push({dist[adjNode], adjNode});
            }
        }
    }
}
```

6.7 Eulerian Circuit [16 lines] - 9da20d99

```
unordered_map<int, int> Start, End, Val;
unordered_map<int, pair<int, int>> Range;
int start = 0;
void dfs(int node) {
    visited[node] = true;
    Start[node] = start++;
    for (auto child : adj[node]) {
        if (!visited[child]) dfs(child);
    }
    End[node] = start - 1;
}

dfs(1);
vector<int> FlatArray(start + 5);
for (auto i : Start) {
    FlatArray[i.second] = Val[i.first];
    Range[i.first] = {i.second, End[i.first]};
}
```

6.8 Floyd Warshall [13 lines] - 4ea8fd7d

```
const int inf = 1e9;
const int MAXN = 505;
int dist[MAXN][MAXN];
void floydWarshall(int n) {
    for (int k = 0; k < n; ++k) {
        for (int i = 0; i < n; ++i) {
```

```

    for (int j = 0; j < n; ++j) {
        if (dist[i][k] < inf && dist[k][j] < inf)
            dist[i][j] = min(dist[i][j], dist[i][k] +
                             dist[k][j]);
    }
}
}
}

```

6.9 Heavy Light Decomposition [100 lines] - 7b1a5885

```

vector<pair<int, int>> g[N];
int edge_to_ch[N];
int par[N], dep[N], sz[N];
void dfs(int u, int p = 0) {
    sz[u] = 1, par[u] = p;
    dep[u] = dep[p] + 1;
    int mx = 0;
    for (auto &[v, idx]: g[u]) {
        if (v == p) continue;
        edge_to_ch[idx] = v;
        dfs(v, u);
        sz[u] += sz[v];
        if (sz[v] > mx) {
            mx = sz[v];
            swap(v, g[u][0].first);
        }
    }
}

int T, head[N], st[N], en[N];
void dfs_hld(int u, int p = 0) {
    st[u] = ++T;
    head[u] = (p != 0 && g[p][0].first == u) ? head[p] :
        u;
    for (auto [v, idx]: g[u]) {
        if (v == p) continue;
        dfs_hld(v, u);
    }
    en[u] = T;
}

int lca(int a, int b) {
    for (; head[a] != head[b]; b = par[head[b]]) {
        if (dep[head[a]] > dep[head[b]]) swap(a, b);
    }
    if (dep[a] > dep[b]) swap(a, b);
    return a;
}

int n;
// process node u upto it's ancestor a
// if excl is true, a won't process
i64 chain_process(int a, int u, bool excl = false) {
    i64 ans = 0;
    for (; head[u] != head[a]; u = par[head[u]]) {
        ans = max(ans, query(1, 1, n, st[head[u]],
                             st[u]));
    }
    ans = max(ans, query(1, 1, n, st[a] + excl, st[u]));
    return ans;
}

// process path from node a to b
// if excl is true, lca won't process
i64 path_process(int a, int b, bool excl = false) {
    i64 ans = 0;
    for (; head[a] != head[b]; b = par[head[b]]) {
        if (dep[head[a]] > dep[head[b]]) swap(a, b);
        ans = max(ans, query(1, 1, n, st[head[b]], st[b]));
    }
}

```

```

    if (dep[a] > dep[b]) swap(a, b);
    ans = max(ans, query(1, 1, n, st[a] + excl, st[b]));
    return ans;
}

// update path from node u to v
// if excl is true, lca won't update
void path_update(int a, int b, int val, bool excl =
    false) {
    for (; head[a] != head[b]; b = par[head[b]]) {
        if (dep[head[a]] > dep[head[b]]) swap(a, b);
        update(1, 1, n, st[head[b]], st[b], val);
    }
    if (dep[a] > dep[b]) swap(a, b);
    update(1, 1, n, st[a] + excl, st[b], val);
}

/*
    dfs(1);
    head[1] = 1;
    dfs_hld(1);
    build(1, 1, n);
*/
void solve() {
    cin >> n;
    int q;
    cin >> q;
    for (int i = 1; i < n; i++) {
        int u, v, c;
        cin >> u >> v >> c;
        g[u].push_back({v, i});
        g[v].push_back({u, i});
        edge_cost[i] = c;
    }
    dfs(1);
    head[1] = 1;
    dfs_hld(1);
    for (int i = 1; i < n; i++) {
        int u = edge_to_ch[i];
        arr[st[u]] = edge_cost[i];
    }
    build(1, 1, n);
    while (q--) {
        int u, v, val;
        cin >> u >> v >> val;
        path_update(u, v, val, true);
        cout << path_process(u, v, true) << '\n';
    }
}

```

6.10 K'th Shortest path [40 lines] - 726428ad

```

int m, n, deg[MM], source, sink, K, val[MM] [12];
struct edge {
    int v, w;
} adj[MM] [500];
struct info {
    int v, w, k;
    bool operator<(const info &b) const {
        return w > b.w;
    }
};
priority_queue<info, vector<info>> Q;
void kthBestShortestPath() {
    int i, j;
    info u, v;
    for (i = 0; i < n; i++)
        for (j = 0; j < K; j++) val[i][j] = inf;
    u.v = source, u.k = 0, u.w = 0;
}

```

```

Q.push(u);
while (!Q.empty()) {
    u = Q.top();
    Q.pop();
    for (i = 0; i < deg[u.v]; i++) {
        v.v = adj[u.v][i].v;
        int cost = adj[u.v][i].w + u.w;
        for (v.k = u.k; v.k < K; v.k++) {
            if (cost == inf) break;
            if (val[v.v][v.k] > cost) {
                swap(cost, val[v.v][v.k]);
                v.w = val[v.v][v.k];
                Q.push(v);
                break;
            }
        }
        for (v.k++; v.k < K; v.k++) {
            if (cost == inf) break;
            if (val[v.v][v.k] > cost) swap(cost, val[v.v][v.k]);
        }
    }
}
}
}
}

```

6.11 Kruskal [13 lines] - 22efc58b

```

vector<pair<int, pair<int, int>>> Kruskal(
    vector<pair<int, pair<int, int>>>& edges, int n) {
    sort(edges.begin(), edges.end());
    vector<pair<int, pair<int, int>>> ans;
    DisjointSet D(n);
    for (auto it : edges) {
        if (D.findUPar(it.second.first) !=
            D.findUPar(it.second.second)) {
            ans.push_back({it.first, {it.second.first,
                                         it.second.second}});
            D.unionBySize(it.second.first, it.second.second);
        }
    }
    return ans;
}
}

```

6.12 LCA using Segment Tree [80 lines] - e99ed31c

```

struct LCA {
    vector<int> height, euler, first, segtree, parent;
    vector<bool> visited;
    vector<vector<int>> jump;
    int n;
    LCA(vector<vector<int>> &adj, int root = 0) {
        n = adj.size();
        height.resize(n);
        first.resize(n);
        parent.resize(n);
        euler.reserve(n * 2);
        visited.assign(n, false);
        dfs(adj, root);
        int m = euler.size();
        segtree.resize(m * 4);
        build(1, 0, m - 1);
        jump.resize(n, vector<int>(32, -1));

        for (int i = 0; i < n; i++) {
            jump[i][0] = parent[i];
        }
        for (int j = 1; j < 20; j++) {
            for (int i = 0; i < n; i++) {
                int mid = jump[i][j - 1];
            }
        }
    }
}

```

```

    if (mid != -1) jump[i][j] = jump[mid][j-1];
}
}
void dfs(vector<vector<int>> &adj, int node, int h = 0) {
    visited[node] = true;
    height[node] = h;
    first[node] = euler.size();
    euler.push_back(node);
    for (auto to : adj[node]) {
        if (!visited[to]) {
            parent[to] = node;
            dfs(adj, to, h + 1);
            euler.push_back(node);
        }
    }
}
void build(int node, int b, int e) {
    if (b == e) {
        segtree[node] = euler[b];
    } else {
        int mid = (b + e) / 2;
        build(node << 1, b, mid);
        build(node << 1 | 1, mid + 1, e);
        int l = segtree[node << 1], r = segtree[node << 1 | 1];
        segtree[node] = (height[l] < height[r]) ? l : r;
    }
}
int query(int node, int b, int e, int L, int R) {
    if (b > R || e < L)
        return -1;
    if (b >= L && e <= R)
        return segtree[node];
    int mid = (b + e) >> 1;

    int left = query(node << 1, b, mid, L, R);
    int right = query(node << 1 | 1, mid + 1, e, L, R);
    if (left == -1)
        return right;
    if (right == -1)
        return left;
    return height[left] < height[right] ? left : right;
}
int lca(int u, int v) {
    int left = first[u], right = first[v];
    if (left > right)
        swap(left, right);
    return query(1, 0, euler.size() - 1, left, right);
}
int kthParent(int u, int k) {
    for (int i = 20; i >= 0; i--) {
        if (k & (1LL << i)) u = jump[u][i];
    }
    return u;
}
};

```

6.13 LCA [40 lines] - bfc676c0

```

const int N = 1e5 + 5, LG = 17;
vector<int> g[N];
int depth[N], parent[N][LG];
void dfs(int u, int p) {
    depth[u] = depth[p] + 1;
    parent[u][0] = p;

```

```

    for (int i = 1; i < LG; i++) {
        parent[u][i] = parent[parent[u][i - 1]][i - 1];
    }
    for (int v : g[u]) {
        if (v == p) continue;
        dfs(v, u);
    }
}
int lca(int u, int v) {
    if (depth[u] < depth[v]) swap(u, v);
    int diff = depth[u] - depth[v];
    for (int i = 0; i < LG; i++) {
        if (diff >> i & 1) {
            u = parent[u][i];
        }
    }
    if (u == v) return u;
    for (int i = LG - 1; i >= 0; i--) {
        if (parent[u][i] != parent[v][i]) {
            u = parent[u][i];
            v = parent[v][i];
        }
    }
    return parent[u][0];
}
int dist(int u, int v) { return depth[u] + depth[v] - 2 * depth[lca(u, v)]; }
int kthParent(int u, int k) {
    for (int i = 0; i < LG; i++) {
        if (k >> i & 1) {
            u = parent[u][i];
        }
    }
    return u;
}
}

```

6.14 SCC [47 lines] - a8ab7ad2

```

vector<bool> visited; // keeps track of which vertices
                        // are already visited
// runs depth first search starting at vertex v.
// each visited vertex is appended to the output vector
// when dfs leaves it.
void dfs(int v, vector<vector<int>> const &adj,
        vector<int> &output) {
    visited[v] = true;
    for (auto u : adj[v])
        if (!visited[u])
            dfs(u, adj, output);
    output.push_back(v);
}
// input: adj -- adjacency list of G
// output: components -- the strongly connected
//         components in G
// output: adj_cond -- adjacency list of G^SCC (by root
//         vertices)
void scc(vector<vector<int>> const &adj,
        vector<vector<int>> &components,
        vector<vector<int>> &adj_cond) {
    int n = adj.size();
    components.clear(), adj_cond.clear();
    vector<int> order; // will be a sorted list of G's
                        // vertices by exit time
    visited.assign(n, false);
    // first series of depth first searches
    for (int i = 0; i < n; i++)
        if (!visited[i])

```

```

        dfs(i, adj, order);
    // create adjacency list of G^T
    vector<vector<int>> adj_rev(n);
    for (int v = 0; v < n; v++)
        for (int u : adj[v])
            adj_rev[u].push_back(v);
    visited.assign(n, false);
    reverse(order.begin(), order.end());
    vector<int> roots(n, 0); // gives the root vertex of a
                            // vertex's SCC
    // second series of depth first searches
    for (auto v : order)
        if (!visited[v]) {
            std::vector<int> component;
            dfs(v, adj_rev, component);
            components.push_back(component);
            int root = *min_element(begin(component),
                                    end(component));
            for (auto u : component)
                roots[u] = root;
        }
    // add edges to condensation graph
    adj_cond.assign(n, {});
    for (int v = 0; v < n; v++)
        for (auto u : adj[v])
            if (roots[v] != roots[u])
                adj_cond[roots[v]].push_back(roots[u]);
}

```

6.15 SPFA O(V*E) [57 lines] - 68121e58

```

int q[3001] = {0}; // queue for node
int d[1001] = {0}; // record shortest path
from start to ith node bool f[1001] = {0};
int a[1001][1001] = {0}; // adjacency list
int w[1001][1001] = {0}; // adjacency matrix
int main(void) {
    int n = 0, m = 0;
    cin >> n >> m;
    for (int i = 1; i <= m; i++) {
        int x = 0, y = 0, z = 0;
        cin >> x >> y >> z;
        // node x to node y has weight z
        a[x][0]++;
        a[x][a[x][0]] = y;
        w[x][y] = z;
        /*
        // for undirected graph
        a[x][0]++;
        a[y][a[y][0]] = x;
        w[y][x] = z;
        */
    }
    int s = 0, e = 0;
    cin >> s >> e; // s: start, e: end
    SPFA(s);
    cout << d[e] << endl;
    return 0;
}
void SPFA(int v0) {
    int t, h, u, v;
    for (int i = 0; i < 1001; i++) d[i] = INT_MAX;
    for (int i = 0; i < 1001; i++) f[i] = false;
    d[v0] = 0;
    h = 0;
    t = 1;
    q[1] = v0;

```

```

f[v0] = true;
while (h != t) {
    h++;
    if (h > 3000) h = 1;
    u = q[h];
    for (int j = 1; j <= a[u][0]; j++) {
        v = a[u][j];
        if (d[u] + w[u][v] < d[v]) // change to > if
            calculating longest path
        {
            d[v] = d[u] + w[u][v];
            if (!f[v]) {
                t++;
                if (t > 3000) t = 1;
                q[t] = v;
                f[v] = true;
            }
        }
    }
    f[u] = false;
}
}

```

6.16 Topological Sort [33 lines] - 2725b3e1

```

vector<int> topologicalSort(int V, vector<vector<int>>&
    g) {
    vector<int> inDegree(V, 0);
    vector<int> result;
    queue<int> q;
    for (int u = 0; u < V; u++) {
        for (int v : g[u]) {
            inDegree[v]++;
        }
    }
    for (int i = 0; i < V; i++) {
        if (inDegree[i] == 0) {
            q.push(i);
        }
    }
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        result.push_back(u);
        for (int v : g[u]) {
            inDegree[v]--;
            if (inDegree[v] == 0) {
                q.push(v);
            }
        }
    }
    // You may need to check inDegree of all the vertices
    // is 0
    if (result.size() != V) {
        cout << "Graph contains a cycle, topological sort
            not possible!" << endl;
        return {};
    }

    return result;
}

```

6.17 Tree Rerooting [97 lines] - a06a53a6

```

namespace reroot {
const auto exclusive = [](const auto& a, const auto&
    base,
                        const auto& merge_into, int
                        vertex) {

```

```

    int n = (int)a.size();
    using Aggregate = std::decay_t<decltype(base)>;
    std::vector<Aggregate> b(n, base);
    for (int bit = (int)std::lg(n); bit >= 0; --bit) {
        for (int i = n - 1; i >= 0; --i) b[i] = b[i >> 1];
        int sz = n - (n & !bit);
        for (int i = 0; i < sz; ++i) {
            int index = (i >> bit) ^ 1;
            b[index] = merge_into(b[index], a[i], vertex, i);
        }
    }
    return b;
};

// MergeInto : Aggregate * Value * Vertex(int) *
// EdgeIndex(int) -> Aggregate
// Base : Vertex(int) -> Aggregate
// FinalizeMerge : Aggregate * Vertex(int) *
// EdgeIndex(int) -> Value
const auto rerooter = [](const auto& g, const auto&
    base,
                        const auto& merge_into, const
                        auto& finalize_merge) {

    int n = (int)g.size();
    using Aggregate = std::decay_t<decltype(base(0))>;
    using Value =
        std::decay_t<decltype(finalize_merge(base(0), 0,
            0))>;
    std::vector<Value> root_dp(n, dp(n));
    std::vector<std::vector<Value>> edge_dp(n,
        redge_dp(n));
    std::vector<int> bfs, parent(n);
    bfs.reserve(n);
    bfs.push_back(0);
    for (int i = 0; i < n; ++i) {
        int u = bfs[i];
        for (auto v : g[u]) {
            if (parent[u] == v) continue;
            parent[v] = u;
            bfs.push_back(v);
        }
    }
    for (int i = n - 1; i >= 0; --i) {
        int u = bfs[i];
        int p_edge_index = -1;
        Aggregate aggregate = base(u);
        for (int edge_index = 0; edge_index <
            (int)g[u].size(); ++edge_index) {
            int v = g[u][edge_index];
            if (parent[u] == v) {
                p_edge_index = edge_index;
                continue;
            }
            aggregate = merge_into(aggregate, dp[v], u,
                edge_index);
        }
        dp[u] = finalize_merge(aggregate, u, p_edge_index);
    }
}

```

```

for (auto u : bfs) {
    dp[parent[u]] = dp[u];
    edge_dp[u].reserve(g[u].size());
    for (auto v : g[u]) edge_dp[u].push_back(dp[v]);
    auto dp_exclusive = exclusive(edge_dp[u], base(u),
        merge_into, u);
    redge_dp[u].reserve(g[u].size());
    for (int i = 0; i < (int)dp_exclusive.size(); ++i) {

```

```

        auto merge_value =
            finalize_merge(dp_exclusive[i], u, i);
        redge_dp[u].push_back(merge_value);
    }
    root_dp[u] = finalize_merge(
        n > 1 ? merge_into(dp_exclusive[0],
            edge_dp[u][0], u, 0) : base(u), u,
        -1);
    for (int i = 0; i < (int)g[u].size(); ++i) {
        dp[g[u][i]] = redge_dp[u][i];
    }
}

return std::make_tuple(std::move(root_dp),
    std::move(edge_dp),
                        std::move(redge_dp));
};
} // namespace reroot

void solve() {
    using Aggregate = int;
    using Value = int;

    auto base = [](int vertex) -> Aggregate { return 0; };
    auto merge_into = [](Aggregate vertex_dp, Value
        neighbor_dp, int vertex,
                        int edge_index) -> Aggregate {
        return vertex_dp + std::max(neighbor_dp, 0);
    };
    auto finalize_merge = [&](Aggregate vertex_dp, int
        vertex,
                        int edge_index) -> Value {
        return vertex_dp + 2 * color[vertex] - 1;
    };

    auto [reroot_result, edge_dp, redge_dp] =
        reroot::rerooter(g, base, merge_into,
            finalize_merge);

    for (auto dp : reroot_result) {
        std::cout << dp << ' ';
    }
    std::cout << '\n';
}

```

7 Misc

7.1 Bit count in O(1) [5 lines] - c2d40607

```

int BitCount(unsigned int u) {
    unsigned int uCount;
    uCount = u - ((u >> 1) & 033333333333) - ((u >> 2) &
        011111111111);
    return ((uCount + (uCount >> 3)) & 030707070707) % 63;
}

```

7.2 Bit hacks [16 lines] - 96eab638

```

# x & -x is the least bit in x.
# iterate over all the subsets of the mask
for (int s=m; ; s=(s-1)&m) {
    ... you can use s ...
    if (s==0) break;
}
# c = x&-x, r = x+c; (((r^x) >> 2)/c) | r is the
next number after x with the same number of bits set.
# __builtin_popcount(x) //number of ones in binary

```

```
__builtin_popcountll(x) // for long long
# __builtin_clz(x) // number of leading zeros
__builtin_ctz(x) // number of trailing zeros, they
    also have long long version
# bitset<N> b; //N is size of bitset
b.count(); // return number of bits set 0(N / 64)
b.to_string(); // return string representation of
    bitset
b.any() // return true if any bit is set 0(N / 64)
```

7.3 Bitset C++ [13 lines] - 096a3812

```
bitset<17>BS;
BS[1] = BS[7] = 1;
cout<<BS._Find_first()<<endl; // prints 1
bs._Find_next(idx). This function returns first set bit
    after index idx. for example:
```

```
bitset<17>BS;
BS[1] = BS[7] = 1;
cout<<BS._Find_next(1)<<' ';<<BS._Find_next(3)<<endl; //
    prints 7,7
So this code will print all of the set bits of BS:
```

```
for(int i=BS._Find_first();i< BS.size();i =
    BS._Find_next(i))
    cout<<i<<endl;
//Note that there isn't any set bit after idx,
    BS._Find_next(idx) will return BS.size(); same as
    calling BS._Find_first() when bitset is clear;
```

7.4 Knight Moves [2 lines] - 28da3d5e

```
int X[8]={2,1,-1,-2,-2,-1,1,2};
int Y[8]={1,2,2,1,-1,-2,-2,-1};
```

7.5 Random Generator [6 lines] - 19e7d615

```
#define accuracy
    chrono::steady_clock::now().time_since_epoch().count()
mt19937 rng(accuracy);
int rand(int l, int r) {
    uniform_int_distribution<int> ludo(l, r);
    return ludo(rng);
}
```

7.6 Special DS [22 lines] - 31b89845

```
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
template <typename T> using o_set = tree<T, null_type,
    less<T>, rb_tree_tag,
    tree_order_statistics_node_update>;
template <typename T> using o_multiset = tree<pair<T,
    int>, null_type,
    less<pair<T, int>>, rb_tree_tag,
    tree_order_statistics_node_update>;
/*
o_set<int> st;
*st.find_by_order(0); // 0-th element
o_multiset<int> mst;
int timer = 0; // use a global/local timer for unique
    IDs
mst.insert({5, timer++});
mst.erase(mst.lower_bound({5, 0})); // Erases exactly
    ONE instance of 5
mst.order_of_key({5, 0}); // strictly less than 5
*/
// Faster hash
gp_hash_table<int, int> mp;
```

```
// Or
unordered_map<int, int> mp;
mp.reserve(n * 2);
mp.max_load_factor(0.7);
```

7.7 Usefull Things [9 lines] - c67addfa

```
C++:
#pragma GCC optimize("Ofast")
#pragma GCC target("avx,avx2,fma")
ios_base::sync_with_stdio(false), cin.tie(nullptr),
    cout.tie(nullptr);
freopen("input.txt", "r", stdin);
Python:
import sys
input = sys.stdin.readline
sys.stdout.write("-----")
```

7.8 VScode setup [7 lines] - 3e225a41

```
{
    "key": "f5",
    "command": "workbench.action.terminal.sendSequence",
    "args": {
        "text": "clear && g++
            ${fileBasenameNoExtension}.cpp -o
            ${fileBasenameNoExtension} &&
            ./${fileBasenameNoExtension} < in.txt >
            out.txt\n"
    }
} // need "files.autoSaveDelay": 100
```

7.9 stress [25 lines] - 4a84e7fd

```
#!/usr/bin/env bash
g++ -g "$1".cpp -DONPC -o "$1"
g++ -g "$2".cpp -DONPC -o "$2"
g++ -g "$3".cpp -DONPC -o "$3"
for ((testNum=0;testNum<$4;testNum++))
do
    ./$3 > stdinput
    ./$2 < stdinput > outSlow
    ./$1 < stdinput > outWrong
    H1=`md5sum outWrong`
    H2=`md5sum outSlow`
    if ![cmp -s "outWrong" "outSlow"]
    then
        echo "Error found!"
        echo "Input:"
        cat stdinput
        echo "Wrong Output:"
        cat outWrong
        echo "Slow Output:"
        cat outSlow
        exit
    fi
done
echo Passed $4 tests
# ./stress.sh wrong correct gen times
```

7.10 vimrc [12 lines] - 1f47305c

```
"install xclip, vim-gtk3
set nopl ai bs=2 hls ic is lbr ls=2 mouse=a nu ru sc scs
    smd so=3 sw=2 ts=2 rnu
filetype plugin indent on
syn on
map gA m'ggVG"+y''
inoremap {<CR> {<CR>}<Esc>ko
nnoremap = mzgg=G`z
vnoremap <C-k> :s/^s*\zs\\/\ /<CR>:nohl<CR>
```

```
nnoremap <C-k> :s/^s*\zs\\/\ /<CR>:nohl<CR>
vnoremap <C-l> :s/^s*\zs\\/\ /<CR>:nohl<CR>
nnoremap <C-l> :s/^s*\zs\\/\ /<CR>:nohl<CR>
autocmd FileType cpp map <F9> :w<CR> :!clear; g++
    --std=c++17 % -DONPC -o %:r && ./%:r<CR>
```

8 Number Theory

8.1 10-ary to m-ary [22 lines] - e6c26ef1

```
char a[16]={'0','1','2','3','4','5','6','7',
    '8','9','A','B','C','D','E','F'};
string tenToM(int n, int m){
    int temp=n;
    string result="";
    while (temp!=0){
        result=a[temp%m]+result;
        temp/=m;
    }
    return result;
}
// m-ary to 10-ary
string num = "0123456789ABCDE";
int mToTen(string n, int m){
    int multi=1;
    int result=0;
    for (int i=n.size()-1; i>=0; i--) {
        result += num.find(n[i])*multi;
        multi*=m;
    }
    return result;
}
```

8.2 Basis Vector [89 lines] - 409325f7

```
// T: Data type (int or long long), B: Max bits (31 for
    int, 62 for long long)
template<typename T = long long, int B = 62>
struct Basis {
    T basis[B];
    int sz, n; //sz: Number of independent basis vectors
        (rank)
    Basis() {
        memset(basis, 0, sizeof(basis));
        sz = 0; n = 0;
    }
    bool insert(T x) {
        n++;
        for (int i = B - 1; i >= 0; i--) {
            if (x >> i & 1) {
                if (!basis[i]) {
                    basis[i] = x;
                    sz++;
                    return true;
                }
                x ^= basis[i];
            }
        }
        return false;
    }
}
// Checks if there is any subset whose XOR sum
    equals exactly x
bool can(T x) {
    for (int i = B - 1; i >= 0; i--) {
        x = min(x, x ^ basis[i]);
    }
    return x == 0;
}
```

```
// Returns the maximum subset XOR sum
T max_xor(T x = 0) {
    for (int i = B - 1; i >= 0; i--) {
        x = max(x, x ^ basis[i]);
        //x = min(x, x ^ basis[i]); //For minimum
        subset XOR sum
    }
    return x;
}

// Finds the k-th DISTINCT subset XOR sum in
strictly increasing order (1-based, k=1 returns
0)
T kth(unsigned long long k) {
    if (k < 1 || k > (1ULL << sz)) return -1;
    T x = 0;
    unsigned long long cnt = (1ULL << sz);
    for (int i = B - 1; i >= 0; i--) {
        if (basis[i]) {
            cnt >>= 1;
            if (k > cnt) {
                if (!(x >> i & 1)) x ^= basis[i]; //
                Force the bit ON
                k -= cnt;
            } else {
                if (x >> i & 1) x ^= basis[i]; //
                Force the bit OFF
            }
        }
    }
    return x;
}

// Returns the number of DISTINCT subset XOR sums
strictly less than x
unsigned long long count_lt(T x) {
    if (x < 0) return 0;
    unsigned long long ans = 0, cnt = (1ULL << sz);
    T mask = 0;
    for (int i = B - 1; i >= 0; i--) {
        if (basis[i]) {
            cnt >>= 1;
            if (x >> i & 1) {
                ans += cnt;
                if (!(mask >> i & 1)) mask ^= basis[i];
            } else {
                if (mask >> i & 1) mask ^= basis[i];
            }
        } else {
            if ((x >> i & 1) != (mask >> i & 1)) {
                return (x >> i & 1) ? ans + cnt : ans;
            }
        }
    }
    return ans;
}
};
```

/* 1. SUBSET COUNTING MATH:

- Valid combinations that XOR to 0: $2^{(n - sz)}$
- Valid non-empty combinations XOR to 0: $(2^{(n - sz)} - 1)$

- If can(X) is true, ways to form X: $2^{(n - sz)}$

2. DISTINCT VS TOTAL SUBSETS:

- This struct works with DISTINCT XOR sums!
- There are exactly $(1ULL << sz)$ distinct XOR sums.
- Every distinct XOR sum is formed by exactly $2^{(n - sz)}$ identical subsets.
- If question asks for K-th out of ALL subsets:

Pass: $K = \text{ceil}(K / 2^{(n - sz)})$ into kth() */

8.3 Binary Exponentiation [9 lines] - 57b21c36

```
int power(long long n, long long k, int mod = 1e9+7) {
    int ans = 1 % mod; n %= mod; if (n < 0) n += mod;
    while (k) {
        if (k & 1) ans = (long long) ans * n % mod;
        n = (long long) n * n % mod;
        k >>= 1;
    }
    return ans;
}
```

8.4 CRT [21 lines] - 1d2ddbec

```
ll egcd(ll a, ll b, ll &x, ll &y){
    if(b == 0) { x=1, y=0; return a;}
    ll g = egcd(b, a%b, y, x);
    y -= a/b*x; return g;
}

ll crt(ll r1, ll m1, ll r2, ll m2){
    if(m1<m2) swap(r1, r2), swap(m1, m2);
    ll p, q, g = egcd(m1, m2, p, q);
    if((r2-r1)%g !=0) return -1; //no solution
    ll x = (r2-r1)%m2*p/m2*m1/g + r1;
    return x<0? x+m1*m2/g: x;
}

ll crt(vector<ll>& r, vector<ll>& m){
    ll x = r[0], M=m[0];
    for (int i = 1; i < r.size(); ++i){
        x = crt(x, M, r[i], m[i]);
        ll g = __gcd(M, m[i]);
        M = (M/g)*(m[i]/g);
    }
    return x;
}
```

8.5 Catalan Numbers [8 lines] - 1e8c9e0a

```
void catalan(int n) {
    int res = 1;
    cout << res << " ";
    for (int i = 1; i < n; i++) {
        res = (res * (4 * i - 2)) / (i + 1);
        cout << res << " ";
    }
}
```

8.6 Count 1s 0 to n [9 lines] - 9292bf04

```
int cntOnes(int n) {
    int cnt = 0;
    for (int i = 1; i <= n; i <= 1) {
        int x = (n + 1) / (i < 1);
        cnt += x * i;
        if ((n + 1) % i && n & i) cnt += (n + 1) % i;
    }
    return cnt;
}
```

8.7 Divisors multiple info [35 lines] - 1866b9dd

```
constexpr int N = 1000005;

void Divisors(int n) {
    int sum = 1, total = 1;
    int mnP = INT_MAX, mxP = INT_MIN, cntP = 0, totalP = 0;
    for (int i = 0; i < N && Prime[i] * Prime[i] <= n; i++) {
        if (n % Prime[i] == 0) {
            mnP = min(mnP, Prime[i]);

```

```
mxP = max(mnP, Prime[i]);
            int k = 0;
            cntP++;
            while (n % Prime[i] == 0) {
                k++;
                n /= Prime[i];
            }
            sum *= (k + 1); // NOD
            totalP += k;
            int s = 0, p = 1;
            while (k-- >= 0) {
                s += p;
                p *= Prime[i];
            };
            total *= s; // SOD
        }
    }
    if (n > 1) {
        cntP++, totalP++;
        sum *= 2;
        total *= (1 + n);
        mnP = min(mnP, n);
        mxP = max(mxP, n);
    }
    cout << mnP << " " << mxP << " " << cntP << " " <<
        totalP << " " << sum << " " <<
        total << "\n";
}
```

8.8 Extended GCD [8 lines] - cdfca975

```
// return {x,y} such that ax+by=gcd(a,b)
int exgcd(int a, int b, int &x, int &y) {
    if (b == 0) {
        x = 1; y = 0; return a; }
    int g = exgcd(b, a % b, y, x);
    y -= a / b * x;
    return g;
} // bezout's identity: a.x +b.y = gcd(a,b)
```

8.9 Find numbers in L to R divisible by all array elements [12 lines] - 833394ad

```
solve(int* arr, int N, int L, int R) {
    int LCM = arr[0];
    for (int i = 1; i < N; i++) {
        LCM = (LCM * arr[i]) / (__gcd(LCM, arr[i]));
    }
    if ((LCM < L && LCM * 2 > R) || LCM > R) {
        return;
    }
    int k = (L / LCM) * LCM;
    if (k < L) k = k + LCM;
    for (int i = k; i <= R; i = i + LCM) cout << i << ' ';
}
```

8.10 GaussElimination [39 lines] - fd4e4aaf

```
template<typename ld>
int gauss(vector<vector<ld>>& a, vector<ld>& ans) {
    const ld EPS = 1e-9;
    int n = a.size(); //number of equations
    int m = a[0].size() - 1; //number of variables
    vector<int> where(m, -1); //indicates which row
    contains the solution
    int row, col;
    for (col = 0, row = 0; col < m && row < n; ++col) {

```

```

int sel = row;///which row contains the maximum value/
for (int i = row + 1; i < n; i++)
    if (abs(a[i][col]) > abs(a[sel][col]))
        sel = i;
if (abs(a[sel][col]) < EPS) continue;///it's basically 0.
a[sel].swap(a[row]);///taking the max row up
where[col] = row;
ld t = a[row][col];
for (int i = col; i <= m; i++) a[row][i] /= t;
for (int i = 0; i < n; i++) {
    if (i != row) {
        ld c = a[i][col];
        for (int j = col; j <= m; j++)
            a[i][j] -= a[row][j] * c;
    }
}
row++;
}
ans.assign(m, 0);
for (int i = 0; i < m; i++)
    if (where[i] != -1)
        ans[i] = a[where[i]][m] / a[where[i]][i];
for (int i = 0; i < n; i++) {
    ld sum = 0;
    for (int j = 0; j < m; j++)
        sum += ans[j] * a[i][j];
    if (abs(sum - a[i][m]) > EPS) ///L.H.S!=R.H.S
        ans.clear();///No solution
}
return row;
}

```

8.11 Largest Power of n! [11 lines] - dc59263a

// Returns largest power of p that divides n!

```

int largestPower(int n, int p) {
    int res = 0;

    // Calculate res = n/p + n/(p^2) + n/(p^3) + ....
    while (n > 0) {
        n /= p;
        res += n;
    }
    return res;
}

```

8.12 Leap Year [13 lines] - 8ff2b7cb

```

bool isLeap(int n){
    if (n%100==0)
        if (n%400==0) return true;
        else return false;
    if (n%4==0) return true;
    else return false;
}
// Num of Leap year in between
int calNum(int year) {
    return (year / 4) - (year / 100) +
        (year / 400);
}
int leapNum(int l, int r) { return calNum(r) -
    calNum(--l); }

```

8.13 Logab [3 lines] - 1ababcba

```

int logab (int a, int b){
    return log2(a) / log2(b);
}

```

8.14 Matrix [105 lines] - 57e4b34b

```

template<typename T>
struct Matrix {
    T MOD = 1e9 + 7;///change if necessary
    T add(T a, T b) const {
        T res = a + b;
        if (res >= MOD) return res - MOD;
        return res;
    }
    T sub(T a, T b) const {
        T res = a - b;
        if (res < 0) return res + MOD;
        return res;
    }
    T mul(T a, T b) const {
        T res = a * b;
        if (res >= MOD) return res % MOD;
        return res;
    }
    int R, C;
    vector<vector<T>>mat;
    Matrix(int _R = 0, int _C = 0) {
        R = _R, C = _C;
        mat.resize(R);
        for (auto& v : mat) v.assign(C, 0);
    }
    void print() {
        for (int i = 0; i < R; i++)
            for (int j = 0; j < C; j++)
                cout << mat[i][j] << " \n"[j == C - 1];
    }
    void createIdentity() {
        for (int i = 0; i < R; i++)
            for (int j = 0; j < C; j++)
                mat[i][j] = (i == j);
    }
    Matrix operator+(const Matrix& o) const {
        Matrix res(R, C);
        for (int i = 0; i < R; i++)
            for (int j = 0; j < C; j++)
                res[i][j] = add(mat[i][j] + o.mat[i][j]);
    }
    Matrix operator-(const Matrix& o) const {
        Matrix res(R, C);
        for (int i = 0; i < R; i++)
            for (int j = 0; j < C; j++)
                res[i][j] = sub(mat[i][j] + o.mat[i][j]);
    }
    Matrix operator*(const Matrix& o) const {
        Matrix res(R, o.C);
        for (int i = 0; i < R; i++)
            for (int j = 0; j < o.C; j++)
                for (int k = 0; k < C; k++)
                    res.mat[i][j] = add(res.mat[i][j],
                        mul(mat[i][k], o.mat[k][j]));
        return res;
    }
    Matrix pow(long long x) {
        Matrix res(R, C);
        res.createIdentity();
        Matrix<T> o = *this;
        while (x) {
            if (x & 1) res = res * o;
            o = o * o;
            x >>= 1;
        }
    }
}

```

```

return res;
}
Matrix inverse()///Only square matrix && non-zero determinant
{
    Matrix res(R, R + R);
    for (int i = 0; i < R; i++) {
        for (int j = 0; j < R; j++)
            res.mat[i][j] = mat[i][j];
        res.mat[i][R + i] = 1;
    }
    for (int i = 0; i < R; i++) {
        ///find row 'r' with highest value at [r][i]
        int tr = i;
        for (int j = i + 1; j < R; j++)
            if (abs(res.mat[j][i]) > abs(res.mat[tr][i]))
                tr = j;
        ///swap the row
        res.mat[tr].swap(res.mat[i]);
        ///make 1 at [i][i]
        T val = res.mat[i][i];
        for (int j = 0; j < R + R; j++) res.mat[i][j] /= val;
        ///eliminate [r][i] from every row except i.
        for (int j = 0; j < R; j++) {
            if (j == i) continue;
            for (int k = R + R - 1; k >= i; k--) {
                res.mat[j][k] -= res.mat[i][k] * res.mat[j][i]
                    / res.mat[i][i];
            }
        }
    }
    Matrix ans(R, R);
    for (int i = 0; i < R; i++)
        for (int j = 0; j < R; j++)
            ans.mat[i][j] = res.mat[i][R + j];
    return ans;
}
};
// Matrix<long long> base(2, 2);
// base.mat[0][0] = 1LL; base.mat[0][1] = 1LL;
// base.mat[1][0] = 1LL; base.mat[1][1] = 0LL;
// Matrix<long long> result = base.pow(n - 1);
// cout << result.mat[0][0] << '\n'; // nth Fibonacci number

```

8.15 Miller-Rabin-Pollard-Rho [35 lines] - b1755b01

```

using u64 = uint64_t;
using u128 = __uint128_t;
u64 binpower(u64 base, u64 e, u64 mod) {
    u64 result = 1;
    base %= mod;
    while (e) {
        if (e & 1) result = (u128)result * base % mod;
        base = (u128)base * base % mod;
        e >>= 1;
    }
    return result;
}
bool check_composite(u64 n, u64 a, u64 d, int s) {
    u64 x = binpower(a, d, n);
    if (x == 1 || x == n - 1) return false;
    for (int r = 1; r < s; r++) {
        x = (u128)x * x % n;
    }
}

```

```

    if (x == n - 1) return false;
}
return true;
};
bool MillerRabin(u64 n, int iter = 5) { // returns true
    if n is probably prime, else returns false.
    if (n < 4) return n == 2 || n == 3;
    int s = 0;
    u64 d = n - 1;
    while ((d & 1) == 0) {
        d >>= 1;
        s++;
    }
    for (int i = 0; i < iter; i++) {
        int a = 2 + rand() % (n - 3);
        if (check_composite(n, a, d, s)) return false;
    }
    return true;
}

```

8.16 Mobius [11 lines] - b11a0bce

```

const int N = 11;
int mob[N];
void mobius() {
    mob[1] = 1;
    for (int i = 2; i < N; i++){
        mob[i]--;
        for (int j = i + i; j < N; j += i) {
            mob[j] -= mob[i];
        }
    }
}

```

8.17 Mod Inverse [5 lines] - 5a017bdc

```

int modInv(int a, int m) {
    int x, y; //if g==1 Inverse doesn't exist
    int g = gcdExt(a, m, x, y);
    return (x % m + m) % m;
}

```

8.18 Modular Operations [12 lines] - f875804f

```

int add(int x, int y) {
    x += y;
    if (x >= mod) x -= mod;
    if (x < 0) x += mod;
    return x;
}
int mul(int x, int y) {
    return (x%mod) * 1LL * (y%mod) % mod;
}
int divide(int x, int y) {
    return mul(x, power(y, mod - 2));
}

```

8.19 NOD of n! [13 lines] - 60fcf48f

```

ull factorialDivisors(ull n) {
    ull result = 1;
    for (int i = 0; i < allPrimes.size(); i++) {
        ull p = allPrimes[i];
        ull exp = 0;
        while (p <= n) {
            exp = exp + (n / p);
            p = p * allPrimes[i];
        }
        result = result * (exp + 1);
    }
    return result;
}

```

8.20 No of Digits in n! in base B [7 lines] - 888ae2de

```

ll NoOfDigitInNFactInBaseB(ll N, ll B) {
    ll i;
    double ans = 0;
    for (i = 1; i <= N; i++) ans += log(i);
    ans = ans / log(B), ans = ans + 1;
    return (ll)ans;
}

```

8.21 Principle of Inclusion Exclusion [21 lines] - 7692d42f

```

// count the numbers between 1 and n (inclusive) that
// are not divisible by any
// of the integers in the given array a
// is n - (div by one number - div by two number + div
// by three number - ...)
int PIE(int div[], int n, int num) {
    int sum = 0;
    for (int msk = 1; msk < (1 << n); ++msk) {
        int bit_cnt = 0;
        int cur_lcm = 1;
        for (int i = 0; i < n; ++i) {
            if (msk & (1 << i)) {
                ++bit_cnt;
                cur_lcm = LCM(cur_lcm, div[i]);
            }
        }
        int cur = num / cur_lcm;
        if (bit_cnt & 1) sum += cur;
        else sum -= cur;
    }
    return num - sum;
}

```

8.22 Print Calander of Any Year [44 lines] - e4845a4b

```

int dayNumber(int day, int month, int year) {
    static int t[] = {0, 3, 2, 5, 0, 3, 5, 1, 4, 6, 2, 4};
    year -= month < 3;
    return (year + year / 4 - year / 100 + year / 400 +
            t[month - 1] + day) % 7;
}
string getMonthName(int monthNumber) {
    string months[] = {"January", "February", "March",
                      "April", "May", "June", "July",
                      "August", "September", "October",
                      "November", "December"};
    return (months[monthNumber]);
}
int numberOfDays(int monthNumber, int year) {
    if (monthNumber == 1 && isLeapYear(year)) return 29;
    int monthDays[] = {31, 28, 31, 30, 31, 30, 31, 31,
                       30, 31, 30, 31};
    return (monthDays[monthNumber]);
}
void printCalendar(int year) {
    printf("Calendar - %d\n\n", year);
    int days;
    int current = dayNumber(1, 1, year);
    // i|-> Iterate through all the months
    // j|-> Iterate through all the days of
    the month - i for (int i = 0; i < 12; i++) {
        days = numberOfDays(i, year);
        cout << "      |" << getMonthName(i).c_str() <<
              " |" << endl;
    }
}

```

```

printf(" Sun Mon Tue Wed Thu Fri
      Sat\n");
int k;
for (k = 0; k < current; k++)
    printf("      ");
for (int j = 1; j <= days; j++) {
    printf("%4d", j);
    if (++k > 6) {
        k = 0;
        cout << endl;
    }
    if (k)
        cout << endl;
    cout <<
    "-----\n";
    current = k;
}
}

```

8.23 SOD, NOD Upto N [30 lines] - ad992d27

```

int SOD_upto_N(int N) { // sqrt(N)
    int res = 0;
    for (int i = 1; i <= N; i++) {
        int j = N / (N / i); // Last number with same
        quotient
        res += (N / i) * (i + j) * (j - i + 1) / 2;
        i = j;
    }
    return res;
}
int NOD_upto_N(ll N) { // sqrt(N)
    int res = 0;
    int u = sqrt(N);
    for (int i = 1; i <= u; i++) {
        res += (N / i) - i;
    }
    res = res * 2 + u;
    return res;
}
void NOD_per_number_upto_N(int n) { // n loglog(n)
    for (int i = 1; i <= n; i++) {
        for (int j = i; j <= n; j += i) {
            d[j]++;
            // d[j] += i // for sum of divisors
        }
    }
    for (int i = 1; i <= n; i++) {
        cout << d[i] << ' ';
    }
    return 0;
}

```

8.24 SPF [10 lines] - 764405a0

```

int spf[N];
void buildSpf() {
    for (int i = 2; i < N; i++) {
        spf[i] = i;
    }
    for (ll i = 2; 1LL * i * i < N; i++)
        if (spf[i] == i)
            for (ll j = i * i; j < N; j += i)
                if (spf[j] == j) spf[j] = i;
}

```

8.25 Segmented Sieve [17 lines] - 034da99c

```

void segmentedSieve(int L, int R) {
    bool isPrime[R - L + 1];
    for (int i = 0; i <= R - L + 1; i++) isPrime[i] =
        true;
    if (L == 1) isPrime[0] = false;
    for (int i = 0; primes[i] * primes[i] <= R; i++) {
        int curPrime = primes[i];
        int base = curPrime * curPrime;
        if (base < L) {
            base = ((L + curPrime - 1) / curPrime) * curPrime;
        }
        for (int j = base; j <= R; j += curPrime) isPrime[j
            - L] = false;
    }
    for (int i = 0; i <= R - L; i++) {
        if (isPrime[i] == true) cout << L + i << '\n';
    }
    cout << '\n';
}

```

8.26 Sieve Phi Mobius [13 lines] - 88190466

```

const int N = 5000005;
int phi[N];
unsigned long long phiSum[N];
void phiCalc() {
    for (int i = 1; i < N; i++) phi[i] = i;
    for (int i = 2; i < N; i++) {
        if (phi[i] == i) {
            for (int j = i; j < N; j += i) {
                phi[j] -= phi[j] / i;
            }
        }
        for (int i = 2; i < N; i++) {
            phiSum[i] = (unsigned long long)phi[i] * (unsigned
                long long)phi[i] + phiSum[i - 1];
        }
    }
}

```

8.27 Sieve upto 1e9 [71 lines] - a03ff5a3

```

vector<int> sieve(const int N, const int Q = 17, const
    int L = 1 << 15) {
    static const int rs[] = {1, 7, 11, 13, 17, 19, 23,
        29};
    struct P {
        P(int p) : p(p) {}
        int p; int pos[8];
    };
    auto approx_prime_count = [] (const int N) -> int {
        return N > 60184 ? N / (log(N) - 1.1)
            : max(1., N / (log(N) - 1.11)) + 1;
    };
    const int v = sqrt(N), vv = sqrt(v);
    vector<bool> isp(v + 1, true);
    for (int i = 2; i <= vv; ++i) if (isp[i]) {
        for (int j = i * i; j <= v; j += i) isp[j] = false;
    }
    const int rsize = approx_prime_count(N + 30);
    vector<int> primes = {2, 3, 5}; int psize = 3;
    primes.resize(rsize);

```

```

    vector<P> sprimes; size_t pbeg = 0;
    int prod = 1;
    for (int p = 7; p <= v; ++p) {
        if (!isp[p]) continue;
        if (p <= Q) prod *= p, ++pbeg, primes[psize++] = p;
        auto pp = P(p);
        for (int t = 0; t < 8; ++t) {

```

```

            int j = (p <= Q) ? p : p * p;
            while (j % 30 != rs[t]) j += p << 1;
            pp.pos[t] = j / 30;
        }
        sprimes.push_back(pp);
    }

    vector<unsigned char> pre(prod, 0xFF);
    for (size_t pi = 0; pi < pbeg; ++pi) {
        auto pp = sprimes[pi]; const int p = pp.p;
        for (int t = 0; t < 8; ++t) {
            const unsigned char m = ~(1 << t);
            for (int i = pp.pos[t]; i < prod; i += p) pre[i]
                &= m;
        }
    }
    const int block_size = (L + prod - 1) / prod * prod;
    vector<unsigned char> block(block_size); unsigned
        char* pblock = block.data();
    const int M = (N + 29) / 30;

    for (int beg = 0; beg < M; beg += block_size, pblock
        += block_size) {
        int end = min(M, beg + block_size);
        for (int i = beg; i < end; i += prod) {
            copy(pre.begin(), pre.end(), pblock + i);
        }
        if (beg == 0) pblock[0] &= 0xFE;
        for (size_t pi = pbeg; pi < sprimes.size(); ++pi) {
            auto& pp = sprimes[pi];
            const int p = pp.p;
            for (int t = 0; t < 8; ++t) {
                int i = pp.pos[t]; const unsigned char m = ~(1
                    << t);
                for (; i < end; i += p) pblock[i] &= m;
                pp.pos[t] = i;
            }
        }
        for (int i = beg; i < end; ++i) {
            for (int m = pblock[i]; m > 0; m &= m - 1) {
                primes[psize++] = i * 30 + rs[__builtin_ctz(m)];
            }
        }
    }
    assert(psize <= rsize);
    while (psize > 0 && primes[psize - 1] > N) --psize;
    primes.resize(psize);
    return primes;
}

```

8.28 Sieve [16 lines] - 8babdb35

```

const int N = 1e7 + 3;
vector<int> primes;
int notprime[N];

void sieve() {
    primes.push_back(2);
    for (int i = 4; i < N; i += 2)
        notprime[i] = true;
    for (ll i = 3; i < N; i += 2) {
        if (!notprime[i]) {
            primes.push_back(i);
            for (ll j = 1LL * i * i; j < N; j += 2 * i)
                notprime[j] = true;
        }
    }
}

```

8.29 String Mod [5 lines] - 15587fee

```

int mod(string& num, int a) {
    int res = 0;
    for (int i = 0; i < num.length(); i++) res = (res * 10
        + num[i] - '0') % a;
    return res;
}

```

8.30 nCr [39 lines] - 8a93b828

```

const int N = 1e6 + 5, mod = 1e9 + 7;
ll fact[N], ifact[N];

void preFact() {
    fact[0] = 1;
    for (ll i = 1; i < N; i++) {
        fact[i] = 1LL * fact[i - 1] * i % mod;
    }
    ifact[N - 1] = power(fact[N - 1], mod - 2);
    for (ll i = N - 2; i >= 0; i--) {
        ifact[i] = 1LL * ifact[i + 1] * (i + 1) % mod;
    }
}

ll nCr(int n, int r) {
    if (n < r || n < 0) return 0;
    return 1LL * fact[n] * ifact[r] % mod * ifact[n - r]
        % mod;
}

// more space less time
const int MOD = 1e9 + 7;
const int MAX = 1e7 + 10;
vector<int> fact(MAX), inv(MAX);
void factorial() {
    fact[0] = 1;
    for (int i = 1; i < MAX; i++)
        fact[i] = (i * fact[i - 1]) % MOD;
}
binaryExp(int a, int n, int M = MOD); //needs to
    implement
void inverse() {
    for (int i = 0; i < MAX; ++i)
        inv[i] = bigmod(fact[i], MOD - 2);
}

int nCr(int a, int b) {
    if (a < b or a < 0 or b < 0)
        return 0;
    int de = (inv[b] * inv[a - b]) % MOD;
    return (fact[a] * de) % MOD;
}

// nCr ends here
int ModInv(int a, int M) { return bigmod(a, M - 2, M); }

```

9 Some Algorithms**9.1 2D Prefix Sum** [2 lines] - fa2a0bef

```

pref[i][j] = a[i][j] + pref[i - 1][j] + pref[i][j - 1]
    - pref[i - 1][j - 1];
Sum of region = pref[row2][col2] - pref[row2][col1 - 1]
    - pref[row1 - 1][col2] + pref[row1 - 1][col1 - 1];

```

9.2 Big Integer [89 lines] - 88146b73

```
struct BigInteger {
    string str;
    // Constructor to initialize
    // BigInteger with a string
    BigInteger(string s) { str = s; }
    // Overload + operator to add
    // two BigInteger objects
    BigInteger operator+(const BigInteger& b) {
        string a = str, c = b.str;
        int alen = a.length(), clen = c.length();
        int n = max(alen, clen);
        if (alen > clen)
            c.insert(0, alen - clen, '0');
        else if (alen < clen)
            a.insert(0, clen - alen, '0');
        string res(n + 1, '0');
        int carry = 0;
        for (int i = n - 1; i >= 0; i--) {
            int digit = (a[i] - '0') + (c[i] - '0')
                + carry;
            carry = digit / 10;
            res[i + 1] = digit % 10 + '0';
        }
        if (carry == 1) {
            res[0] = '1';
            return BigInteger(res);
        } else
            return BigInteger(res.substr(1));
    }
    // Overload - operator to subtract
    // first check which number is greater and then
    // subtract
    BigInteger operator-(const BigInteger& b) {
        string a = str;
        string c = b.str;
        int alen = a.length(), clen = c.length();
        int n = max(alen, clen);
        if (alen > clen)
            c.insert(0, alen - clen, '0');
        else if (alen < clen)
            a.insert(0, clen - alen, '0');
        if (a < c) {
            swap(a, c);
            swap(alen, clen);
        }
        string res(n, '0');
        int carry = 0;
        for (int i = n - 1; i >= 0; i--) {
            int digit = (a[i] - '0') - (c[i] - '0') - carry;
            if (digit < 0)
                digit += 10, carry = 1;
            else
                carry = 0;
            res[i] = digit + '0';
        }
        // remove leading zeros
        int i = 0;
        while (i < n && res[i] == '0') i++;
        if (i == n) return BigInteger("0");
        return BigInteger(res.substr(i));
    }
    // Overload * operator to multiply
    // two BigInteger objects
    BigInteger operator*(const BigInteger& b) {
        string a = str, c = b.str;
```

```
        int alen = a.length(), clen = c.length();
        int n = alen + clen;
        string res(n, '0');
        for (int i = alen - 1; i >= 0; i--) {
            int carry = 0;
            for (int j = clen - 1; j >= 0; j--) {
                int digit = (a[i] - '0') *
                    (c[j] - '0') + (res[i + j + 1] - '0') + carry;
                carry = digit / 10;
                res[i + j + 1] = digit % 10 + '0';
            }
            res[i] += carry;
        }
        int i = 0;
        while (i < n && res[i] == '0') i++;
        if (i == n) return BigInteger("0");
        return BigInteger(res.substr(i));
    }
    // Overload << operator to output
    // BigInteger object
    friend ostream& operator<<(ostream& out, const
        BigInteger& b) {
        out << b.str;
        return out;
    }
};
```

9.3 Expression Parsing [85 lines] - 47499dbc

```
bool delim(char c) { return c == ' '; }
bool is_op(char c) { return c == '+' || c == '-' || c
    == '*' || c == '/'; }
bool is_unary(char c) { return c == '+' || c == '-'; }
int priority(char op) {
    if (op < 0) // unary operator
        return 3;
    if (op == '+' || op == '-') return 1;
    if (op == '*' || op == '/') return 2;
    return -1;
}
void process_op(stack<int>& st, char op) {
    if (op < 0) {
        int l = st.top();
        st.pop();
        switch (-op) {
            case '+':
                st.push(l);
                break;
            case '-':
                st.push(-l);
                break;
        }
    } else {
        int r = st.top();
        st.pop();
        int l = st.top();
        st.pop();
        switch (op) {
            case '+':
                st.push(l + r);
                break;
            case '-':
                st.push(l - r);
                break;
            case '*':
                st.push(l * r);
                break;
```

```
            case '/':
                st.push(l / r);
                break;
        }
    }
}
int evaluate(string& s) {
    stack<int> st;
    stack<char> op;
    bool may_be_unary = true;
    for (int i = 0; i < (int)s.size(); i++) {
        if (delim(s[i])) continue;
        if (s[i] == '(') {
            op.push('(');
            may_be_unary = true;
        } else if (s[i] == ')') {
            while (op.top() != '(') {
                process_op(st, op.top());
                op.pop();
            }
            op.pop();
            may_be_unary = false;
        } else if (is_op(s[i])) {
            char cur_op = s[i];
            if (may_be_unary && is_unary(cur_op)) cur_op =
                -cur_op;
            while (!op.empty() &&
                ((cur_op >= 0 && priority(op.top()) >=
                    priority(cur_op)) ||
                (cur_op < 0 && priority(op.top()) >
                    priority(cur_op)))) {
                process_op(st, op.top());
                op.pop();
            }
            op.push(cur_op);
            may_be_unary = true;
        } else {
            int number = 0;
            while (i < (int)s.size() && isalnum(s[i]))
                number = number * 10 + s[i++] - '0';
            --i;
            st.push(number);
            may_be_unary = false;
        }
    }
    while (!op.empty()) {
        process_op(st, op.top());
        op.pop();
    }
    return st.top();
}
```

9.4 Infix to Postfix [94 lines] - 5c5d4f41

```
bool delim(char c) { return c == ' '; }
bool is_op(char c) {
    return c == '+' || c == '-' || c == '*'
        || c == '/' || c == '^';
}
bool is_unary(char c) {
    return c == '+' || c == '-';
}
int priority(char op) {
    if (op < 0) return 3;
    if (op == '+' || op == '-') return 1;
    if (op == '*' || op == '/') return 2;
```

```

    if (op == '^') return 4;
    return -1;
}

void process_op(string& output, char op) {
    if (op < 0) {
        switch (-op) {
            case '+':
                output += "+ ";
                break;
            case '-':
                output += "- ";
                break;
        }
    }
    else {
        switch (op) {
            case '+':
                output += "+ ";
                break;
            case '-':
                output += "- ";
                break;
            case '*':
                output += "* ";
                break;
            case '/':
                output += "/ ";
                break;
            case '^':
                output += "^ ";
                break;
        }
    }
}

string InfixToPostFix(string& s) {
    string output;
    stack<char> op;
    bool may_be_unary = true;
    for (int i = 0; i < (int)s.size(); i++){
        if (delim(s[i]))
            continue;
        if (s[i] == '(') {
            op.push('(');
            may_be_unary = true;
        }
        else if (s[i] == ')') {
            while (op.top() != '(') {
                process_op(output, op.top());
                op.pop();
            }
            op.pop();
            may_be_unary = false;
        }
        else if (is_op(s[i])) {
            char cur_op = s[i];
            if (may_be_unary && is_unary(cur_op))
                cur_op = -cur_op;
            while (!op.empty() &&
                ((cur_op >= 0 && priority(op.top())
                 >= priority(cur_op)) ||
                 (cur_op < 0 && priority(op.top()) >
                  priority(cur_op)))) {
                process_op(output, op.top());
                op.pop();
            }
            op.push(cur_op);
        }
    }
}

```

```

        may_be_unary = true;
    }
    else {
        char number;
        while (i < (int)s.size() && isalnum(s[i]))
            number = s[i++];
        --i;
        output.push_back(number);
        output.push_back(' ');
        may_be_unary = false;
    }
}

while (!op.empty()) {
    process_op(output, op.top());
    op.pop();
}

return output;
}

```

9.5 Kadanes [9 lines] - 6304cec2

```

// return maximum subarray sum.
int kadanes(int arr[], int n) {
    int maxsum = arr[0], curr_sum = arr[0];
    for (int i = 1; i < n; i++) {
        curr_sum = max(arr[i], curr_sum + arr[i]);
        maxsum = max(maxsum, curr_sum);
    }
    return maxsum;
}

```

9.6 Monotonic Stack (next greater) [7 lines] - 96018665

```

for (int i = n - 1; i >= 0; i--) {
    while (!stk.empty() && v[i] >= v[stk.top()])
        stk.pop();
    ind[i] = stk.empty() ? -1 : stk.top();
    stk.push(i);
}

// 3 1 5 4 10
// 2 2 4 4 -1

```

9.7 Spirally Traverse [25 lines] - 7ebd7ad5

```

vector<int> spirallyTraverse(vector<vector<int>>& mat) {
    int m = mat.size();
    int n = mat[0].size();
    vector<int> res;
    vector<vector<bool>> vis(m, vector<bool>(n, false));
    vector<int> dr = {0, 1, 0, -1};
    vector<int> dc = {1, 0, -1, 0};
    int r = 0, c = 0;
    int idx = 0;
    for (int i = 0; i < m * n; ++i) {
        res.push_back(mat[r][c]);
        vis[r][c] = true;
        int newR = r + dr[idx];
        int newC = c + dc[idx];
        if (0 <= newR && newR < m && 0 <= newC && newC < n
            && !vis[newR][newC]) {
            r = newR;
            c = newC;
        }
        else {
            idx = (idx + 1) % 4;
            r += dr[idx];
            c += dc[idx];
        }
    }
    return res;
}

```

9.8 Ternary Search [10 lines] - 20b1a65d

```

double ternary_search(double l, double r) {
    double eps = 1e-9; // error limit
    while (r - l > eps) {
        double m1 = l + (r - l) / 3, m2 = r - (r - l) / 3;
        double f1 = f(m1), f2 = f(m2); // evaluates the
            function at m1, m2
        if (f1 < f2) l = m1;
        else r = m2;
    }
    return f(l); // return the maximum of f(x) in [l, r]
}

```

10 String

10.1 AhoCorasick [55 lines] - 53423257

```

struct AhoCorasick {
    struct Node {
        int nxt[26]{};
        int fail = 0, term = 0, cnt = 0, id = -1;
    };
    vector<Node> t;
    AhoCorasick() : t(1) {} // Root is at index 0
    void insert(const string& s, int idx) {
        int u = 0;
        for (char c : s) {
            int v = c - 'a';
            if (!t[u].nxt[v]) {
                t[u].nxt[v] = t.size();
                t.emplace_back();
            }
            u = t[u].nxt[v];
        }
        t[u].cnt++;
        t[u].id = idx;
    }

    void build() {
        queue<int> q;
        for (int i = 0; i < 26; i++) {
            if (t[0].nxt[i]) q.push(t[0].nxt[i]);
        }
        while (!q.empty()) {
            int u = q.front(); q.pop();
            t[u].cnt += t[t[u].fail].cnt;
            t[u].term = (t[t[u].fail].id != -1) ?
                t[t[u].fail].term;
            for (int i = 0; i < 26; i++) {
                if (t[u].nxt[i]) {
                    t[t[u].nxt[i]].fail =
                        t[t[u].fail].nxt[i];
                    q.push(t[u].nxt[i]);
                }
                else {
                    t[u].nxt[i] = t[t[u].fail].nxt[i];
                }
            }
        }
    }

    long long matches(const string& txt) {
        long long matches = 0;
        int u = 0;
        for (int i = 0; i < txt.size(); i++) {
            u = t[u].nxt[txt[i] - 'a'];
            matches += t[u].cnt;
            int cur = u;
            if (t[cur].id == -1) cur = t[cur].term;
        }
    }
}

```

```

    while(cur>0){
        //exact match
        cur = t[cur].term;
    }
    return matches;
}
};

10.2 Hashing [44 lines] - 856b95a5
const int N = 2e6 + 9;
const int M1 = 1e9 + 7, M2 = 1e9 + 9, B1 = 137, B2 = 277;
pair<int, int> pw[N];

void init_hash() {
    pw[0] = {1, 1};
    for (int i = 1; i < N; i++) {
        pw[i].first = 1LL * pw[i - 1].first * B1 % M1;
        pw[i].second = 1LL * pw[i - 1].second * B2 % M2;
    }
}

struct Hash {
    string s;
    vector<pair<int, int>> hs;
    Hash(const string& _s) : s(_s) {
        hs.assign(s.size() + 1, {0, 0});
        for (int i = 0; i < s.size(); i++) {
            hs[i + 1].first = (1LL * hs[i].first * B1 + s[i]) % M1;
            hs[i + 1].second = (1LL * hs[i].second * B2 + s[i]) % M2;
        }
    }
    pair<int, int> get(int l, int r) {
        int h1 = (hs[r + 1].first - 1LL * hs[l].first * pw[r - l + 1].first % M1 + M1) % M1;
        int h2 = (hs[r + 1].second - 1LL * hs[l].second * pw[r - l + 1].second % M2 + M2) % M2;
        return {h1, h2};
    }
    int lcp(int i1, int j1, int i2, int j2) {
        int l = 1, r = min(j1 - i1 + 1, j2 - i2 + 1), ans = 0;
        while (l <= r) {
            int mid = (l + r) / 2;
            if (get(i1, i1 + mid - 1) == get(i2, i2 + mid - 1)) ans = mid, l = mid + 1;
            else r = mid - 1;
        }
        return ans;
    }
    int compare(int i1, int j1, int i2, int j2) {
        int l = lcp(i1, j1, i2, j2);
        int len1 = j1 - i1 + 1, len2 = j2 - i2 + 1;
        if (l == len1 && l == len2) return 0;
        if (l == len1) return -1;
        if (l == len2) return 1;
        return s[i1 + l] < s[i2 + l] ? -1 : 1;
    }
};

```

10.3 KMP [22 lines] - e87ecc3e

```

struct KMP {
    string s; //must declare s before n
    int n; vector<int> pi;

```

```

    KMP(const string& _s) : s(_s), n(s.size()), pi(n, 0) {
        for (int i = 1, j = 0; i < n; i++) {
            while (j > 0 && s[i] != s[j]) j = pi[j - 1];
            if (s[i] == s[j]) j++;
            pi[i] = j;
        }
    }
    vector<vector<int>> build_nxt(int A = 26, char base = 'a') {
        vector<vector<int>> nxt(n + 1, vector<int>(A, 0));
        for (int i = 0; i <= n; i++) for (int c = 0; c < A; c++)
            if (i < n && s[i] - base == c) nxt[i][c] = i + 1;
            else if (i > 0) nxt[i][c] = nxt[pi[i - 1]][c];
        return nxt;
    }
};

// MATCH: KMP k(pat + "#" + txt); int m = pat.size();
// for(int i = m+1; i < k.n; i++) if(k.pi[i] == m) { /*
// Match starts at txt[i - 2*m] */ }
// STR DP: auto nxt = KMP(pat).build_nxt(); // states: 0
// to m. (st == m means fully matched)
// dp[idx+1][nxt[st][c]] += dp[idx][st]; // If avoiding
// pat: ensure nxt[st][c] != m

10.4 Suffix Array [134 lines] - 595a0dc9
array<vector<int>, 2> get_sa(string& s, int lim=128) {
    // for integer, just change string to vector<int>
    // and minimum value of vector must be >= 1
    int n = s.size() + 1, k = 0, a, b;
    vector<int> x(begin(s), end(s)+1), y(n), sa(n), lcp(n), ws(max(n, lim)), rank(n);
    x.back() = 0;
    iota(begin(sa), end(sa), 0);
    for (int j = 0, p = 0; p < n; j = max(1, j * 2), lim = p) {
        p = j, iota(begin(y), end(y), n - j);
        for (int i = 0; i < n; ++i) {
            if (sa[i] >= j) y[p++] = sa[i] - j;
        }
        fill(begin(ws), end(ws), 0);
        for (int i = 0; i < n; ++i) ws[x[i]]++;
        for (int i = 1; i < lim; ++i) ws[i] += ws[i - 1];
        for (int i = n; i--;) sa[--ws[x[y[i]]]] = y[i];
        swap(x, y), p = 1, x[sa[0]] = 0;
        for (int i = 1; i < n; ++i) {
            a = sa[i - 1], b = sa[i], x[b] = (y[a] == y[b] && y[a + j] == y[b + j]) ? p - 1 : p++;
        }
    }
    for (int i = 1; i < n; ++i) rank[sa[i]] = i;
    for (int i = 0, j; i < n - 1; lcp[rank[i++]] = k) {
        for (k && k--, j = sa[rank[i] - 1]; s[i + k] == s[j + k]; k++);
    }
    sa.erase(sa.begin()), lcp.erase(lcp.begin());
    return {sa, lcp};
}

## Comparing Two Substrings
auto compare = [&] (int l1, int r1, int l2, int r2) {

```

```

    int len1 = r1 - l1 + 1, len2 = r2 - l2 + 1;
    int len = min(len1, len2);
    int i = pos[l1], j = pos[l2], x;
    if (l1 != l2) x = st.query(i, j);
    else x = len;
    if (x >= len) {
        if (len1 == len2) return 0;
        if (len1 < len2) return -1;
        return 1;
    }
    if (s[l1 + x] < s[l2 + x]) return -1;
    return 1;
};

## Kth Unique Substring
auto kth = [&] (ll k) {
    int i = 0;
    while (i + 1 < n and k > n - sa[i] - lcp[i]) {
        k -= n - sa[i] - lcp[i];
        i++;
    }
    k = min(k, 0ll + n - sa[i] - lcp[i]);
    array<int, 2> ret = {sa[i], k + lcp[i]};
    return ret;
};

## Kth Unique Substring (Multiple Queries)
vector<ll> pref(n + 1);
for (int i = 0; i < n; ++i) {
    pref[i + 1] = pref[i] + (n - sa[i] - lcp[i]);
}
auto kth = [&] (ll k) {
    int i = lower_bound(pref.begin(), pref.end(), k) - pref.begin();
    i--;
    k -= pref[i];
    return array<int, 2>{sa[i], k + lcp[i]};
};

auto [i, len] = kth(k);
cout << s.substr(i, len) << "\n";
## Kth Substring (not necessarily unique)
ll k; cin >> k;
auto ok = [&] (ll x) {
    auto [i, len] = kth(x);
    ll tot = 0;
    for (int j = 0; j < pos[i]; ++j) {
        tot += n - sa[j];
    }
    tot += len;
    int mn = len;
    for (int j = pos[i] + 1; j < n; ++j) {
        mn = min(mn, lcp[j]);
        tot += mn;
    }
    return tot >= k;
};

ll lo = 1, hi = 1;
while (!ok(hi)) hi = hi << 1;
while (lo <= hi) {
    ll mid = (lo + hi) >> 1;
    if (ok(mid)) hi = mid - 1;
    else lo = mid + 1;
}

## Several Consecutive Identical Substrings
auto [sa, lcp] = get_sa(s);
Sparse st(sa, lcp);
auto rev_s = s;

```

```
reverse(rev_s.begin(), rev_s.end());
auto [rev_sa, rev_lcp] = get_sa(rev_s);
Sparse rev_st(rev_sa, rev_lcp);
int k = 1;
for (int len = 1; len <= n / 2; ++len) {
    for (int i = 0; i + len < n; i += len) {
        int er = st.get_lcp(i, i + len);
        int el = 0;
        if (i) el = rev_st.get_lcp(n - i, n - i - len); //
        // rev lcp of (i - 1, i + len - 1)
        k = max(k, 1 + (er + el) / len);
    }
}
## Sparse Table for LCP Array
struct Sparse {
    int n;
    vector<array<int, K>> st;
    vector<int> pos;
    Sparse (vector<int> sa, vector<int> &lcp) {
        n = sa.size();
        pos.resize(n);
        for (int i = 0; i < n; ++i) {
            pos[sa[i]] = i;
        }
        st.resize(n);
        for (int i = 0; i < n; ++i) st[i][0] = lcp[i];
        for (int k = 0; k + 1 < K; ++k)
            for (int i = 0; i + (2 << k) <= n; ++i)
                st[i][k + 1] = min(st[i][k], st[i + (1 << k)][k]);
    }

    int get_lcp(int l, int r) {
        l = pos[l];
        r = pos[r];
        if (l > r) swap(l, r);
        assert(l < r);
        l++;
        int k = lg[r - l + 1];
        return min(st[l][k], st[r - (1 << k) + 1][k]);
    }
};
```

10.5 Suffix Automaton [156 lines] - 835183e3

```
struct SA {
    // For large alphabets (e.g., integers), change `int`
    next[26]` to `map<int, int> next`
    // If using map, change `!t[p].next[c]` to
    `!t[p].next.count(c)` everywhere!
    struct Node {
        int nxt[26]{}; lnk = -1, len = 0, focc = -1;
        long long cnt = 0, dp = -1;
    };

    vector<Node> t;
    int lst = 0;
    vector<int> ord;
    SA(int n = 0) {
        t.clear(); ord.clear();
        t.reserve(2 * n + 1);
        t.emplace_back();
        lst = 0;

        void add(char ch, int idx = -1) {
            int c = ch - 'a', p = lst;
```

```
            if (t[p].nxt[c]) {
                int q = t[p].nxt[c];
                if (t[p].len + 1 == t[q].len) {
                    lst = q;
                } else {
                    int clone = t.size();
                    t.push_back(t[q]);
                    t[clone].len = t[p].len + 1;
                    t[clone].cnt = 0;
                    while (p != -1 && t[p].nxt[c] == q) {
                        t[p].nxt[c] = clone; p = t[p].lnk;
                    }
                    t[q].lnk = clone;
                    lst = clone;
                }
            }
            t[lst].cnt++;
            return;
        }

        int cur = t.size();
        t.emplace_back();
        t[cur].len = t[p].len + 1;
        t[cur].focc = idx;
        t[cur].cnt = 1; // ONLY pure prefix nodes get a
        ! (Set to 0 if only unique counts matter in
        Gen. SA)
        lst = cur;

        while (p != -1 && !t[p].nxt[c]) {
            t[p].nxt[c] = cur; p = t[p].lnk;
        }
        if (p == -1) { t[cur].lnk = 0; return; }

        int q = t[p].nxt[c];
        if (t[p].len + 1 == t[q].len) { t[cur].lnk = q;
            return; }

        int clone = t.size();
        t.push_back(t[q]);
        t[clone].len = t[p].len + 1;
        t[clone].cnt = 0; // Cloned nodes get 0!

        while (p != -1 && t[p].nxt[c] == q) {
            t[p].nxt[c] = clone; p = t[p].lnk;
        }
        t[q].lnk = t[cur].lnk = clone;
    }

    void build(const string& s) {
        for (int i = 0; i < s.size(); i++) add(s[i], i);
    }

    // Topo Sort + Suffix link Tree DP (Calculates exact
    frequency of each state)
    void count() {
        int n = t.size(); ord.resize(n);
        vector<int> c(n + 1, 0);
        for (int i = 0; i < n; i++) c[t[i].len]++;
        for (int i = 1; i <= n; i++) c[i] += c[i - 1];
        for (int i = 0; i < n; i++) ord[--c[t[i].len]]
            = i;
        for (int i = n - 1; i > 0; i--)
            t[t[ord[i]].lnk].cnt += t[ord[i]].cnt;
    }

    void reset_dp() { for (auto& node : t) node.dp =
        -1; }
```

```
    // DAG DP (Calculates valid paths for K-th
    substring, or total substrings)
    // MAKE SURE to call count() first if dist ==
    false!
    long long calc_dp(int u, bool dist) {
        if (t[u].dp != -1) return t[u].dp;
        t[u].dp = dist ? 1 : t[u].cnt; // Base case for
        custom DP logic
        for (int i = 0; i < 26; i++)
            if (t[u].nxt[i]) t[u].dp +=
                calc_dp(t[u].nxt[i], dist);
        return t[u].dp;
    }

    // Find lexicographically K-th Substring
    string get_kth(long long k, bool dist) {
        if (t[0].dp == -1) calc_dp(0, dist);
        if (k > t[0].dp - (dist ? 1 : t[0].cnt)) return
            "-1";
        string ans = "";
        kth(0, k, ans, dist);
        return ans;
    }

    void kth(int u, long long& k, string& ans, bool
        dist) {
        if (k <= 0) return;
        for (int i = 0; i < 26; i++) {
            int v = t[u].nxt[i];
            if (!v) continue;
            if (k > t[v].dp) { k -= t[v].dp; continue; }
            ans += (char)('a' + i);
            k -= (dist ? 1 : t[v].cnt);
            kth(v, k, ans, dist);
            return;
        }
    }

};

/* --- NODE VARIABLES (BUCKETS) ---
    len : Max string len in bucket (Min len = t[lnk].len
        + 1)
    focc : 0-based index of FIRST occurrence's end
        position (first in endpos)
    cnt : Exact Occ (VALID AFTER calling count()), for
        distinct occ use 1
    lnk : Suffix link (longest suffix in a different
        bucket)
    nxt : DAWG transitions (edges). dp : DAG DP
        memoization state.
    lst : holds the Node ID that represents the entire
        string you have built so far (prefix)
    Reconstruct longest string (at u): s.substr(t[u].focc
        - t[u].len + 1, t[u].len)

    --- 1. BUILD & GENERALIZED SA (GSA) ---
    SA sa(s.size()); sa.build(s);
    For GSA: for(auto& str: strings) { sa.lst = 0;
        sa.build(str); }

    --- 2. COUNTING & K-TH SUBSTRING (Always call
        sa.count() first!) ---
    Distinct Subs : sa.calc_dp(0, 1) - 1 // -1
        excludes empty string
    Total Subs : sa.calc_dp(0, 0) - t[0].cnt
    K-th Distinct : sa.get_kth(K, 1)
```

K-th Total : `sa.get_kth(K, 0)`

```
--- 3. PATTERN MATCHING (Is Substr? / Occurrences /
    First Index) ---
int u = 0; bool ok = true; // Call sa.count() first if
    querying `cnt`
for(char c : p) if(!(u = sa.t[u].nxt[c-'a'])) { ok =
    false; break; }
// If ok == true:
// - Occurrences = sa.t[u].cnt
// - First Occ Index (0-based) = sa.t[u].focc -
    p.size() + 1
```

```
--- 4. LONGEST COMMON SUBSTRING (LCS of s1 & s2) ---
SA sa(s1.size()); sa.build(s1);
int u = 0, l = 0, max_l = 0, best_pos = 0;
for(int i = 0; i < s2.size(); i++) {
    int c = s2[i] - 'a';
    while(u != -1 && !sa.t[u].nxt[c]) { u =
        sa.t[u].lnk; l = u == -1 ? 0 : sa.t[u].len; }
    if(u != -1) { u = sa.t[u].nxt[c]; if(++l > max_l)
        { max_l = l; best_pos = i; } }
    else { u = 0; l = 0; }
} // LCS = s2.substr(best_pos - max_l + 1, max_l)
```

```
--- 5. SMALLEST CYCLIC SHIFT (Lexicographically
    Smallest Rotation) ---
SA sa(2 * s.size()); sa.build(s + s);
int u = 0; string ans = "";
for(int i = 0; i < s.size(); i++) {
    for(int c = 0; c < 26; c++) if(sa.t[u].nxt[c])
        { ans += (char)(c + 'a'); u = sa.t[u].nxt[c];
            break; }
}
```

* }
LCP of suffixes translates to LCS of prefixes in the
reverse string
*/

10.6 Trie [43 lines] - d276b245

```
struct Trie {
    static const int K = 26;
    static const char BASE = 'a';
    struct Node {
        int nxt[K]{}; // {} zero-initializes the array
        int eow = 0, cnt = 0;
    };
    vector<Node> t;
    Trie() : t(1) {} // Initializes with root at index 0

    //d = 1 for insert, d = -1 for erase
    void insert(const string& s, int d = 1) {
        int u = 0;
        t[u].cnt += d;
        for (char c : s) {
            int v = c - BASE;
            if (!t[u].nxt[v]) {
                t[u].nxt[v] = t.size();
                t.emplace_back();
            }
            u = t[u].nxt[v];
            t[u].cnt += d;
        }
        t[u].eow += d;
    }
    int search(const string& s) {
        int u = 0;
```

```
    for (char c : s) {
        int v = c - BASE;
        if (!t[u].nxt[v]) return 0;
        u = t[u].nxt[v];
    }
    return t[u].eow;
}
int count_prefix(const string& s) {
    int u = 0;
    for (char c : s) {
        int v = c - BASE;
        if (!t[u].nxt[v]) return 0;
        u = t[u].nxt[v];
    }
    return t[u].cnt;
}
};
```

11 Random

11.1 Combinatorics

$$\sum_{k=0}^n \binom{n-k}{k} = Fib_{n+1}$$

$$\binom{n}{k} + \binom{n}{k+1} = \binom{n+1}{k+1}$$

$$k \binom{n}{k} = n \binom{n-1}{k-1}$$


• Number of binary sequences of length n such that no two 0's are adjacent = Fib_{n+1}

• Number of non-negative solution of $x_1 + x_2 + x_3 + \dots + x_k = n$ is $\binom{n+k-1}{n}$

11.1.1 Catalan Number

• **Reflection Principle** ($n = 3$)

Count paths $(0, 0) \rightarrow (n, n)$ below $y = x$.



– **Bad Path:** Touches $y = x + 1$.

– **Reflection:** Flip path after first touch.

– **Mapping:** Bad path to $(n, n) \iff$ Path to $(n-1, n+1)$.

$$C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$C_0 = 1, C_1 = 1, C_n = \sum_{k=0}^{n-1} C_k C_{n-1-k}$$

• 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786

• Number of correct bracket sequences consisting of n opening brackets.

• Number of ways to completely parenthesize $n+1$ factors.

• The number of triangulations of a convex polygon with $+2$ sides (i.e. the number of partitions of polygon into disjoint triangles by using the diagonals).

• The number of ways to connect the $2n$ points on a circle to form n disjoint i.e. non-intersecting chords.

• The number of monotonic lattice paths from point $(0,0)$ to point (n,n) in a square lattice of size $n \times n$, which do not pass above the main diagonal

• Number of permutation of length n that can be stack sorted.

• The number of non-crossing partitions of a set of n elements.

• The number of rooted full binary tree with $n+1$ leaves.

• The number of Dyck words of length $2n$. A string consisting of n X's and n Y's such that no string prefix has more Y's than X's.

• Number of permutation of length n with no three-term increasing subsequence.

• Number of ways to tile a staircase shape of height n with n rectangle.

• $C_n^k = \frac{k+1}{n+1} \binom{2n-k}{n-k}$ denote the number of bracket sequences of size $2n$ with the first k elements being (.

$$N(n, k) = \frac{1}{n} \binom{n}{k} \binom{n}{k-1}$$

• The number of expressions containing n pairs of correct parentheses, which contain k distinct nestings.
 $N(4, 2) = 6$
 $()((()))$, $((())())$, $((())())$, $((())())$, $((())())$, $((())())$

• The number of paths from $(0,0)$ to $(2n, 0)$ with steps only northeast and southeast, not staying below the x -axis with k peaks. And sum of all number of peaks is Catalan number.

11.1.2 Stirling Number of the First Kind

- Count permutation according to their number of cycles.
- $S(n, k)$ count the number of permutation of n elements with k disjoint cycles.
- $S(n, k) = (n-1) \times S(n-1, k) + S(n-1, k-1)$, $S(0, 0) = 1$, $S(n, 0) = S(0, n) = 0$
- $S(n, 1) = (n-1)!$
- $S(n, n-1) = \binom{n}{2}$
- $\sum_{k=0}^n S(n, k) = n!$

11.1.3 Stirling Numbers of the Second Kind

- Number of ways to partition a set of n objects into k non-empty subsets.
- $S(n, k) = k * S(n-1, k) + S(n-1, k-1)$, $S(0, 0) = 1$, $S(n, 0) = S(0, n) = 0$
- $S(n, 2) = 2^{n-1} - 1$
- $S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$
- $S(n, k) * k! =$ number of ways to color n nodes using colors from 1 to k such that each color is used at least once.

11.1.4 Bell Number

- Counts the number of partitions of a set.
- $B_{n+1} = \sum_{k=0}^n \binom{n}{k} * B_k$
- $B_n = \sum_{k=0}^n S(n, k)$, where S is Stirling number of second kind.
- The number of multiplicative partitions of a square free number with i prime factors is the i -th Bell number.
- $B(p^m + n) \equiv mB(n) + B(n+1) \pmod{p}$
- If a deck is shuffled by removing and reinserting the top card n times, there are n^n possible shuffles. The number of shuffles that return the deck to its original order is B_n , so the probability of returning to the original order is B_n/n^n .

11.1.5 Lucas Theorem

- If p is prime then $\binom{p^a}{k} \equiv 0 \pmod{p}$
- For non-negative integers m and n and a prime p :

$$\binom{m}{n} = \prod_{i=0}^k \binom{m_i}{n_i} \pmod{p}$$
 where $m = m_k p^k + m_{k-1} p^{k-1} + \dots + m_1 p + m_0$ $n = n_k p^k + n_{k-1} p^{k-1} + \dots + n_1 p + n_0$ are the base p expansion.
- Let n and k be non-negative integers, and let p be a prime. Let the base- p expansions of n and k be:

$$n = n_m p^m + n_{m-1} p^{m-1} + \dots + n_1 p^1 + n_0 p^0$$

$$k = k_m p^m + k_{m-1} p^{m-1} + \dots + k_1 p^1 + k_0 p^0$$

where $0 \leq n_i < p$ and $0 \leq k_i < p$ are the base- p digits of n and k , respectively.

The theorem states:

$$\binom{n}{k} \equiv \prod_{i=0}^m \binom{n_i}{k_i} \pmod{p}$$

Note: The individual terms $\binom{n_i}{k_i}$ are calculated using standard arithmetic, and the final product is taken modulo p .

- Example:** $\binom{10}{2} \pmod{2}$

$$n = 10_{10} = 1010_2$$

$$k = 2_{10} = 0010_2$$

Applying Lucas's Theorem:

$$\begin{aligned} \binom{10}{2} &\equiv \binom{1}{0} \cdot \binom{0}{0} \cdot \binom{1}{1} \cdot \binom{0}{0} \pmod{2} \\ &\equiv 1 \cdot 1 \cdot 1 \cdot 1 \equiv 1 \pmod{2} \end{aligned}$$

Bitwise check: $1010_2 \& 0010_2 = 0010_2$. Since $2 = 2$, the result is 1.

$$\binom{n}{k} \pmod{2} = \begin{cases} 1 & \text{if } (n \& k) = k \\ 0 & \text{otherwise} \end{cases}$$

11.1.6 Derangement

- A permutation such that no element appears in its original position.
- $d(n) = (n-1) * (d(n-1) + d(n-2))$, $d(0) = 1$, $d(1) = 0$
- $d(n) = nd(n-1) + (-1)^n = \lfloor \frac{n!}{e} \rfloor$, $n \geq 1$

11.1.7 Burnside Lemma

Given a group G of symmetries and a set X , the number of elements of X up to symmetry equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|$$

where X^g are the elements fixed by g ($g.x = x$) If $f(n)$ counts "configurations" of some sort of length n , we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(\gcd(n, k)) = \frac{1}{n} \sum_{k|n} f(k) \phi(n/k)$$

11.1.8 Eulerian Number

- $E(n, k)$ is the number of permutations of the numbers 1 to n in which exactly k elements are greater than the previous element.
- $E(n, k) = (n-k)E(n-1, k-1) + (k+1)E(n-1, k)$, $E(n, 0) = E(n, n-1) = 1$
- $E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k+1-j)^n$
- $E(n, k) = E(n, n-1-k)$
- $E(0, k) = [k=0]$
- $E(n, 1) = 2^n - n - 1$

11.2 Number Theory

11.2.1 Mobius Function and Inversion

- define $\mu(n)$ as the sum of the primitive n th roots of unity depending on the factorization of n into prime factors:

$$\mu(x) = \begin{cases} 0 & \text{n is not square free} \\ 1 & \text{n has even number of prime factors} \\ -1 & \text{n has odd number of prime factors} \end{cases}$$

- Mobius Inversion:

$$g(n) = \sum_{d|n} f(d) \leftrightarrow f(n) = \sum_{d|n} \mu(d) g(n/d)$$

- $\sum_{d|n} \mu(d) = [n=1]$
- $\phi(n) = \sum_{d|n} \mu(d) \cdot \frac{n}{d} = n \sum_{d|n} \frac{\mu(d)}{d} = \sum_{d|n} d \cdot \mu\left(\frac{n}{d}\right)$
- $a|b \rightarrow \phi(a)|\phi(b)$

- $\phi(mn) = \phi(m) \cdot \phi(n) \cdot \frac{d}{\phi(d)}$ where $d = \gcd(m, n)$
- $\phi(n^m) = n^{m-1} \phi(n)$
- $\sum_{i=1}^n [\gcd(i, n) = k] = \phi\left(\frac{n}{k}\right)$
- $\sum_{i=1}^n \gcd(i, n) = \sum_{d|n} d \cdot \phi\left(\frac{n}{d}\right)$
- $\sum_{i=1}^n \frac{1}{\gcd(i, n)} = \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{1}{n} \sum_{d|n} d \cdot \phi(d)$
- $\sum_{i=1}^n \frac{i}{\gcd(i, n)} = \frac{n}{2} \cdot \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{n}{2} \cdot \frac{1}{n} \sum_{d|n} d \cdot \phi(d)$
- $\sum_{i=1}^n \frac{n}{\gcd(i, n)} = 2 \cdot \sum_{i=1}^n \frac{i}{\gcd(i, n)} - 1$

11.2.2 GCD and LCM

- $\gcd(a, b) = \gcd(b, a \bmod b)$
- If $a|b \cdot c$, and $\gcd(a, b) = d$, then $(a/d)|c$.
- GCD is a multiplicative function.
- $\gcd(a, \text{lcm}(b, c)) = \text{lcm}(\gcd(a, b), \gcd(a, c))$
- $\gcd(n^a - 1, n^b - 1) = n^{\gcd(a, b)} - 1$

11.2.3 Gauss Circle Theorem

- Determine the number of lattice points in a circle centered at the origin with radius r .
- number of pairs (m, n) such that $m^2 + n^2 \leq r^2$
- $N(r) = 1 + 4 \sum_{i=0}^{\infty} (\lfloor \frac{r^2}{4i+1} \rfloor - \lfloor \frac{r^2}{4i+3} \rfloor)$

11.2.4 Pick's Theorem

According to Pick's Theorem We can calculate the area of any polygon by just counting the number of Interior and Boundary lattice points of that polygon. If number of interior points are I and number of boundary lattice points are B then Area (A) of polygon will be:

$$\text{Area} = I + B/2 - 1$$

where I is the number of points in the interior shape, B stands for the number of points on the boundary of the shape.

11.2.5 Formula Cheatsheet

- $\sum_{i=1}^n = \frac{1}{m+1} [(n+1)^{m+1} - 1 - \sum_{i=1}^n ((i+1)^{m+1} - i^{m+1} - (m+1)i^m)]$
- $\sum_{i=0}^n c^i = \frac{c^{n+1}-1}{c-1}, c \neq 1$
- $\sum_{i=0}^{\infty} c^i = \frac{1}{1-c}, \sum_{i=1}^{\infty} c^i = \frac{c}{1-c}, |c| < 1$
- $H_n = \sum_{i=1}^n \frac{1}{n}, \sum_{i=1}^n i H_i = \frac{n(n+1)}{2} H_n - \frac{n(n-1)}{4}$
- $\sum_{k=0}^n \binom{r+k}{k} = \binom{r+n+1}{n}$

11.2.6 Geometry and Formulas

• Area Formulas

- Rectangle: $A = l \times w$
- Square: $A = s^2$
- Triangle: $A = \frac{1}{2}bh$
- Circle: $A = \pi r^2$
- Parallelogram: $A = bh$
- Pyramid Base: $A = \frac{1}{2}b \times h_{slant}$
- Polygon: $A = \frac{1}{2} |\sum_{i=1}^{n-1} (x_i y_{i+1})|$
- Pick's formula: $A = I + \frac{B}{2} - 1$ where I = interior points, B = boundary points

• Perimeter Formulas

- Rectangle: $P = 2(l + w)$
- Square: $P = 4s$
- Triangle: $P = a + b + c$
- Circle: $P = 2\pi r$

• Volume Formulas

- Cube: $V = s^3$
- Rect. Prism: $V = lwh$
- Cylinder: $V = \pi r^2 h$
- Sphere: $V = \frac{4}{3}\pi r^3$
- Pyramid: $V = \frac{1}{3}A_{base}h$

• Surface Area Formulas

- Cube: $SA = 6s^2$

- Rect. Prism: $SA = 2(lw + lh + wh)$
- Cylinder: $SA = 2\pi r(r + h)$
- Sphere: $SA = 4\pi r^2$
- Pyramid: $SA = A_{base} + \frac{1}{2}P_{base}h_{slant}$

• Triangles

- Side Lengths: a, b, c
- Semi Perimeter: $p = \frac{a+b+c}{2}$
- Area (Heron's): $A = \sqrt{p(p-a)(p-b)(p-c)}$
- Circumradius: $R = \frac{abc}{4A}$
- Inradius: $r = \frac{A}{p}$

• Summation Of Series

- $c^k + c^{k+1} + \dots + c^n = \frac{c^{n+1}-c^k}{c-1}$
- $1 + 2 + 3 + \dots + n = \frac{n(n+1)}{2}$
- $1^2 + 2^2 + 3^2 + \dots + n^2 = \frac{n(n+1)(2n+1)}{6}$
- $1^3 + 2^3 + 3^3 + \dots + n^3 = \left(\frac{n(n+1)}{2}\right)^2$
- $1^4 + 2^4 + 3^4 + \dots + n^4 = \frac{n(n+1)(2n+1)(3n^2+3n-1)}{30}$
- **Arithmetic:** $S_n = \frac{n}{2} [2a + (n-1)d]$
- **Geometric:** $S_n = a \cdot \frac{r^n-1}{r-1}$

• Triangle Laws

- **Law of Sines:** $\frac{a}{\sin A} = \frac{b}{\sin B} = \frac{c}{\sin C} = 2R$
- **Law of Cosines:** $a^2 = b^2 + c^2 - 2bc \cos A$
- **Law of Tangents:** $\frac{a+b}{a-b} = \frac{\tan\left(\frac{A+B}{2}\right)}{\tan\left(\frac{A-B}{2}\right)}$

• Angle Sum and Difference

$$\begin{aligned}\sin(A+B) &= \sin A \cos B + \cos A \sin B \\ \cos(A+B) &= \cos A \cos B - \sin A \sin B \\ \sin(A-B) &= \sin A \cos B - \cos A \sin B \\ \cos(A-B) &= \cos A \cos B + \sin A \sin B \\ \tan(A+B) &= \frac{\tan A + \tan B}{1 - \tan A \tan B} \\ \tan(A-B) &= \frac{\tan A - \tan B}{1 + \tan A \tan B}\end{aligned}$$

- Double Angle Formulas

$$\begin{aligned}\sin 2\theta &= 2 \sin \theta \cos \theta \\ \cos 2\theta &= \cos^2 \theta - \sin^2 \theta \\ \tan 2\theta &= \frac{2 \tan \theta}{1 - \tan^2 \theta}\end{aligned}$$

- Half Angle Formulas

$$\begin{aligned}\sin\left(\frac{\theta}{2}\right) &= \pm\sqrt{\frac{1-\cos\theta}{2}} \\ \cos\left(\frac{\theta}{2}\right) &= \pm\sqrt{\frac{1+\cos\theta}{2}} \\ \tan\left(\frac{\theta}{2}\right) &= \frac{1-\cos\theta}{\sin\theta}\end{aligned}$$

- **Sum-to-Product Formulas**

$$\begin{aligned}\sin r + \sin w &= 2 \sin \left(\frac{r+w}{2} \right) \cos \left(\frac{r-w}{2} \right) \\ \cos r + \cos w &= 2 \cos \left(\frac{r+w}{2} \right) \cos \left(\frac{r-w}{2} \right) \\ (V+W) \tan \left(\frac{r-w}{2} \right) &= (V-W) \tan \left(\frac{r+w}{2} \right)\end{aligned}$$

- Linear Combinations

$$\begin{aligned} a \cos x + b \sin x &= r \cos(x - \phi) \\ a \sin x - b \cos x &= r \sin(x - \phi) \end{aligned}$$

where $r = \sqrt{a^2 + b^2}$, $\phi = \arctan(b/a)$

11.2.8 Pascal's Triangle

$$\begin{array}{ccccccccccccccccc}
& & & & & & & & 1 & & & & & & & & \\
& & & & & & & & 1 & & 1 & & & & & & \\
& & & & & & & & 1 & & 2 & & 1 & & & & \\
& & & & & & & & 1 & & 3 & & 3 & & 1 & & \\
& & & & & & & & 1 & & 4 & & 6 & & 4 & & 1 \\
& & & & & & & & 1 & & 5 & & 10 & & 10 & & 5 & & 1 \\
& & & & & & & & 1 & & 6 & & 15 & & 20 & & 15 & & 6 & & 1 \\
& & & & & & & & 1 & & 7 & & 21 & & 35 & & 35 & & 21 & & 7 & & 1 \\
& & & & & & & & 1 & & 8 & & 28 & & 56 & & 70 & & 56 & & 28 & & 8 & & 1 \\
& & & & & & & & 1 & & 9 & & 36 & & 84 & & 126 & & 126 & & 84 & & 36 & & 9 & & 1 \\
& & & & & & & & 1 & & 10 & & 45 & & 120 & & 210 & & 252 & & 210 & & 120 & & 45 & & 10 & & 1
\end{array}$$

11.2.9 Logarithm Rules

- $\log_b(xy) = \log_b x + \log_b y$
- $\log_b\left(\frac{x}{y}\right) = \log_b x - \log_b y$
- $\log_b(x^k) = k \log_b x$
- $\log_b b = 1$
- $\log_b 1 = 0$

11.2.10 Miscellaneous

- $2^{100} = 2^{50} \times 2^{50}$
- Fibonacci Matrix

$$\begin{bmatrix} F_n \\ F_{n-1} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ 1 & 0 \end{bmatrix}^{n-1} \begin{bmatrix} F_1 \\ F_0 \end{bmatrix}$$

- $\log(n!) = \log 1 + \log 2 + \cdots + \log n$
- $\gcd(a, b) = \gcd(a - b, b)$
- Prime p in $n!$:

$$\left\lfloor \frac{n}{p} \right\rfloor + \left\lfloor \frac{n}{p^2} \right\rfloor + \left\lfloor \frac{n}{p^3} \right\rfloor + \dots$$

- Catalan: $\binom{2n}{n} - \binom{2n}{n-1}$

- Divisors of $p^x q^y$: $(x+1)(y+1)$
- Sum of divisors of $p^x q^y$:

$$(1 + p + p^2 + \cdots + p^x)(1 + q + q^2 + \cdots + q^y)$$

- Divisibility rules:

- 3:** Sum of digits divisible by 3
- 4:** Last two digits divisible by 4
- 5:** Last digit 0 or 5
- 6:** Divisible by both 2 and 3
- 7:** Double last digit, subtract from rest. Continue till manageable.
- 8:** Last three digits divisible by 8
- 9:** Sum of digits divisible by 9
- 11:** $(\text{sum of odd digits}) - (\text{sum of even digits}) \equiv 0 \pmod{11}$

- Derangement: $D_n = (n-1)D_{n-2} + (n-1)D_{n-1}$
- Golden Ratio: $\Phi = \frac{1+\sqrt{5}}{2} \approx 1.618034$
- n -th Fibonacci:

$$F_n = \frac{\Phi^n - (1 - \Phi)^n}{\sqrt{5}}$$

- Stars & Bars: Solutions of $x_1 + x_2 + \cdots + x_k = n$ $x_i \geq 0$: $\binom{n+k-1}{k-1}$

- **Throwing Dice (Matrix Exponentiation)**

- **Recurrence Relation** The number of ways to achieve a sum n is given by the linear recurrence:

$$f(n) = f(n-1) + f(n-2) + f(n-3) + f(n-4) + f(n-5) + f(n-6)$$

with the base case $f(0) = 1$ and $f(k) = 0$ for $k < 0$.

- **State Transition** The relationship between the new state vector (V_i) and the old state vector (V_{i-1}) is:

$$\underbrace{\begin{bmatrix} f(i) \\ f(i-1) \\ f(i-2) \\ f(i-3) \\ f(i-4) \\ f(i-5) \end{bmatrix}}_{V_i} = \underbrace{\begin{bmatrix} 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \end{bmatrix}}_T \times \underbrace{\begin{bmatrix} f(i-1) \\ f(i-2) \\ f(i-3) \\ f(i-4) \\ f(i-5) \\ f(i-6) \end{bmatrix}}_{V_{i-1}}$$

– **Final Answer** The n -th term is found by: $f(n) = (T^n)_{1,1} \times f(0)$, where $f(0) = 1$.

$$f(n) = (T^n)_{1,1}$$

11.2.7 Most Number of Divisors

Max Value	Number	Divisors
10^3	83,160	128
10^6	720,720	240
10^7	9,609,600	640
10^8	98,280,000	672
10^9	735,134,400	1,344
10^{10}	7,242,460,800	2,688
10^{11}	73,346,256,000	5,376
10^{12}	936,966,912,400	10,752

11.3 Probability and Expectation

- Let X be a discrete random variable with probability $p_X(x)$ of assuming the value x . It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x xp_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where σ is the standard deviation. If X is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

- Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent X and Y ,

$$V(aX + bY) = a^2V(X) + b^2V(Y).$$

- **Discrete distributions**

- **Binomial distribution:** The number of successes in n independent yes/no experiments, each which yields success with probability p is $\text{Bin}(n, p)$, $n = 1, 2, \dots$, $0 \leq p \leq 1$.

$$p(k) = \binom{n}{k} p^k (1-p)^{n-k}$$

$$\mu = np, \sigma^2 = np(1-p)$$

$\text{Bin}(n, p)$ is approximately $\text{Po}(np)$ for small p .

- **First success distribution:** The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability p is $\text{Fs}(p)$, $0 \leq p \leq 1$.

$$p(k) = p(1-p)^{k-1}, k = 1, 2, \dots$$

$$\mu = \frac{1}{p}, \sigma^2 = \frac{1-p}{p^2}$$

- **Poisson distribution:** The number of events occurring in a fixed period of time t if these events occur with a known average rate κ and independently of the time since the last event is $\text{Po}(\lambda)$, $\lambda = t\kappa$.

$$p(k) = e^{-\lambda} \frac{\lambda^k}{k!}, k = 0, 1, 2, \dots$$

$$\mu = \lambda, \sigma^2 = \lambda$$

- **Continuous distributions**

- **Uniform distribution:** If the probability density function is constant between a and b and 0 elsewhere it is $\text{U}(a, b)$, $a < b$.

$$f(x) = \begin{cases} \frac{1}{b-a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$

$$\mu = \frac{a+b}{2}, \sigma^2 = \frac{(b-a)^2}{12}$$

- **Exponential distribution:** The time between events in a Poisson process is $\text{Exp}(\lambda)$, $\lambda > 0$.

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$

$$\mu = \frac{1}{\lambda}, \sigma^2 = \frac{1}{\lambda^2}$$

- **Normal distribution:** Most real random values with mean μ and variance σ^2 are well described by $\mathcal{N}(\mu, \sigma^2)$, $\sigma > 0$.

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

If $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$ and $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$ then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$