

MIST_Jackdaw Team Notebook

Md Saif Ahmed, Al Muhimen,
Md Rafsan Hasan Ratul

Contents

1	000	1
1.1	Remember [9 lines] - 575b8cdd	1
2	Data Structure	1
2.1	DSU [34 lines] - 9039fc52	1
2.2	Fenwick Tree [38 lines] - 8d0c1e90	2
2.3	MO with Update [61 lines] - f9eca766	2
2.4	MO [58 lines] - 727b1684	2
2.5	Persistent Segment Tree [114 lines] - 861d1673	3
2.6	SQRT Decomposition [69 lines] - a6182018	3
2.7	Segment Tree Lazy [66 lines] - 1229c3a7	4
2.8	Segment Tree [33 lines] - 4d0540d8	4
2.9	Special Range Query Example Fixing Right Posi- tion [74 lines] - 24e14b44	4
2.10	Sqrt Tricks [8 lines] - 8f8b610b	5
2.11	Trie Bit [40 lines] - cd88ce8e	5
3	Dynamic Programming	5
3.1	All Possible Subarray Sum [6 lines] - 18ee4984	5
3.2	CHT [48 lines] - bc8514ba	5
3.3	Digit DP [15 lines] - 5ea603bd	5
3.4	Divide and Conquer DP [26 lines] - 1949a056	5
3.5	LCIS o(n*m) [22 lines] - b70a45ab	6
3.6	LCS [62 lines] - 2e950914	6
3.7	LIS O(nlogn) with full path [41 lines] - a74c1ccc	6
3.8	MCM [26 lines] - e8d61odd	6
3.9	Maximum Submatrix [34 lines] - 30548291	6
3.10	SOS DP [63 lines] - 2e55972d	7
4	Game Theory	7
4.1	Points to be noted [14 lines] - 85ddc883	7
5	Geometry	7
5.1	2D Convex Hull [67 lines] - 0b5204d1	7
5.2	Computational Geometry [74 lines] - a0efcafa	8
6	Graph	8
6.1	Articulation Bridges [41 lines] - b120c1d4	8
6.2	Articulation Points [40 lines] - 94a1ef65	8
6.3	Bellmanford [22 lines] - b8e770fd	8
6.4	Block Cut Tree [83 lines] - b31a5c97	9
6.5	Centroid Decomposition [30 lines] - 2ab608d6	9
6.6	Dijkstra [22 lines] - 3621521c	9
6.7	Eularian Circuit [16 lines] - b13e8b7b	9
6.8	Floyed Warshall [13 lines] - 7e17addb	9
6.9	Heavy Light Decomposition [103 lines] - ac779cb8	10
6.10	K'th Shortest path [40 lines] - 5a50a704	10
6.11	Kruskal [13 lines] - 7c746046	10
6.12	LCA using Segment Tree [89 lines] - fa80d47b	10
6.13	LCA [40 lines] - e4c6dfdc	11

6.14	SCC [57 lines] - 060054f3	11
6.15	SPFA O(V*E) [57 lines] - 7cd7bdcb	11
6.16	Topological Sort [33 lines] - 3ddc7df6	12
6.17	Tree Rerooting [99 lines] - c3cafbac	12
7	Misc	12
7.1	Bit count in O(1) [5 lines] - 8f60ac14	12
7.2	Bit hacks [16 lines] - 96eab638	13
7.3	Bitset C++ [13 lines] - 28766a3c	13
7.4	Knight Moves [2 lines] - 6c4e6fbc	13
7.5	Random Generator [6 lines] - 2b02ac44	13
7.6	Special DS [23 lines] - ef50f014	13
7.7	Usefull Things [9 lines] - c67addfa	13
7.8	VScode setup [7 lines] - 3e225a41	13
7.9	stress [25 lines] - 4a84e7fd	13
7.10	vimrc [12 lines] - 1f47305c	13
8	Number Theory	13
8.1	10-ary to m-ary [22 lines] - e6c26ef1	13
8.2	Basis Vector [89 lines] - 409325f7	13
8.3	Binary Exponentiation [9 lines] - c1fcbefe	14
8.4	CRT [16 lines] - 0991117f	14
8.5	Catalan Numbers [8 lines] - 17405386	14
8.6	Count 1s 0 to n [9 lines] - 6b5041db	14
8.7	Divisors multiple info [36 lines] - 3aff6f8b	14
8.8	Extended GCD [8 lines] - 5998ac10	14
8.9	Find numbers in L to R divisible by all array ele- ments [12 lines] - 12567a3c	14
8.10	GaussElimination [39 lines] - 8a474ce2	15
8.11	Largest Power of n! [11 lines] - ffd3d40	15
8.12	Leap Year [13 lines] - 8ff2b7cb	15
8.13	Logab [3 lines] - 1b0f688c	15
8.14	Matrix [105 lines] - 0cf635bb	15
8.15	Miller-Rabin-Pollard-Rho [36 lines] - c62079b7	15
8.16	Mobius [12 lines] - f7c84b43	16
8.17	Mod Inverse [5 lines] - 6e1326cf	16
8.18	Modular Operations [12 lines] - e4857b5b	16
8.19	NOD of n! [13 lines] - e777f444	16
8.20	No of Digits in n! in base B [7 lines] - 1f8efcc5	16
8.21	Principle of Inclusion Exclusion [21 lines] - cb2ccfa4	16
8.22	Print Calander of Any Year [44 lines] - 1a53cdae	16
8.23	SOD, NOD Upto N [30 lines] - aa4e95d9	16
8.24	SPF [10 lines] - 0b6c01c3	17
8.25	Segmented Sieve [17 lines] - b1ac5ad7	17
8.26	Sieve Phi Mobius [13 lines] - fd92a8a5	17
8.27	Sieve upto 1e9 [71 lines] - 5fa0292a	17
8.28	Sieve [16 lines] - 8babdb35	17
8.29	String Mod [5 lines] - fce25f9e	17
8.30	nCr [39 lines] - 8a93b828	17
9	Some Algorithms	18
9.1	2D Prefix Sum [2 lines] - 00be5300	18
9.2	Big Integer [92 lines] - ec448d52	18
9.3	Expression Parsing [92 lines] - c4a451ed	18
9.4	Infix to Postfix [96 lines] - 92843ab9	19
9.5	Kadanes [9 lines] - 6304cec2	19
9.6	Monotonic Stack (next greater) [7 lines] - b69c792c	19
9.7	Spirally Traverse [25 lines] - 04cd0672	19

9.8	Ternary Search [10 lines] - d44f71ce	19
10	String	19
10.1	AhoCorasick [57 lines] - de83ab1a	19
10.2	Hashing [44 lines] - 856b95a5	20
10.3	KMP [22 lines] - f876980b	20
10.4	Suffix Array [177 lines] - 3df3c95c	20
10.5	Trie [46 lines] - 95af9856	21
11	Random	21
11.1	Combinatorics	21
11.1.1	Catalan Number	21
11.1.2	Stirling Number of the First Kind	22
11.1.3	Stirling Numbers of the Second Kind	22
11.1.4	Bell Number	22
11.1.5	Lucas Theorem	22
11.1.6	Derangement	22
11.1.7	Burnside Lemma	23
11.1.8	Eulerian Number	23
11.2	Number Theory	23
11.2.1	Mobius Function and Inversion	23
11.2.2	GCD and LCM	23
11.2.3	Gauss Circle Theorem	23
11.2.4	Pick's Theorem	23
11.2.5	Formula Cheatsheet	23
11.2.6	Geometry and Formulas	23
11.2.7	Most Number of Divisors	24
11.2.8	Pascal's Triangle	24
11.2.9	Logarithm Rules	24
11.2.10	Miscellaneous	24
11.3	Probability and Expectation	25
1	000	
1.1	Remember [9 lines] - 575b8cdd	
# Don't stuck in one approach		
# Bruteforce is sometimes the best way to go		
# Reset global variables		
# Check for overflow		
# Read the problem carefully		
# Break the problem into smaller parts (go step by step)		
# Check for negative numbers, zero, one or small cases		
# For problems like making string A to B, try to work backwards from B to A or it may be easier to make both A and B to some C		
# L > R can occur		
2	Data Structure	
2.1	DSU [34 lines] - 9039fc52	
struct DSU { vector<int> par, sz, minElmt, maxElmt, cntElmt; int cc; public: DSU(int n) { par.resize(n + 1); sz.resize(n + 1, 1); minElmt.resize(n + 1);		

```

maxElmt.resize(n + 1);
cntElmt.resize(n + 1, 1);
cc = n;
for (int i = 1; i <= n; i++) par[i] = minElmt[i] =
    maxElmt[i] = i;
}
int find(int u) {
    if (u == par[u]) return u;
    return par[u] = find(par[u]);
}
void unite(int u, int v) {
    int pU = find(u);
    int pV = find(v);
    if (pU == pV) return;
    if (sz[pU] < sz[pV]) swap(pU, pV);
    par[pV] = pU;
    sz[pU] += sz[pV];
    cc--;
    cntElmt[pU] += cntElmt[pV];
    minElmt[pU] = min(minElmt[pU], minElmt[pV]);
    maxElmt[pU] = max(maxElmt[pU], maxElmt[pV]);
}
int getMinElementIntheSet(int u) { return
    minElmt[find(u)]; }
int getMaxElementIntheSet(int u) { return
    maxElmt[find(u)]; }
int getNumofElementIntheSet(int u) { return
    cntElmt[find(u)]; }
};

```

2.2 Fenwick Tree [38 lines] - 8d0c1e90

```

int fenwick[N];
void update(int ind, int val) {
    while (ind < N) {
        fenwick[ind] += val;
        ind += ind & -ind;
    }
}
int query(int ind) {
    int sum = 0;
    while (ind > 0) {
        sum += fenwick[ind];
        ind -= ind & -ind;
    }
    return sum;
}
struct Fenwick2D {
    vector<vector<int>>> t;
    int n, m;
    Fenwick2D(int n, int m) : n(n), m(m), t(n + 1,
        vector<int>(m + 1, 0)) {}

    void update(int i, int j, int v) {
        for (int x = i; x <= n; x += x & -x)
            for (int y = j; y <= m; y += y & -y) t[x][y] += v;
    }

    int query(int i, int j) {
        int s = 0;
        for (int x = i; x > 0; x -= x & -x)
            for (int y = j; y > 0; y -= y & -y) s += t[x][y];
        return s;
    }

    int query(int r1, int c1, int r2, int c2) {

```

```

        return query(r2, c2) - query(r1 - 1, c2) -
            query(r2, c1 - 1) +
            query(r1 - 1, c1 - 1);
    }
};

```

2.3 MO with Update [61 lines] - f9eca766

```

// 1 indexed
// Complexity:  $O(S \times Q + Q \times \frac{N^2}{S^2})$ 
//  $S = (2 * n^2)^{1/3}$ 
const int block_size = 2720; // 4310 for 2e5
const int mx = 1e5 + 5;
struct Query {
    int L, R, T, id;
    Query() {}
    Query(int _L, int _R, int _T, int _id) : L(_L),
        R(_R), T(_T), id(_id) {}
    bool operator<(const Query& x) const {
        if (L / block_size == x.L / block_size) {
            if (R / block_size == x.R / block_size) return T <
                x.T;
            return R / block_size < x.R / block_size;
        }
        return L / block_size < x.L / block_size;
    }
} Q[mx];
struct Update {
    int pos;
    int old, cur;
    Update() {}
    Update(int _p, int _o, int _c) : pos(_p), old(_o),
        cur(_c) {}
} U[mx];
int ans[mx];
inline void add(int id) {}
inline void remove(int id) {}
inline void update(int id, int L, int R) {
    // If update position is in current range [L,R]
    if (L <= U[id].pos && U[id].pos <= R) {
        remove(U[id].pos); // Remove old value
        arr[U[id].pos] = U[id].cur; // Apply update
        add(U[id].pos); // Add new value
    } else {
        arr[U[id].pos] = U[id].cur; // Just update array
    }
}
inline void undo(int id, int L, int R) {
    // Similar to update but revert to old value
    if (L <= U[id].pos && U[id].pos <= R) {
        remove(U[id].pos);
        arr[U[id].pos] = U[id].old;
        add(U[id].pos);
    } else {
        arr[U[id].pos] = U[id].old;
    }
}
inline int get() {}
void MO(int nq, int nu) {
    sort(Q + 1, Q + nq + 1);
    int L = 1, R = 0, T = nu;
    for (int i = 1; i <= nq; i++) {
        Query q = Q[i];
        while (T < q.T) update(++T, L, R);
        while (T > q.T) undo(T--, L, R);
        while (L > q.L) add(--L);
        while (R < q.R) add(++R);
    }
}

```

```

        while (L < q.L) remove(L++);
        while (R > q.R) remove(R--);
        ans[q.id] = get();
    }
}

```

2.4 MO [58 lines] - 727b1684

```

const int N = 1e6 + 5;
int arr[N], freq[N], cnt = 0;

void remove(int idx) {
    int v = arr[idx];
    freq[v]--;
    if (freq[v] == 0) cnt--;
}
void add(int idx) {
    int v = arr[idx];
    freq[v]++;
    if (freq[v] == 1) cnt++;
}
int get_answer() {
    return cnt;
}

int block_size = 700;

struct Query {
    int l, r, idx;
    bool operator<(Query other) const {
        if (l / block_size != other.l / block_size) return l /
            block_size < other.l / block_size;
        return r < other.r;
    }
};

vector<int> mo_s_algorithm(vector<Query> queries) {
    vector<int> answers(queries.size());
    sort(queries.begin(), queries.end());

    // TODO: initialize data structure

    int cur_l = 0;
    int cur_r = -1;
    // invariant: data structure will always reflect the
    // range [cur_l, cur_r]
    for (Query q : queries) {
        while (cur_l > q.l) {
            cur_l--;
            add(cur_l);
        }
        while (cur_r < q.r) {
            cur_r++;
            add(cur_r);
        }
        while (cur_l < q.l) {
            remove(cur_l);
            cur_l++;
        }
        while (cur_r > q.r) {
            remove(cur_r);
            cur_r--;
        }
        answers[q.idx] = get_answer();
    }
    return answers;
}

```

}

2.5 Persistent Segment Tree [114 lines] - 861d1673

```
#include <bits/stdc++.h>
using namespace std;
#define i64 long long
#ifdef ONPC
#include "mydebug.h"
#else
#define debug(...) 1
#endif

const int N = 30000 + 5;
int arr[N];
struct Node {
    int val;
    Node* lc;
    Node* rc;
    Node() {
        lc = NULL;
        rc = NULL;
    }
};
Node* versions[N];

Node* build(int l, int r) {
    Node* node = new Node();
    if (l == r) {
        node->val = 0;
        return node;
    }
    int mid = (l + r) / 2;
    node->lc = build(l, mid);
    node->rc = build(mid + 1, r);
    node->val = node->lc->val + node->rc->val;
    return node;
}

int query(Node* node, int l, int r, int ql, int qr) {
    if (l > qr || r < ql) return 0;
    if (ql <= l && r <= qr) {
        return node->val;
    }
    int mid = (l + r) / 2;
    int left = query(node->lc, l, mid, ql, qr);
    int right = query(node->rc, mid + 1, r, ql, qr);
    return left + right;
}

Node* update(Node* node, int l, int r, int ind, int val) {
    Node* newnode = new Node();
    if (l == r) {
        newnode->val = node->val + val;
        return newnode;
    }
    int mid = (l + r) / 2;
    if (l <= ind && ind <= mid) {
        newnode->lc = update(node->lc, l, mid, ind, val);
        newnode->rc = node->rc;
    } else {
        newnode->lc = node->lc;
        newnode->rc = update(node->rc, mid + 1, r, ind, val);
    }
}
```

```
newnode->val = newnode->lc->val + newnode->rc->val;
return newnode;
}

void solve() {
    int n;
    cin >> n;
    vector<int> comp;
    for (int i = 1; i <= n; i++) {
        cin >> arr[i];
        comp.push_back(arr[i]);
    }

    sort(comp.begin(), comp.end());
    comp.erase(unique(comp.begin(), comp.end()),
        comp.end());
    int sz = comp.size();

    for (int i = 1; i <= n; i++) {
        arr[i] = lower_bound(comp.begin(), comp.end(),
            arr[i]) - comp.begin();
    }

    versions[0] = build(0, sz - 1);

    for (int v = 1; v <= n; v++) {
        versions[v] = update(versions[v - 1], 0, sz - 1,
            arr[v], +1);
    }

    int q;
    cin >> q;
    vector<int> ans(q + 1);
    for (int i = 1; i <= q; i++) {
        int a, b, c;
        cin >> a >> b >> c;
        int l = a ^ ans[i - 1];
        int r = b ^ ans[i - 1];
        int k = c ^ ans[i - 1];
        l = max(1, l);
        r = min(n, r);
        if (l > r) {
            ans[i] = 0;
            continue;
        }
        k = upper_bound(comp.begin(), comp.end(), k) -
            comp.begin();
        if (k >= sz) {
            ans[i] = 0;
            continue;
        }
        ans[i] = query(versions[r], 0, sz - 1, k, sz - 1) -
            query(versions[l - 1], 0, sz - 1, k, sz - 1);
    }
    for (int i = 1; i <= q; i++) {
        cout << ans[i] << '\n';
    }
}
```

2.6 SQRT Decomposition [69 lines] - a6182018

// <https://www.spoj.com/problems/GIVEAWAY/>
 // 0 l r k : count of numbers >= k in [l, r]
 // 1 idx val : update a[idx] = val

```
const int N = 5e5 + 5, BLK = 700;
```

```
vector<int> block[N / BLK + 5];
int get_block(int idx) { return idx / BLK; }

void solve() {
    int n;
    cin >> n;
    vector<int> a(n);
    for (int i = 0; i < n; i++) cin >> a[i];
    for (int i = 0; i < n; i++) {
        block[get_block(i)].push_back(a[i]);
    }
    int last_blk = get_block(n - 1);
    for (int i = 0; i <= last_blk; i++) {
        sort(block[i].begin(), block[i].end());
    }
    int q;
    cin >> q;
    while (q--) {
        int ty;
        cin >> ty;
        if (ty == 0) {
            // query
            // O(sqrt(n) log(sqrt(n)))
            int l, r, k;
            cin >> l >> r >> k;
            l--, r--;
            int bl = get_block(l);
            int br = get_block(r);
            int ans = 0;
            if (bl == br) {
                // just brute force
                for (int i = l; i <= r; i++) {
                    if (a[i] >= k) ans++;
                }
            } else {
                for (int i = l; get_block(i) < (bl + 1); i++) {
                    if (a[i] >= k) ans++;
                }
                for (int i = r; get_block(i) > (br - 1); i--) {
                    if (a[i] >= k) ans++;
                }
                for (int b = bl + 1; b < br; b++) {
                    // sorted vector, [1, 5, 10, 20], k
                    // = 6, ans += 2
                    auto it =
                        lower_bound(block[b].begin(),
                            block[b].end(), k);
                    ans += block[b].end() - it;
                }
            }
            cout << ans << '\n';
        } else {
            // update
            // O(sqrt(n) log(sqrt(n)))
            int idx, val;
            cin >> idx >> val;
            idx--;
            int old = a[idx];
            int b = get_block(idx);
            auto it = lower_bound(block[b].begin(),
                block[b].end(), old);
            *it = val;
            sort(block[b].begin(), block[b].end());
        }
    }
}
```

```
a[idx] = val;
```

```
}
```

```
}
```

```
}
```

2.7 Segment Tree Lazy [66 lines] - 1229c3a7

/* 1. TO ADAPT FOR ANY PROBLEM, ONLY EDIT THESE 4 THINGS:

- `Node` struct : Add your variables (sum, mx, pref, suff). Ensure Node() is a neutral/identity element!
- `combine()` : How to merge the left and right children.
- `applySet()` : How setting a range to `v` changes a Node. (Updates lzSet, clears lzAdd).
- `applyAdd()` : How adding `v` to a range changes a Node. (Updates lzAdd).
- 2. NEVER TOUCH `push()`, `update()`, OR `query()`! They are mathematically bug-proof.
- 3. WHY applySet CLEARS lzAdd? Overwriting a range completely destroys its previous history (adds).
- 4. WHY push SET BEFORE ADD? "Set this to X, then add Y" implies Set happened first.
- 5. FOR TOGGLE/XOR/INVERSION: Change `lzAdd` to `lzXor`, delete `Set` logic, update `applyAdd`.
- 6. 1-BASED INDEXING: Use `seg.build(a)`, `seg.add(l, r, v)`, `seg.query(l, r)`.

*/

```
struct Node {
    ll sum;
    Node(ll _sum = 0) { sum = _sum; }
};

struct STLazy {
    int n; vector<Node> seg; vector<ll> lzAdd, lzSet;
    vector<bool> hasSet;
    STLazy(int _n) : n(_n), seg(4*_n+5), lzAdd(4*_n+5, 0), lzSet(4*_n+5, 0), hasSet(4*_n+5, 0) {}

    Node combine(Node l, Node r) {
        Node res; res.sum = l.sum + r.sum;
        return res;
    }

    void applySet(int node, int l, int r, ll v) {
        seg[node].sum = (ll)(r - l + 1) * v;
        lzSet[node] = v; hasSet[node] = 1; lzAdd[node] = 0;
    }

    void applyAdd(int node, int l, int r, ll v) {
        seg[node].sum += (ll)(r - l + 1) * v;
        lzAdd[node] += v;
    }

    void push(int node, int l, int r) {
        if (l == r) return;
        int mid = (l + r) >> 1, lc = node << 1, rc = node << 1 | 1;
        if (hasSet[node]) {
            applySet(lc, l, mid, lzSet[node]);
            applySet(rc, mid + 1, r, lzSet[node]);
            hasSet[node] = 0;
        }
        if (lzAdd[node] != 0) {
            applyAdd(lc, l, mid, lzAdd[node]);
            applyAdd(rc, mid + 1, r, lzAdd[node]);
        }
    }
};
```

```
lzAdd[node] = 0;
```

```
}
```

```
}
```

```
void build(int node, int l, int r, const vector<ll>& a) {
    if (l == r) { seg[node] = Node(a[l]); return; }
    int mid = (l + r) >> 1;
    build(node<<1, l, mid, a); build(node<<1|1, mid+1, r, a);
    seg[node] = combine(seg[node<<1], seg[node<<1|1]);
}

void update(int node, int l, int r, int ql, int qr, ll v, int type) {
    if (ql > r || qr < l) return;
    if (ql <= l && r <= qr) { type == 1 ? applyAdd(node, l, r, v) : applySet(node, l, r, v); return; }
    push(node, l, r);
    int mid = (l + r) >> 1;
    update(node<<1, l, mid, ql, qr, v, type);
    update(node<<1|1, mid+1, r, ql, qr, v, type);
    seg[node] = combine(seg[node<<1], seg[node<<1|1]);
}

Node query(int node, int l, int r, int ql, int qr) {
    if (ql > r || qr < l) return Node();
    if (ql <= l && r <= qr) return seg[node];
    push(node, l, r);
    int mid = (l + r) >> 1;
    return combine(query(node<<1, l, mid, ql, qr), query(node<<1|1, mid+1, r, ql, qr));
}

};

2.8 Segment Tree [33 lines] - 4d0540d8

struct Node {
    ll sum;
    Node() { sum = 0; }
};

struct ST {
    int n; vector<Node> seg;
    ST(int _n) : n(_n), seg(4*_n+5) {}

    Node combine(Node l, Node r) {
        Node res; res.sum = l.sum + r.sum;
        return res;
    }

    void build(int node, int l, int r, const vector<ll>& a) {
        if (l == r) { seg[node].sum = a[l]; return; }
        int mid = (l + r) >> 1;
        build(node<<1, l, mid, a); build(node<<1|1, mid+1, r, a);
        seg[node] = combine(seg[node<<1], seg[node<<1|1]);
    }

    void update(int node, int l, int r, int pos, ll v) {
        if (l == r) { seg[node].sum = v; return; }
        int mid = (l + r) >> 1;
        if (pos <= mid) update(node<<1, l, mid, pos, v);
        else update(node<<1|1, mid+1, r, pos, v);
        seg[node] = combine(seg[node<<1], seg[node<<1|1]);
    }
};
```

```
}
```

```
Node query(int node, int l, int r, int ql, int qr) {
    if (ql > r || qr < l) return Node();
    if (ql <= l && r <= qr) return seg[node];
    int mid = (l + r) >> 1;
    return combine(query(node<<1, l, mid, ql, qr), query(node<<1|1, mid+1, r, ql, qr));
}

};
```

2.9 Special Range Query Example Fixing Right Position

[74 lines] - 24e14b44

```
/*
https://codeforces.com/gym/106107/problem/B
We need to count "good subarrays" [l, r] where:
1. Length >= 2
2. a[l] exists somewhere in b[l...r]
3. a[r] does NOT exist in b[l...r]
*/

#include <bits/stdc++.h>
using namespace std;
#define i64 long long
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;

const int N = 5e5 + 5;
i64 fenwick[N];

void update(int ind, int val) {
    while (ind < N) {
        fenwick[ind] += val;
        ind += ind & -ind;
    }
}

i64 query(int ind) {
    i64 sum = 0;
    while (ind > 0) {
        sum += fenwick[ind];
        ind -= ind & -ind;
    }
    return sum;
}

void solve() {
    int n;
    cin >> n;
    vector<int> comp;
    vector<int> a(n + 1), b(n + 1);
    gp_hash_table<int, vector<int>>> mp;
    for (int i = 1; i <= n; i++) cin >> a[i];
    for (int i = 1; i <= n; i++) {
        cin >> b[i];
        mp[b[i]].push_back(i);
    }
    vector<int> rend(n + 1, n + 1);
    for (int i = 1; i <= n; i++) {
        if (mp[a[i]].empty()) continue;
        auto it = lower_bound(mp[a[i]].begin(), mp[a[i]].end(), i);
        if (it == mp[a[i]].end()) continue;
        rend[i] = max(i + 1, *it); // length >= 2, l < r
    }
    vector<vector<int>> active(n + 2);
    for (int i = 1; i <= n; i++) {
        if (rend[i] <= n) {
```

```

    active[rend[i]].push_back(i); // i to rend[i] is a
        segment
    }
}
gp_hash_table<int, int> last;
i64 seg_count = 0, ans = 0;
for (int r = 1; r <= n; r++) {
    last[b[r]] = r;
    for (auto l : active[r]) {
        update(l, 1);
        seg_count++;
    }
    int last_pos = (last.find(a[r]) != last.end()) ?
        last[a[r]] : 0;
    i64 bad = query(last_pos);
    ans += seg_count - bad;
}
cout << ans << '\n';

// clear fenwick tree
for (int r = 1; r <= n; r++) {
    for (auto l : active[r]) update(l, -1);
}
}

```

2.10 Sqrt Tricks [8 lines] - 8f8b610b

1. Size of the block is not always Sqrt, adjust it as necessary. if $o(n/b+b)$ then take $n/b = b$ and calculate b.
2. MO's Algorithm
*it is possible to solve a Mo problem without any remove operation. For L in one block R only increases, for every range we can start L from the last of that block
3. Sqrt Decomposition by time of queries.
*keep overall solution and sqrt(n) updates in a vector and for a query iterate over all of them, when the vector size exceeds sqrt(n) you can add these updates with overall solution using $o(n)$
4. If sum of N positive numbers are S, there are at most sqrt(S) distinct values.
5. Randomization
6. Baby step, gaint step

2.11 Trie Bit [40 lines] - cd88ce8e

```

struct BitTrie {
    static const int BT = 62; // Use 30 for numbers <=
        10^9
    struct Node {
        int nxt[2]{}; // {} zero-initializes the array
        int cnt = 0;
    };
    vector<Node> t;
    BitTrie() : t(1) {} // Initializes with root at
        index 0

    //d = 1 for insert, d = -1 for remove
    void insert(long long x, int d = 1) {
        int u = 0;
        t[u].cnt += d; // Track total elements at root
        for (int i = BT - 1; i >= 0; i--) {
            int v = (x >> i) & 1;
            if (!t[u].nxt[v]) {
                t[u].nxt[v] = t.size();
                t.emplace_back();
            }
        }
    }
}

```

```

        u = t[u].nxt[v];
        t[u].cnt += d;
    }
}

long long query(long long x) {
    if (!t[0].cnt) return 0;
    int u = 0;
    long long mx = 0;
    for (int i = BT - 1; i >= 0; i--) {
        int r = (x >> i) & 1;
        if (t[u].nxt[r ^ 1] && t[t[u].nxt[r ^
            1]].cnt > 0) {
            mx |= (1LL << i);
            u = t[u].nxt[r ^ 1];
        } else {
            u = t[u].nxt[r];
        }
    }
    return mx;
}
};

```

3 Dynamic Programming

3.1 All Possible Subarray Sum [6 lines] - 18ee4984

```

bitset<100005> bs = 1;
for (auto i : a) {
    bs |= (bs << i); // if previous 1 value pos is
        possible now ith bit or ith sm
        // is also possible
}
cout << bs.count() - 1 << endl;

```

3.2 CHT [48 lines] - bc8514ba

```

#define x first
#define y second
// Warning: replace __int128 with long double if using
    floating point lines or if unsure about the
    compiler
// Queries maximum by default, pass false in constructor
    to query minimum
// Line = pair (m, c) for a line y = mx + c
// Make sure lines are inserted in non-decreasing order
    for maximum queries, and non-increasing order for
    minimum queries
template<typename T, class Line = pair<T, T>> // Make
    sure multiplications fit in T
class CHT {
private:
    vector<Line> lines;
    bool maximum;
public:
    CHT(bool maximum = true) { this->maximum = maximum; }
    void addLine(Line line) {
        if (!maximum) line.first = -line.first, line.second
            = -line.second;
        insert(line);
    }
    T query(const T &x) {
        assert(!lines.empty());

        int L = 0, R = lines.size() - 1;
        while (L != R) {
            int mid1 = L + (R - L) / 3;
            int mid2 = R - (R - L) / 3;
            if (lines[mid1].x * x + lines[mid1].y

```

```

                >= lines[mid2].x * x + lines[mid2].y
            ) R = mid2 - 1;
            else L = mid1 + 1;
        }

        T res = lines[L].x * x + lines[L].y;
        return maximum ? res : -res;
    }
private:
    bool bad(const Line &line1, const Line &line2, const
        Line &line3) {
        return __int128(line3.y - line1.y) *
            __int128(line1.x - line2.x)
            <= __int128(line2.y - line1.y) *
                __int128(line1.x - line3.x);
    }
    void insert(const Line &line) {
        while (lines.size() > 0 && lines.back().x == line.x)
            lines.pop_back();
        lines.push_back(line);
        int sz = lines.size();
        while (sz >= 3 && bad(lines[sz - 3], lines[sz - 2],
            lines[sz - 1])) {
            lines.erase(lines.end() - 2);
            sz--;
        }
    }
};

```

3.3 Digit DP [15 lines] - 5ea603bd

```

int f(int pos, int up, int under, int nz) {
    if (pos == n) return 0;
    int& ans = dp[pos][under][up][nz];
    if (ans != -1) return ans;
    int ans = 0;
    int start = up ? 0 : s[pos] - '0';
    int end = under ? 9 : t[pos] - '0';
    for (int d = start; d <= end; d++) {
        int n_up = up || (d > s[pos] - '0');
        int n_under = under || (d < t[pos] - '0');
        int n_nz = nz || (d != 0);
        ans += f(pos + 1, n_under, n_up, n_nz);
    }
    return ans;
}

```

3.4 Divide and Conquer DP [26 lines] - 1949a056

```

ll G,L;///total group,cell size
ll dp[8001][801],cum[8001];
ll C[8001];///value of each cell
inline ll cost(ll l,ll r){
    return(cum[r]-cum[l-1])*(r-l+1);
}
void fn(ll g,ll st,ll ed,ll r1,ll r2){
    if(st>ed)return;
    ll mid=(st+ed)/2,pos=-1;
    dp[mid][g]=inf;
    for(int i=r1;i<=r2;i++){
        ll tcost=cost(i,mid)+dp[i-1][g-1];
        if(tcost<dp[mid][g]){
            dp[mid][g]=tcost,pos=i;
        }
    }
    fn(g,st,mid-1,r1,pos);
    fn(g,mid+1,ed,pos,r2);
}

```

```

}
int main(){
    for(int i=1;i<=L;i++){
        cum[i]=cum[i-1]+C[i];
        for(int i=1;i<=L;i++){
            dp[i][1]=cost(1,i);
        }
        for(int i=2;i<=G;i++){fn(i,1,L,1,L);
    }
}

```

3.5 LCIS $O(n*m)$ [22 lines] - b70a45ab

```

int a[100] = {0}, b[100] = {0}, f[100] = {0};
int n = 0, m = 0;
int main(void) {
    cin >> n;
    for (int i = 1; i <= n; i++) cin >> a[i];
    cin >> m;
    for (int i = 1; i <= m; i++) cin >> b[i];
    for (int i = 1; i <= n; i++) {
        int k = 0;
        for (int j = 1; j <= m; j++) {
            if (a[i] > b[j] && f[j] > k)
                k = f[j];
            else if (a[i] == b[j] && k + 1 > f[j])
                f[j] = k + 1;
        }
    }
    int ans = 0;
    for (int i = 1; i <= m; i++)
        if (f[i] > ans) ans = f[i];
    cout << ans << endl;
    return 0;
}

```

3.6 LCS [62 lines] - 2e950914

```

// LCS DP Table and LCS Length
vector<vector<int>> dp(s.size() + 1,
    vector<int>(t.size() + 1));
for (int i = 1; i <= s.size(); i++) {
    for (int j = 1; j <= t.size(); j++) {
        if (s[i - 1] == t[j - 1])
            dp[i][j] = dp[i - 1][j - 1] + 1;
        else
            dp[i][j] = max(dp[i - 1][j], dp[i][j - 1]);
    }
}
cout << dp[s.size()][t.size()] << "\n";

```

// Any LCS String

```

string a;
int i = s.size();
int j = t.size();
while (i > 0 && j > 0) {
    if (s[i - 1] == t[j - 1]) {
        a += s[i - 1];
        i--, j--;
    } else if (dp[i][j - 1] > dp[i - 1][j])
        j--;
    else
        i--;
}
reverse(a.begin(), a.end());
cout << a << "\n";

```

// Lexicographically smallest LCS

```

vector<vector<string>> dpp(s.size() + 1,
    vector<string>(t.size() + 1));
for (int i = 1; i <= s.size(); i++) {

```

```

    for (int j = 1; j <= t.size(); j++) {
        if (s[i - 1] == t[j - 1])
            dpp[i][j] = dpp[i - 1][j - 1] + s[i - 1];
        else if (dp[i][j - 1] < dp[i - 1][j])
            dpp[i][j] = dpp[i - 1][j];
        else if (dp[i][j - 1] > dp[i - 1][j])
            dpp[i][j] = dpp[i][j - 1];
        else
            dpp[i][j] = min(dpp[i][j - 1], dpp[i - 1][j]);
    }
}
cout << dpp[s.size()][t.size()] << "\n";

// number of distinct LCS sequences
int MOD = 1e9 + 7;
vector<vector<int>> cnt(s.size() + 1,
    vector<int>(t.size() + 1, 1));
for (int i = 1; i <= s.size(); i++) {
    for (int j = 1; j <= t.size(); j++) {
        if (s[i - 1] == t[j - 1])
            cnt[i][j] = cnt[i - 1][j - 1];
        else if (dp[i][j - 1] < dp[i - 1][j])
            cnt[i][j] = cnt[i - 1][j];
        else if (dp[i][j - 1] > dp[i - 1][j])
            cnt[i][j] = cnt[i][j - 1];
        else {
            cnt[i][j] = cnt[i - 1][j] + cnt[i][j - 1];
            if (dp[i][j] == dp[i - 1][j - 1]) cnt[i][j] -= cnt[i - 1][j - 1];
            cnt[i][j] = (cnt[i][j] + MOD) % MOD;
        }
    }
}
}

```

3.7 LIS $O(n \log n)$ with full path [41 lines] - a74c1ccc

```

//1. LIS Length(Change lower_bound to upper_bound to
    allow EQUAL elements)
int LIS(vector<int>& v) {
    vector<int> seq;
    for (int x:v) { auto it =
        lower_bound(seq.begin(), seq.end(), x);
        if(it==seq.end()) seq.push_back(x); else *it=x; }
    return seq.size();
}

//2. LIS with Reconstruction
vector<int> getLIS(vector<int>& v) {
    int n=v.size(); vector<int> seq, id, p(n,-1), ans;
    for(int i=0;i<n;i++) {
        int pos = lower_bound(seq.begin(), seq.end(), v[i]) -
            seq.begin();
        if(pos>0) p[i]=id[pos-1]; // Link current element to
            previous best
        if(pos==seq.size()) {seq.push_back(v[i]);
            id.push_back(i);}
        else {seq[pos]=v[i]; id[pos]=i;}
    }
    // Backtrack using parent array p
    for(int c=id.empty()-1;id.back(); c!=-1; c=p[c])
        ans.push_back(v[c]);
    reverse(ans.begin(), ans.end()); return ans;
}

//3. SEGMENT LIS WRAPPER: For Weights, Counts, and
    Restrictions.  $O(N \log N)$ 

```

```

//Assumes you have a Point Update, Range Max Query
    SegTree ready.
ll getLIS_SegTree(vector<int>& a, vector<ll>& w) {
    vector<int> b=a; ll ans=0;
    // Coordinate Compression: SegTree leaves [1..M]
        represent the SORTED VALUES
    sort(b.begin(), b.end());
    b.erase(unique(b.begin(), b.end()), b.end());
    int M = b.size();
    //Call build(1, 1, M) here to initialize SegTree
        leaves to 0
    for(int i=0;i<a.size();i++) {
        // x is the 1-based compressed index of value a[i]
        int x = lower_bound(b.begin(), b.end(), a[i]) -
            b.begin()+1;
        // 1. Strictly Increasing: query(1, 1, M, 1, x - 1)
        // 2. Non-Decreasing (equal allowed): query(1, 1, M,
            1, x)
        // 3. Condition (e.g. diff >= K): Find pos of
            (a[i]-K) in 'b' and query up to pos
        ll mx = (x==1) ? 0 : query(1, 1, M, 1, x-1);
        mx += w[i]; ans = max(ans, mx);
        // Update the max value ending exactly at compressed
            value 'x'
        update(1, 1, M, x, mx);
    }
    return ans;
}

```

3.8 MCM [26 lines] - e8d610dd

```

const int N = 1005;
vector<int> v;
int dp[N][N], mark[N][N];
int MCM(int i, int j) {
    if (i == j) return dp[i][j] = 0;
    if (dp[i][j] != -1) return dp[i][j];
    int mn = INT_MAX;
    for (int k = i; k < j; k++) {
        int x = mn;
        mn = min(mn, MCM(i, k) + MCM(k + 1, j) + v[i - 1] *
            v[k] * v[j]);
        if (x != mn) mark[i][j] = k;
    }
    return dp[i][j] = mn;
}

void print_order(int i, int j) {
    if (i == j)
        cout << "X" << i;
    else {
        cout << "(";
        print_order(i, mark[i][j]);
        print_order(mark[i][j] + 1, j);
        cout << ")";
    }
}

// memset(dp, -1, sizeof dp);
// print_order(1, n);

```

3.9 Maximum Submatrix [34 lines] - 30548291

```

int a[150][150] = {0};
int c[200] = {0};
int maxarray(int n) {
    int b = 0, sum = -100000000;
    for (int i = 1; i <= n; i++) {
        if (b > 0)
            b += c[i];
        else

```

```

    b = c[i];
    if (b > sum) sum = b;
}
return sum;
}

int maxmatrix(int n) {
    int sum = -100000000, max = 0;
    for (int i = 1; i <= n; i++) {
        for (int j = 1; j <= n; j++) c[j] = 0;
        for (int j = i; j <= n; j++) {
            for (int k = 1; k <= n; k++) c[k] += a[j][k];
            max = maxarray(n);
            if (max > sum) sum = max;
        }
    }
    return sum;
}

int main(void) {
    int n = 0;
    cin >> n;
    for (int i = 1; i <= n; i++)
        for (int j = 1; j <= n; j++) cin >> a[i][j];
    cout << maxmatrix(n);
    return 0;
}

```

3.10 SOS DP [63 lines] - 2e55972d

```

// sum over subsets
// fact: need sum of submasks
void SOS(vector<int>& v) {
    const int BITS = log2(*max_element(v.begin(),
        v.end())) + 1;
    vector<int> freq(1 << BITS, 0);
    for (int mask : v) freq[mask]++;

    vector<vector<int>> dp(BITS + 1, vector<int>(1 <<
        BITS, 0));
    for (int mask = 0; mask < 1 << BITS; mask++) {
        dp[0][mask] = freq[mask];
    }

    for (int bits = 1; bits <= BITS; bits++) {
        for (int mask = 0; mask < 1 << BITS; mask++) {
            if ((mask & (1 << (bits - 1))) == 0) {
                dp[bits][mask] = dp[bits - 1][mask];
            } else {
                int other_mask = mask - (1 << (bits - 1));
                dp[bits][mask] = dp[bits - 1][mask] + dp[bits -
                    1][other_mask];
            }
        }
    }

    for (int mask : v) cout << dp[BITS][mask] << '\n';
}

// O(BITS * 2 ^ BITS)
// dp[bits][mask] means left most 'bits' of submasks can
// be differ (submask)
// for dp[1][11] 01, 00 are not allow because leftmost 1
// bit can be differ. 10
// and 11 are allowed. for travarsing all the submask of
// a mask we can use
// submask = mask
// do {
//     submask = (submask - 1) & mask

```

```

// } while (submask)
// O(3 ^ BITS)

const int MAXN = 1 << 20, MLOG = 20;
int dp[MAXN], freq[MAXN];

// Sum over subsets (SOS Down)
void forward1() {
    for (int bit = 0; bit < MLOG; bit++)
        for (int i = 0; i < MAXN; i++)
            if (i & (1 << bit)) dp[i] += dp[i ^ (1 << bit)];
}

void backward1() {
    for (int bit = 0; bit < MLOG; bit++)
        for (int i = MAXN - 1; i >= 0; i--)
            if (i & (1 << bit)) dp[i] -= dp[i ^ (1 << bit)];
}

// Sum over supersets (SOS Up)
void forward2() {
    for (int bit = 0; bit < MLOG; bit++)
        for (int i = MAXN - 1; i >= 0; i--)
            if (i & (1 << bit)) dp[i ^ (1 << bit)] += dp[i];
}

void backward2() {
    for (int bit = 0; bit < MLOG; bit++)
        for (int i = 0; i < MAXN; i++)
            if (i & (1 << bit)) dp[i ^ (1 << bit)] -= dp[i];
}

```

4 Game Theory

4.1 Points to be noted [14 lines] - 85ddc883

```

>[First Write a Brute Force solution]
>Nim = all xor
>Misere Nim = Nim + corner case: if all piles are 1,
    reverse(nim)
>Bogus Nim = Nim
>Staircase Nim = Odd indexed pile Nim (Even indexed pile
    doesnt matter, as one player can give bogus moves to
    drop all even piles to ground)
>Sprague Grundy: [Every impartial game under the normal
    play convention is equivalent to a one-heap game of
    nim]
Every tree = one nim pile = tree root value; tree leaf
    value = 0; tree node value = mex of all child nodes.
[Careful: one tree node can become multiple new tree
    roots(multiple elements in one node), then the value
    of that node = xor of all those root values]
>Hackenbush(Given a rooted tree; cut an edge in one
    move; subtree under that edge gets removed; last
    player to cut wins):
    Colon: //G(u) = (G(v1) + 1) ⊕ (G(v2) + 1) ⊕ ... [v1, v2, ...
        are childs of u]
For multiple trees ans is their xor
>Hackenbush on graph (instead of tree given an rooted
    graph):
fusion: All edges in a cycle can be fused to get a tree
    structure; build a super node, connect some single
    nodes with that super node, number of single nodes
    is the number of edges in the cycle.

```

Sol: [Bridge component tree] mark all bridges, a group of edges that are not bridges, becomes one component and contributes number of edges to the hackenbush. (even number of edges contributes 0, odd number of edges contributes 1)

5 Geometry

5.1 2D Convex Hull [67 lines] - 0b5204d1

```

struct point {
    ll x, y;
    bool operator==(point const& t) const { return (x ==
        t.x && y == t.y); }
};

int orientation(point a, point b, point c) {
    ll d = (c.y - b.y) * (b.x - a.x) - (c.x - b.x) * (b.y
        - a.y);
    if (d < 0)
        return -1; // clockwise
    else if (d > 0)
        return 1; // anticlockwise
    return 0; // collinear
}

bool clockwise(point a, point b, point c, bool
    include_collinear) {
    int o = orientation(a, b, c);
    if (o < 0) return true;
    if (o > 0) return false;
    return include_collinear;
}

bool collinear(point a, point b, point c) { return
    orientation(a, b, c) == 0; }

bool cmp_points(point& p1, point& p2) {
    return make_pair(p1.x, p1.y) < make_pair(p2.x, p2.y);
}

ll distance_sq(point a, point b) {
    ll d = (a.x - b.x) * (a.x - b.x) + (a.y - b.y) * (a.y
        - b.y);
    return d;
}

void print(vector<point>& v) {
    for (auto it : v) {
        cout << "(" << it.x << ", " << it.y << ")" << "\n";
    }
}

vector<point> convex_hull(vector<point>& points,
    bool include_collinear =
        false) {
    int sz = (int)points.size();
    point p0 = *min_element(points.begin(), points.end(),
        cmp_points);
    vector<point> convex_hull_vector = points;
    sort(convex_hull_vector.begin(),
        convex_hull_vector.end(),
        [&p0](const point& p1, const point& p2) {
            int o = orientation(p0, p1, p2);
            if (o == 0) {
                return distance_sq(p0, p1) < distance_sq(p0,
                    p2);
            }
            return o < 0;
        });
    if (include_collinear) {
        int idx = sz - 1;
        while (idx >= 0 &&

```

```

collinear(p0, convex_hull_vector[idx],
convex_hull_vector.back()))
idx--;
reverse(convex_hull_vector.begin() + idx + 1,
convex_hull_vector.end());
}
vector<point> st;
for (int i = 0; i < sz; i++) {
while (st.size() >= 2 &&
!clockwise(st[st.size() - 2], st.back(),
convex_hull_vector[i],
include_collinear)) {
st.pop_back();
}
st.push_back(convex_hull_vector[i]);
}
if (!include_collinear && st.size() == 2 && st[0] ==
st[1]) {
st.pop_back();
}
return st;
}

```

5.2 Computational Geometry [74 lines] - a0efcafa

```

typedef long long int T;
typedef double Tf;
Tf eps = 1e-10;

// int sgn(Tf x)
// {
//     if (fabs(x) < eps) return 0;
//     if (x > 0) return 1;
//     return -1;
// }

```

```

int sgn(T x) {
if (x == 0) return 0;
if (x > 0)
return 1;
else
return -1;
}

```

```

struct point {
T x, y;
point(T x = 0, T y = 0) {
this->x = x;
this->y = y;
}
point operator+(point p) { return point(x + p.x, y +
p.y); }
point operator-(point p) { return point(x - p.x, y -
p.y); }
Tf len() { return sqrt(x * x + y * y); }
T norm() { return x * x + y * y; }
point operator*(T a) { return point(x * a, y * a); }
point operator/(T a) { return point(x / a, y / a); }
// integer
bool operator==(point p) { return p.x == x && p.y ==
y; }
// float
// bool operator==(point p) {
//     return sgn(p.x - x) == 0 && sgn(p.y - y) == 0;
// }
bool operator<(point p) {
if (x == p.x) return y < p.y;
return x < p.x;
}

```

```

}
// float
// bool operator<(point p) {
//     if (sgn(p.x - x) == 0) return sgn(y - p.y) ==
-1;
//     return sgn(x - p.x) == -1;
// }
};
T dot(point a, point b) { return a.x * b.x + a.y * b.y;
}
T cross(point a, point b) { return a.x * b.y - b.x *
a.y; }
T orien(point a, point b, point c) { return cross(a -
b, a - c); }

Tf area(point a, point b, point c) { return
abs(orien(a, b, c)) / (Tf)2; }

struct segment {
point a, b;
bool onSegment(point p) {
if (sgn(orien(a, b, p)) != 0) return false;
return sgn(dot(p - a, p - b)) <= 0;
}
bool intersection(segment s) {
if (onSegment(s.a)) return true;
if (onSegment(s.b)) return true;
if (s.onSegment(a)) return true;
if (s.onSegment(b)) return true;
int s1 = sgn(orien(a, b, s.a));
int s2 = sgn(orien(a, b, s.b));
int s3 = sgn(orien(s.a, s.b, a));
int s4 = sgn(orien(s.a, s.b, b));
if (s1 * s2 < 0 && s3 * s4 < 0) return true;
return false;
}
};
ostream& operator<<(ostream& os, point p) {
return os << "(" << p.x << "," << p.y << ")";
}

```

6 Graph

6.1 Articulation Bridges [41 lines] - b120c1d4

```

const int N = 2e5 + 5;
vector < pair < int, int >> g[N];
int vis[N], st[N], low[N];
int clk, n;
vector < pair < int, int >> bridges;

void dfs(int u, int p, int edg) {
vis[u] = 1;
++clk;
st[u] = clk;
low[u] = clk;
for (auto[v, id]: g[u]) {
// handled parallel edges between u, v
if (v == p && id == edg) continue;
if (vis[v]) {
low[u] = min(low[u], st[v]);
} else {
dfs(v, u, id);
low[u] = min(low[u], low[v]);
if (st[u] < low[v]) {
// edge u, v has bridge
bridges.push_back({
u,

```

```

v
});
}
}
}
}
void find_bridges() {
clk = 0;
for (int i = 1; i <= n; i++) {
vis[i] = 0;
st[i] = low[i] = -1;
}
for (int i = 1; i <= n; i++) {
if (!vis[i]) {
dfs(i, 0, -1);
}
}
}
}

```

6.2 Articulation Points [40 lines] - 94a1ef65

```

const int N = 2e5 + 5;
vector < int > g[N];
int vis[N], st[N], low[N], adjComp[N];
int clk, n;

void dfs(int u, int p) {
vis[u] = 1;
++clk;
st[u] = clk;
low[u] = clk;
int child = 0;
for (int v: g[u]) {
if (v == p) continue;
if (vis[v]) {
low[u] = min(low[u], st[v]);
} else {
dfs(v, u);
low[u] = min(low[u], low[v]);
if (low[v] >= st[u] && p != 0) {
adjComp[u]++;
}
child++;
}
}
if (p == 0 && child > 1) {
adjComp[u] = child - 1;
}
}
}
void find_vertices() {
clk = 0;
for (int i = 1; i <= n; i++) {
vis[i] = 0;
st[i] = low[i] = -1;
}
for (int i = 1; i <= n; i++) {
if (!vis[i]) {
dfs(i, 0);
}
}
}
}

```

6.3 Bellmanford [22 lines] - b8e770fd

```

void bellmanFord(int num_of_nd, int src) {
dist[src] = 0;
for (int step = 0; step < num_of_nd; step) {

```

```

for (int i = 1; i <= num_of_nd; i++) {
    for (auto it : adj[i]) {
        int u = i;
        int v = it.first;
        int wt = it.second;
        if (dist[u] != inf && ((dist[u] + wt) <
            dist[v])) {
            if (step == num_of_nd - 1) {
                cout << "Negative cycle found\n ";
                return;
            }
            dist[v] = dist[u] + wt;
            parent[v] = u;
        }
    }
}
for (int i = 1; i <= num_of_nd; i++) cout << dist[i]
    << " ";
cout << endl;
}

```

6.4 Block Cut Tree [83 lines] - b31a5c97

```
const int N = 2e5 + 5;
```

```

vector<int> g[N], bct[2 * N];
int vis[N], low[N], disc[N], is_art[N];
stack<int> stk;
vector<int> block_of[N];
int clk, n, m, bct_nodes, root;

```

```

void dfs(int u, int p) {
    vis[u] = 1;
    disc[u] = low[u] = ++clk;
    stk.push(u);
    int child = 0;

    for (int v : g[u]) {
        if (v == p) continue;
        if (!vis[v]) {
            child++;
            dfs(v, u);
            low[u] = min(low[u], low[v]);

            if ((p == -1 && child > 1) || (p != -1 && low[v]
                >= disc[u])) {
                is_art[u] = 1;
                vector<int> block;
                while (stk.top() != v) {
                    block.push_back(stk.top());
                    stk.pop();
                }
                block.push_back(stk.top());
                stk.pop();
                block.push_back(u);

                int block_id = ++bct_nodes;
                for (int x : block) {
                    block_of[x].push_back(block_id);
                    if (is_art[x]) {
                        bct[x].push_back(block_id);
                        bct[block_id].push_back(x);
                    }
                }
            }
        }
    }
}

```

```

        low[u] = min(low[u], disc[v]);
    }
}

void build_bct() {
    clk = 0;
    bct_nodes = n;
    for (int i = 1; i <= n; i++) {
        vis[i] = is_art[i] = 0;
        block_of[i].clear();
        bct[i].clear();
    }
    for (int i = n + 1; i <= 2 * n; i++) bct[i].clear();

    for (int i = 1; i <= n; i++) {
        if (!vis[i]) {
            dfs(i, -1);
            if (!stk.empty()) {
                int block_id = ++bct_nodes;
                while (!stk.empty()) {
                    int x = stk.top();
                    stk.pop();
                    block_of[x].push_back(block_id);
                    if (is_art[x]) {
                        bct[x].push_back(block_id);
                        bct[block_id].push_back(x);
                    }
                }
            }
        }
    }

    root = n + 1;
    for (int i = 1; i <= n; i++) {
        if (is_art[i]) {
            root = i;
            break;
        }
    }
}

```

6.5 Centroid Decomposition [30 lines] - 2ab608d6

```

const int N = 1e5 + 5;
vector<int> g[N];
int sz[N], dead[N], cenpar[N];
void dfs_sz(int u, int p) {
    sz[u] = 1;
    for (int v : g[u]) {
        if (v == p || dead[v]) continue;
        dfs_sz(v, u);
        sz[u] += sz[v];
    }
}

int find_centroid(int num, int u, int p) {
    for (int v : g[u]) {
        if (v != p && !dead[v] && 2 * sz[v] > num) {
            return find_centroid(num, v, u);
        }
    }
    return u;
}

void decompose(int u, int p) {
    dfs_sz(u, p);
    int cent = find_centroid(sz[u], u, p);
    dead[cent] = true;
}

```

```

cenpar[cent] = p;
for (int v : g[cent]) {
    if (!dead[v]) {
        decompose(v, cent);
    }
}
}

```

6.6 Dijkstra [22 lines] - 3621521c

```

void Dijkstra(int start) {
    // vector<pair<int, int>> adj[N];
    priority_queue<pair<int, int>, vector<pair<int,
        int>>, greater<pair<int, int>>> pq;
    pq.push({0, start});
    while (!pq.empty()) {
        auto it = pq.top();
        pq.pop();
        int wt = it.first;
        int u = it.second;
        if (vis[u])
            continue;
        vis[u] = 1;
        for (pair<int, int> i : adj[u]) {
            int adjWt = i.second;
            int adjNode = i.first;
            if (dist[adjNode] > wt + adjWt) {
                dist[adjNode] = wt + adjWt;
                pq.push({dist[adjNode], adjNode});
            }
        }
    }
}

```

6.7 Eulerian Circuit [16 lines] - b13e8b7b

```

unordered_map<int, int> Start, End, Val;
unordered_map<int, pair<int, int>> Range;
int start = 0;
void dfs(int node) {
    visited[node] = true;
    Start[node] = start++;
    for (auto child : adj[node]) {
        if (!visited[child]) dfs(child);
    }
    End[node] = start - 1;
}
dfs(1);
vector<int> FlatArray(start + 5);
for (auto i : Start) {
    FlatArray[i.second] = Val[i.first];
    Range[i.first] = {i.second, End[i.first]};
}

```

6.8 Floyd Warshall [13 lines] - 7e17addb

```

const int inf = 1e9;
const int MAXN = 505;
int dist[MAXN][MAXN];
void floydWarshall(int n) {
    for (int k = 0; k < n; ++k) {
        for (int i = 0; i < n; ++i) {
            for (int j = 0; j < n; ++j) {
                if (dist[i][k] < inf && dist[k][j] < inf)
                    dist[i][j] = min(dist[i][j], dist[i][k] +
                        dist[k][j]);
            }
        }
    }
}

```

6.9 Heavy Light Decomposition [103 lines] - ac779cb8

```

vector<pair<int, int>> g[N];
int edge_to_ch[N];
int par[N], dep[N], sz[N];

void dfs(int u, int p = 0) {
    sz[u] = 1, par[u] = p;
    dep[u] = dep[p] + 1;
    int mx = 0;
    for (auto &[v, idx]: g[u]) {
        if (v == p) continue;
        edge_to_ch[idx] = v;
        dfs(v, u);
        sz[u] += sz[v];
        if (sz[v] > mx) {
            mx = sz[v];
            swap(v, g[u][0].first);
        }
    }
}

int T, head[N], st[N], en[N];

void dfs_hld(int u, int p = 0) {
    st[u] = ++T;
    head[u] = (p != 0 && g[p][0].first == u) ? head[p] :
        u;
    for (auto [v, idx]: g[u]) {
        if (v == p) continue;
        dfs_hld(v, u);
    }
    en[u] = T;
}

int lca(int a, int b) {
    for (; head[a] != head[b]; b = par[head[b]]) {
        if (dep[head[a]] > dep[head[b]]) swap(a, b);
    }
    if (dep[a] > dep[b]) swap(a, b);
    return a;
}

int n;
// process node u upto it's ancestor a
// if excl is true, a won't process
i64 chain_process(int a, int u, bool excl = false) {
    i64 ans = 0;
    for (; head[u] != head[a]; u = par[head[u]]) {
        ans = max(ans, query(1, 1, n, st[head[u]],
            st[u]));
    }
    ans = max(ans, query(1, 1, n, st[a] + excl, st[u]));
    return ans;
}

// process path from node a to b
// if excl is true, lca won't process
i64 path_process(int a, int b, bool excl = false) {
    i64 ans = 0;
    for (; head[a] != head[b]; b = par[head[b]]) {
        if (dep[head[a]] > dep[head[b]]) swap(a, b);
        ans = max(ans, query(1, 1, n, st[head[b]], st[b]));
    }
    if (dep[a] > dep[b]) swap(a, b);
    ans = max(ans, query(1, 1, n, st[a] + excl, st[b]));
    return ans;
}

// update path from node u to v
// if excl is true, lca won't update

```

```

void path_update(int a, int b, int val, bool excl =
    false) {
    for (; head[a] != head[b]; b = par[head[b]]) {
        if (dep[head[a]] > dep[head[b]]) swap(a, b);
        update(1, 1, n, st[head[b]], st[b], val);
    }
    if (dep[a] > dep[b]) swap(a, b);
    update(1, 1, n, st[a] + excl, st[b], val);
}

/*
    dfs(1);
    head[1] = 1;
    dfs_hld(1);
    build(1, 1, n);
*/
void solve() {
    cin >> n;
    int q;
    cin >> q;
    for (int i = 1; i < n; i++) {
        int u, v, c;
        cin >> u >> v >> c;
        g[u].push_back({v, i});
        g[v].push_back({u, i});
        edge_cost[i] = c;
    }
    dfs(1);
    head[1] = 1;
    dfs_hld(1);
    for (int i = 1; i < n; i++) {
        int u = edge_to_ch[i];
        arr[st[u]] = edge_cost[i];
    }
    build(1, 1, n);
    while (q--) {
        int u, v, val;
        cin >> u >> v >> val;
        path_update(u, v, val, true);
        cout << path_process(u, v, true) << '\n';
    }
}

```

6.10 K'th Shortest path [40 lines] - 5a50a704

```

int m, n, deg[MM], source, sink, K, val[MM] [12];
struct edge {
    int v, w;
} adj[MM] [500];
struct info {
    int v, w, k;
    bool operator<(const info &b) const {
        return w > b.w;
    }
};
priority_queue<info, vector<info>> Q;
void kthBestShortestPath() {
    int i, j;
    info u, v;
    for (i = 0; i < n; i++)
        for (j = 0; j < K; j++) val[i][j] = inf;
    u.v = source, u.k = 0, u.w = 0;
    Q.push(u);
    while (!Q.empty()) {
        u = Q.top();
        Q.pop();
        for (i = 0; i < deg[u.v]; i++) {
            v.v = adj[u.v][i].v;

```

```

            int cost = adj[u.v][i].w + u.w;
            for (v.k = u.k; v.k < K; v.k++) {
                if (cost == inf) break;
                if (val[v.v][v.k] > cost) {
                    swap(cost, val[v.v][v.k]);
                    v.w = val[v.v][v.k];
                    Q.push(v);
                    break;
                }
            }
            for (v.k++; v.k < K; v.k++) {
                if (cost == inf) break;
                if (val[v.v][v.k] > cost) swap(cost, val[v.v][v.k]);
            }
        }
    }
}

```

6.11 Kruskal [13 lines] - 7c746046

```

vector<pair<int, pair<int, int>>> Kruskal(
    vector<pair<int, pair<int, int>>> &edges, int n) {
    sort(edges.begin(), edges.end());
    vector<pair<int, pair<int, int>>> ans;
    DisjointSet D(n);
    for (auto it : edges) {
        if (D.findUPar(it.second.first) !=
            D.findUPar(it.second.second)) {
            ans.push_back({it.first, {it.second.first,
                it.second.second}});
            D.unionBySize(it.second.first, it.second.second);
        }
    }
    return ans;
}

```

6.12 LCA using Segment Tree [89 lines] - fa80d47b

```

struct LCA {
    vector<int> height, euler, first, segtree, parent;
    vector<bool> visited;
    vector<vector<int>> jump;

    int n;

    LCA(vector<vector<int>> &adj, int root = 0) {
        n = adj.size();
        height.resize(n);
        first.resize(n);
        parent.resize(n);
        euler.reserve(n * 2);
        visited.assign(n, false);
        dfs(adj, root);
        int m = euler.size();
        segtree.resize(m * 4);
        build(1, 0, m - 1);

        jump.resize(n, vector<int>(32, -1));

        for (int i = 0; i < n; i++) {
            jump[i][0] = parent[i];
        }

        for (int j = 1; j < 20; j++) {
            for (int i = 0; i < n; i++) {
                int mid = jump[i][j - 1];
                if (mid != -1) jump[i][j] = jump[mid][j - 1];
            }
        }
    }
}

```

```

    }
}

void dfs(vector<vector<int>> &adj, int node, int h = 0) {
    visited[node] = true;
    height[node] = h;
    first[node] = euler.size();
    euler.push_back(node);
    for (auto to : adj[node]) {
        if (!visited[to]) {
            parent[to] = node;
            dfs(adj, to, h + 1);
            euler.push_back(node);
        }
    }
}

void build(int node, int b, int e) {
    if (b == e) {
        segtree[node] = euler[b];
    } else {
        int mid = (b + e) / 2;
        build(node << 1, b, mid);
        build(node << 1 | 1, mid + 1, e);
        int l = segtree[node << 1], r = segtree[node << 1 | 1];
        segtree[node] = (height[l] < height[r]) ? l : r;
    }
}

int query(int node, int b, int e, int L, int R) {
    if (b > R || e < L)
        return -1;
    if (b >= L && e <= R)
        return segtree[node];
    int mid = (b + e) >> 1;

    int left = query(node << 1, b, mid, L, R);
    int right = query(node << 1 | 1, mid + 1, e, L, R);
    if (left == -1)
        return right;
    if (right == -1)
        return left;
    return height[left] < height[right] ? left : right;
}

int lca(int u, int v) {
    int left = first[u], right = first[v];
    if (left > right)
        swap(left, right);
    return query(1, 0, euler.size() - 1, left, right);
}

int kthParent(int u, int k) {
    for(int i = 20; i >= 0; i--) {
        if(k & (1LL << i)) u = jump[u][i];
    }
    return u;
}
};

```

6.13 LCA [40 lines] - e4c6dffd

```

const int N = 1e5 + 5, LG = 17;
vector<int> g[N];
int depth[N], parent[N][LG];

```

```

void dfs(int u, int p) {
    depth[u] = depth[p] + 1;
    parent[u][0] = p;
    for (int i = 1; i < LG; i++) {
        parent[u][i] = parent[parent[u][i - 1]][i - 1];
    }
    for (int v : g[u]) {
        if (v == p) continue;
        dfs(v, u);
    }
}

int lca(int u, int v) {
    if (depth[u] < depth[v]) swap(u, v);
    int diff = depth[u] - depth[v];
    for (int i = 0; i < LG; i++) {
        if (diff >> i & 1) {
            u = parent[u][i];
        }
    }
    if (u == v) return u;
    for (int i = LG - 1; i >= 0; i--) {
        if (parent[u][i] != parent[v][i]) {
            u = parent[u][i];
            v = parent[v][i];
        }
    }
    return parent[u][0];
}

int dist(int u, int v) { return depth[u] + depth[v] - 2 * depth[lca(u, v)]; }
int kthParent(int u, int k) {
    for (int i = 0; i < LG; i++) {
        if (k >> i & 1) {
            u = parent[u][i];
        }
    }
    return u;
}

```

6.14 SCC [57 lines] - 060054f3

```

vector<bool> visited; // keeps track of which vertices
                      // are already visited

// runs depth first search starting at vertex v.
// each visited vertex is appended to the output vector
// when dfs leaves it.
void dfs(int v, vector<vector<int>> const &adj,
         vector<int> &output) {
    visited[v] = true;
    for (auto u : adj[v])
        if (!visited[u])
            dfs(u, adj, output);
    output.push_back(v);
}

// input: adj -- adjacency list of G
// output: components -- the strongly connected
//         components in G
// output: adj_cond -- adjacency list of G^SCC (by root
//         vertices)
void scc(vector<vector<int>> const &adj,
         vector<vector<int>> &components,
         vector<vector<int>> &adj_cond) {
    int n = adj.size();
    components.clear(), adj_cond.clear();
}

```

```

vector<int> order; // will be a sorted list of G's
                  // vertices by exit time

visited.assign(n, false);

// first series of depth first searches
for (int i = 0; i < n; i++)
    if (!visited[i])
        dfs(i, adj, order);

// create adjacency list of G^T
vector<vector<int>> adj_rev(n);
for (int v = 0; v < n; v++)
    for (int u : adj[v])
        adj_rev[u].push_back(v);

visited.assign(n, false);
reverse(order.begin(), order.end());

vector<int> roots(n, 0); // gives the root vertex of a
                        // vertex's SCC

// second series of depth first searches
for (auto v : order)
    if (!visited[v]) {
        std::vector<int> component;
        dfs(v, adj_rev, component);
        components.push_back(component);
        int root = *min_element(begin(component),
                                end(component));
        for (auto u : component)
            roots[u] = root;
    }

// add edges to condensation graph
adj_cond.assign(n, {});
for (int v = 0; v < n; v++)
    for (auto u : adj[v])
        if (roots[v] != roots[u])
            adj_cond[roots[v]].push_back(roots[u]);
}

```

6.15 SPFA $O(V \cdot E)$ [57 lines] - 7cd7bdcb

```

int q[3001] = {0}; // queue for node
int d[1001] = {0}; // record shortest path
from start to ith node bool f[1001] = {0};
int a[1001][1001] = {0}; // adjacency list
int w[1001][1001] = {0}; // adjacency matrix
int main(void) {
    int n = 0, m = 0;
    cin >> n >> m;
    for (int i = 1; i <= m; i++) {
        int x = 0, y = 0, z = 0;
        cin >> x >> y >> z;
        // node x to node y has weight z
        a[x][0]++;
        a[x][a[x][0]] = y;
        w[x][y] = z;
        /*
        // for undirected graph
        a[x][0]++;
        a[y][a[y][0]] = x;
        w[y][x] = z;
        */
    }
    int s = 0, e = 0;
}

```

```

cin >> s >> e; // s: start, e: end
SPFA(s);
cout << d[e] << endl;
return 0;
}

void SPFA(int v0) {
    int t, h, u, v;
    for (int i = 0; i < 1001; i++) d[i] = INT_MAX;
    for (int i = 0; i < 1001; i++) f[i] = false;
    d[v0] = 0;
    h = 0;
    t = 1;
    q[1] = v0;
    f[v0] = true;
    while (h != t) {
        h++;
        if (h > 3000) h = 1;
        u = q[h];
        for (int j = 1; j <= a[u][0]; j++) {
            v = a[u][j];
            if (d[u] + w[u][v] < d[v]) // change to > if
                calculating longest path
            {
                d[v] = d[u] + w[u][v];
                if (!f[v]) {
                    t++;
                    if (t > 3000) t = 1;
                    q[t] = v;
                    f[v] = true;
                }
            }
        }
        f[u] = false;
    }
}

```

6.16 Topological Sort [33 lines] - 3ddc7df6

```

vector<int> topologicalSort(int V, vector<vector<int>>&
    g) {
    vector<int> inDegree(V, 0);
    vector<int> result;
    queue<int> q;
    for (int u = 0; u < V; u++) {
        for (int v : g[u]) {
            inDegree[v]++;
        }
    }
    for (int i = 0; i < V; i++) {
        if (inDegree[i] == 0) {
            q.push(i);
        }
    }
    while (!q.empty()) {
        int u = q.front();
        q.pop();
        result.push_back(u);
        for (int v : g[u]) {
            inDegree[v]--;
            if (inDegree[v] == 0) {
                q.push(v);
            }
        }
    }
    // You may need to check inDegree of all the vertices
    // is 0
    if (result.size() != V) {

```

```

        cout << "Graph contains a cycle, topological sort
            not possible!" << endl;
        return {};
    }

    return result;
}

```

6.17 Tree Rerooting [99 lines] - c3cafbac

```

namespace reroot {
    const auto exclusive = [] (const auto& a, const auto&
        base,
                                const auto& merge_into, int
                                vertex) {

        int n = (int)a.size();
        using Aggregate = std::decay_t<decltype(base)>;
        std::vector<Aggregate> b(n, base);
        for (int bit = (int)std::lg(n); bit >= 0; --bit) {
            for (int i = n - 1; i >= 0; --i) b[i] = b[i >> 1];
            int sz = n - (n & !bit);
            for (int i = 0; i < sz; ++i) {
                int index = (i >> bit) ^ 1;
                b[index] = merge_into(b[index], a[i], vertex, i);
            }
        }
        return b;
    };

    // MergeInto : Aggregate * Value * Vertex(int) *
    // EdgeIndex(int) -> Aggregate
    // Base : Vertex(int) -> Aggregate
    // FinalizeMerge : Aggregate * Vertex(int) *
    // EdgeIndex(int) -> Value
    const auto rerooter = [] (const auto& g, const auto&
        base,
                                const auto& merge_into, const
                                auto& finalize_merge) {

        int n = (int)g.size();
        using Aggregate = std::decay_t<decltype(base(0))>;
        using Value =
            std::decay_t<decltype(finalize_merge(base(0), 0,
                0))>;
        std::vector<Value> root_dp(n, dp(n));
        std::vector<std::vector<Value>> edge_dp(n,
            redge_dp(n);

        std::vector<int> bfs, parent(n);
        bfs.reserve(n);
        bfs.push_back(0);
        for (int i = 0; i < n; ++i) {
            int u = bfs[i];
            for (auto v : g[u]) {
                if (parent[u] == v) continue;
                parent[v] = u;
                bfs.push_back(v);
            }
        }

        for (int i = n - 1; i >= 0; --i) {
            int u = bfs[i];
            int p_edge_index = -1;
            Aggregate aggregate = base(u);
            for (int edge_index = 0; edge_index <
                (int)g[u].size(); ++edge_index) {
                int v = g[u][edge_index];
                if (parent[u] == v) {
                    p_edge_index = edge_index;

```

```

                continue;
            }
            aggregate = merge_into(aggregate, dp[v], u,
                edge_index);
        }
        dp[u] = finalize_merge(aggregate, u, p_edge_index);
    }

    for (auto u : bfs) {
        dp[parent[u]] = dp[u];
        edge_dp[u].reserve(g[u].size());
        for (auto v : g[u]) edge_dp[u].push_back(dp[v]);
        auto dp_exclusive = exclusive(edge_dp[u], base(u),
            merge_into, u);
        redge_dp[u].reserve(g[u].size());
        for (int i = 0; i < (int)dp_exclusive.size(); ++i) {
            auto merge_value =
                finalize_merge(dp_exclusive[i], u, i);
            redge_dp[u].push_back(merge_value);
        }
        root_dp[u] = finalize_merge(
            n > 1 ? merge_into(dp_exclusive[0],
                edge_dp[u][0], u, 0) : base(u), u,
            -1);
        for (int i = 0; i < (int)g[u].size(); ++i) {
            dp[g[u][i]] = redge_dp[u][i];
        }
    }

    return std::make_tuple(std::move(root_dp),
        std::move(edge_dp),
                                std::move(redge_dp));
};

// namespace reroot

void solve() {
    using Aggregate = int;
    using Value = int;

    auto base = [] (int vertex) -> Aggregate { return 0; };
    auto merge_into = [] (Aggregate vertex_dp, Value
        neighbor_dp, int vertex,
                                int edge_index) -> Aggregate {
        return vertex_dp + std::max(neighbor_dp, 0);
    };
    auto finalize_merge = [&] (Aggregate vertex_dp, int
        vertex,
                                int edge_index) -> Value {
        return vertex_dp + 2 * color[vertex] - 1;
    };

    auto [reroot_result, edge_dp, redge_dp] =
        reroot::rerooter(g, base, merge_into,
            finalize_merge);

    for (auto dp : reroot_result) {
        std::cout << dp << ' ';
    }
    std::cout << '\n';
}

7 Misc

7.1 Bit count in O(1) [5 lines] - 8f60ac14
int BitCount(unsigned int u) {
    unsigned int uCount;

```

```
uCount = u - ((u >> 1) & 033333333333) - ((u >> 2) &
011111111111);
return ((uCount + (uCount >> 3)) & 030707070707) % 63;
}
```

7.2 Bit hacks [16 lines] - 96eab638

```
# x & -x is the least bit in x.
# iterate over all the subsets of the mask
for (int s=m; ; s=(s-1)&m) {
    ... you can use s ...
    if (s==0) break;
}
# c = x&-x, r = x+c; (((r^x) >> 2)/c) | r is the
next number after x with the same number of bits set.
# __builtin_popcount(x) //number of ones in binary
__builtin_popcountll(x) // for long long
# __builtin_clz(x) // number of leading zeros
__builtin_ctz(x) // number of trailing zeros, they
also have long long version
# bitset<N> b; //N is size of bitset
b.count(); // return number of bits set 0(N / 64)
b.to_string(); // return string representation of
bitset
b.any() // return true if any bit is set 0(N / 64)
```

7.3 Bitset C++ [13 lines] - 28766a3c

```
bitset<17>BS;
BS[1] = BS[7] = 1;
cout<<BS._Find_first()<<endl; // prints 1
bs._Find_next(idx). This function returns first set bit
after index idx.for example:
```

```
bitset<17>BS;
BS[1] = BS[7] = 1;
cout<<BS._Find_next(1)<<' '<<BS._Find_next(3)<<endl; //
prints 7,7
So this code will print all of the set bits of BS:
```

```
for(int i=BS._Find_first();i< BS.size();i =
BS._Find_next(i))
cout<<i<<endl;
//Note that there isn't any set bit after idx,
BS._Find_next(idx) will return BS.size(); same as
calling BS._Find_first() when bitset is clear;
```

7.4 Knight Moves [2 lines] - 6c4e6fbc

```
int X[8]={2,1,-1,-2,-2,-1,1,2};
int Y[8]={1,2,2,1,-1,-2,-2,-1};
```

7.5 Random Generator [6 lines] - 2b02ac44

```
#define accuracy
chrono::steady_clock::now().time_since_epoch().count()
mt19937 rng(accuracy);
int rand(int l, int r) {
    uniform_int_distribution<int> ludo(l, r);
    return ludo(rng);
}
```

7.6 Special DS [23 lines] - ef50f014

```
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
using namespace __gnu_pbds;
template <typename T> using o_set = tree<T, null_type,
less<T>, rb_tree_tag,
tree_order_statistics_node_update>;
template <typename T> using o_multiset = tree<pair<T,
int>, null_type,
```

```
less<pair<T, int>>, rb_tree_tag,
tree_order_statistics_node_update>;
/*
o_set<int> st;
*st.find_by_order(0); // 0-th element
o_multiset<int> mst;
int timer = 0; // use a global/local timer for unique
IDs
mst.insert({5, timer++});
mst.erase(mst.lower_bound({5, 0})); // Erases exactly
ONE instance of 5
mst.order_of_key({5, 0}); // strictly less than 5
*/
```

```
// Faster hash
gp_hash_table<int, int> mp;
// Or
unordered_map<int, int> mp;
mp.reserve(n * 2);
mp.max_load_factor(0.7);
```

7.7 Usefull Things [9 lines] - c67addfa

```
C++:
#pragma GCC optimize("Ofast")
#pragma GCC target("avx,avx2,fma")
ios_base::sync_with_stdio(false), cin.tie(nullptr),
cout.tie(nullptr);
freopen("input.txt", "r", stdin);
Python:
import sys
input = sys.stdin.readline
sys.stdout.write("-----")
```

7.8 VScode setup [7 lines] - 3e225a41

```
{
    "key": "f5",
    "command": "workbench.action.terminal.sendSequence",
    "args": {
        "text": "clear && g++
${fileBasenameNoExtension}.cpp -o
${fileBasenameNoExtension} &&
./${fileBasenameNoExtension} < in.txt >
out.txt\n"
    }
} // need "files.autoSaveDelay": 100
```

7.9 stress [25 lines] - 4a84e7fd

```
#!/usr/bin/env bash
g++ -g "$1".cpp -DONPC -o "$1"
g++ -g "$2".cpp -DONPC -o "$2"
g++ -g "$3".cpp -DONPC -o "$3"
for ((testNum=0;testNum<$4;testNum++))
do
    ./$3 > stdinput
    ./$2 < stdinput > outSlow
    ./$1 < stdinput > outWrong
    H1=`md5sum outWrong`
    H2=`md5sum outSlow`
    if !(cmp -s "outWrong" "outSlow")
    then
        echo "Error found!"
        echo "Input:"
        cat stdinput
        echo "Wrong Output:"
        cat outWrong
        echo "Slow Output:"
        cat outSlow
```

```
exit
fi
done
echo Passed $4 tests
# ./stress.sh wrong correct gen times
```

7.10 vimrc [12 lines] - 1f47305c

```
"install xclip, vim-gtk3
set nocp ai bs=2 hls ic is lbr ls=2 mouse=a nu ru sc scs
smd so=3 sw=2 ts=2 rnu
filetype plugin indent on
syn on
map gA m'ggVG"+y''
inoremap {<CR> {<CR>><Esc>k<CR>
nnoremap = mzgg=G`z
vnoremap <C-k> :s/\s*\zs\\/\ /<CR>:nohl<CR>
nnoremap <C-k> :s/\s*\zs\\/\ /<CR>:nohl<CR>
vnoremap <C-l> :s/\s*\zs\\/\ /<CR>:nohl<CR>
nnoremap <C-l> :s/\s*\zs\\/\ /<CR>:nohl<CR>
autocmd FileType cpp map <F9> :w<CR> :!clear; g++
--std=c++17 % -DONPC -o %:r && ./%:r<CR>
```

8 Number Theory

8.1 10-ary to m-ary [22 lines] - e6c26ef1

```
char a[16]={ '0','1','2','3','4','5','6','7',
'8','9','A','B','C','D','E','F'};
string tenToM(int n, int m){
    int temp=n;
    string result="";
    while (temp!=0){
        result=a[temp%m]+result;
        temp/=m;
    }
    return result;
}
// m-ary to 10-ary
string num = "0123456789ABCDE";
int mToTen(string n, int m){
    int multi=1;
    int result=0;
    for (int i=n.size()-1; i>=0; i--) {
        result += num.find(n[i])*multi;
        multi*=m;
    }
    return result;
}
```

8.2 Basis Vector [89 lines] - 409325f7

```
// T: Data type (int or long long), B: Max bits (31 for
int, 62 for long long)
template<typename T = long long, int B = 62>
struct Basis {
    T basis[B];
    int sz, n; //sz: Number of independent basis vectors
(rank)
    Basis() {
        memset(basis, 0, sizeof(basis));
        sz = 0; n = 0;
    }
    bool insert(T x) {
        n++;
        for (int i = B - 1; i >= 0; i--) {
            if (x >> i & 1) {
                if (!basis[i]) {
                    basis[i] = x;
```

```

        sz++;
        return true;
    }
    x ^= basis[i];
}
return false;
}
// Checks if there is any subset whose XOR sum
// equals exactly x
bool can(T x) {
    for (int i = B - 1; i >= 0; i--) {
        x = min(x, x ^ basis[i]);
    }
    return x == 0;
}
// Returns the maximum subset XOR sum
T max_xor(T x = 0) {
    for (int i = B - 1; i >= 0; i--) {
        x = max(x, x ^ basis[i]);
        //x = min(x, x ^ basis[i]); //For minimum
        //subset XOR sum
    }
    return x;
}
// Finds the k-th DISTINCT subset XOR sum in
// strictly increasing order (1-based, k=1 returns
// 0)
T kth(unsigned long long k) {
    if (k < 1 || k > (1ULL << sz)) return -1;
    T x = 0;
    unsigned long long cnt = (1ULL << sz);
    for (int i = B - 1; i >= 0; i--) {
        if (basis[i]) {
            cnt >>= 1;
            if (k > cnt) {
                if (!(x >> i & 1)) x ^= basis[i]; //
                // Force the bit ON
                k -= cnt;
            } else {
                if (x >> i & 1) x ^= basis[i]; //
                // Force the bit OFF
            }
        }
    }
    return x;
}
// Returns the number of DISTINCT subset XOR sums
// strictly less than x
unsigned long long count_lt(T x) {
    if (x < 0) return 0;
    unsigned long long ans = 0, cnt = (1ULL << sz);
    T mask = 0;
    for (int i = B - 1; i >= 0; i--) {
        if (basis[i]) {
            cnt >>= 1;
            if (x >> i & 1) {
                ans += cnt;
                if (!(mask >> i & 1)) mask ^= basis[i];
            } else {
                if (mask >> i & 1) mask ^= basis[i];
            }
        }
    }
    if ((x >> i & 1) != (mask >> i & 1)) {
        return (x >> i & 1) ? ans + cnt : ans;
    }
}

```

```

    }
    return ans;
}
};
/* 1. SUBSET COUNTING MATH:
- Valid combinations that XOR to 0: 2^(n - sz)
- Valid non-empty combinations XOR to 0: (2^(n - sz))
- 1
- If can(X) is true, ways to form X: 2^(n - sz)
2. DISTINCT VS TOTAL SUBSETS:
- This struct works with DISTINCT XOR sums!
- There are exactly (1ULL << sz) distinct XOR sums.
- Every distinct XOR sum is formed by exactly 2^(n -
  sz) identical subsets.
- If question asks for K-th out of ALL subsets:
  Pass: K = ceil(K / 2^(n - sz)) into kth() */

```

8.3 Binary Exponentiation [9 lines] - c1fcbebe

```

int power(long long n, long long k, int mod = 1e9+7) {
    int ans = 1 % mod; n %= mod; if (n < 0) n += mod;
    while (k) {
        if (k & 1) ans = (long long) ans * n % mod;
        n = (long long) n * n % mod;
        k >>= 1;
    }
    return ans;
}

```

8.4 CRT [16 lines] - 0991117f

```

struct Congruence{
    long long a, m;
};
ll CRT(vector<Congruence> const &congruences){
    ll M = 1;
    for (auto const &congruence : congruences)
        M *= congruence.m;
    ll solution = 0;
    for (auto const &congruence : congruences){
        ll a_i = congruence.a;
        ll M_i = M / congruence.m;
        ll N_i = mod_inv(M_i, congruence.m);
        solution = (solution + a_i * M_i % M * N_i) % M;
    }
    return solution;
}

```

8.5 Catalan Numbers [8 lines] - 17405386

```

void catalan(int n) {
    int res = 1;
    cout << res << " ";
    for (int i = 1; i < n; i++) {
        res = (res * (4 * i - 2)) / (i + 1);
        cout << res << " ";
    }
}

```

8.6 Count 1s 0 to n [9 lines] - 6b5041db

```

int cntOnes(int n) {
    int cnt = 0;
    for (int i = 1; i <= n; i <= 1) {
        int x = (n + 1) / (i << 1);
        cnt += x * i;
        if ((n + 1) % i && n & i) cnt += (n + 1) % i;
    }
    return cnt;
}

```

8.7 Divisors multiple info [36 lines] - 3aff6f8b

```

constexpr int N = 1000005;

void Divisors(int n) {
    int sum = 1, total = 1;
    int mnP = INT_MAX, mxP = INT_MIN, cntP = 0, totalP = 0;
    for (int i = 0; i < N && Prime[i] * Prime[i] <= n; i++) {
        if (n % Prime[i] == 0) {
            mnP = min(mnP, Prime[i]);
            mxP = max(mxP, Prime[i]);
            int k = 0;
            cntP++;
            while (n % Prime[i] == 0) {
                k++;
                n /= Prime[i];
            }

            sum *= (k + 1); // NOD
            totalP += k;
            int s = 0, p = 1;
            while (k-- >= 0) {
                s += p;
                p *= Prime[i];
            };
            total *= s; // SOD
        }
    }
    if (n > 1) {
        cntP++, totalP++;
        sum *= 2;
        total *= (1 + n);
        mnP = min(mnP, n);
        mxP = max(mxP, n);
    }
    cout << mnP << " " << mxP << " " << cntP << " " <<
        totalP << " " << sum << " " <<
        << total << "\n";
}

```

8.8 Extended GCD [8 lines] - 5998ac10

```

// return {x,y} such that ax+by=gcd(a,b)
int exgcd(int a, int b, int &x, int &y) {
    if (b == 0) {
        x = 1; y = 0; return a; }
    int g = exgcd(b, a % b, y, x);
    y -= a / b * x;
    return g;
} // bezout's identity: a.x + b.y = gcd(a,b)

```

8.9 Find numbers in L to R divisible by all array elements [12 lines] - 12567a3c

```

solve(int* arr, int N, int L, int R) {
    int LCM = arr[0];
    for (int i = 1; i < N; i++) {
        LCM = (LCM * arr[i]) / (__gcd(LCM, arr[i]));
    }
    if ((LCM < L && LCM * 2 > R) || LCM > R) {
        return;
    }
    int k = (L / LCM) * LCM;
    if (k < L) k = k + LCM;
    for (int i = k; i <= R; i = i + LCM) cout << i << ' ';
}

```

8.10 GaussElimination [39 lines] - 8a474ce2

```
template<typename ld>
int gauss(vector<vector<ld>>& a, vector<ld>& ans) {
    const ld EPS = 1e-9;
    int n = a.size();///number of equations
    int m = a[0].size() - 1;///number of variables
    vector<int>where(m, -1);///indicates which row
contains the solution
    int row, col;
    for (col = 0, row = 0; col < m && row < n; ++col) {
        int sel = row;///which row contains the maximum
value/
        for (int i = row + 1; i < n; i++)
            if (abs(a[i][col]) > abs(a[sel][col]))
                sel = i;
        if (abs(a[sel][col]) < EPS) continue;///it's
basically 0.
        a[sel].swap(a[row]);///taking the max row up
        where[col] = row;
        ld t = a[row][col];
        for (int i = col; i <= m; i++) a[row][i] /= t;
        for (int i = 0; i < n; i++) {
            if (i != row) {
                ld c = a[i][col];
                for (int j = col; j <= m; j++)
                    a[i][j] -= a[row][j] * c;
            }
        }
        row++;
    }
    ans.assign(m, 0);
    for (int i = 0; i < m; i++)
        if (where[i] != -1)
            ans[i] = a[where[i]][m] / a[where[i]][i];
    for (int i = 0; i < n; i++) {
        ld sum = 0;
        for (int j = 0; j < m; j++)
            sum += ans[j] * a[i][j];
        if (abs(sum - a[i][m]) > EPS) ///L.H.S!=R.H.S
            ans.clear();///No solution
    }
    return row;
}
```

8.11 Largest Power of n! [11 lines] - ffed3d40*/// Returns largest power of p that divides n!*

```
int largestPower(int n, int p) {
    int res = 0;

    /// Calculate res = n/p + n/(p^2) + n/(p^3) + ....
    while (n > 0) {
        n /= p;
        res += n;
    }
    return res;
}
```

8.12 Leap Year [13 lines] - 8ff2b7cb

```
bool isLeap(int n){
    if (n%100==0)
        if (n%400==0) return true;
        else return false;
    if (n%4==0) return true;
    else return false;
}
/// Num of Leap year in between
int calNum(int year) {
```

```
    return (year / 4) - (year / 100) +
           (year / 400);
}
int leapNum(int l, int r) { return calNum(r) -
    calNum(--l);}
```

8.13 Logab [3 lines] - 1b0f688c

```
int logab (int a, int b){
    return log2(a) / log2(b);
}
```

8.14 Matrix [105 lines] - 0cf635bb

```
template<typename T>
struct Matrix {
    T MOD = 1e9 + 7;///change if necessary
    T add(T a, T b) const {
        T res = a + b;
        if (res >= MOD) return res - MOD;
        return res;
    }
    T sub(T a, T b) const {
        T res = a - b;
        if (res < 0) return res + MOD;
        return res;
    }
    T mul(T a, T b) const {
        T res = a * b;
        if (res >= MOD) return res % MOD;
        return res;
    }
    int R, C;
    vector<vector<T>>mat;
    Matrix(int _R = 0, int _C = 0) {
        R = _R, C = _C;
        mat.resize(R);
        for (auto& v : mat) v.assign(C, 0);
    }
    void print() {
        for (int i = 0; i < R; i++)
            for (int j = 0; j < C; j++)
                cout << mat[i][j] << " \n"[j == C - 1];
    }
    void createIdentity() {
        for (int i = 0; i < R; i++)
            for (int j = 0; j < C; j++)
                mat[i][j] = (i == j);
    }
    Matrix operator+(const Matrix& o) const {
        Matrix res(R, C);
        for (int i = 0; i < R; i++)
            for (int j = 0; j < C; j++)
                res[i][j] = add(mat[i][j] + o.mat[i][j]);
    }
    Matrix operator-(const Matrix& o) const {
        Matrix res(R, C);
        for (int i = 0; i < R; i++)
            for (int j = 0; j < C; j++)
                res[i][j] = sub(mat[i][j] + o.mat[i][j]);
    }
    Matrix operator*(const Matrix& o) const {
        Matrix res(R, o.C);
        for (int i = 0; i < R; i++)
            for (int j = 0; j < o.C; j++)
                for (int k = 0; k < C; k++)
                    res.mat[i][j] = add(res.mat[i][j],
                        mul(mat[i][k], o.mat[k][j]));
        return res;
    }
```

```

    }
    Matrix pow(long long x) {
        Matrix res(R, C);
        res.createIdentity();
        Matrix<T> o = *this;
        while (x) {
            if (x & 1) res = res * o;
            o = o * o;
            x >>= 1;
        }
        return res;
    }
    Matrix inverse()///Only square matrix && non-zero
determinant
    {
        Matrix res(R, R + R);
        for (int i = 0; i < R; i++) {
            for (int j = 0; j < R; j++)
                res.mat[i][j] = mat[i][j];
            res.mat[i][R + i] = 1;
        }
        for (int i = 0; i < R; i++) {
            ///find row 'r' with highest value at [r][i]
            int tr = i;
            for (int j = i + 1; j < R; j++)
                if (abs(res.mat[j][i]) > abs(res.mat[tr][i]))
                    tr = j;
            ///swap the row
            res.mat[tr].swap(res.mat[i]);
            ///make 1 at [i][i]
            T val = res.mat[i][i];
            for (int j = 0; j < R + R; j++) res.mat[i][j] /=
                val;
            ///eliminate [r][i] from every row except i.
            for (int j = 0; j < R; j++) {
                if (j == i) continue;
                for (int k = R + R - 1; k >= i; k--) {
                    res.mat[j][k] -= res.mat[i][k] * res.mat[j][i]
                        / res.mat[i][i];
                }
            }
        }
        Matrix ans(R, R);
        for (int i = 0; i < R; i++)
            for (int j = 0; j < R; j++)
                ans.mat[i][j] = res.mat[i][R + j];
        return ans;
    }
};
/// Matrix<long long> base(2, 2);
/// base.mat[0][0] = 1LL; base.mat[0][1] = 1LL;
/// base.mat[1][0] = 1LL; base.mat[1][1] = 0LL;
/// Matrix<long long> result = base.pow(n - 1);
/// cout << result.mat[0][0] << '\n'; // nth Fibonacci
number
```

8.15 Miller-Rabin-Pollard-Rho [36 lines] - c62079b7

```
using u64 = uint64_t;
using u128 = __uint128_t;
u64 binpower(u64 base, u64 e, u64 mod) {
    u64 result = 1;
    base %= mod;
    while (e) {
        if (e & 1) result = (u128)result * base % mod;
        base = (u128)base * base % mod;
        e >>= 1;
    }
```

```

}
return result;
}
bool check_composite(u64 n, u64 a, u64 d, int s) {
    u64 x = binpower(a, d, n);
    if (x == 1 || x == n - 1) return false;
    for (int r = 1; r < s; r++) {
        x = (u128)x * x % n;
        if (x == n - 1) return false;
    }
    return true;
};
bool MillerRabin(u64 n, int iter = 5) { // returns true
    if n is probably prime, else returns false.
    if (n < 4) return n == 2 || n == 3;
    int s = 0;
    u64 d = n - 1;
    while ((d & 1) == 0) {
        d >>= 1;
        s++;
    }

    for (int i = 0; i < iter; i++) {
        int a = 2 + rand() % (n - 3);
        if (check_composite(n, a, d, s)) return false;
    }
    return true;
}

```

8.16 Mobius [12 lines] - f7c84b43

```

const int N = 11;
int mob[N];
void mobius() {
    mob[1] = 1;
    for (int i = 2; i < N; i++){
        mob[i]--;
        for (int j = i + i; j < N; j += i) {
            mob[j] -= mob[i];
        }
    }
}

```

8.17 Mod Inverse [5 lines] - 6e1326cf

```

int modInv(int a, int m) {
    int x, y; //if g==1 Inverse doesn't exist
    int g = gcdExt(a, m, x, y);
    return (x % m + m) % m;
}

```

8.18 Modular Operations [12 lines] - e4857b5b

```

int add(int x, int y) {
    x += y;
    if (x >= mod) x -= mod;
    if (x < 0) x += mod;
    return x;
}
int mul(int x, int y) {
    return (x%mod) * 1LL * (y%mod) % mod;
}
int divide(int x, int y) {
    return mul(x, power(y, mod - 2));
}

```

8.19 NOD of n! [13 lines] - e777f444

```

ull factorialDivisors(ull n) {
    ull result = 1;

```

```

    for (int i = 0; i < allPrimes.size(); i++) {
        ull p = allPrimes[i];
        ull exp = 0;
        while (p <= n) {
            exp = exp + (n / p);
            p = p * allPrimes[i];
        }
        result = result * (exp + 1);
    }
    return result;
}

```

8.20 No of Digits in n! in base B [7 lines] - 1f8efcc5

```

ll NoOfDigitInNFactInBaseB(ll N, ll B) {
    ll i;
    double ans = 0;
    for (i = 1; i <= N; i++) ans += log(i);
    ans = ans / log(B), ans = ans + 1;
    return (ll)ans;
}

```

8.21 Principle of Inclusion Exclusion [21 lines] - cb2ccfa4

```

// count the numbers between 1 and n (inclusive) that
// are not divisible by any
// of the integers in the given array a
// is n - (div by one number - div by two number + div
// by three number - ...)
int PIE(int div[], int n, int num) {
    int sum = 0;
    for (int msk = 1; msk < (1 << n); ++msk) {
        int bit_cnt = 0;
        int cur_lcm = 1;
        for (int i = 0; i < n; ++i) {
            if (msk & (1 << i)) {
                ++bit_cnt;
                cur_lcm = LCM(cur_lcm, div[i]);
            }
        }
        int cur = num / cur_lcm;
        if (bit_cnt & 1) sum += cur;
        else sum -= cur;
    }
    return num - sum;
}

```

8.22 Print Calander of Any Year [44 lines] - 1a53cdae

```

int dayNumber(int day, int month, int year) {
    static int t[] = {0, 3, 2, 5, 0, 3, 5, 1, 4, 6, 2, 4};
    year -= month < 3;
    return (year + year / 4 - year / 100 + year / 400 +
            t[month - 1] + day) % 7;
}
string getMonthName(int monthNumber) {
    string months[] = {"January", "February", "March",
                       "April", "May", "June", "July",
                       "August", "September", "October",
                       "November", "December"};
    return (months[monthNumber]);
}
int numberOfDays(int monthNumber, int year) {
    if (monthNumber == 1 && isLeapYear(year)) return 29;
    int monthDays[] = {31, 28, 31, 30, 31, 30, 31, 31,
                       30, 31, 30, 31};
    return (monthDays[monthNumber]);
}

```

```

}
void printCalendar(int year) {
    printf("    Calendar - %d\n\n", year);
    int days;
    int current = dayNumber(1, 1, year);
    // i/-> Iterate through all the months
    // j/-> Iterate through all the days of
    the month - i for (int i = 0; i < 12; i++) {
        days = numberOfDays(i, year);
        cout << "    |" << getMonthName(i).c_str() <<
            " |" << endl;
        printf("    Sun Mon Tue Wed Thu Fri
            Sat\n");
        int k;
        for (k = 0; k < current; k++)
            printf("    ");
        for (int j = 1; j <= days; j++) {
            printf("%4d", j);
            if (++k > 6) {
                k = 0;
                cout << endl;
            }
            if (k)
                cout << endl;
            cout <<
                "-----\n";
            current = k;
        }
    }
}

```

8.23 SOD, NOD Upto N [30 lines] - aa4e95d9

```

int SOD_upto_N(int N) { // sqrt(N)
    int res = 0;
    for (int i = 1; i <= N; i++) {
        int j = N / (N / i); // Last number with same
            quotient
        res += (N / i) * (i + j) * (j - i + 1) / 2;
        i = j;
    }
    return res;
}
int NOD_upto_N(ll N) { // sqrt(N)
    int res = 0;
    int u = sqrt(N);
    for (int i = 1; i <= u; i++) {
        res += (N / i) - i;
    }
    res = res * 2 + u;
    return res;
}
void NOD_per_number_upto_N(int n) { // n loglog(n)
    for (int i = 1; i <= n; i++) {
        for (int j = i; j <= n; j += i) {
            d[j]++;
            // d[j] += i // for sum of divisors
        }
    }
    for (int i = 1; i <= n; i++) {
        cout << d[i] << ' ';
    }
    return 0;
}

```

8.24 SPF [10 lines] - 0b6c01c3

```
int spf[N];
void buildSpf() {
    for (int i = 2; i < N; i++) {
        spf[i] = i;
    }
    for (ll i = 2; 1LL * i * i < N; i++)
        if (spf[i] == i)
            for (ll j = i * i; j < N; j += i)
                if (spf[j] == j) spf[j] = i;
}
```

8.25 Segmented Sieve [17 lines] - b1ac5ad7

```
void segmentedSieve(int L, int R) {
    bool isPrime[R - L + 1];
    for (int i = 0; i <= R - L + 1; i++) isPrime[i] = true;
    if (L == 1) isPrime[0] = false;
    for (int i = 0; primes[i] * primes[i] <= R; i++) {
        int curPrime = primes[i];
        int base = curPrime * curPrime;
        if (base < L) {
            base = ((L + curPrime - 1) / curPrime) * curPrime;
        }
        for (int j = base; j <= R; j += curPrime) isPrime[j - L] = false;
    }
    for (int i = 0; i <= R - L; i++) {
        if (isPrime[i] == true) cout << L + i << '\n';
    }
    cout << '\n';
}
```

8.26 Sieve Phi Mobius [13 lines] - fd92a8a5

```
const int N = 5000005;
int phi[N];
unsigned long long phiSum[N];
void phiCalc() {
    for (int i = 1; i < N; i++) phi[i] = i;
    for (int i = 2; i < N; i++) {
        if (phi[i] == i) {
            for (int j = i; j < N; j += i) {
                phi[j] -= phi[j] / i;
            }
        }
        for (int i = 2; i < N; i++) {
            phiSum[i] = (unsigned long long)phi[i] * (unsigned long long)phi[i] + phiSum[i - 1];
        }
    }
}
```

8.27 Sieve upto 1e9 [71 lines] - 5fa0292a

```
vector<int> sieve(const int N, const int Q = 17, const int L = 1 << 15) {
    static const int rs[] = {1, 7, 11, 13, 17, 19, 23, 29};
    struct P {
        P(int p) : p(p) {}
        int p; int pos[8];
    };
    auto approx_prime_count = [] (const int N) -> int {
        return N > 60184 ? N / (log(N) - 1.1) : max(1., N / (log(N) - 1.11)) + 1;
    };
    const int v = sqrt(N), vv = sqrt(v);
    vector<bool> isp(v + 1, true);
    for (int i = 2; i <= vv; ++i) if (isp[i]) {
        for (int j = i * i; j <= v; j += i) isp[j] = false;
    }
}
```

```
const int rsize = approx_prime_count(N + 30);
vector<int> primes = {2, 3, 5}; int psize = 3;
primes.resize(rsize);
```

```
vector<P> sprimes; size_t pbeg = 0;
int prod = 1;
for (int p = 7; p <= v; ++p) {
    if (!isp[p]) continue;
    if (p <= Q) prod *= p, ++pbeg, primes[psize++] = p;
    auto pp = P(p);
    for (int t = 0; t < 8; ++t) {
        int j = (p <= Q) ? p : p * p;
        while (j % 30 != rs[t]) j += p << 1;
        pp.pos[t] = j / 30;
    }
    sprimes.push_back(pp);
}
```

```
vector<unsigned char> pre(prod, 0xFF);
for (size_t pi = 0; pi < pbeg; ++pi) {
    auto pp = sprimes[pi]; const int p = pp.p;
    for (int t = 0; t < 8; ++t) {
        const unsigned char m = ~(1 << t);
        for (int i = pp.pos[t]; i < prod; i += p) pre[i] ^= m;
    }
}
const int block_size = (L + prod - 1) / prod * prod;
vector<unsigned char> block(block_size); unsigned char* pblock = block.data();
const int M = (N + 29) / 30;
```

```
for (int beg = 0; beg < M; beg += block_size, pblock -= block_size) {
    int end = min(M, beg + block_size);
    for (int i = beg; i < end; i += prod) {
        copy(pre.begin(), pre.end(), pblock + i);
    }
    if (beg == 0) pblock[0] ^= 0xFE;
    for (size_t pi = pbeg; pi < sprimes.size(); ++pi) {
        auto& pp = sprimes[pi];
        const int p = pp.p;
        for (int t = 0; t < 8; ++t) {
            int i = pp.pos[t]; const unsigned char m = ~(1 << t);
            for (; i < end; i += p) pblock[i] ^= m;
            pp.pos[t] = i;
        }
    }
    for (int i = beg; i < end; ++i) {
        for (int m = pblock[i]; m > 0; m &= m - 1) {
            primes[psize++] = i * 30 + rs[__builtin_ctz(m)];
        }
    }
    assert(psize <= rsize);
    while (psize > 0 && primes[psize - 1] > N) --psize;
    primes.resize(psize);
    return primes;
}
```

8.28 Sieve [16 lines] - 8babdb35

```
const int N = 1e7 + 3;
vector<int> primes;
int notprime[N];
```

```
void sieve() {
    primes.push_back(2);
    for (int i = 4; i < N; i += 2)
        notprime[i] = true;
    for (ll i = 3; i < N; i += 2) {
        if (!notprime[i]) {
            primes.push_back(i);
            for (ll j = 1LL * i * i; j < N; j += 2 * i)
                notprime[j] = true;
        }
    }
}
```

8.29 String Mod [5 lines] - fce25f9e

```
int mod(string& num, int a) {
    int res = 0;
    for (int i = 0; i < num.length(); i++) res = (res * 10 + num[i] - '0') % a;
    return res;
}
```

8.30 nCr [39 lines] - 8a93b828

```
const int N = 1e6 + 5, mod = 1e9 + 7;
ll fact[N], ifact[N];

void preFact() {
    fact[0] = 1;
    for (ll i = 1; i < N; i++) {
        fact[i] = 1LL * fact[i - 1] * i % mod;
    }
    ifact[N - 1] = power(fact[N - 1], mod - 2);
    for (ll i = N - 2; i >= 0; i--) {
        ifact[i] = 1LL * ifact[i + 1] * (i + 1) % mod;
    }
}

ll nCr(int n, int r) {
    if (n < r || n < 0) return 0;
    return 1LL * fact[n] * ifact[r] % mod * ifact[n - r] % mod;
}

// more space less time
const int MOD = 1e9 + 7;
const int MAX = 1e7 + 10;
vector<int> fact(MAX), inv(MAX);
void factorial(){
    fact[0] = 1;
    for (int i = 1; i < MAX; i++)
        fact[i] = (i * fact[i - 1]) % MOD;
}
binaryExp(int a, int n, int M = MOD); //needs to implement
void inverse(){
    for (int i = 0; i < MAX; ++i)
        inv[i] = bigmod(fact[i], MOD - 2);
}

int nCr(int a, int b){
    if (a < b or a < 0 or b < 0)
        return 0;
    int de = (inv[b] * inv[a - b]) % MOD;
    return (fact[a] * de) % MOD;
}

// nCr ends here
int ModInv(int a, int M){ return bigmod(a, M - 2, M);}
```

9 Some Algorithms

9.1 2D Prefix Sum [2 lines] - 00be5300

```
pref[i][j] = a[i][j] + pref[i - 1][j] + pref[i][j - 1]
            - pref[i - 1][j - 1];
Sum of region = pref[row2][col2] - pref[row2][col1 - 1]
              - pref[row1 - 1][col2] + pref[row1 - 1][col1 - 1];
```

9.2 Big Integer [92 lines] - ec448d52

```
struct BigInteger {
    string str;
    // Constructor to initialize
    // BigInteger with a string
    BigInteger(string s) { str = s; }
    // Overload + operator to add
    // two BigInteger objects
    BigInteger operator+(const BigInteger& b) {
        string a = str, c = b.str;
        int alen = a.length(), clen = c.length();
        int n = max(alen, clen);
        if (alen > clen)
            c.insert(0, alen - clen, '0');
        else if (alen < clen)
            a.insert(0, clen - alen, '0');
        string res(n + 1, '0');
        int carry = 0;
        for (int i = n - 1; i >= 0; i--) {
            int digit = (a[i] - '0') + (c[i] - '0')
                + carry;
            carry = digit / 10;
            res[i + 1] = digit % 10 + '0';
        }
        if (carry == 1) {
            res[0] = '1';
            return BigInteger(res);
        } else
            return BigInteger(res.substr(1));
    }

    // Overload - operator to subtract
    // first check which number is greater and then
    // subtract
    BigInteger operator-(const BigInteger& b) {
        string a = str;
        string c = b.str;
        int alen = a.length(), clen = c.length();
        int n = max(alen, clen);
        if (alen > clen)
            c.insert(0, alen - clen, '0');
        else if (alen < clen)
            a.insert(0, clen - alen, '0');
        if (a < c) {
            swap(a, c);
            swap(alen, clen);
        }
        string res(n, '0');
        int carry = 0;
        for (int i = n - 1; i >= 0; i--) {
            int digit = (a[i] - '0') - (c[i] - '0') - carry;
            if (digit < 0)
                digit += 10, carry = 1;
            else
                carry = 0;
            res[i] = digit + '0';
        }
        // remove leading zeros
        int i = 0;
```

```
while (i < n && res[i] == '0') i++;
if (i == n) return BigInteger("0");
return BigInteger(res.substr(i));
}

// Overload * operator to multiply
// two BigInteger objects
BigInteger operator*(const BigInteger& b) {
    string a = str, c = b.str;
    int alen = a.length(), clen = c.length();
    int n = alen + clen;
    string res(n, '0');
    for (int i = alen - 1; i >= 0; i--) {
        int carry = 0;
        for (int j = clen - 1; j >= 0; j--) {
            int digit = (a[i] - '0') *
                (c[j] - '0') + (res[i + j + 1] - '0') + carry;
            carry = digit / 10;
            res[i + j + 1] = digit % 10 + '0';
        }
        res[i] += carry;
    }
    int i = 0;
    while (i < n && res[i] == '0') i++;
    if (i == n) return BigInteger("0");
    return BigInteger(res.substr(i));
}

// Overload << operator to output
// BigInteger object
friend ostream& operator<<(ostream& out, const
    BigInteger& b) {
    out << b.str;
    return out;
}
};
```

9.3 Expression Parsing [92 lines] - c4a451ed

```
bool delim(char c) { return c == ' '; }

bool is_op(char c) { return c == '+' || c == '-' || c
    == '*' || c == '/'; }

bool is_unary(char c) { return c == '+' || c == '-'; }

int priority(char op) {
    if (op < 0) // unary operator
        return 3;
    if (op == '+' || op == '-') return 1;
    if (op == '*' || op == '/') return 2;
    return -1;
}

void process_op(stack<int>& st, char op) {
    if (op < 0) {
        int l = st.top();
        st.pop();
        switch (-op) {
            case '+':
                st.push(l);
                break;
            case '-':
                st.push(-l);
                break;
        }
    } else {
```

```
int r = st.top();
st.pop();
int l = st.top();
st.pop();
switch (op) {
    case '+':
        st.push(l + r);
        break;
    case '-':
        st.push(l - r);
        break;
    case '*':
        st.push(l * r);
        break;
    case '/':
        st.push(l / r);
        break;
}
}

int evaluate(string& s) {
    stack<int> st;
    stack<char> op;
    bool may_be_unary = true;
    for (int i = 0; i < (int)s.size(); i++) {
        if (delim(s[i])) continue;

        if (s[i] == '(') {
            op.push('(');
            may_be_unary = true;
        } else if (s[i] == ')') {
            while (op.top() != '(') {
                process_op(st, op.top());
                op.pop();
            }
            op.pop();
            may_be_unary = false;
        } else if (is_op(s[i])) {
            char cur_op = s[i];
            if (may_be_unary && is_unary(cur_op)) cur_op =
                -cur_op;
            while (!op.empty() &&
                ((cur_op >= 0 && priority(op.top()) >=
                    priority(cur_op)) ||
                (cur_op < 0 && priority(op.top()) >
                    priority(cur_op)))) {
                process_op(st, op.top());
                op.pop();
            }
            op.push(cur_op);
            may_be_unary = true;
        } else {
            int number = 0;
            while (i < (int)s.size() && isalnum(s[i]))
                number = number * 10 + s[i++] - '0';
            --i;
            st.push(number);
            may_be_unary = false;
        }
    }

    while (!op.empty()) {
        process_op(st, op.top());
        op.pop();
    }
}
```

```

}
return st.top();
}

```

9.4 Infix to Postfix [96 lines] - 92843ab9

```

bool delim(char c) { return c == ' '; }
bool is_op(char c) {
    return c == '+' || c == '-' || c == '*'
        || c == '/' || c == '^';
}
bool is_unary(char c) {
    return c == '+' || c == '-';
}
int priority(char op) {
    if (op < 0) return 3;
    if (op == '+' || op == '-') return 1;
    if (op == '*' || op == '/') return 2;
    if (op == '^') return 4;
    return -1;
}

```

```

void process_op(string& output, char op) {
    if (op < 0) {
        switch (-op) {
            case '+':
                output += "+ ";
                break;
            case '-':
                output += "- ";
                break;
        }
    }
    else {
        switch (op) {
            case '+':
                output += "+ ";
                break;
            case '-':
                output += "- ";
                break;
            case '*':
                output += "* ";
                break;
            case '/':
                output += "/ ";
                break;
            case '^':
                output += "^ ";
                break;
        }
    }
}

```

```

string InfixToPostFix(string& s) {
    string output;
    stack<char> op;
    bool may_be_unary = true;
    for (int i = 0; i < (int)s.size(); i++) {
        if (delim(s[i]))
            continue;
        if (s[i] == '(') {
            op.push('(');
            may_be_unary = true;
        }
        else if (s[i] == ')') {
            while (op.top() != '(') {

```

```

                process_op(output, op.top());
                op.pop();
            }
            op.pop();
            may_be_unary = false;
        }
        else if (is_op(s[i])) {
            char cur_op = s[i];
            if (may_be_unary && is_unary(cur_op))
                cur_op = -cur_op;
            while (!op.empty() &&
                ((cur_op >= 0 && priority(op.top())
                 >= priority(cur_op)) ||
                 (cur_op < 0 && priority(op.top()) >
                  priority(cur_op)))) {
                process_op(output, op.top());
                op.pop();
            }
            op.push(cur_op);
            may_be_unary = true;
        }
        else {
            char number;
            while (i < (int)s.size() && isalnum(s[i]))
                number = s[i++];
            --i;
            output.push_back(number);
            output.push_back(' ');
            may_be_unary = false;
        }
    }
    while (!op.empty()) {
        process_op(output, op.top());
        op.pop();
    }
    return output;
}

```

9.5 Kadanes [9 lines] - 6304cec2

```

// return maximum subarray sum.
int kadanec(int arr[], int n) {
    int maxsum = arr[0], curr_sum = arr[0];
    for (int i = 1; i < n; i++) {
        curr_sum = max(arr[i], curr_sum + arr[i]);
        maxsum = max(maxsum, curr_sum);
    }
    return maxsum;
}

```

9.6 Monotonic Stack (next greater) [7 lines] - b69c792c

```

for (int i = n - 1; i >= 0; i--) {
    while (!stk.empty() && v[i] >= v[stk.top()])
        stk.pop();
    ind[i] = stk.empty() ? -1 : stk.top();
    stk.push(i);
}
// 3 1 5 4 10
// 2 2 4 4 -1

```

9.7 Spirally Traverse [25 lines] - 04cd0672

```

vector<int> spirallyTraverse(vector<vector<int>>& mat) {
    int m = mat.size();
    int n = mat[0].size();
    vector<int> res;
    vector<vector<bool>> vis(m, vector<bool>(n, false));
    vector<int> dr = {0, 1, 0, -1};
    vector<int> dc = {1, 0, -1, 0};

```

```

    int r = 0, c = 0;
    int idx = 0;
    for (int i = 0; i < m * n; ++i) {
        res.push_back(mat[r][c]);
        vis[r][c] = true;
        int newR = r + dr[idx];
        int newC = c + dc[idx];
        if (0 <= newR && newR < m && 0 <= newC && newC < n
            && !vis[newR][newC]) {
            r = newR;
            c = newC;
        }
        else {
            idx = (idx + 1) % 4;
            r += dr[idx];
            c += dc[idx];
        }
    }
    return res;
}

```

9.8 Ternary Search [10 lines] - d44f71ce

```

double ternary_search(double l, double r) {
    double eps = 1e-9; // error limit
    while (r - l > eps) {
        double m1 = l + (r - l) / 3, m2 = r - (r - l) / 3;
        double f1 = f(m1), f2 = f(m2); // evaluates the
            function at m1, m2
        if (f1 < f2) l = m1;
        else r = m2;
    }
    return f(l); // return the maximum of f(x) in [l, r]
}

```

10 String

10.1 AhoCorasick [57 lines] - de83ab1a

```

struct AhoCorasick {
    static const int K = 26;
    static const char BASE = 'a';

    struct Node {
        int nxt[K]{}; // Auto-initializes to 0
        int fail = 0, cnt = 0;
    };
    vector<Node> t;
    AhoCorasick() : t(1) {} // Root is at index 0

    void insert(const string& s) {
        int u = 0;
        for (char c : s) {
            int v = c - BASE;
            if (!t[u].nxt[v]) {
                t[u].nxt[v] = t.size();
                t.emplace_back();
            }
            u = t[u].nxt[v];
        }
        t[u].cnt++; // Or store pattern ID here if
            needed
    }

    void build() {
        queue<int> q;
        for (int i = 0; i < K; i++) {
            if (t[0].nxt[i]) q.push(t[0].nxt[i]);
        }
    }
}

```

```

while (!q.empty()) {
    int u = q.front(); q.pop();

    // Accumulate matches from proper suffixes
    // (fail links)
    t[u].cnt += t[t[u].fail].cnt;

    for (int i = 0; i < K; i++) {
        if (t[u].nxt[i]) {
            t[t[u].nxt[i]].fail =
                t[t[u].fail].nxt[i];
            q.push(t[u].nxt[i]);
        } else {
            // Virtual DFA edges for O(1)
            // transitions
            t[u].nxt[i] = t[t[u].fail].nxt[i];
        }
    }
}

}

long long count_matches(const string& text) {
    long long matches = 0;
    int u = 0;
    for (char c : text) {
        u = t[u].nxt[c - BASE];
        matches += t[u].cnt;
    }
    return matches;
}

};

10.2 Hashing [44 lines] - 856b95a5
const int N = 2e6 + 9;
const int M1 = 1e9 + 7, M2 = 1e9 + 9, B1 = 137, B2 =
277;
pair<int, int> pw[N];

void init_hash() {
    pw[0] = {1, 1};
    for (int i = 1; i < N; i++) {
        pw[i].first = 1LL * pw[i - 1].first * B1 % M1;
        pw[i].second = 1LL * pw[i - 1].second * B2 % M2;
    }
}

struct Hash {
    string s;
    vector<pair<int, int>> hs;
    Hash(const string& _s) : s(_s) {
        hs.assign(s.size() + 1, {0, 0});
        for (int i = 0; i < s.size(); i++) {
            hs[i + 1].first = (1LL * hs[i].first * B1 +
                s[i]) % M1;
            hs[i + 1].second = (1LL * hs[i].second * B2
                + s[i]) % M2;
        }
    }
    pair<int, int> get(int l, int r) {
        int h1 = (hs[r + 1].first - 1LL * hs[l].first *
            pw[r - l + 1].first % M1 + M1) % M1;
        int h2 = (hs[r + 1].second - 1LL * hs[l].second
            * pw[r - l + 1].second % M2 + M2) % M2;
        return {h1, h2};
    }
    int lcp(int i1, int j1, int i2, int j2) {
        int l = 1, r = min(j1 - i1 + 1, j2 - i2 + 1),
            ans = 0;

```

```

while (l <= r) {
    int mid = (l + r) / 2;
    if (get(i1, i1 + mid - 1) == get(i2, i2 +
        mid - 1)) ans = mid, l = mid + 1;
    else r = mid - 1;
}
return ans;
}

int compare(int i1, int j1, int i2, int j2) {
    int l = lcp(i1, j1, i2, j2);
    int len1 = j1 - i1 + 1, len2 = j2 - i2 + 1;
    if (l == len1 && l == len2) return 0;
    if (l == len1) return -1;
    if (l == len2) return 1;
    return s[i1 + l] < s[i2 + l] ? -1 : 1;
}

};

10.3 KMP [22 lines] - f876980b
vector<int> prefix_function(const string &s) {
    int n = (int)s.length();
    vector<int> pi(n);
    for (int i = 1; i < n; i++) {
        int j = pi[i - 1];
        while (j > 0 && s[i] != s[j]) j = pi[j - 1];
        if (s[i] == s[j]) j++;
        pi[i] = j;
    }
    return pi;
}

vector<int> find_matches(const string &text, const
    string &pat) {
    int n = pat.length(), m = text.length();
    string s = pat + "$" + text;
    vector<int> pi = prefix_function(s), ans;
    for (int i = n; i <= n + m; i++) {
        if (pi[i] == n) {
            ans.push_back(i - 2 * n);
        }
    }
    return ans;
}

};

10.4 Suffix Array [177 lines] - 3df3c95c
struct SuffixArray {
    // p suffix array 1 base, 0 index for dollar
    // rank will show 1 index value
    // 0 base suffix array -> suf[rank[i] - 1] = i
    vector<int> p, c, rank, lcp;
    vector<vector<int>>> st;
    SuffixArray(string const& s) {
        build_suffix(s + char(1));
        build_rank(p.size());
        build_lcp(s + char(1));
        build_sparse_table(lcp.size());
    }
    void build_suffix(string const& s) {
        int n = s.size();
        const int MX_ASCII = 256;
        vector<int> cnt(max(MX_ASCII, n), 0);
        p.resize(n); c.resize(n);
        for (int i = 0; i < n; i++) cnt[s[i]]++;
        for (int i = 1; i < MX_ASCII; i++) cnt[i] += cnt[i - 1];
        for (int i = 0; i < n; i++) p[--cnt[s[i]]] = i;
        c[p[0]] = 0;
        int classes = 1;
        for (int i = 1; i < n; i++) {

```

```

            if (s[p[i]] != s[p[i - 1]]) classes++;
            c[p[i]] = classes - 1;
        }
        vector<int> pn(n), cn(n);
        for (int h = 0; (1 << h) < n; ++h) {
            for (int i = 0; i < n; i++) {
                pn[i] = p[i] - (1 << h);
                if (pn[i] < 0) pn[i] += n;
            }
            fill(cnt.begin(), cnt.begin() + classes, 0);
            for (int i = 0; i < n; i++) cnt[c[pn[i]]]++;
            for (int i = 1; i < classes; i++) cnt[i] += cnt[i - 1];
            for (int i = n - 1; i >= 0; i--) p[--cnt[c[pn[i]]]] = pn[i];
            cn[p[0]] = 0; classes = 1;
            for (int i = 1; i < n; i++) {
                pair<int, int> cur = {c[p[i]], c[(p[i] + (1 <<
                    h)) % n]};
                pair<int, int> prev = {c[p[i - 1]], c[(p[i - 1] + (1
                    << h)) % n]};
                if (cur != prev) ++classes;
                cn[p[i]] = classes - 1;
            }
            c.swap(cn);
        }
    }
    void build_rank(int n) {
        rank.resize(n, 0);
        for (int i = 0; i < n; i++) rank[p[i]] = i;
    }
    void build_lcp(string const& s) {
        int n = s.size(), k = 0;
        lcp.resize(n - 1, 0);
        for (int i = 0; i < n; i++) {
            if (rank[i] == n - 1) {
                k = 0;
                continue;
            }
            int j = p[rank[i] + 1];
            while (i + k < n && j + k < n && s[i + k] == s[j + k])
                k++;
            lcp[rank[i]] = k;
            if (k) k--;
        }
    }
    void build_sparse_table(int n) {
        int lim = __lg(n);
        st.resize(lim + 1, vector<int>(n)); st[0] = lcp;
        for (int k = 1; k <= lim; k++)
            for (int i = 0; i + (1 << k) <= n; i++)
                st[k][i] = min(st[k - 1][i], st[k - 1][i + (1 <<
                    (k - 1))]);
    }
    int get_lcp(int i) { return lcp[i]; }
    int get_lcp(int i, int j) {
        if (j < i) swap(i, j);
        j--; /*for lcp from i to j we don't need last lcp*/
        int K = __lg(j - i + 1);
        return min(st[K][i], st[K][j - (1 << K) + 1]);
    }
    // Compare two substrings (l1, r1) and (l2, r2)
    int compare(int l1, int r1, int l2, int r2) {
        int len1 = r1 - l1 + 1;
        int len2 = r2 - l2 + 1;
        int pos1 = rank[l1];

```

```

int pos2 = rank[l2];
if (pos1 == pos2) {
    if (len1 != len2) return len1 < len2 ? -1 : 1;
    return 0;
}
int common = get_lcp(min(pos1, pos2), max(pos1, pos2));
int compare_len = min(min(len1, len2), common);
if (compare_len == len1 && compare_len == len2)
    return 0;
if (compare_len == len1) return -1;
if (compare_len == len2) return 1;
return pos1 < pos2 ? -1 : 1;
}
};
// s.compare(suf[mid], min(n - suf[mid], m), t) ->
// -1(small), 0(equal), 1(large)

// https://cses.fi/problemset/task/2109/
// You are given a string of length n. If all of its
// substrings (not necessarily distinct) are ordered
// lexicographically, what is the kth smallest of
// them?

```

```

void solve() {
    string s;
    cin >> s;
    int k, n = s.size();
    cin >> k;
    SuffixArray suff(s);
    vector<int> sa(n), pref(n);
    for (int i = 0; i < n; i++) {
        sa[suff.rank[i] - 1] = i;
    }
    pref[0] = n - sa[0];
    for (int i = 1; i < n; i++) {
        pref[i] = pref[i - 1] + n - sa[i];
    }
}

```

```

auto get_string = [&](int l, int r) {
    int sum = pref[r];
    if (l - 1 >= 0) sum -= pref[l - 1];
    return sum;
};

```

```

int L = 0, R = n - 1;
int depth = 0;
while (true) {
    if (depth > 0) {
        int count = R - L + 1;
        if (k <= count) {
            cout << s.substr(sa[L], depth) << '\n';
            return;
        }
        k -= count;
    }
    int cur = L;
    // skip all suffixes which are already ended
    while (cur <= R && sa[cur] + depth >= n) cur++;
    assert(cur <= R);

    while (cur <= R) {
        // extend to next level with a character c
        // cur = starting index of current character
        // branch

```

```

// cur_end = ending index of current character
// branch
// binary search to find cur_end
char c = s[sa[cur] + depth];
int low = cur, high = R, cur_end = cur;
while (low <= high) {
    int mid = (low + high) / 2;
    if (sa[mid] + depth < n && s[sa[mid] + depth]
        == c) {
        cur_end = mid;
        low = mid + 1;
    } else if (sa[mid] + depth >= n) {
        low = mid + 1;
    } else {
        high = mid - 1;
    }
}

int total = get_string(cur, cur_end);
int branch = total - (cur_end - cur + 1) * depth;

if (k <= branch) {
    // search in this branch
    L = cur;
    R = cur_end;
    depth++;
    goto next_level;
} else {
    // search in next branch
    k -= branch;
    cur = cur_end + 1;
}

next_level:;
}
}

```

10.5 Trie [46 lines] - 95af9856

```

struct Trie {
    static const int K = 26;
    static const char BASE = 'a';
    struct Node {
        int nxt[K]{}; // {} zero-initializes the array
        int eow = 0, cnt = 0;
    };
    vector<Node> t;
    Trie() : t(1) {} // Initializes with root at index 0

    //d = 1 for insert, d = -1 for erase
    void insert(const string& s, int d = 1) {
        int u = 0;
        t[u].cnt += d;
        for (char c : s) {
            int v = c - BASE;
            if (!t[u].nxt[v]) {
                t[u].nxt[v] = t.size();
                t.emplace_back();
            }
            u = t[u].nxt[v];
            t[u].cnt += d;
        }
        t[u].eow += d;
    }
}

```

```

int search(const string& s) {
    int u = 0;
    for (char c : s) {
        int v = c - BASE;
        if (!t[u].nxt[v]) return 0;
        u = t[u].nxt[v];
    }
    return t[u].eow;
}

int count_prefix(const string& s) {
    int u = 0;
    for (char c : s) {
        int v = c - BASE;
        if (!t[u].nxt[v]) return 0;
        u = t[u].nxt[v];
    }
    return t[u].cnt;
}
};

```

11 Random

11.1 Combinatorics

$$\bullet \sum_{k=0}^n \binom{n-k}{k} = Fib_{n+1}$$

$$\bullet \binom{n}{k} + \binom{n}{k+1} = \binom{n+1}{k+1}$$

$$\bullet k \binom{n}{k} = n \binom{n-1}{k-1}$$


- Number of binary sequences of length n such that no two 0's are adjacent = Fib_{n+1}

- Number of non-negative solution of $x_1 + x_2 + x_3 + \dots + x_k = n$ is $\binom{n+k-1}{n}$

11.1.1 Catalan Number

- **Reflection Principle** ($n = 3$)

Count paths $(0, 0) \rightarrow (n, n)$ below $y = x$.



- **Bad Path:** Touches $y = x + 1$.
- **Reflection:** Flip path after first touch.
- **Mapping:** Bad path to $(n, n) \iff$ Path to $(n-1, n+1)$.

$$\bullet C_n = \frac{1}{n+1} \binom{2n}{n} = \binom{2n}{n} - \binom{2n}{n+1} = \frac{(2n)!}{(n+1)!n!}$$

$$\bullet C_0 = 1, C_1 = 1, C_n = \sum_{k=0}^{n-1} C_k C_{n-1-k}$$

$$\bullet 1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786$$

- Number of correct bracket sequences consisting of n opening brackets.
- Number of ways to completely parenthesize $n+1$ factors.
- The number of triangulations of a convex polygon with $+2$ sides (i.e. the number of partitions of polygon into disjoint triangles by using the diagonals).
- The number of ways to connect the $2n$ points on a circle to form n disjoint i.e. non-intersecting chords.
- The number of monotonic lattice paths from point $(0,0)$ to point (n,n) in a square lattice of size $n \times n$, which do not pass above the main diagonal
- Number of permutation of length n that can be stack sorted.
- The number of non-crossing partitions of a set of n elements.
- The number of rooted full binary tree with $n+1$ leaves.
- The number of Dyck words of length $2n$. A string consisting of n X's and n Y's such that no string prefix has more Y's than X's.
- Number of permutation of length n with no three-term increasing subsequence.
- Number of ways to tile a staircase shape of height n with n rectangle.
- $C_n^k = \frac{k+1}{n+1} \binom{2n-k}{n-k}$ denote the number of bracket sequences of size $2n$ with the first k elements being $($.
- $N(n, k) = \frac{1}{n} \binom{n}{k} \binom{n}{k-1}$
- The number of expressions containing n pairs of correct parentheses, which contain k distinct nestings. $N(4, 2) = 6$
 $()((())), ()()(), ()(()), ((())), ((())()), (((())))$
- The number of paths from $(0,0)$ to $(2n, 0)$ with steps only northeast and southeast, not staying below the x-axis with k peaks. And sum of all number of peaks is Catalan number.

11.1.2 Stirling Number of the First Kind

- Count permutation according to their number of cycles.
- $S(n, k)$ count the number of permutation of n elements with k disjoint cycles.
- $S(n, k) = (n-1) \times S(n-1, k) + S(n-1, k-1), S(0, 0) = 1, S(n, 0) = S(0, n) = 0$
- $S(n, 1) = (n-1)!$
- $S(n, n-1) = \binom{n}{2}$
- $\sum_{k=0}^n S(n, k) = n!$

11.1.3 Stirling Numbers of the Second Kind

- Number of ways to partition a set of n objects into k non-empty subsets.
- $S(n, k) = k * S(n-1, k) + S(n-1, k-1), S(0, 0) = 1, S(n, 0) = S(0, n) = 0$
- $S(n, 2) = 2^{n-1} - 1$
- $S(n, k) = \frac{1}{k!} \sum_{j=0}^k (-1)^{k-j} \binom{k}{j} j^n$
- $S(n, k) * k! =$ number of ways to color n nodes using colors from 1 to k such that each color is used at least once.

11.1.4 Bell Number

- Counts the number of partitions of a set.
- $B_{n+1} = \sum_{k=0}^n \binom{n}{k} * B_k$
- $B_n = \sum_{k=0}^n S(n, k)$, where S is Stirling number of second kind.
- The number of multiplicative partitions of a square free number with i prime factors is the i -th Bell number.
- $B(p^m + n) \equiv mB(n) + B(n+1) \pmod{p}$
- If a deck is shuffled by removing and reinserting the top card n times, there are n^n possible shuffles. The number of shuffles that return the deck to its original order is B_n , so the probability of returning to the original order is B_n/n^n .

11.1.5 Lucas Theorem

- If p is prime then $\binom{p^a}{k} \equiv 0 \pmod{p}$
- For non-negative integers m and n and a prime p :
 $\binom{m}{n} = \prod_{i=0}^k \binom{m_i}{n_i} \pmod{p}$ where
 $m = m_k p^k + m_{k-1} p^{k-1} + \dots + m_1 p + m_0$ $n = n_k p^k + n_{k-1} p^{k-1} + \dots + n_1 p + n_0$ are the base p expansion.
- Let n and k be non-negative integers, and let p be a prime. Let the base- p expansions of n and k be:

$$n = n_m p^m + n_{m-1} p^{m-1} + \dots + n_1 p^1 + n_0 p^0$$

$$k = k_m p^m + k_{m-1} p^{m-1} + \dots + k_1 p^1 + k_0 p^0$$

where $0 \leq n_i < p$ and $0 \leq k_i < p$ are the base- p digits of n and k , respectively.

The theorem states:

$$\binom{n}{k} \equiv \prod_{i=0}^m \binom{n_i}{k_i} \pmod{p}$$

Note: The individual terms $\binom{n_i}{k_i}$ are calculated using standard arithmetic, and the final product is taken modulo p .

- **Example:** $\binom{10}{2} \pmod{2}$

$$n = 10_{10} = 1010_2$$

$$k = 2_{10} = 0010_2$$

Applying Lucas's Theorem:

$$\begin{aligned} \binom{10}{2} &\equiv \binom{1}{0} \cdot \binom{0}{0} \cdot \binom{1}{1} \cdot \binom{0}{0} \pmod{2} \\ &\equiv 1 \cdot 1 \cdot 1 \cdot 1 \equiv 1 \pmod{2} \end{aligned}$$

Bitwise check: $1010_2 \& 0010_2 = 0010_2$. Since $2 = 2$, the result is 1.

$$\binom{n}{k} \pmod{2} = \begin{cases} 1 & \text{if } (n \& k) = k \\ 0 & \text{otherwise} \end{cases}$$

11.1.6 Derangement

- A permutation such that no element appears in its original position.
- $d(n) = (n-1) * (d(n-1) + d(n-2)), d(0) = 1, d(1) = 0$
- $d(n) = nd(n-1) + (-1)^n = \lfloor \frac{n!}{e} \rfloor, n \geq 1$

11.1.7 Burnside Lemma

Given a group G of symmetries and a set X , the number of elements of X up to symmetry equals

$$\frac{1}{|G|} \sum_{g \in G} |X^g|$$

where X^g are the elements fixed by g ($g.x = x$) If $f(n)$ counts "configurations" of some sort of length n , we can ignore rotational symmetry using $G = \mathbb{Z}_n$ to get

$$g(n) = \frac{1}{n} \sum_{k=0}^{n-1} f(gcd(n, k)) = \frac{1}{n} \sum_{k|n} f(k) \phi(n/k)$$

11.1.8 Eulerian Number

- $E(n, k)$ is the number of permutations of the numbers 1 to n in which exactly k elements are greater than the previous element.
- $E(n, k) = (n - k)E(n - 1, k - 1) + (k + 1)E(n - 1, k)$, $E(n, 0) = E(n, n - 1) = 1$
- $E(n, k) = \sum_{j=0}^k (-1)^j \binom{n+1}{j} (k + 1 - j)^n$
- $E(n, k) = E(n, n - 1 - k)$
- $E(0, k) = [k = 0]$
- $E(n, 1) = 2^n - n - 1$

11.2 Number Theory

11.2.1 Mobius Function and Inversion

- define $\mu(n)$ as the sum of the primitive n th roots of unity depending on the factorization of n into prime factors:

$$\mu(x) = \begin{cases} 0 & n \text{ is not square free} \\ 1 & n \text{ has even number of prime factors} \\ -1 & n \text{ has odd number of prime factors} \end{cases}$$

- Mobius Inversion:

$$g(n) = \sum_{d|n} f(d) \leftrightarrow f(n) = \sum_{d|n} \mu(d) g(n/d)$$

- $\sum_{d|n} \mu(d) = [n = 1]$
- $\phi(n) = \sum_{d|n} \mu(d) \cdot \frac{n}{d} = n \sum_{d|n} \frac{\mu(d)}{d} = \sum_{d|n} d \cdot \mu\left(\frac{n}{d}\right)$
- $a|b \rightarrow \phi(a)|\phi(b)$

- $\phi(mn) = \phi(m) \cdot \phi(n) \cdot \frac{d}{\phi(d)}$ where $d = gcd(m, n)$
- $\phi(n^m) = n^{m-1} \phi(n)$
- $\sum_{i=1}^n [gcd(i, n) = k] = \phi\left(\frac{n}{k}\right)$
- $\sum_{i=1}^n gcd(i, n) = \sum_{d|n} d \cdot \phi\left(\frac{n}{d}\right)$
- $\sum_{i=1}^n \frac{1}{gcd(i, n)} = \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{1}{n} \sum_{d|n} d \cdot \phi(d)$
- $\sum_{i=1}^n \frac{i}{gcd(i, n)} = \frac{n}{2} \cdot \sum_{d|n} \frac{1}{d} \cdot \phi\left(\frac{n}{d}\right) = \frac{n}{2} \cdot \frac{1}{n} \sum_{d|n} d \cdot \phi(d)$
- $\sum_{i=1}^n \frac{n}{gcd(i, n)} = 2 \cdot \sum_{i=1}^n \frac{i}{gcd(i, n)} - 1$

11.2.2 GCD and LCM

- $gcd(a, b) = gcd(b, a \bmod b)$
- If $a|b \cdot c$, and $gcd(a, b) = d$, then $(a/d)|c$.
- GCD is a multiplicative function.
- $gcd(a, lcm(b, c)) = lcm(gcd(a, b), gcd(a, c))$
- $gcd(n^a - 1, n^b - 1) = n^{gcd(a, b)} - 1$

11.2.3 Gauss Circle Theorem

- Determine the number of lattice points in a circle centered at the origin with radius r .
- number of pairs (m, n) such that $m^2 + n^2 \leq r^2$
- $N(r) = 1 + 4 \sum_{i=0}^{\infty} (\lfloor \frac{r^2}{4i+1} \rfloor - \lfloor \frac{r^2}{4i+3} \rfloor)$

11.2.4 Pick's Theorem

According to Pick's Theorem We can calculate the area of any polygon by just counting the number of Interior and Boundary lattice points of that polygon. If number of interior points are I and number of boundary lattice points are B then Area (A) of polygon will be:

$$Area = I + B/2 - 1$$

where I is the number of points in the interior shape, B stands for the number of points on the boundary of the shape.

11.2.5 Formula Cheatsheet

- $\sum_{i=1}^n = \frac{1}{m+1} [(n+1)^{m+1} - 1 - \sum_{i=1}^n ((i+1)^{m+1} - i^{m+1} - (m+1)i^m)]$
- $\sum_{i=0}^n c^i = \frac{c^{n+1}-1}{c-1}, c \neq 1$
- $\sum_{i=0}^{\infty} c^i = \frac{1}{1-c}, \sum_{i=1}^{\infty} c^i = \frac{c}{1-c}, |c| < 1$
- $H_n = \sum_{i=1}^n \frac{1}{n}, \sum_{i=1}^n i H_i = \frac{n(n+1)}{2} H_n - \frac{n(n-1)}{4}$
- $\sum_{k=0}^n \binom{r+k}{k} = \binom{r+n+1}{n}$

11.2.6 Geometry and Formulas

• Area Formulas

- Rectangle: $A = l \times w$
- Square: $A = s^2$
- Triangle: $A = \frac{1}{2}bh$
- Circle: $A = \pi r^2$
- Parallelogram: $A = bh$
- Pyramid Base: $A = \frac{1}{2}b \times h_{slant}$
- Polygon: $A = \frac{1}{2} |\sum_{i=1}^{n-1} (x_i y_{i+1})|$
- Pick's formula: $A = I + \frac{B}{2} - 1$ where I = interior points, B = boundary points

• Perimeter Formulas

- Rectangle: $P = 2(l + w)$
- Square: $P = 4s$
- Triangle: $P = a + b + c$
- Circle: $P = 2\pi r$

• Volume Formulas

- Cube: $V = s^3$
- Rect. Prism: $V = lwh$
- Cylinder: $V = \pi r^2 h$
- Sphere: $V = \frac{4}{3}\pi r^3$
- Pyramid: $V = \frac{1}{3}A_{base}h$

• Surface Area Formulas

- Cube: $SA = 6s^2$

- **Divisibility rules:**

3: Sum of digits divisible by 3

4: Last two digits divisible by 4

5: Last digit 0 or 5

6: Divisible by both 2 and 3

7: Double last digit, subtract from rest. Continue till manageable.

8: Last three digits divisible by 8

9: Sum of digits divisible by 9

11: $(\text{sum of odd digits}) - (\text{sum of even digits}) \equiv 0 \pmod{11}$

- Derangement: $D_n = (n-1)D_{n-2} + (n-1)D_{n-1}$

- Golden Ratio: $\Phi = \frac{1+\sqrt{5}}{2} \approx 1.618034$

- n -th Fibonacci:

$$F_n = \frac{\Phi^n - (1 - \Phi)^n}{\sqrt{5}}$$

- Stars & Bars: Solutions of $x_1 + x_2 + \dots + x_k = n$ $x_i > 0$: $\binom{n-1}{k-1}$, $x_i \geq 0$: $\binom{n+k-1}{k-1}$

- **Throwing Dice (Matrix Exponentiation)**

- **Recurrence Relation** The number of ways to achieve a sum n is given by the linear recurrence:

$$f(n) = f(n-1) + f(n-2) + f(n-3) + f(n-4) + f(n-5) + f(n-6)$$

with the base case $f(0) = 1$ and $f(k) = 0$ for $k < 0$.

- **State Transition** The relationship between the new state vector (V_i) and the old state vector (V_{i-1}) is:

$$\underbrace{\begin{bmatrix} f(i) \\ f(i-1) \\ f(i-2) \\ f(i-3) \\ f(i-4) \\ f(i-5) \end{bmatrix}}_{V_i} = \underbrace{\begin{bmatrix} 1 & 1 & 1 & 1 & 1 & 1 \\ 1 & 0 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 & 0 \\ 0 & 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & 0 & 1 & 0 & 0 \\ 0 & 0 & 0 & 0 & 1 & 0 \end{bmatrix}}_T \times \underbrace{\begin{bmatrix} f(i-1) \\ f(i-2) \\ f(i-3) \\ f(i-4) \\ f(i-5) \\ f(i-6) \end{bmatrix}}_{V_{i-1}}$$

- **Final Answer** The n -th term is found by: $f(n) = (T^n)_{1,1} \times f(0)$, where $f(0) = 1$.

$$f(n) = (T^n)_{1,1}$$

11.3 Probability and Expectation

- Let X be a discrete random variable with probability $p_X(x)$ of assuming the value x . It will then have an expected value (mean) $\mu = \mathbb{E}(X) = \sum_x x p_X(x)$ and variance $\sigma^2 = V(X) = \mathbb{E}(X^2) - (\mathbb{E}(X))^2 = \sum_x (x - \mathbb{E}(X))^2 p_X(x)$ where σ is the standard deviation. If X is instead continuous it will have a probability density function $f_X(x)$ and the sums above will instead be integrals with $p_X(x)$ replaced by $f_X(x)$.

- Expectation is linear:

$$\mathbb{E}(aX + bY) = a\mathbb{E}(X) + b\mathbb{E}(Y)$$

For independent X and Y ,

$$V(aX + bY) = a^2 V(X) + b^2 V(Y).$$

- **Discrete distributions**

- **Binomial distribution:** The number of successes in n independent yes/no experiments, each which yields success with probability p is $\text{Bin}(n, p)$, $n = 1, 2, \dots$, $0 \leq p \leq 1$.

$$p(k) = \binom{n}{k} p^k (1-p)^{n-k}$$

$$\mu = np, \sigma^2 = np(1-p)$$

$\text{Bin}(n, p)$ is approximately $\text{Po}(np)$ for small p .

- **First success distribution:** The number of trials needed to get the first success in independent yes/no experiments, each which yields success with probability p is $\text{Fs}(p)$, $0 \leq p \leq 1$.

$$p(k) = p(1-p)^{k-1}, k = 1, 2, \dots$$

$$\mu = \frac{1}{p}, \sigma^2 = \frac{1-p}{p^2}$$

- **Poisson distribution:** The number of events occurring in a fixed period of time t if these events occur with a known average rate κ and independently of the time since the last event is $\text{Po}(\lambda)$, $\lambda = t\kappa$.

$$p(k) = e^{-\lambda} \frac{\lambda^k}{k!}, k = 0, 1, 2, \dots$$

$$\mu = \lambda, \sigma^2 = \lambda$$

- **Continuous distributions**

- **Uniform distribution:** If the probability density function is constant between a and b and 0 elsewhere it is $\text{U}(a, b)$, $a < b$.

$$f(x) = \begin{cases} \frac{1}{b-a} & a < x < b \\ 0 & \text{otherwise} \end{cases}$$

$$\mu = \frac{a+b}{2}, \sigma^2 = \frac{(b-a)^2}{12}$$

- **Exponential distribution:** The time between events in a Poisson process is $\text{Exp}(\lambda)$, $\lambda > 0$.

$$f(x) = \begin{cases} \lambda e^{-\lambda x} & x \geq 0 \\ 0 & x < 0 \end{cases}$$

$$\mu = \frac{1}{\lambda}, \sigma^2 = \frac{1}{\lambda^2}$$

- **Normal distribution:** Most real random values with mean μ and variance σ^2 are well described by $\mathcal{N}(\mu, \sigma^2)$, $\sigma > 0$.

$$f(x) = \frac{1}{\sqrt{2\pi\sigma^2}} e^{-\frac{(x-\mu)^2}{2\sigma^2}}$$

If $X_1 \sim \mathcal{N}(\mu_1, \sigma_1^2)$ and $X_2 \sim \mathcal{N}(\mu_2, \sigma_2^2)$ then

$$aX_1 + bX_2 + c \sim \mathcal{N}(\mu_1 + \mu_2 + c, a^2\sigma_1^2 + b^2\sigma_2^2)$$