

28/09/26

Day 3

docker stop container_name. => stop pandrathukku.

docker rm container_name => remove the container

docker ps -a

running-la irukkura container-a remove panna mudiyathu

docker rm -f container_name (or) id => force panni
container remove
pandrathu.

RUN Commands

docker run -d --name container_name image_name => this
↳ ~~daemon~~ command
used for create
and start
automatically

-d => stands for daemon

↳ background process.

docker run -d --name sjc-devops httpd

docker ps

create container without -d

-d => without -d => frontend-la run agum => client
UI-la
open agum.

ctrl + c => shutting down.

again

docker ps

docker ps -a new
-> status => Exited => stop

docker start sjc-devops -i

docker ps

How to open ^{the} Container:

Command:

`docker exec -it containername /bin/bash`

↳ stands for interactive terminal
-it $\Rightarrow$ open terminal mode

/bin/bash $\Rightarrow$ this terminal has which path.

`docker exec -it sic-devops /bin/bash`

exit $\Rightarrow$ back to the normal terminal.

Configure

first update.

apt update $\Rightarrow$ update apache

apache engine root directory $\Rightarrow$ source code
Configure
Pannuraga

ls

cd

htdocs

↳ root directory.

ls $\Rightarrow$ show file name: index.html

cat file name.

cat index.html.

exit

assign port number:

* docker run -d --name test -p 8082:80 httpd

Port forwarding

8082:80 Apache.
default port

forward this port.

80 → 8082. ⇒ forward.
host port.

map the container & laptop port.

assign the 8082 port into container.

Copy the my ip

the page the ip : port number.

~~https://10.31~~

http://10.31.12.133:8082

It can't change the already created container port number.

when ^{should} port forwarding ⇒ if port is already allocated.

open the container:

docker exec -it test /bin/bash

cd /httpd

ls

apt update

apt install

⇒ first update the container then install the required

vi file_name $\Rightarrow$ change the content inside file
vi index.html
cat index.html

config ip $\Rightarrow$ intel, I/O $\Rightarrow$ ip use paravirtual
 $\Rightarrow$ translate the ip

NAT $\Rightarrow$ network address Translation.

bridge $\Rightarrow$ provide ip from nicard $\Rightarrow$ my laptop
Vm-ku separate ip.

my ip & vmware ip $\Rightarrow$ b/w range same

NAT $\Rightarrow$ It translate the lap ip to vm ip

cd /etc

ls

vi index.html

apt install

vim -y

apt update

$\rightarrow$ yes for all

apt install vim -y

vi index.html

cat index.html

Snapshot the Container: and create the image

docker commit container_name snapshot: 1.0

$\rightarrow$ image name tag

Container-a image-a create parrot inuk.com

Save Panna image - a load . pandhathurru where it is
load to Docker images
↳ docker load -i demobackup.tar
↳ backup panna img.

docker run -f mapping:1.0

docker ps -a

docker images

docker exec -it mapping:1.0

Dockerfile

~~syn~~ Docker can build images automatically by reading the instructions from a dockerfile. A dockerfile is a text document that contains all the commands a user could call on the command line to assemble an image.

Syntax:

INSTRUCTION arguments

FROM ⇒ Create a new build image from base img.

RUN ⇒ execute build commands.

COPY index.html /var/www/html/

↳ where the file is placed
↳ path

that place give properly the path is clearly give
eg: src/demo/demo/index.html should be

copy index.html /var/www/html/
↳ source ↳ destination

EXPOSE ⇒ set the default port

WORKDIR ⇒ change working directory

ENV ⇒ set environment variables

CMD ⇒ specify default commands. it can be overwritten

ENTRYPOINT ⇒ specify default executable. it can't be overwritten

Build Image:

cat dockerfile.txt

notepad index.html

docker build -t Customing: latest .
↳ tag ↳ version ↳ current directory
↳ failed to build ↳ image name ↳ complete path

mv dockerfile.txt dockerfile

rename command ⇒ cmd prompt ->

rename oldname : newname

rename dockerfile.txt dockerfile

Docker N/w:

Developing ⇒ best phase ⇒ None ⇒ no network access

Host ⇒ best for testing

Bridge ⇒ if not mention the n/w defaultly launched the container in Bridge.