Orphos EIP — Compose Inventory

Services, MCP servers, and agents declared across the Docker Compose files

`D:\Orphos_1\Orphos---EIP` · branch **`main`** @ `9a682f3` · 22 Aug 2026

> Scope: this is the **declared** inventory read from the YAML files. The Docker daemon was not queried, so nothing here asserts live container state.

Summary

Category	YAML file	Services	Composition
INFRA	`docker-compose.infra.yml`	13	Proxy, DB, sign-in, secrets, observability, event bus
DATA	`docker-compose.data.yml`	3	Graph, RDF/SPARQL, vector store
AI	`docker-compose.ai.yml`	2	Two Ollama tiers
AI	`docker-compose.remote-ai.yml`	3	Alternative off-host AI tier (replaces, not adds)
APP	`docker-compose.app.yml`	39	8 MCP · 6 agents · 15 services · 7 frontend · 4 support
OVERRIDE	`docker-compose.tokenfix.yml`	0	Env-only patch to 2 existing app services

57 declared containers for a standard full start (infra + data + ai + app). `remote-ai.yml` and `tokenfix.yml` are both manual-only — no launcher script references them.

1 · docker-compose.infra.yml INFRA

13 services · declares the shared `eip-net` network and volumes `postgres_data`, `infisical_db_data`, `infisical_svc`, `eip_connections`, `kafka_data`, `victorialogs_data`.

Service	Image	Host port	Role
`traefik`	`traefik:v3`	`80, 443`	Reverse proxy / ingress
`postgres`	`postgres:16-alpine`	`5432`	Platform relational database
`keycloak`	`quay.io/keycloak/keycloak:24.0`	`8443 → 8080`	Sign-in / identity provider
`infisical-db`	`postgres:16-alpine`	–	Dedicated database for Infisical
`infisical-redis`	`valkey/valkey:8-alpine`	–	Infisical cache
`infisical`	`infisical/infisical:latest-postgres` *(digest-pinned)*	`8222 → 8080`	Secrets manager
`infisical-seed`	`curlimages/curl:8.10.1`	–	One-shot secret seeding
`connections-seed`	`busybox:1.36`	–	One-shot connection seeding
`jaeger`	`jaegertracing/all-in-one:1.62.0`	`16686, 4318`	Tracing — UI, plus OTLP/HTTP intake
`victoria-logs`	`victoriametrics/victoria-logs:v1.3.2`	`9428`	Log store
`fluent-bit`	`fluent/fluent-bit:3.1.9`	`24224`	Log shipper — the `fluentd` driver target for every other stack

kafka	apache/kafka:3.7.0	9092	Event bus

2 · docker-compose.data.yml DATA

3 services · volumes arcadedb_data, fuseki_data, qdrant_data.

Service	Image	Host port	Role
arcadedb	arcadedata/arcadedb *(digest-pinned)*	2480, 2424	Knowledge graph
fuseki	eip-fuseki *(locally built)*	3030	Apache Jena — RDF / SPARQL
qdrant	qdrant/qdrant:v1.13.0	6333	Vector store

3 · docker-compose.ai.yml AI

2 services · volumes ollama_data, ollama_hi_data.

Service	Container	Host port	Notes
ollama	eip-ollama	11434	Chat tier. OLLAMA_MAX_LOADED_MODELS=1, KEEP_ALIVE=5m. File comments name Granite 3.1-dense (Apache-2.0) and Phi-3.5 Mini (MIT).
ollama-hi	eip-ollama-hi	11435 → 11434	Second tier. MAX_LOADED_MODELS=2 so embeddings never evict the chat model.

4 · docker-compose.remote-ai.yml AI — ALTERNATE

3 services · self-contained; a **replacement** for the AI tier, not an addition to it.

Intended to run on a second machine (192.168.10.2) to shed roughly 13 GB off the primary host, whose WSL2 allocation caps at 12 GB while the full fleet declares about 27 GB of memory limits.

Service	Host port	Notes
ollama	11434	Models pulled by hand: granite3.1-dense:2b, phi3.5
ollama-hi	11435 → 11434	Models pulled by hand: qwen2.5:1.5b, bge-m3
docling	5001	Relocated here from the app layer

Per its own header it differs from ai.yml in exactly three ways: no external eip-net (that bridge exists only on the primary), json-file logging instead of fluentd, and docling folded in. Image digests, memory limits, and host ports are deliberately kept identical to the upstream definitions.

5 · docker-compose.app.yml APP

39 services · this single file contains every MCP server and every agent.

5a · MCP servers — 8

Service	Image	Host port	Source module
mcp-priority	eip-mcp-priority	8101	mcp/eip-mcp-priority
mcp-decision	eip-mcp-decision	8102	mcp/eip-mcp-decision
mcp-rag	eip-mcp-rag	8105	mcp/eip-mcp-rag
mcp-mail	eip-mcp-mail	8106	mcp/eip-mcp-mail
mcp-reasoning	eip-mcp-reasoning	8107	mcp/eip-mcp-reasoning
mcp-graph	eip-mcp-graph	8108	mcp/eip-mcp-graph
mcp-ingest	eip-mcp-ingest	8109	mcp/eip-mcp-ingest
mcp-comms	eip-mcp-comms	8112	mcp/eip-mcp-comms

> The mcp/ source directories and the compose entries line up exactly — eight of each, no orphans in either direction.

5b · Agents — 5, plus 1 orchestrator

Service	Image	Host port	Container	Source module
agent-orchestrator	eip-agent-orchestrator	8085	eip-agents	*— none under agents/*
agent-briefing	eip-agent-briefing	8103	eip-agent-briefing	agents/eip-agent-briefing
agent-decision	eip-agent-decision	8104	eip-agent-decision	agents/eip-agent-decision
agent-email-triage	eip-agent-email-triage	8110	eip-agent-email-triage	agents/eip-agent-email-triage
agent-attention	eip-agent-attention	8111	eip-agent-attention	agents/eip-agent-attention
agent-comms-triage	eip-agent-comms-triage	8113	eip-agent-comms-triage	agents/eip-agent-comms-triage

> The orchestrator has no agents/eip-agent-orchestrator directory — its eip-agent-orchestrator image is built from elsewhere in the tree, most likely under services/. Note also that its container is named eip-agents, not eip-agent-orchestrator.

Every MCP and agent container listens on **8080 internally**, published into the contiguous 8101–8113 host range.

5c · Core business services — 15

Service	Image	Host port	Layer role
data-ingestion	eip-data-ingestion	8096	Source-system intake
okg-ingest	eip-okg-ingest	8081	Graph ingest

okg-reasoning	eip-okg-reasoning	8088	Graph reasoning
graph-proxy	eip-graph-proxy	8080	Graph access layer
nl-query	eip-nl-query	8082	Natural-language query
priority-engine	eip-priority-engine	8083	Attention / prioritisation
briefing-service	eip-briefing	8084	Briefings
decision-log	eip-decision-log	8086	Decision record
notification-service	eip-notification	8087	Notifications
platform-registry	eip-platform-registry	8093	Service / plugin registry
platform-core	eip-platform-core	8090	Platform core
admin-console	eip-admin-console	8094	Admin backend
widgets	eip-widgets	8095	Widget backend
doc-ingest	eip-doc-ingest	8091	Document ingest
mail-insight	eip-mail-insight	8092	Mail analysis

5d · Frontend — shell and micro-frontend plugins — 7

Service	Image	Host port	Notes
shell	eip-shell	3001 → 80	**Application entry point** — http://localhost:3001
plugin-ai-copilot	eip-plugin-ai-copilot	3011 → 80	Copilot panel
plugin-email-scanner	eip-plugin-email-scanner	3012 → 80	Email scanning UI
plugin-doc-ingest	eip-plugin-doc-ingest	3013 → 80	Document ingest UI
plugin-rag-search	eip-plugin-rag-search	3014 → 80	RAG search UI
plugin-widgets	eip-plugin-widgets	3015 → 80	Widgets UI
plugin-decision-log	eip-plugin-decision-log	3016 → 80	Decision log UI

5e · Third-party and support, declared in the app file — 4

Service	Image	Host port	Notes
secrets-ready	curlimages/curl:8.10.1	–	One-shot gate; waits on Infisical before the fleet proceeds
docling	docling-serve-cpu *(digest-pinned)*	5001	Document parsing — AI-adjacent, but declared in the app layer; `remote-ai.yml` relocates it
prometheus	prom/prometheus:v2.52.0	9090	Metrics
perses	persesdev/perses:v0.47.0	3000 → 8080	Dashboards

6 · docker-compose.tokenfix.yml OVERRIDE FRAGMENT

0 new services · 7 lines · no images, no ports.

An overlay meant to be passed as an extra `-f` alongside `docker-compose.app.yml`. It patches the environment of two existing app services only:

Service patched	Change
`platform-registry`	Sets `EIP_SECURITY_INTERNAL_SERVICE_TOKEN`
`platform-core`	Sets the same `EIP_SECURITY_INTERNAL_SERVICE_TOKEN`

> **Two issues worth flagging.** First, the file is not referenced by `start.ps1`, `start.bat`, or the `Makefile`, so it is effectively dead unless invoked by hand. Second, it carries a hard-coded 48-character hexadecimal internal service token committed into version control — a real secret in the repository, regardless of whether the overlay is ever wired up. The value is deliberately not reproduced in this report.

Observations

Item	Detail
Container count	A standard full start declares **57 containers**. The README's figure of about 35 containers across four layers undercounts by a wide margin.
Orchestrator source	`agent-orchestrator` is the only agent with no matching `agents/` module.
Unwired files	`remote-ai.yml` and `tokenfix.yml` are invoked manually only.
Committed secret	`tokenfix.yml` contains a plaintext internal service token.
Layer placement	`docling` sits in the app layer despite being an AI-tier workload by function.
