


Asymmetric Cryptography






Current Cryptographic Standards




Cryptography revisited



Two properties of symmetric (secret-key) crypto-systems:

- The **same secret key K** is used for encryption and decryption
- Encryption and Decryption are very similar (or even identical) functions

Symmetric Cryptography: Analogy




Safe with a strong lock, only Alice and Bob have a copy of the key

- Alice encrypts → locks message in the safe with her key
- Bob decrypts → uses his copy of the key to open the safe

- Open and close using shared secret keys
- Secret key agreement required !

Symmetric Cryptography: Analogy




Symmetric Cryptography Shortcomings


- Key distribution problem: The secret key must be **transported securely**
- Number of keys: In a network, each pair of users requires an individual key
 - n users in the network require $\frac{n \cdot (n - 1)}{2}$ keys, each user stores $(n-1)$ keys
- No support for message **integrity**: verifying that a message comes intact from the sender
- No support for “**non-repudiation**”
 - **Example**: Alice can claim that she never ordered a TV on-line from Bob (he could have fabricated her order)

Symmetric Cryptography Shortcomings

Question: How many secret-keys needed to be exchanged in order to set up a system of n-users?



10 key-exchanges for 5 users



$\frac{n(n-1)}{2}$ keys for n users

For 10 000 users we need 50 million key-exchanges !

Public-Key system **drops out** the secret key-agreement completely

Idea behind Asymmetric Cryptography

New Idea:

Use the “good old mailbox” principle:


Everyone can drop a letter



But: Only the owner has the correct key to open the box




Asymmetric Cryptography: Analogy




- Open and close with different keys!!
- No Secret Key Agreement required

Asymmetric Cryptography: Analogy

User B gets a secured message from A)



Asymmetric Cryptography



- **Key Distribution Problem** solved
- Anyone can encrypt messages using the public key, but only the holder of the **paired private key** can decrypt. Security depends on the secrecy of the private key.
- During the key generation, a key pair K_{pub} and K_{pr} is computed

Public Key Cryptography Applications

The asymmetric cryptography (e.g., RSA) are mainly used for:

- **Key Distribution** without a pre-shared secret (key)
- **Digital Signatures** to provide message integrity and non-repudiation


Rarely used for:

- **Encryption** because it is computationally very intensive (1000 times slower than symmetric Algorithms!)

Applications for Public-Key Cryptosystems



Algorithm	Encryption/Decryption	Digital Signature	Key Exchange
RSA	Yes	Yes	Yes
Elliptic Curve	Yes	Yes	Yes
Diffie-Hellman	No	No	Yes

Digital Signatures



- 1) Alice signs a message with her private key
- 2) Bob can verify that Alice sent the message (i.e., non-repudiation) and that the message has not been modified (i.e., integrity)

Public-Key Signature Process



If the hashes are equal, the signature is valid.


Basic Key Transport Protocol 1/2

In practice: **Hybrid systems**, incorporating asymmetric and symmetric algorithms

1. **Key exchange** (for symmetric schemes) and **digital signatures** are performed with (slow) **asymmetric** algorithms
2. **Encryption** of data is done using (fast) symmetric ciphers, e.g., **block ciphers or stream ciphers**

Basic Key Transport Protocol 2/2


Example: Hybrid protocol with AES as the symmetric cipher



Key Exchange with Public Key Crypto

- Alice creates a secret key, encrypts it with Bob's public key and sends it off
- Bob decrypts the message with his private key
- Use shared key for further communication
- This is how many applications work
- Could encrypt/decrypt using public key cryptography but it is slow

RSA Cryptosystem



Rivest



Shamir





Adleman

- Developed by Rivest, Shamir, and Adleman in 1977
- Until now, RSA is the most widely use asymmetric cryptosystem although elliptic curve cryptography (ECC) becomes increasingly popular
- RSA is mainly used for two applications: Key exchange & Digital signatures

RSA One-way Function (Lock)

Asymmetric schemes are based on a “**one-way function**” $f()$:

- Computing $y = f(x)$ is computationally easy
- Computing the inverse $x = f^{-1}(y)$ is computationally infeasible
- One way functions are based on **mathematically hard problems**
- RSA security relies on the difficulty of **factoring** large integers
 - Multiplying two primes is easy (e.g., $1889 \times 3547 = 6,700,283$)
 - Given a composite integer n , find its prime factors is mathematically hard!
(e.g., It is hard to find Prime_1 and Prime_2 such that $\text{Prime}_1 \times \text{Prime}_2 = 6,700,283$)



Factorization
Problem (RSA Lock)

Encryption and Decryption

- Encryption and decryption are simply exponentiations

Definition

Given the public key $(n, e) = k_{pub}$ and the private key $d = k_{pr}$ we write


$$c = e_{k_{pub}}(m) = m^e \bmod n$$

$$m = d_{k_{pr}}(c) = c^d \bmod n$$

$e_{k_{pub}}()$ is the encryption operation and $d_{k_{pr}}()$ is the decryption operation.

- In practice d and n are very long integer numbers (≥ 1024 bits)
- The security of the scheme relies on the fact that it is hard to derive the private key d given the public-key (n, e)

RSA Example



Key Generation

- RSA has set-up phase during which the private and public keys are computed

Algorithm: RSA Key Generation

Output: public key: $k_{pub} = (n, e)$ and private key $k_{pr} = d$

1. Choose two large primes p, q
2. Compute $n = p * q$
3. Compute $\Phi(n) = (p-1) * (q-1)$
4. Select the public exponent e such that $1 < e < \Phi(n)$ and *does not share any factor with $\Phi(n)$*
5. Compute the private key d such that $(d * e) \bmod \Phi(n) = 1$
the extended **Euclidean algorithm** is used to compute d .
6. **RETURN** $k_{pub} = (n, e), k_{pr} = d$

Φ is called Phi

Example: RSA with small numbers

ALICE

Message **$m = 4$**

BOB

1. Choose $p = 3$ and $q = 11$
2. Compute $n = p * q = 33$
3. $\Phi(n) = (3-1) * (11-1) = 20$
4. Choose $e = 3$
5. $d \equiv e^{-1} \equiv 7 \text{ mod } 20 = 7$

$K_{\text{pub}} = (33, 3)$



$$c = m^e = 4^3 \text{ mod } 33 = 31$$

$c = 31$



$$c^d = 31^7 \text{ mod } 33 = \mathbf{4}$$

Asymmetric Key Cryptography – RSA Encryption Algorithm

- Message: $m = 3$
- Choose 2 random, prime numbers: $p = 19, q = 13$
- $n = pq, n = 247$
- Choose a random # to be e (encryption key): $e = 7$
- $\Phi(n) = (p-1)(q-1) = 216$
- Compute d (decryption key) (private key)
 $d * e \bmod \Phi(n) = 1$ (need to solve for d)
 $d = 31$ (using Extended Euclidean Algorithm)
- Public key = $(n, e) = (247, 7)$
- To encrypt: $c = m^e \bmod n \rightarrow c = 3^7 \bmod 247 \rightarrow$
 $c = 211$ (ciphertext)
- To decrypt: $m = c^d \bmod n \rightarrow m = 211^{31} \bmod 247 \rightarrow$
 $m = 3$ (plaintext)

Attacks and Countermeasures

- **Brute force key search**

- using exhaustive search for factoring of n in order to obtain $\Phi(n)$
- Can be prevented using a sufficiently large modulus n
- The current factoring record is 664 bits. Thus, it is recommended that n should have a bit length between 1024 and 3072 bits

- Implementation attacks such **Side-channel analysis**

- Exploit physical leakage of RSA implementation (e.g., power consumption, etc.)
- Timing attacks on running of decryption can Infer operand size based on time taken

Summary

- RSA is the most widely used public-key cryptosystem
- RSA is mainly used for key transport and digital signatures
- RSA relies on the fact that it is hard to factorize n
- Currently 1024-bit cannot be factored, but progress in factorization could bring this into reach within 10-15 years. Hence, RSA with a 2048 or 3076 bit modulus should be used for long-term security

References

- RSA Wikipedia page

https://en.wikipedia.org/wiki/Public-key_cryptography

[https://en.wikipedia.org/wiki/RSA_\(cryptosystem\)](https://en.wikipedia.org/wiki/RSA_(cryptosystem))