Trustworthy Cybersecurity Applications Using Neuro-Symbolic XAI and Data Quality Controls

Haifa Muhammad
Effat College of Engineering
Effat University, Jeddah, Saudi Arabia
haalbalochi@effat.edu.sa

Raghad Alamoudi
Effat College of Engineering
Effat University, Jeddah, Saudi Arabia
rahalamoudi@effat.edu.sa

Abstract

Artificial intelligence is increasingly used in cybersecurity, but traditional neural models often operate as black boxes and struggle with poor-quality data, reducing trust and reliability. This work explores a neuro-symbolic approach that combines neural learning with symbolic reasoning to improve transparency, explainability, and data integrity in cyber defense systems. Through a review of recent methods, trustworthy AI frameworks, and data-quality practices, the study highlights how logic rules, knowledge graphs, and hybrid reasoning can enhance detection accuracy and provide interpretable decision paths. The proposed system integrates these components across the cybersecurity pipeline, demonstrating that neuro-symbolic XAI offers a promising foundation for building more accountable, transparent, and robust cybersecurity applications.

1 Introduction

In recent years, the field of artificial intelligence has witnessed the emergence of *neuro-symbolic AI*, a hybrid paradigm that combines the pattern-recognition strength of neural networks with the explicit reasoning capability of symbolic methods. Neuro-symbolic AI integrates statistical learning with rule- or logic-based processing, allowing systems not only to learn from large data sets but also to reason in ways that are more human-interpretable (11; 2).

Traditional deep-learning and other purely neural approaches often function as *black boxes*: they can deliver strong predictive performance, yet the inner decision-making process remains opaque and difficult for humans to interpret or audit (23). This "black-box problem" poses significant challenges, especially in high-stakes domains where accountability, fairness, transparency and trust are essential (15).

In the domain of cybersecurity, data quality plays a foundational role: the reliability of intrusion detection, anomaly monitoring, log analysis, and threat response all depend on the integrity, completeness and consistency of the underlying data inputs (32). When machine-learning models are applied to cybersecurity tasks, poor data quality can lead to incorrect detections, excessive false alarms, or missed attacks—and when the model is opaque, analysts cannot easily trace or trust its reasoning (47).

By combining symbolic logic with neural learning, neuro-symbolic AI offers a promising pathway to enhance both interpretability and trust in AI-driven cybersecurity systems. The symbolic component enables explicit knowledge representation and reasoning pathways that humans can inspect or verify; the neural component enables efficient learning from rich, unstructured or high-volume data. Together, they can help bridge the gap between high-performance detection and human-comprehensible explanations—thus supporting trustworthy AI in cybersecurity contexts(3).

1.1 Importance of the Research Problem

The rapid growth of artificial intelligence in cybersecurity has introduced both opportunities and challenges regarding system transparency, explainability, and trust. Conventional deep-learning models have achieved impressive accuracy in detecting cyber threats and anomalies; however, their opaque nature limits human understanding of how specific conclusions are reached. This lack of interpretability undermines trust among cybersecurity analysts and decision-makers, particularly in high-stakes environments that require verifiable reasoning and accountability. Neuro-symbolic AI presents a potential solution by integrating neural learning with symbolic reasoning, enabling AI systems to combine adaptive data-driven inference with interpretable, logic-based decision processes. This hybrid approach is especially significant in cybersecurity, where trust, data quality, and inter-

pretability are foundational for defending against evolving, complex attacks. Addressing this research problem contributes to advancing trustworthy AI — a critical requirement for ensuring reliability, transparency, and ethical governance in cyber defense systems.

1.1.1 Research Question

This project aims to address the following research question:

> **How can Neuro-Symbolic AI architectures be developed to enhance the transparency, interpretability, and reliability of reasoning processes in AI-enabled cybersecurity environments?**

1.1.2 Research Aim

The aim of this study is to investigate and construct a trustworthy neuro-symbolic AI model that integrates data-quality assessment, symbolic reasoning, and explainable machine-learning techniques to strengthen the interpretability, robustness, and accountability of cybersecurity analytics.

1.1.3 Objectives

The primary objective of this review is to analyze how neuro-symbolic AI can enable more explainable and trustworthy reasoning in cybersecurity systems. Specifically, it aims to:

1. Identify key neuro-symbolic models and architectures applied to cybersecurity.
2. Assess how these approaches improve interpretability, transparency, and trustworthiness over traditional machine-learning methods.
3. Examine the influence of data quality and knowledge representation on reliable AI-driven cyber defense.
4. Outline current challenges, research gaps, and future directions for developing robust and explainable neuro-symbolic cybersecurity frameworks.

1.2 SDG's

Our project aligns with several United Nations Sustainable Development Goals. First, it advances **SDG 9: Industry, Innovation, and Infrastructure** by proposing an innovative neuro-symbolic XAI framework that strengthens the reliability, resilience, and security of digital infrastructures through improved data-quality management and transparent AI-driven cyber defense. It also supports **SDG 16: Peace, Justice, and Strong Institutions** by enhancing accountability, trust, and governance within cybersecurity systems, ensuring that AI decisions are explainable, auditable, and aligned with responsible data practices. Additionally, the project contributes to **SDG 4: Quality Education** by generating research knowledge, promoting advanced AI literacy, and providing a model that supports skill development in trustworthy AI, cybersecurity analytics, and data governance.

2 Methodology

2.1 Keywords Used

The following keywords were employed to identify and analyze relevant research works related to Neuro-Symbolic Artificial Intelligence and Data Quality within cybersecurity and explainable AI contexts:

> *"Neuro-Symbolic AI", "Explainable AI (XAI)", "Trustworthy AI", "Data Quality in Cybersecurity", "AI Transparency", "Hybrid Reasoning Systems", "Interpretable Machine Learning", "Cyber Threat Detection", "Data Integrity Assurance".*




Figure 1: Network visualization of publications on **Neuro-Symbolic AI**, **Explainable AI**, and **Reasoning**, illustrating the relationships among cognition, machine learning, and human–AI interaction.




Figure 2: Network visualization of research on **Neuro-Symbolic AI** and **Data Quality**, showing key links between explainable reasoning, machine learning, and trustworthy data management.

2.2 Databases/Tools Used

IEEE Xplore, ScienceDirect, SpringerLink, ACM Digital Library, arXiv, Google Scholar, and MDPI Open Access Journals.

2.3 Selection Criteria

The reviewed materials were chosen using specific inclusion and exclusion criteria to maintain academic reliability and alignment with the research scope. The inclusion criteria covered peer-reviewed articles, conference papers, and reputable preprints published between 2015 and 2025, addressing:

- Neuro-symbolic AI models and architectures;
- Explainable or interpretable AI techniques relevant to cybersecurity;
- Trustworthy AI frameworks emphasizing reasoning transparency;
- Studies addressing data quality, integrity, and reliability in cyber defense systems.

The exclusion criteria ruled out publications that:

- Focused exclusively on conventional machine learning without symbolic reasoning;
- Addressed explainability or trust in domains unrelated to cybersecurity;
- Lacked methodological or empirical depth.

3 Core Technique Explanation

3.1 Background: Trustworthy Neuro-Symbolic AI

Neuro-symbolic Artificial Intelligence (NSAI) represents a hybrid paradigm that merges the learning power of neural networks with the reasoning capabilities of symbolic logic. Neural networks excel in recognizing patterns and learning from large, unstructured datasets, while symbolic reasoning enables explicit rule-based inference that is interpretable and verifiable (20). The combination allows systems to both learn from complex data and reason in ways that align with human logic and accountability principles.

Trustworthy AI emphasizes not only performance but also fairness, reliability, and explainability (19). In this context, NSAI systems can enhance trustworthiness by incorporating logic-based structures that validate and constrain neural outputs, ensuring decisions remain transparent and ethically grounded. The symbolic component provides a reasoning trace, while the neural layer adapts to dynamic environments such as cybersecurity. This hybrid approach reduces uncertainty and supports interpretability, which is essential for critical decision-making systems (12).

Key Insight: Trustworthy NSAI bridges the gap between high-performance learning and human-understandable reasoning, offering a foundation for explainable and reliable AI in cybersecurity applications.

The final corpus was curated from reputable academic databases including IEEE Xplore, ScienceDirect, SpringerLink, ACM Digital Library, arXiv, Google Scholar, and MDPI Open Access Journals, ensuring a comprehensive and credible evidence base for synthesis and analysis.

3.2 Frameworks for Trustworthy and Explainable AI

In high-stakes domains such as cybersecurity, the deployment of Artificial Intelligence (AI) systems demands frameworks that systematically embed **trustworthiness**, **transparency**, and **explainability** throughout the system lifecycle. The *National Institute of Standards and Technology (NIST) AI Risk Management Framework (AI RMF, 2023)* establishes a lifecycle-based model structured around four core functions: *Map*, *Measure*, *Manage*, and

Govern (33). This framework identifies seven essential characteristics of trustworthy AI systems: validity and reliability, safety, security and resiliency, accountability and transparency, explainability and interpretability, privacy enhancement, and fairness, including bias mitigation(34).




Figure 3: Core principles of trustworthy AI—fairness, accountability, transparency, privacy, robustness, and safety—aligned with the NIST AI Risk Management Framework.

Complementary approaches, such as the *Taxonomy of Trustworthiness for Artificial Intelligence* from the University of California, Berkeley, further categorize these properties into over 150 measurable attributes across AI development stages(9). These frameworks support developers in aligning design objectives with ethical, legal, and societal expectations, while also promoting responsible AI governance.

In the context of **neuro-symbolic AI**, these frameworks provide a foundation for integrating symbolic reasoning with neural perception. The symbolic layer enhances interpretability and rule-based reasoning, while the neural layer provides adaptability and learning from data. When combined, these elements allow the construction of systems that are both high-performing and explainable.

By aligning the RMF's stages with the hybrid architecture of neuro-symbolic AI, designers can ensure continuous risk monitoring, transparent decision logic, and data governance that aligns with accountability principles(42).




Figure 4: Integration of trustworthy AI principles throughout the machine-learning lifecycle—from data collection and curation to model evaluation and implementation—supporting explainable reasoning in hybrid AI systems.




Figure 5: Comprehensive framework for implementing trustworthy AI, linking ethical foundations, key requirements, and assessment stages for continuous monitoring and accountability.

Key Insights:

- Adopt a lifecycle approach from context mapping to governance and continuous assurance.
- Implement explainability at both model and data levels using symbolic logic for reasoning traceability.
- Link trustworthiness attributes directly with system design requirements for fairness, privacy, and accountability.
- Ensure cross-disciplinary collaboration between data scientists, cybersecurity experts, and AI ethicists.

3.3 Data-Quality Management in Cybersecurity AI

Reliable and secure AI-based cybersecurity systems are fundamentally dependent on the **quality of the data** they process. Poor data quality—including missing values, inconsistent formats, incorrect labels, or data drift—can significantly reduce model reliability, leading to false positives, missed attacks, and biased predictions(1). Maintaining accuracy, completeness, and timeliness in cybersecurity data streams is therefore critical for trustworthy AI performance(50).




Figure 6: Five stages of the data-quality lifecycle management process, showing iterative phases from metric identification and assessment to data repair, storage, and exploration.

Recent studies emphasize that data quality management (DQM) should be treated as a continuous process integrated into cybersecurity pipelines. Frameworks highlight six essential dimensions of data quality—accuracy, completeness, consistency, timeliness, validity, and uniqueness—that directly influence model outcomes and decision reliability(57). In AI-driven environments, automated tools such as anomaly detectors, outlier identification modules, and adversarial data monitors are increasingly used to maintain high data integrity(54).

In cybersecurity, the complexity is magnified by large-scale, heterogeneous datasets (e.g., logs, telemetry, and network traffic) and evolving threats that create data drift. Addressing these challenges requires context-aware and adaptive DQM mechanisms. Integrating neuro-symbolic AI enables the development of explainable reasoning systems where symbolic rules validate data sources, and neural modules enhance pattern detection across massive datasets. This combination ensures both the **explainability** and **trustworthiness** of AI decision-making pipelines(4).




Figure 7: Conceptual framework for data-quality management in AI pipelines, linking baseline quality metrics, rule authoring, and monitoring components with downstream analytical systems.




Figure 8: Intersection between data quality and data governance, illustrating how auditing, validation, and compliance jointly support explainable and trustworthy AI in cybersecurity contexts.

Key Insights:

- Treat data quality management as a core trust-enabling process within cybersecurity AI.
- Utilize symbolic reasoning to enforce rules for data provenance, consistency, and integrity.
- Employ adaptive neural models to detect and correct errors in dynamic and adversarial environments.
- Align DQM practices with trustworthiness frameworks (e.g., NIST AI RMF) to ensure dependable system performance.

3.4 Neuro-Symbolic Techniques for Explainable Reasoning

Explainable reasoning in neuro-symbolic systems arises from integrating logical inference with deep learning. Several key techniques have emerged to achieve this synthesis:

- Logic Tensor Networks (LTNs) embed first-order logic constraints into differentiable neural networks, enabling systems to reason over

symbolic knowledge bases while learning from data (20).

- Differentiable Inductive Logic Programming (DILP) generalizes traditional logic programming to differentiable spaces, allowing simultaneous learning and reasoning (55).
- Graph Neural–Symbolic Models represent entities and relationships through graph structures, supporting relational reasoning for tasks like anomaly or threat detection (56).
- Probabilistic Logic Networks (PLNs) handle uncertain or incomplete information by integrating probabilistic reasoning with symbolic logic.
- Constraint-Guided Neural Models use symbolic rules as constraints that guide the learning process to maintain explainability and compliance with domain logic (22).

These methods enable hybrid AI systems to provide interpretable decision pathways that can be audited and understood by human experts. For cybersecurity, this means analysts can trace anomaly detections or risk assessments back to symbolic rules or policy violations, enhancing both trust and operational transparency.

Key Insights: Neuro-symbolic techniques transform opaque neural outputs into logic-based reasoning steps that strengthen interpretability and accountability.

4 Survey of Recent Advances

4.1 Applications in Cybersecurity Data Quality

Data quality is a cornerstone of effective and trustworthy cybersecurity systems. Poor data quality—such as incomplete, inconsistent, or biased inputs—can result in false positives, missed attacks, or unreliable predictions (1). Neuro-symbolic AI provides innovative solutions for managing these issues by integrating reasoning mechanisms directly into data pipelines.

In intrusion detection systems, symbolic logic can encode predefined security policies or behavioral baselines, while neural networks detect deviations from these patterns (56). The hybrid model not only flags anomalies but also explains why a detection occurred, supporting interpretability and auditability. Similarly, in threat intelligence and log analysis, symbolic layers can integrate structured knowledge sources (e.g., MITRE ATT and CK frameworks) with unstructured network data to enhance reasoning transparency (22).

Neuro-symbolic models also play a key role in data integrity assurance. Symbolic reasoning validates data provenance and consistency, while neural components monitor dynamic or adversarial data streams for anomalies (54). This dual mechanism ensures that cybersecurity data pipelines remain reliable and explainable throughout their lifecycle.

Key Insights: Neuro-symbolic AI enhances cybersecurity data quality by combining symbolic validation of data integrity with neural adaptability for real-time detection and reasoning.

4.2 Opportunities

- **Adaptive Knowledge Graphs:** Dynamic and self-updating graphs can evolve with new threat intelligence, reducing manual maintenance and improving symbolic reasoning (22).
- **Lightweight NSAI Architectures:** Emerging work explores resource-efficient hybrid models suitable for real-time cybersecurity applications while maintaining interpretability (12).
- **Standardized Trust and Explainability Metrics:** Development of unified benchmarks aligned with frameworks like the NIST AI RMF can strengthen evaluation, fairness, and trustworthiness (34).
- **Human–AI Co-Reasoning Interfaces:** Interactive tools can help analysts understand reasoning paths, enhancing decision-making, trust calibration, and operational transparency (42).
- **Integration of Ethical and Policy Rules:** Embedding privacy, compliance, and governance constraints directly into symbolic reasoning can improve responsible and accountable deployment (31).

Key Insight: While challenges persist—especially in scalability, data quality, and standardiza-

tion—opportunities such as adaptive knowledge structures, unified metrics, and human–AI collaboration point toward more transparent, ethical, and reliable neuro-symbolic cybersecurity systems.

4.3 Comparative Analysis Table

Paper Title	Problem Discussed	Solution Provided	Methods and Techniques Used	Final Solutions	Future Recommendations	Refs
Pipino, Lee & Wang (2002) – *Data Quality Assessment Framework*	No systematic DQ measurement	Introduced hybrid quantitative–qualitative assessment	Metrics, surveys, and rule-based analysis	Provided first hybrid DQ evaluation model	Automate data-quality scoring in enterprises	(38)
Batini & Scannapieco (2006) – *Data Quality: Concepts, Methodologies and Techniques*	Lack of unified DQ theory	Proposed comprehensive taxonomy and lifecycle model	Analytical modeling and case studies	Defined DQ dimensions and governance process	Extend to Big Data and AI systems	(5)
Strong, Lee & Wang (2009) – *Organizational Data Quality Management*	Poor governance in information systems	Developed process-centric DQ management	Interviews and process design mapping	Achieved business-process level DQ improvement	Extend framework to real-time applications	(48)
Batini et al. (2009) – *Data Quality in E-Government*	Inconsistent records across public agencies	E-Gov DQ governance model	Metadata registry, ontology mapping	Cross-agency data trust improvement	Apply to interdepartmental cybersecurity systems	(6)
Oliveira et al. (2005) – *Assessing Data Warehouse Quality*	Inaccurate warehouse data for BI	ETL-phase profiling and validation	Metrics and rule-based profiling tools	Improved DW reliability for decision-making	Automate ETL quality assurance	(36)
Scannapieco et al. (2004) – *Designing DQ Metrics*	Absence of quantifiable quality metrics	DQ metrics design at schema level	Constraint-based modeling	Standardized metrics for relational data	Extend metrics to unstructured formats	(44)
Redman (2001) – *Data Quality for the Information Age*	Lack of enterprise-wide DQ ownership	Corporate DQ management blueprint	Governance model + case studies	Institutionalized DQ accountability	Align DQ with enterprise risk management	(39)
English (2009) – *Information Quality Applied*	Data-quality improvement not embedded in operations	Data stewardship program for enterprises	Policy modeling and stewardship audits	Enhanced data reliability and process trust	Integrate DQ with data-governance tools	(17)
Batini et al. (2010) – *DQ Framework for Information Systems*	Fragmented DQ approaches across industries	Model integrating process, data, and organization	Multi-dimensional DQ architecture	Holistic governance framework	Extend model to big-data workflows	(7)
Lee & Strong (2004) – *Measuring Information Quality*	Lack of practical DQ measurement tools	DQ measurement using user perspectives	Surveys and validation testing	Cross-validated perception-based DQ metrics	Develop predictive quality KPIs	(27)

Table 1: Data quality foundations and early enterprise frameworks (2000–2010).

Paper Title	Problem Discussed	Solution Provided	Methods and Techniques Used	Final Solutions	Future Recommendations	Refs
Fan et al. (2013) – *Data Quality in Big Data*	Unreliable data in large datasets	Scalable rule-based DQ framework	MapReduce, statistical repair	Improved DQ repair performance	Combine with ML validation	(18)
Strong et al. (2014) – *Managing DQ in Enterprise Systems*	Lack of DQ ownership in ERP	Strategic five-phase methodology	Audits, KPIs, training	Reliable analytics	Develop certification systems	(49)
Scannapieco & Catarci (2015) – *Quality-Aware Data Integration*	Integration errors in heterogeneous data	DQ-aware ETL pipelines	Metadata lineage, constraints	Accurate data integration	Automate semantic matching	(45)
Wang et al. (2016) – *DQ Beyond Consistency and Deduplication*	Missing timestamps, uncertain records	Unified logic-based DQ repair	CFDs, denial constraints	Better completeness and repair	Automate constraint discovery	(18)
Sambasivan et al. (2021) – *Data Cascades in ML*	Downstream model failure from poor data	Framework for upstream DQ governance	Case studies, interviews	Human–data interaction insights	Institutionalize DQ culture	(43)
Breck et al. (2017) – *ML Test Score*	ML pipelines lack DQ checks	Testing framework for ML	Data validation metrics	Reduced errors in production	Embed in MLOps tools	(8)
Northcutt et al. (2021) – *Confident Learning*	Hidden label errors in datasets	Statistical noise estimation	Confidence learning algorithm	Detected mislabels automatically	Use for large AI datasets	(35)
Sculley et al. (2015) – *Hidden Technical Debt in ML*	Fragile data dependencies	Checklist for ML reliability	Case analysis, testing	Reliable data pipelines	Standardize MLOps checks	(46)
Kandel et al. (2012) – *Wrangler: Interactive Data Cleaning*	Tedious manual data cleaning	Visual transformation platform	Pattern inference, UIs	Interactive DQ correction	Expand to web-scale data	(25)
Chu et al. (2016) – *Data Cleaning Research*	Lack of automated tools	End-to-end cleaning pipeline	Detection + repair models	Unified cleaning architecture	Integrate AI-driven rules	(10)

Table 2: Big Data and AI-era data quality methods and tools (2011–2020).

Paper Title	Problem Discussed	Solution Provided	Methods and Techniques Used	Final Solutions	Future Recommendations	Refs
Zhou et al. (2024) – *A Survey on DQ Dimensions for ML*	Undefined DQ in AI pipelines	Consolidated taxonomy for ML data quality	Review + experiment meta-analysis	Six key DQ dimensions for AI	Standardize DQ evaluation metrics	(57)
AIMultiple (2024) – *Data Quality in AI*	Inaccurate, incomplete training data	Practical AI DQ pipeline guidance	Profiling, anomaly detection, dashboards	End-to-end enterprise DQ workflow	Combine governance + AI validation	(1)
TechStrong (2024) – *AI Data Quality Management*	Accuracy and timeliness gaps in AI data	Continuous DQ monitoring framework	ML-based outlier detection	Improved integrity for AI decisions	Introduce AI-based alerting systems	(50)
Australian Cyber Centre (2024) – *AI Data Security Guidelines*	Weak DQ in cybersecurity AI	National governance framework	Policy-driven integrity checks	Secure, explainable data pipelines	Combine with DQ monitoring AI	(4)
Li et al. (2025) – *Trustworthy AI: Safety, Bias, and Privacy*	Unreliable datasets reduce AI trust	Survey on trustworthy AI practices	Case analysis + bias detection	Comprehensive trustworthy-AI taxonomy	Link DQ to explainability	(52)
Colelough & Regli (2025) – *Neuro-Symbolic AI in 2025*	Lack of trust in hybrid models	Systematic review of NeSy frameworks	Literature synthesis	Transparent AI integration models	Include data-quality indicators	(12)
Grov et al. (2024) – *Neurosymbolic Cyber Defense*	Poor interpretability of AI security tools	Hybrid symbolic–neural reasoning	Rule-based + learning fusion	Enhanced cyber-threat explainability	Scale to cloud-level datasets	(22)
Zhang et al. (2024) – *Explainable NeSy for Cybersecurity*	Unexplainable ML in IDS	XAI + neuro-symbolic model	SHAP, logic inference, neural layers	Transparent detection pipeline	Add fairness-aware mechanisms	(56)
Xu & Silver (2024) – *Bridging Learning and Reasoning*	Reasoning gap in AI pipelines	Hybrid symbolic + deep learning review	Survey + evaluation	Unified NeSy reasoning taxonomy	Extend to data-quality validation	(55)
VLDB TaDA Workshop (2024) – *Toward Adaptive Data Quality in AI Pipelines*	Static DQ pipelines fail under data drift	Adaptive rule-driven data-quality management	Real-time anomaly detection, KPIs	Continuous AI data-quality governance	Merge with trustworthy AI RMF	(54)

Table 3: Recent studies connecting AI, data quality, and cybersecurity governance (2021–2025).

4.4 Discussion and Future Directions

The evolution of neuro-symbolic AI (NSAI) marks a significant shift in cybersecurity research, moving from purely data-driven models toward hybrid systems that integrate symbolic reasoning with neural learning. This combination directly addresses the long-standing "black-box problem" in deep learning by making system decisions more transparent, auditable, and aligned with human reasoning (20; 55). As a result, NSAI enables cybersecurity analysts to trace detection logic, verify model outputs, and apply explicit policy- or rule-based constraints during threat analysis.

In parallel, the rise of trustworthy AI frameworks has strengthened the movement toward ethical, transparent, and accountable cyber defense systems. Frameworks such as the NIST AI Risk Management Framework and the Berkeley Taxonomy of Trustworthiness highlight the need for explainability, fairness, resilience, and governance across the full AI lifecycle (33; 9). These principles align naturally with the capabilities of neuro-symbolic architectures, which inherently support logic-based validation, explicit reasoning steps, and interpretable outputs.

Current research trends indicate growing interest in integrating NSAI with lifecycle-based governance practices. This includes incorporating trustworthiness requirements—such as transparency, privacy preservation, interpretability, and accountability—from the earliest design stages rather than as an afterthought. Studies consistently show that such integration improves analyst confidence and supports more reliable, compliant cybersecurity systems (19).

Overall, the literature reflects a clear trajectory: neuro-symbolic AI is emerging as a foundational approach for building transparent, trustworthy cybersecurity systems. While the field is still developing, current research demonstrates strong momentum toward systems that blend adaptive learning with interpretable reasoning, setting the stage for more robust and responsible cyber defense technologies.

5 Challenges and Research Gaps

5.1 Challenges

- **Scalability:** Integrating symbolic reasoning with neural models increases computational complexity, making real-time cybersecurity deployment difficult.
- **Knowledge Base Maintenance:** Symbolic reasoning relies on curated rules and ontologies that must be frequently updated to reflect evolving cyber threats, requiring substantial manual effort.
- **Explainability–Performance Trade-off:** Enhancing interpretability through symbolic logic can reduce predictive performance, while optimizing neural accuracy often decreases explainability.
- **Data Bias and Incomplete Logs:** NSAI systems are highly sensitive to data quality; biased datasets, missing logs, or noisy telemetry can propagate errors across symbolic and neural layers.
- **Lack of Evaluation Standards:** There are no universally accepted benchmarks for assessing trustworthiness, explainability, or reasoning quality in neuro-symbolic AI systems.

5.2 Discussion and Future Directions (Key Challenges)

The second half of the discussion highlights several unresolved limitations that must be addressed to advance trustworthy neuro-symbolic AI in cybersecurity:

- **Trust Calibration Issues:** Human analysts may either over-trust or under-trust hybrid AI outputs. Misalignment between perceived system reliability and actual model performance can lead to false confidence, ignored alerts, or poor decision-making.
- **Need for Uncertainty Quantification:** Most NSAI systems do not provide clear measures of uncertainty in their predictions or reasoning paths. Transparent uncertainty estimates are essential for helping cybersecurity professionals judge when to rely on automated decisions.
- **Human–AI Misunderstanding:** Even when explanations are provided, analysts may misinterpret symbolic outputs, neural confidence levels, or mixed reasoning steps. Improved co-explanation interfaces and intuitive visualizations are required to bridge human–AI understanding gaps.
- **Governance Limitations:** Current governance frameworks are not consistently inte-

grated across the full NSAI lifecycle. Trustworthiness requirements—such as fairness, accountability, transparency, and privacy—must be embedded from system design through deployment and continuous monitoring.

5.3 Future Work

Future work in trustworthy neuro-symbolic AI should address the following key directions:

- **Scalable Neuro-Symbolic Architectures:** Develop distributed, lightweight, and resource-efficient NSAI models capable of operating at the scale of real-world cybersecurity data while preserving interpretability.
- **Adaptive Knowledge Graphs:** Create dynamic symbolic knowledge bases and knowledge graphs that update automatically as threat intelligence evolves, enabling real-time reasoning about emerging cyber-attacks.
- **Standardized Trust and Explainability Metrics:** Establish formal benchmarks and evaluation standards for measuring transparency, fairness, robustness, and accountability in hybrid AI systems, aligned with frameworks such as NIST AI RMF and ISO/IEC AI standards.
- **Human–AI Co-Reasoning Interfaces:** Design interactive tools that allow security analysts to collaboratively explore symbolic reasoning paths and neural evidence, improving transparency and decision-making.
- **Ethical and Adversarial Robustness:** Strengthen NSAI systems against adversarial manipulation while integrating ethical constraints, privacy safeguards, and data provenance validation directly into symbolic reasoning layers.

6 Proposed System/Application

The proposed system is a **Neuro-Symbolic Explainable AI (XAI) cybersecurity framework** that integrates data-quality management, neural models, symbolic rules, and explainability modules into a single architecture (see Appendix A). The goal is to provide cybersecurity analysts with alerts that are not only accurate, but also transparent, traceable, and based on high-quality data.

The architecture is organized into four main layers:

1. **Data Collection Layer**
   This layer ingests heterogeneous cybersecurity data from multiple operational sources, such as:
   - system and application logs,
   - security alerts and intrusion detection events,
   - external threat intelligence feeds (e.g., known malicious IPs, malware indicators),
   - user and device information (roles, assets, and activity).

   By aggregating diverse data streams, the system builds a rich view of the environment that supports both pattern-based detection and symbolic reasoning.

2. **Data Cleaning & Quality Layer**
   The second layer focuses on data reliability and trust. It performs:
   - detection and handling of missing values,
   - identification and removal of duplicate records,
   - detection of statistical and contextual outliers,
   - identification of potential labeling errors,
   - normalization of formats and timestamps across sources.

   For each record, the system computes a *Data Quality Score* that summarizes completeness and detected issues. This score is propagated to downstream modules so that both the AI models and the explanations can reflect data-quality considerations.

3. **AI + Rule Analysis Layer**
   This core layer combines data-driven learning with explicit knowledge:
   - *Format & Text Representation:* key fields are extracted from logs and alerts, and textual content is converted into numerical embeddings or features suitable for machine learning models.
   - *Neural Models:* anomaly-detection and classification models learn patterns of normal and malicious behavior from historical data. They generate predictions such as “benign,” “suspicious,” or “malicious” along with anomaly scores.

- *Rules & Expert Knowledge:* domain rules, policies, and expert-defined patterns (e.g., blocklists, rate limits, policy violations) are encoded symbolically.
- *Neuro-Symbolic Reasoning:* a hybrid reasoning module combines neural outputs with symbolic constraints. Rules can reinforce or override model predictions, enforce safety policies, and provide structured reasoning traces. This reduces the "black-box" effect by anchoring decisions in explicit logic while still leveraging learned patterns.

4. **Explainability, Trust, and Output Layer**
   The final layer exposes the system behaviour to human analysts and external tools:
   - *Why-explanations:* the system highlights important features, triggered rules, and key evidence that led to each alert or decision.
   - *Risk & Quality View:* alerts are accompanied by confidence scores and the corresponding Data Quality Score, helping analysts judge how much to trust each output.
   - *Drift & Health Monitoring:* dedicated monitors track data drift, model performance, and rule activations over time, signalling when retraining or rule updates may be required.
   - *Alert Dashboard and Clean Threat Intelligence:* alerts, explanations, and cleaned threat indicators are presented via dashboards and exposed through APIs so that SIEM/SOAR platforms and other security tools can consume trustworthy, deduplicated threat data.
   - *Security & Access Control:* access to data, explanations, and configuration is protected through authentication, authorization, and encryption, ensuring that only authorized stakeholders can view or modify the system.

Overall, the proposed system operationalizes trustworthy AI principles by coupling rigorous data-quality management with neuro-symbolic reasoning and rich explainability. Each stage of the pipeline—from data collection to final alerts—is designed to improve transparency, reliability, and analyst trust in AI-assisted cybersecurity decisions.

7 Expected Benefits and Limitations

This section outlines the advantages offered by the proposed Neuro-Symbolic XAI cybersecurity system, followed by key limitations that must be considered for real-world deployment.

7.1 Expected Benefits

1. **Enhanced Data Reliability**
   The integrated Data Quality Layer improves the trustworthiness of cybersecurity data by addressing missing values, duplicate rows, outliers, and labeling errors. The inclusion of a *Data Quality Score* ensures that downstream AI components are aware of data integrity issues and can adjust their decision-making accordingly.

2. **Explainable and Auditable Alerts**
   The Neuro-Symbolic Reasoning module produces alerts that are supported by both neural evidence and explicit rule-based logic. This allows cybersecurity analysts to understand *why* a prediction was made, bridging the gap between deep-learning accuracy and human trust.

3. **Improved Trustworthiness and Transparency**
   The system aligns with core principles from frameworks such as the NIST AI Risk Management Framework, including explainability, reliability, accountability, and transparency. Each alert includes features, rules, confidence scores, and data-quality indicators, strengthening user trust.

4. **Continuous Monitoring and Drift Detection**
   The Drift & Health Monitoring module continuously evaluates data distributions and model behavior, providing early warnings when retraining or rule updates are required. This ensures long-term model relevance in dynamic cybersecurity environments.

5. **High-Quality Threat Intelligence Output**
   The system produces clean, enriched, and deduplicated threat intelligence. This improves interoperability with SIEM, SOAR, and security orchestration tools, supporting faster and more accurate incident response.

7.2 Limitations

1. **Scalability and Computational Overhead**
   Neuro-symbolic architectures combine neural inference with symbolic reasoning, increasing computational load. Real-time detection in high-volume environments may require substantial computing resources or model optimization.

2. **Knowledge-Base Maintenance**
   Symbolic rules and expert-driven policies must be regularly updated to reflect evolving cyber threats. This requires continuous collaboration between security experts and system engineers.

3. **Explainability–Performance Trade-off**
   Enhancing explainability through symbolic constraints may reduce raw neural accuracy or increase inference time. Balancing interpretability and performance remains an active challenge.

4. **Dependence on Data Quality**
   Although the system includes strong data-cleaning capabilities, extremely noisy or adversarial data may still propagate errors. Low-quality or incomplete telemetry can weaken both neural predictions and symbolic reasoning.

5. **Lack of Standard Evaluation Metrics**
   The field of neuro-symbolic explainable cybersecurity lacks unified benchmarks for measuring trustworthiness, reasoning quality, and interpretability. This makes systematic evaluation and comparison across systems difficult.

Overall, while the system offers significant benefits in transparency, trust, and data reliability, it must be developed and deployed with awareness of these practical and methodological limitations.

8 Future Research Directions

The development of neuro-symbolic, explainable, and data-quality–aware cybersecurity systems opens several pathways for future advancement. Building on the identified research gaps and system limitations, the following directions outline the most promising areas for continued exploration.

1. **Scalable and Lightweight Neuro-Symbolic Architectures**
   Future work should focus on designing computationally efficient neuro-symbolic models capable of operating in real-time, high-volume cybersecurity environments. This includes exploring distributed architectures, model compression, and hardware-accelerated reasoning techniques.

2. **Adaptive and Self-Updating Knowledge Graphs**
   Symbolic rules and knowledge structures must evolve with emerging threats. Developing adaptive knowledge graphs that automatically incorporate new threat intelligence, behavioral patterns, and expert policies can significantly reduce manual maintenance effort.

3. **Standardized Metrics for Trustworthiness and Explainability**
   There is a crucial need for unified benchmarks to evaluate transparency, fairness, robustness, and reasoning quality in hybrid AI systems. Future research should contribute to the creation of standardized evaluation protocols aligned with frameworks such as the NIST AI RMF and emerging ISO/IEC AI standards.

4. **Human–AI Co-Reasoning Interfaces**
   As neuro-symbolic systems become more sophisticated, intuitive interfaces are required to help analysts interpret rule activations, neural evidence, and data-quality impacts. Future work should explore interactive visualization tools and collaborative reasoning environments.

5. **Ethical, Privacy-Preserving, and Policy-Aware AI Reasoning**
   Integrating privacy constraints, compliance rules, and ethical considerations into symbolic reasoning layers can enhance responsible cyber defense. Future research may focus on how hybrid reasoning models can enforce legal and ethical constraints without degrading performance.

6. **Adversarially Robust Data Quality Mechanisms**
   As attackers increasingly target data pipelines, future work should investigate robustness techniques for detecting adversarial manipulation

during data collection, cleaning, and quality scoring. This includes improving the resilience of labeling error detection, anomaly identification, and provenance validation.

7. **Automated Rule Learning and Hybrid Optimization**
   Another promising direction involves automatically generating symbolic rules from neural signals or historical threat patterns. Hybrid optimization methods could refine rules and model parameters jointly, improving both interpretability and detection performance.

In summary, future research should continue advancing the interpretability, adaptability, and robustness of neuro-symbolic cybersecurity systems while ensuring rigorous trustworthiness and strong data-quality governance.

9 Conclusion

The proposed Neuro-Symbolic Explainable AI (XAI) framework enhances trust, transparency, and reliability in cybersecurity systems by integrating data-quality controls, neural anomaly detection, symbolic rules, and interpretable outputs. This combination directly addresses challenges such as black-box model behavior and inconsistent or unreliable data.

By ensuring high-quality inputs and unifying neural learning with rule-based reasoning, the system delivers decisions that are both accurate and auditable. Its explainability components confidence scores, key features, and rule-based justifications further support analysts in making clear, trustworthy, and informed cybersecurity decisions.

While the architecture provides strong benefits—such as improved interpretability, better data reliability, and continuous drift monitoring—it also faces challenges related to scalability, symbolic rule maintenance, and the absence of standardized trust metrics. These limitations emphasize the need for continued research on adaptive knowledge structures, efficient hybrid reasoning, and robust data-quality mechanisms.

Overall, the proposed system offers a meaningful step toward trustworthy AI in cybersecurity. By integrating data governance, neuro-symbolic reasoning, and clear explainability, it establishes a foundation for building resilient, transparent, and responsibly governed cyber defense systems.

10 References

References

[1] AI Multiple Research, "Data Quality in AI: Challenges and Best Practices," 2024. [Online]. Available: https://research.aimultiple.com/data-quality-ai/.

[2] Anonymous, "Neurosymbolic AI and its Taxonomy: A Survey," *arXiv preprint* arXiv:2305.08876, 2023.

[3] Anonymous, "Surveying Neuro-Symbolic Approaches for Reliable Artificial Intelligence," *AI Communications*, vol. –, pp. –, 2024.

[4] Australian Cyber Security Centre, "AI Data Security and Quality Guidelines," 2024. [Online]. Available: https://www.cyber.gov.au/business-government/secure-design/artificial-intelligence/ai-data-security.

[5] C. Batini and M. Scannapieco, *Data Quality: Concepts, Methodologies and Techniques*. Springer, 2006. doi: 10.1007/3-540-33173-5.

[6] C. Batini, M. Scannapieco, and A. Barone, "Data quality in e-government: Case studies and assessment methods," *Information Systems*, vol. 34, no. 3, pp. 324–335, 2009. doi: https://www.gov.uk/government/publications/the-government-data-quality-framework/the-government-data-quality-framework-case-studies.

[7] C. Batini, M. Scannapieco, and S. Bergamaschi, "A conceptual data-quality framework for information systems," *Journal of Data and Information Quality*, vol. 2, no. 2, pp. 1–18, 2010. doi: 10.1145/1805286.1805288.

[8] E. Breck, N. Polyzotis, S. Roy, S. Whang, and M. Zinkevich, "The ML Test Score: A Rubric for ML Production Readiness and Technical Debt Reduction," *NIPS ML Systems Workshop*, 2017. Available: https://arxiv.org/abs/1706.02245.

[9] Center for Long-Term Cybersecurity (CLTC), "A Taxonomy of Trustworthiness for Artificial Intelligence," University of California, Berkeley, 2023. Available: https://cltc.berkeley.edu/publication/a-taxonomy-of-trustworthiness-for-artificial-intelligence-standalone-taxonomy/.

[10] X. Chu, I. F. Ilyas, S. Krishnan, and J. Wang, "Data Cleaning: Overview and Emerging Challenges," *SIGMOD*, pp. 2201–2206, 2016. doi: 10.1145/2882903.2912574.

[11] B. C. Colelough and W. Regli, "Neuro-Symbolic AI in 2024: A Systematic Review," *CEUR Workshop Proceedings*, vol. 3819, pp. 1–18, 2024.

[12] A. Colelough and W. Regli, "Neuro-Symbolic AI in 2025: A Systematic Review," *arXiv preprint* arXiv:2501.05435, 2025. Available: https://arxiv.org/abs/2501.05435.

[13] I. Donadello, L. Serafini, and A. d'Avila Garcez, "Logic Tensor Networks for Semantic Image Interpretation," *arXiv preprint* arXiv:1705.08968, 2017. Available: https://arxiv.org/abs/1705.08968.

[14] F. Doshi-Velez and B. Kim, "Towards A Rigorous Science of Interpretable Machine Learning," *arXiv preprint* arXiv:1702.08608, 2017. Available: https://arxiv.org/abs/1702.08608.

[15] European Data Protection Supervisor (EDPS), "Explainable Artificial Intelligence (TechDispatch 2023)," 2023. [Online]. Available: https://www.edps.europa.eu/system/files/2023-11/23-11-16_techdispatch_xai_en.pdf.

[16] European Commission, "EU Artificial Intelligence Act: Ensuring Trustworthy and Safe AI Systems," 2024. [Online]. Available: https://digital-strategy.ec.europa.eu/en/policies/regulatory-framework-ai.

[17] L. P. English, *Information Quality Applied: Best Practices for Improving Business Information, Processes and Systems*. Wiley, 2009.

[18] W. Fan, F. Geerts, J. Li, and M. Xiong, "Discovering Conditional Functional Dependencies," *IEEE Transactions on Knowledge and Data Engineering*, vol. 23, no. 5, pp. 683–698, 2013. doi: https://dl.acm.org/doi/10.1109/TKDE.2010.154.

[19] L. Floridi and J. Cowls, "A Unified Framework for Trustworthy Artificial Intelligence," *AI and Ethics*, vol. 4, no. 2, pp. 211–225, 2023. doi: https://www.pmi.org/blog/trustworthy-ai-framework.

[20] A. d'Avila Garcez, L. C. Lamb, and D. Gabbay, "Neurosymbolic AI: The 2023 Perspective," *Artificial Intelligence Review*, 2023. doi: 10.1007/s10462-023-10448-w.

[21] A. Ghorbani and J. Zou, "Data Shapley: Equitable Valuation of Data for Machine Learning," *arXiv preprint* arXiv:1904.02868, 2019. Available: https://arxiv.org/abs/1904.02868.

[22] E. Grov, P. Johnson, and J. E. Laird, "Neurosymbolic Approaches for Defending Against Cyber Threats," *arXiv preprint* arXiv:2408.04996, 2024. Available: https://arxiv.org/abs/2408.04996.

[23] IBM, "What Is Black Box AI and How Does It Work?," 2024. [Online]. Available: https://www.ibm.com/think/topics/black-box-ai.

[24] ISACA, "Developing Trustworthy AI: Understanding the Inputs," *ISACA Journal*, vol. 4, 2024. Available: https://www.isaca.org/resources/isaca-journal/issues/2024/volume-4/developing-trustworthy-ai-understanding-the-inputs.

[25] S. Kandel, A. Paepcke, J. M. Hellerstein, and J. Heer, "Wrangler: Interactive Visual Specification of Data Transformation Scripts," *CHI '11 Proceedings*, pp. 3363–3372, 2011. doi: 10.1145/1978942.1979444.

[26] P. W. Koh, T. Nguyen, Y. Tang, et al., "Concept Bottleneck Models," *Decision Support Systems*, vol. 41, no. 3, pp. 385–396, 2005. Available: https://www.sciencedirect.com/science/article/abs/pii/S0378720604000230?via%3Dihub.

[27] Y. W. Lee and D. M. Strong, "Measuring Information Quality," *Information & Management*, vol. 42, no. 2, pp. 233–245, 2004. doi: 10.1016/j.im.2003.12.012.

[28] S. M. Lundberg and S.-I. Lee, "A Unified Approach to Interpreting Model Predictions," *arXiv preprint* arXiv:1705.07874, 2017. Available: https://arxiv.org/abs/1705.07874.

[29] R. Manhaeve, S. Dumancic, A. Kimmig, T. Demeester, and L. De Raedt, "DeepProbLog: Neural Probabilistic Logic Programming," *arXiv preprint* arXiv:1805.10872, 2018. Available: https://arxiv.org/abs/1805.10872.

[30] J. Mao, C. Gan, P. Kohli, J. Tenenbaum, and J. Wu, "The Neuro-Symbolic Concept Learner: Interpreting Scenes, Words, and Sentences From Natural Supervision," *arXiv preprint* arXiv:1904.12584, 2019. Available: https://arxiv.org/abs/1904.12584.

[31] McKinsey & Company, "The State of AI 2024: Global Adoption, Risks, and Responsible Use," 2024. [Online]. Available: https://www.mckinsey.com/capabilities/quantumblack/our-insights/the-state-of-ai-2024.

[32] V. Z. Mohale *et al.*, "A Systematic Review on the Integration of Explainable and Trustworthy AI in Cybersecurity," *Frontiers in Artificial Intelligence*, vol. –, pp. –, 2025.

[33] National Institute of Standards and Technology (NIST), "Artificial Intelligence Risk Management Framework (AI RMF 1.0)," U.S. Department of Commerce, Jan. 26, 2023. Available: https://nvlpubs.nist.gov/nistpubs/ai/nist.ai.100-1.pdf.

[34] National Institute of Standards and Technology (NIST), "Characteristics of Trustworthy Artificial Intelligence Systems," AI RMF Resource Center, 2023. Available: https://airc.nist.gov/airmf-resources/airmf/3-sec-characteristics.

[35] C. G. Northcutt, A. Jiang, and I. L. Chuang, "Confident Learning: Estimating Uncertainty in Dataset Labels," *Journal of Machine Learning Research*, vol. 22, no. 185, pp. 1–59, 2021. Available: https://jmlr.org/papers/v22/20-182.html.

[36] J. D. Oliveira, M. Batista, and J. Machado, "Assessing Data Warehouse Quality," *Decision Support Systems*, vol. 38, no. 2, pp. 161–177, 2005. doi:

[37] N. Papernot, P. McDaniel, X. Wu, S. Jha, and A. Swami, "Distillation as a Defense to Adversarial Perturbations," *arXiv preprint* arXiv:1511.04508, 2016. Available: https://arxiv.org/abs/1511.04508.

[38] L. L. Pipino, Y. W. Lee, and R. Y. Wang, "Data Quality Assessment Framework," *Communications of the ACM*, vol. 45, no. 4, pp. 211–218, 2002. doi: 10.1145/505248.506010.

[39] T. C. Redman, *Data Quality for the Information Age*. Artech House, 2001.

[40] M. T. Ribeiro, S. Singh, and C. Guestrin, "Why Should I Trust You? Explaining the Predictions of Any Classifier," *KDD*, 2016. doi: 10.1145/2939672.2939778.

[41] C. Rudin, "Stop Explaining Black Box Machine Learning Models for High Stakes Decisions and Use Interpretable Models Instead," *Nature Machine Intelligence*, vol. 1, pp. 206–215, 2019. doi: 10.1038/s42256-019-0048-x.

[42] W. Saeed and C. Omlin, "Explainable AI (XAI): A Systematic Meta-Survey of Current Challenges and Future Opportunities," *arXiv preprint* arXiv:2111.06420, 2021. Available: https://arxiv.org/abs/2111.06420.

[43] N. Sambasivan, S. Arnesen, B. Hutchinson, et al., "Data Cascades in High-Stakes AI," *ACM FAccT*, 2021. doi: 10.1145/3442188.3445888.

[44] M. Scannapieco, A. Vinci, and T. Tucci, "Designing Data Quality Metrics," *Journal of Data and Information Quality*, vol. 1, no. 1, pp. 37–55, 2004. doi: https://dqops.com/data-quality-metrics/.

[45] M. Scannapieco and T. Catarci, "Data Quality-Aware Integration of Heterogeneous Information Sources," *Information Systems*, vol. 53, pp. 224–241, 2015. doi:

[46] D. Sculley, G. Holt, D. Golovin, et al., "Hidden Technical Debt in Machine Learning Systems," *NeurIPS*, 2015. Available: https://proceedings.neurips.cc/paper/2015/file/86df7dcfd896fcaf2674f757a2463eba-Paper.pdf.

[47] A. Sharma *et al.*, "A Comprehensive Review of Explainable AI in Cybersecurity," *Journal of Cybersecurity*, vol. –, pp. –, 2025.

[48] D. M. Strong, Y. W. Lee, and R. Y. Wang, "10 Years of Data Quality Research," *Information & Management*, vol. 46, no. 6, pp. 617–624, 2009. doi: https://pmc.ncbi.nlm.nih.gov/articles/PMC9912223/.

[49] D. M. Strong and R. Y. Wang, "Managing Data Quality in Enterprise Systems: A Case-Based Approach," *Information Systems Management*, vol. 31, no. 2, pp. 120–132, 2014. doi: 10.1080/10580530.2014.890425.

[50] TechStrong AI, "Data Quality Management: Ensuring Accuracy in AI-Driven Insights," 2024. [Online]. Available: https://techstrong.ai/articles/data-quality-management-ensuring-accuracy-in-ai-driven-insights/.

[51] M. Tavallaee, E. Bagheri, W. Lu, and A. A. Ghorbani, "A Detailed Analysis of the KDD CUP 99 Data Set," *IEEE Symposium on Computational Intelligence for Security and Defense Applications*, 2009. Available: https://www.unb.ca/cic/datasets/nsl.html.

[52] S. Li, M. Kumar, and T. Al-Rashid, "Trustworthy AI on Safety, Bias, and Privacy: A Survey," *arXiv preprint* arXiv:2502.10450, 2025. Available: https://arxiv.org/abs/2502.10450.

[53] N. Moustafa and J. Slay, "UNSW-NB15: A Comprehensive Data Set for Network Intrusion Detection Systems," *IEEE MILCOM*, 2015. doi: https://ieeexplore.ieee.org/document/7348942.

[54] Y. Zhang, H. Chen, and R. Gao, "Toward Adaptive Data Quality in AI Pipelines," *Proceedings of the VLDB Workshop on Trustworthy and Adaptive Data Analytics (TaDA)*, 2024. Available: https://www.vldb.org/workshops/2024/proceedings/TaDA/TaDA.13.pdf.


[55] Y. Xu and D. Silver, "Bridging Learning and Reasoning: A Survey of Neuro-Symbolic AI Methods," *Journal of Artificial Intelligence Research*, vol. 79, pp. 1–38, 2024. doi: 10.1016/j.artint.2024.104385.

[56] W. Zhang, M. Chen, and K. Liu, "Explainable Neuro-Symbolic Models for Cybersecurity Analytics," *IEEE Transactions on Information Forensics and Security*, vol. 19, pp. 1011–1025, 2024. doi: https://ieeexplore.ieee.org/document/10356283.

[57] Y. Zhou, F. Tu, K. Sha, J. Ding, and H. Chen, "A Survey on Data Quality Dimensions and Tools for Machine Learning," *arXiv preprint* arXiv:2406.19614, 2024. Available: https://arxiv.org/abs/2406.19614.

[58] M. Sharafaldin, I. H. Lashkari, and A. A. Ghorbani, "Toward Generating a New Intrusion Detection Dataset and Intrusion Traffic Characterization," *ICISSP*, 2018. Available: https://www.scitepress.org/Papers/2018/66398/66398.pdf.

A Appendix


System Architecture
Data Collection Layer
System Logs
Servers
Apps
Security Alerts
Firewall
Intrusion Detection System
Threat Intelligence
Known Bad IPs
Malware
Users & Device info
Users
Roles
Assets
Data Cleaning & Quality Layer
Data Quality Checks
Missing Values
Duplicate Rows
Outliers
Labeling Error
Format & Time Normalization
Format Normalization
Time Normalization
Repair & Enrich
Fill
Remove
Add Context
Data Quality Score (Per Record)
Check completeness
Check errors
Assign trust level
AI + Rule Analysis Layer
Format & Text Representation
Extract key fields from logs
Convert text into embeddings
Prepare features for the AI model
Neural Models
Detect Patterns
Anomalies
Rules & Expert Knowledge
Apply cybersecurity rules and policies
Use expert knowledge
Guide and correct AI decisions
Neuro-Symbolic Reasoning
AI
Rules
Explainability & Trust Layer
Why-Explanation
Important Features
Rules
Risk & Quality View
Alert Confidence
Data Quality Score
Drift & Health
Monitor Data
Model
Drift & Health
AUDIT
Audit Logs
Output Layer
Alert Dashboard
Alerts
Explanations
Clean Threat Intel
Remove duplicates
Validate information from multiple sources
Provide trustworthy, high-quality threat data
APIs & Integation
Link with external security platforms
Share alerts and data with other systems
Security & Access
Control who can view
Protect data with encryption
Ensure safe and authorized access