

AOC4518R8v06

D8X-2x(690-960)/1427-2690/2x(1695-2200)/2x(2490-2690)/2300-3800-8x65-

15.5i/15.5i/17.5i/17i/17i/17i/17i-8xM-R

EasyRET 2L5H FDD/2.3-3.8GHz 8T8R TDD Antenna with 8 Integrated RCUs - 2.0m



Antenna Specifications

Electrical Properties					
Frequency range (MHz)		2 x (690 - 960) (Lr1 / Rr2)			
		690 - 803	790 - 862	824 - 894	880 - 960
Polarization		+45° , -45°			
Electrical downtilt (°)		0 - 10 , continuously adjustable, each band separately			
Gain (dBi)	at mid Tilt	14.8	15.1	15.3	15.6
	over all Tilts	14.7 ±0.5	15.0 ±0.5	15.2 ±0.5	15.5 ±0.5
Side lobe suppression for first side lobe above main beam (dB)		> 16	> 16	> 16	> 16
Horizontal 3dB beam width (°)		65 ±5	62 ±5	60 ±5	60 ±5
Vertical 3dB beam width (°)		10.9 ±0.7	9.8 ±0.6	9.4 ±0.5	8.9 ±0.5
VSWR		< 1.5			
Cross polar isolation (dB)		≥ 28			
Interband isolation (dB)		≥ 28			
Front to back ratio , ±30° (dB)		> 21	> 22	> 23	> 23
Cross polar ratio (dB)	0°	> 18	> 18	> 18	> 18
Max. power per input (W)		400 (at 50°C ambient temperature)*			
Intermodulation IM3 (dBc)		≤ -150 (2 x 43 dBm carrier)			
Impedance (Ω)		50			
Grounding		DC Ground			

Electrical Properties						
Frequency range (MHz)		1427 - 2690 (Ry3)				
		1427 - 1518	1695 - 1990	1920 - 2200	2200 - 2490	2490 - 2690
Polarization		+45°, -45°				
Electrical downtilt (°)		2 - 12 , continuously adjustable				
Gain (dBi)	at mid Tilt	16.0	17.2	17.4	17.5	17.6
	over all Tilts	15.9 ±0.5	17.1 ±0.5	17.3 ±0.5	17.4 ±0.5	17.5 ±0.5
Side lobe suppression for first side lobe above main beam (dB)		> 16	> 16	> 16	> 16	> 16
Horizontal 3dB beam width (°)		70 ±6	68 ±5	67 ±5	65 ±5	58 ±5
Vertical 3dB beam width (°)		8.7 ±0.5	7.1 ±0.5	6.3 ±0.5	5.6 ±0.5	5.1 ±0.5
VSWR		< 1.5				
Cross polar isolation (dB)		≥ 28				
Interband isolation (dB)		≥ 28				
Front to back ratio , ±30° (dB)		> 25	> 26	> 26	> 26	> 25
Cross polar ratio (dB)	0°	> 18	> 18	> 18	> 18	> 18
Max. power per input (W)		250 (at 50°C ambient temperature)*				
Intermodulation IM3 (dBc)		≤ -150 (2 x 43 dBm carrier)				
Impedance (Ω)		50				
Grounding		DC Ground				

AOC4518R8v06

D8X-2x(690-960)/1427-2690/2x(1695-2200)/2x(2490-2690)/2300-3800-8x65-

15.5i/15.5i/17.5i/17i/17i/17i/17i-8xM-R

EasyRET 2L5H FDD/2.3-3.8GHz 8T8R TDD Antenna with 8 Integrated RCUs - 2.0m



Electrical Properties				
Frequency range (MHz)		1695 - 2200 (Lb1)		2490 - 2690 (Ly1)
		1695 - 1990	1920 - 2200	2490 - 2690
Polarization		+45° , -45°		
Electrical downtilt (°)		2 - 12 , continuously adjustable, each band separately		
Gain (dBi)	at mid Tilt	16.7	16.8	17.0
	over all Tilts	16.6 ±0.5	16.7 ±0.5	16.9 ±0.5
Side lobe suppression for first side lobe above main beam (dB)		> 16	> 16	> 17
Horizontal 3dB beam width (°)		67 ±5	66 ±5	58 ±5
Vertical 3dB beam width (°)		7.5 ±0.5	6.8 ±0.5	5.3 ±0.5
VSWR		< 1.5		
Cross polar isolation (dB)		≥ 28		
Interband isolation (dB)		≥ 28		
Front to back ratio , ±30° (dB)		> 25	> 26	> 25
Cross polar ratio (dB)	0°	> 18	> 18	> 18
Max. power per input (W)		250 (at 50°C ambient temperature)*		
Intermodulation IM3 (dBc)		≤ -150 (2 x 43 dBm carrier)		
Impedance (Ω)		50		
Grounding		DC Ground		

Electrical Properties				
Frequency range (MHz)		1695 - 2200 (Rb2)		2490 - 2690 (Cy2)
		1695 - 1990	1920 - 2200	2490 - 2690
Polarization		+45° , -45°		
Electrical downtilt (°)		2 - 12 , continuously adjustable, each band separately		
Gain (dBi)	at mid Tilt	16.8	16.9	17.2
	over all Tilts	16.7 ±0.5	16.8 ±0.5	17.1 ±0.5
Side lobe suppression for first side lobe above main beam (dB)		> 16	> 16	> 17
Horizontal 3dB beam width (°)		62 ±5	61 ±5	58 ±5
Vertical 3dB beam width (°)		7.6 ±0.5	6.8 ±0.5	5.3 ±0.5
VSWR		< 1.5		
Cross polar isolation (dB)		≥ 28		
Interband isolation (dB)		≥ 28		
Front to back ratio , ±30° (dB)		> 27	> 27	> 26
Cross polar ratio (dB)	0°	> 18	> 18	> 18
Max. power per input (W)		250 (at 50°C ambient temperature)*		
Intermodulation IM3 (dBc)		≤ -150 (2 x 43 dBm carrier)		
Impedance (Ω)		50		
Grounding		DC Ground		

1. Values based on NGMN recommendations on Base Station Antenna Standards (BASTA).

2. Electrical datasheet in XML format is available.

AOC4518R8v06

D8X-2x(690-960)/1427-2690/2x(1695-2200)/2x(2490-2690)/2300-3800-8x65-15.5i/15.5i/17.5i/17i/17i/17i/17i-8xM-R
EasyRET 2L5H FDD/2.3-3.8GHz 8T8R TDD Antenna with 8 Integrated RCUs - 2.0m



General Electrical Properties

	Frequency range (MHz)	2300 - 3800 (p1)	
		2300 - 2690	3300 - 3800
General parameters	Polarization	+45°, -45°	
	Electrical downtilt (°)	2 - 12, continuously adjustable	
	Electrical downtilt tolerance (°)	±1	
	Avg. power capacity (W)*	40	
	Impedance (Ω)	50	
	Grounding	DC Ground	
	Coupling factor between calibration port and each antenna port (dB)	-26 ±2	-26 ±2
Calibration and electrical parameters	Max. amplitude tolerance from calibration port to input ports (dB)	0.7	0.9
	Max. phase tolerance from calibration port to input ports (°)	5	7
	Ports VSWR	1.5	1.5
	Co-polarization isolation between ports (dB)	≥ 20	≥ 20
	Cross-polarization isolation between ports (dB)	≥ 23	≥ 23

* Total power : 1000 W (at 50°C ambient temperature)

TDD LTE Electrical Properties

	Frequency range (MHz)	2300 - 3800 (p1)	
		2300 - 2690	3300 - 3800
Radiation parameters	Single column beam	Gain (dBi)	15.0
		Horizontal 3dB beam width (°)	90
		Front to back ratio (dB)	≥ 25
		Cross polar ratio (0°) (dB)	16
		Vertical 3dB beam width (°)	8.0
		Side lobe suppression for first side lobe above main beam (dB)	≥ 15
	65° Broadcast beam	Gain (dBi)	16.0
		Horizontal 3dB beam width (°)	65
		Front to back ratio (dB)	≥ 26
		Cross polar ratio (0°) (dB)	17
		Vertical 3dB beam width (°)	8.0
		Side lobe suppression for first side lobe above main beam (dB)	≥ 15
	Service beam	0° direct beam gain (dBi)	20.0
		0° direction beam horizontal 3dB beam width (°)	26
		0° direction beam front to back ratio (dB)	30
		0° direction beam cross polar ratio (dB)	19
	Soft split multi-beam	Gain (dBi)	19
		Horizontal 3dB beam width (°)	32
		Front to back ratio (dB)	≥ 30
		Cross polar ratio (0°) (dB)	19
			/
			/
			/
			/

Notes:

65° broadcast beams and multi-beams are applicable in different scenarios. Select one of them for network coverage based on site requirements and auxiliary equipment conditions.

AOC4518R8v06

D8X-2x(690-960)/1427-2690/2x(1695-2200)/2x(2490-2690)/2300-3800-8x65-

15.5i/15.5i/17.5i/17i/17i/17i/17i/17i-8xM-R

EasyRET 2L5H FDD/2.3-3.8GHz 8T8R TDD Antenna with 8 Integrated RCUs - 2.0m



5G NR Electrical Properties


Radiation parameters	Frequency range (MHz)		2300 - 3800 (p1)	
			2300 - 2690	3300 - 3800
	Single column beam	Gain (dBi)	/	15.7
		Horizontal 3dB beam width (°)	/	70
		Front to back ratio (dB)	/	≥ 25
		Cross polar ratio (0°) (dB)	/	15
		Vertical 3dB beam width (°)	/	5.5
		Side lobe suppression for first side lobe above main beam (dB)	/	≥ 15
	NR Broadcast beam (PBCH/PSCH/SSCH with HUAWEI gNodeB)	Gain (dBi)	/	20.8
		Horizontal 3dB beam width (°)	/	65
Front to back ratio (dB)		/	25	
Vertical 3dB beam width (°)		/	5.5	
Side lobe suppression for first side lobe above main beam (dB)		/	≥ 15	
NR Service beam	0°direct beam gain (dBi)	/	21.1	
	0°direction beam horizontal 3dB beam width (°)	/	20	
	0°direction beam front to back ratio (dB)	/	30	
	0°direction beam cross polar ratio (0°) (dB)	/	19	

Notes:

1. The 5G NR broadcast beam is the envelope of SSB(synchronization signal block) sweeping beams and the gain is the maximum gain of SSB sweeping beams.
2. Downlink broadcast beam gain values and pattern files can only be used for broadcast channel coverage prediction.
3. Downlink and uplink budgets need to be calculated based on the gain of single column beam and the correct Tx/Rx number.

Mechanical Properties

Distance between TDD columns (mm)	59
Antenna dimensions (H x W x D) (mm)	2099 x 449 x 196
Packing dimensions (H x W x D) (mm)	2360 x 535 x 240
Antenna weight (kg)	43.0
Clamps weight (kg)	5.8 (2 units)
Antenna packing weight (kg)	54.9 (Included clamps)
Mast diameter supported (mm)	50 - 115
Radome material	GFRPP
Radome colour	Light grey
Operational temperature (°C)	-40 .. +65
Wind load (N)*	Frontal: 615 (at 150 km/h) Lateral: 375 (at 150 km/h) Maximum: 810 (at 150 km/h)
Max. operational wind speed (km/h)	200
Survival wind speed (km/h)	250
Connector	14 x 4.3-10 Female 1 x MQ4 Male + 1 x MQ5 Male
Connector position	Bottom



*Parameters and values based on BASTA Passive Antenna Whitepaper V10.1 Rev1.8 (24 May 2018), and may be changed following the final version.

Accessories

Item	Model	Description	Weight	Units per antenna
Downtilt kit	ASMDT0F01	Mechanical downtilt: 0 - 12 °	3.1 kg	1 (Separate packing)

AOC4518R8v06

D8X-2x(690-960)/1427-2690/2x(1695-2200)/2x(2490-2690)/2300-3800-8x65-

15.5i/15.5i/17.5i/17i/17i/17i/17i/17i-8xM-R

EasyRET 2L5H FDD/2.3-3.8GHz 8T8R TDD Antenna with 8 Integrated RCUs - 2.0m




Antenna Information Management Module (AIMM) Specifications

RET Properties								
RET type	Integrated RET							
RET protocols	AISG 2.0 / 3GPP							
Input voltage range (V)	10 - 30 DC							
Power consumption (W)	< 1.5 (when the motor does not work, 12 V) < 6 (when the motor is working, 12 V) < 10 (when the motor is starting up or shutting down, 12 V)							
Adjustment time (full range) (s)	Typ. 40							
Connectors	4 x 8 pin connector according to IEC 60130-9 Daisy chain in: Male / Daisy chain out: Female							
Pin assignment according AISG	1	2	3	4	5	6	7	8
	DC	n/c	RS-485B	n/c	RS-485A	DC	DC return	n/c
Lightning protection (kA)	10 (8/20 μs)							
RAE Properties								
RAE type	Integrated RAE							
RAE protocols	AISG-ES-RAE V2.1.0							
TDD LTE EasyBeam Properties								
Frequency range (MHz)	2300 - 2690				3300 - 3800			
Electrical downtilt (°)	2 - 12				2 - 12			
Broadcast beam	Horizontal 3dB beam width (°)	30	65	90	30	65	90	
	Electrical azimuth (°)	-15..+15		0	-15..+15		0	
	Electrical azimuth step(°)	1		/	1		/	

Standards: EN/IEC 60950-1(Safety), EN/IEC 60950-22(Safety – Equipment installed outdoor),EN 55032 (Emission), EN 55024 (Immunity), ETSI EN 301 489, FCC Part15, ICES-003


Certification: CE, FCC, IC, RCM, RoHS, REACH, WEEE



r - Red y - Yellow b - Blue p - Purple
L - Left array R - Right array C - Center array

Integrated RET S/N:

- a HWMxxx.....Lr1
- b HWMxxx.....Ly1
- c HWMxxx.....Lb1
- d HWMxxx.....Cy2
- e HWMxxx.....Rb2
- f HWMxxx.....Ry3
- g HWMxxx.....Rr2
- h HWMxxx.....p1



AOC4518R8v06


D8X-2x(690-960)/1427-2690/2x(1695-2200)/2x(2490-2690)/2300-3800-8x65-

15.5i/15.5i/17.5i/17i/17i/17i/17i/17i-8xM-R


EasyRET 2L5H FDD/2.3-3.8GHz 8T8R TDD Antenna with 8 Integrated RCUs - 2.0m




Pattern sample for reference




**690 - 960 MHz
(Lr1 / Rr2)**




**1427 - 2690 MHz
(Ry3)**




**1695 - 2200 MHz
(Lb1)**



**2490 - 2690 MHz
(Ly1)**



**1695 - 2200 MHz
(Rb2)**




**2490 - 2690 MHz
(Cy2)**

AOC4518R8v06


D8X-2x(690-960)/1427-2690/2x(1695-2200)/2x(2490-2690)/2300-3800-8x65-

15.5i/15.5i/17.5i/17i/17i/17i/17i-8xM-R


EasyRET 2L5H FDD/2.3-3.8GHz 8T8R TDD Antenna with 8 Integrated RCUs - 2.0m




**Single column
(2300 - 3800 MHz)**




**65° Broadcast
(2300 - 3800 MHz)**




**Service 0°
(2300 - 3800 MHz)**



**5G NR Broadcast
(3300 - 3800 MHz)**



**Multi-Beam-30°
(2300 - 2690 MHz)**



**Multi-Beam+30°
(2300 - 2690 MHz)**

NOTE

1. Facilities, such as towers and poles, must bear the weight and wind load of antennas.
2. HUAWEI 's standard brackets and accessories must be used for any installation.
3. The antenna working environment must meet the requirements specified in the datasheet.
4. Only qualified personnel are allowed to perform installation. Installation tools and procedures must conform to requirements described in the antenna installation guide.