



Search

Menu ▾

Login

Signup



ES6 Handbook: The Complete Guide

**Shreya** · September 20, 2021

7 minute read · Updated September 27, 2021

#javascript #Es6 #guide #es6 guide

Hey readers! This blog is all about ES6. It includes all the topics related with examples. Before reading further, I want to specify that this was not a blog post initially, these are just my personal notes that I use as a reference guide, so I apologize for any misspells here :)

Table of Contents



Search

Menu ▼

Login

Signup

objects

this

arrow functions

destructuring

spread

classes

modules



Notes

let/const

Before moving to the point, let us understand two concepts here:

1. **Global Scope** - Variable is declared outside the function. This variable is accessible inside every function present in the code.
2. **Function Scope** - Variable is declared inside (within) a function, outside that it is not accessible anywhere.
3. **Block Scope** - In short, block scope means variables which are declared in a `{ }` block are not accessible outside it. This block can be an **if** statement, **for** / **while** loop, etc.

var : function/ global scoped. Eg:



Search

Menu ▼

Login

Signup



```
var name = 'Jack';           // global scope

function message() {
  var msg = 'Hey Jack!'      //function scope
}

console.log(msg);           // ERROR
```

The above line of code will throw an error as there's no variable `msg` outside the function `message` (where we have logged the variable). So it will show as **undefined** .

let : block scoped. Eg:

→ **let** keyword can't be redeclared:

```
let x = 1;
let x = 3;
```

“result: SyntaxError - redeclaration of let x”



Search

Menu ▼

Login

Signup



```
let size = "big";

function box() {
  for (let x = 0; x < 7; x++) {
    console.log(size);

    //Output: ReferenceError - `size` is not defined

    let size = "small";
    console.log(size);
  }
}

box();                // small
console.log(size);    //big
```

Inside the function **box()** when we log the value of `size`, it shows a reference error. That is because, **let** is block scoped.

Anything inside curly braces { } is block scoped. In the above scenario, the function **box()** is a block.

[CHECKOUT OUR LATEST PRODUCT - THE ULTIMATE TAILWINDCSS PAGE CREATOR](#) 

const : block scoped. Eg:

const are very similar to **let** except that they can't be changed and redeclared.

```
const m = 8;
console.log(m);           //m = 8

m = 5;                    // ❌ this will throw an error
console.log(m);

// Uncaught TypeError: invalid assignment to const 'm'.
}
```

→ therefore **let** and **const** are preferred over **var** keyword for declaring variables.

Objects

objects are written within curly braces `{ }` as collection of key:value pairs.



Search

Menu ▼

Login

Signup

value : value of that property

Creating an empty object:

```
const car = {  
  model: 'Tesla',  
  color: 'black',  
  price: 800  
}
```

Talking specifically about ES6, before ES6 we had to specify both (key, value) even if both are of same names.

```
function Boy(name, age) {  
  return(  
    name: name,  
    age: age  
  );  
}
```

ES6 help us to get rid of duplication when we have same key:value names. So now our code will look like this:



Search

Menu ▼

Login

Signup

```
    return(name, age);  
}
```



this

this is a keyword. It basically returns a reference to the object it is placed within

💡 NOTE:

When we call a function as a method in an object, the **this** keyword returns a reference to that object. 🖱️

```
const user = {  
  name: 'Mike';  
  call() {  
    console.log(this);  
  }  
}  
user.call();  
  
// ⚙️ Output: {name: 'Mike', call: f}
```



Search

Menu ▼

Login

Signup

But when we call the function alone, outside the object, `this` returns the global object (browser window) and hence we get the result as *undefined*



```
const user = {  
  name: 'Mike';  
  call() {  
    console.log(this);  
  }  
}
```

```
const myCall = user.call;
```

```
myCall();
```

```
// ⚙️ Output: undefined
```

Arrow Functions

Normally, before ES6:



Search

Menu ▼

Login

Signup

```
    return num * num;  
}
```



In ES6:

```
const square = num => num * num;
```

array.map()

If we have an array -

```
const colors = ["red", "green", "blue"];
```

We want to map the objects. Now there are two methods, **es6** one is shorter and easier.

normal case:

```
const items1 = colors.map(function (color) {  
    return "<li>" + color + "</li>";  
});
```



Search

Menu ▼

Login

Signup

```
const items2 = colors.map((color) => `- ${color} </li>`);

```



Object Destructuring

Let's say we have an object called **girl** such that it has 3 keys as follows:

```
const girl = {  
  name: "",  
  age: "",  
  country: "",  
};
```

Normally, we would do something like this to get the values:

```
const name = girl.name;  
const age = girl.age;  
const country = girl.country;
```



Search

Menu ▼

Login

Signup

we want to get a value. This problem can be solved by object destructuring:



```
const { name, age, country } = girl;
```

"this one line code works same as the previous code. So destructuring made our code shorter and easier to understand."

In case you want to use an alias (a different variable name) for your work:

```
const {country: ctry} = girl;
```

This above line of code means we've defined a new variable called **ctry** and set that equals to **country** .

Spread Operator

"CASE I - COMBINING ARRAYS"

If we want to combine these two arrays:

```
const one = [1, 2, 3];  
const two = [4, 5, 6];
```



Search

Menu ▼

Login

Signup

```
const combined = one.concat(two);
```

With ES6:

```
const combined = [...one, ...two];
```

If we want to add things in-between:

```
const combined = [...one, '9', '7', ...two ];
```

If we want to clone an array:

```
const myDupli = [...two];
```

“CASE II - COMBINING OBJECTS”

If we want to combine these two objects:

```
const alpha = { name: 'Shreya' };  
const beta = { age: 19 };
```

In ES6:

```
const combined = {...alpha, ...beta};
```

If we want to add more properties in b/w:



Search

Menu ▼

Login

Signup

cloning an object:



```
const betaV2 = {...beta};
```

Classes

Let us take an example of an object **boy** here. We have a function called **run** inside it. Now if we've some bug in the future or we've to modify our function for a different object, it would be a long way.

```
const boy = {  
  name: "Sam",  
  run() {  
    console.log("running...");  
  },  
};
```

To overcome this and make our work easier, we use classes:



Search

Menu ▼

Login

Signup

```
    constructor(name) {  
        this.name = name;  
    }  
  
    run() {  
        console.log("running...");  
    }  
}
```



Now that we've created a class, let's try building our object again -

```
const boy = new Boy("Samridh");
```

with this above class, we've implemented the run method in a single line of code. If someday we find a bug here, we've to modify it in just a single place {inside class Boy}. So this is the advantage of using classes in JS.

Inheritance

If we have a class Boy such that -



Search

Menu ▼

Login

Signup

```
    constructor(name) {  
        this.name = name;  
    }  
  
    run() {  
        console.log("running");  
    }  
}
```



and we want to create another class (having similar properties + some specific properties of its own). We can do this using the keyword **extends**

```
class Girl extends Boy {  
    eat() {  
        console.log("eating");  
    }  
}
```

we just created the class **Girl** here. Let us now create a const using this -

```
const myGirl = new Girl("Shreya");
```

and we're done. This code basically means that now the const **myGirl** will have the functions **eat** + **run** + **constructor** property of **Boy** class.



Search

Menu ▼

Login

Signup



```
myGirl.eat();  
myGirl.run();
```

Now let's say we want to create another constructor inside the **Girl** class {which is extended from **Boy** class, So the constructor inside this **Girl** class is called **derived class constructor**}.

We MUST HAVE TO call **super()** constructor inside the new constructor, otherwise we'll get an error (as using **this** in derived class constructor requires **super()** class). Now this must be looking confusing, let's look at the example below -

```
class Girl extends Boy {  
  constructor(age) {  
    this.age = age;  
  }  
  eat() {  
    console.log("eating");  
  }  
}
```

```
// *result - Uncaught ReferenceError: must call super constructor before
```




Search

Menu ▼

Login

Signup



```
class Girl extends Boy {  
  constructor(name, age) {  
    super(name);  
    this.age = age;  
  }  
  eat() {  
    console.log("eating");  
  }  
}  
const myGirl = new Girl("Shreya");
```

In a child class constructor, **this** cannot be used until **super** is called.

Modules

Sometimes we have many no. of classes declared in a single file. This makes the code long, confusing and messy. To avoid this, we separate these classes into different files and import them as a **module** into the main file. This is called modularity.

Let's look it in action. Here's what our folder **src** will look like:



Search

Menu ▼

Login

Signup

// src/boy.js



```
export class Boy {  
  constructor(name) {  
    this.name = name;  
  }  
  
  run() {  
    console.log("running");  
  }  
}
```

// src/girl.js

```
import { Boy } from './src/boy';  
  
export class Girl extends Boy {  
  constructor(name, age) {  
    super(name);  
    this.age = age;  
  }  
  
  eat() {  
    console.log("eating");  
  }  
}
```



Search

Menu ▼

Login

Signup



"We use `import` keyword in line 1 of `girl.js` as it is an extended version of the `Boy` class."

Now half of the work is done. For now, these classes are not accessible in our main `app.js` file. For that we've to import them in our `app.js` file. We can do that by using -

```
import { Boy } from './src/boy';
```

```
import { Girl } from './src/girl';
```

Default and Named Exports

Named Exports

We can export more than one objects from a specific module. This is called named export. Eg:



Search

Menu ▼

Login

Signup

```
    constructor(model) {  
        this.model = model;  
    }  
}
```



```
export function add(a, b){  
    return a + b;  
}
```

Here we exported a class **Car** and a function **add** .

Default Exports

It is basically the main object that is exported from the module. It is generally used in case we've only a single object to export. Let's see how it is -

```
export default class Car {  
    constructor(model) {  
        this.model = model;  
    }  
}
```



Search

Menu ▼

Login

Signup

Instead, we use `import Car from "./car";` in case of default exports.




Default exports -> `import Car from "./car";`

Named exports -> `import { Car } from "./car";`






👏 Woosh! You've made it to the end. Hope I've helped you somehow. I write articles like this whenever I've some spare time. Besides this, I share content related to web development daily on Twitter. Let's connect there! [@eyeshreya](#)


Comments (2)

 Search

Menu ▾

Login Signup





© 2022 DevDojo LLC. All rights reserved.