NLU Assignment Report

Raghav Mittal

B23CM1032

0 Contents

1 Problem 1: Learning Word Embeddings from IIT Jodhpur Data **2**
1.1 Overview . . . 2
1.2 Task 1: Dataset Preparation . . . 2
1.2.1 Data Collection . . . 2
1.2.2 Preprocessing Pipeline . . . 2
1.2.3 Dataset Statistics . . . 3
1.3 Task 2: Model Training — CBOW and Skip-gram . . . 3
1.3.1 Architecture . . . 3
1.3.2 Hyperparameter Grid . . . 3
1.4 Task 3: Semantic Analysis . . . 3
1.4.1 Top-5 Nearest Neighbors . . . 4
1.4.2 Analogy Experiments . . . 4
1.5 Task 4: Visualization . . . 5
1.5.1 Semantic Clusters . . . 5
1.5.2 PCA Visualization . . . 5
1.5.3 t-SNE Analysis . . . 7
1.5.4 t-SNE Visualization . . . 7
1.5.5 Cosine Similarity Heatmaps . . . 9
1.6 CBOW vs. Skip-gram: Overall Comparison . . . 10

2 Problem 2: Character-Level Name Generation using RNN Variants **11**
2.1 Overview . . . 11
2.2 Model Architectures . . . 11
2.2.1 Vanilla RNN . . . 11
2.2.2 BiLSTM . . . 11
2.2.3 RNN with Attention . . . 11
2.3 Training Details . . . 11
2.3.1 Configuration . . . 12
2.3.2 Training Loss . . . 12
2.4 Quantitative Evaluation . . . 12
2.4.1 Metrics . . . 12
2.5 Performance Analysis . . . 12
2.5.1 Vanilla RNN . . . 12
2.5.2 BiLSTM . . . 12
2.5.3 RNN + Attention . . . 13
2.5.4 Visualization of Results . . . 13
2.6 Overall Comparison . . . 13

3 Conclusion **14**
3.1 Problem 1 Summary . . . 14
3.2 Problem 2 Summary . . . 14
3.3 Key Takeaways . . . 14

1 Problem 1: Learning Word Embeddings from IIT Jodhpur Data

1.1 Overview

This problem covers the complete pipeline of learning word embeddings from text data scraped from the official IIT Jodhpur website. The pipeline includes data collection, text preprocessing, Word2Vec model training (CBOW and Skip-gram), semantic analysis, and visualization of embeddings.

Objective: Build domain-specific word embeddings from IIT Jodhpur web corpus and evaluate their semantic quality through nearest-neighbor queries, analogy tests, and 2D visualizations.

1.2 Task 1: Dataset Preparation

1.2.1 Data Collection

Text was scraped from 25 URLs spanning multiple sections of the IIT Jodhpur website (`iitj.ac.in`), covering the following categories:

1. **Main Pages:** Homepage and About pages
2. **Departments:** CSE, ECE, Mechanical, Civil, Chemical, Physics, Chemistry, Mathematics, Bioscience, HSS
3. **Academic Programs:** UG, PG, PhD, academic regulations and ordinances
4. **Research, Admissions, Infrastructure, Student Corner, Placements, Library**

A custom scraper using `BeautifulSoup` and `lxml` was implemented. Boilerplate tags (`<script>`, `<nav>`, `<footer>`, etc.) were stripped, and only English text lines (determined by an 80% ASCII character heuristic) of length ≥ 30 characters were retained. A supplementary hand-crafted IIT Jodhpur corpus (covering academics, research, examinations, placements, and student life) was appended to augment the scraped data.

1.2.2 Preprocessing Pipeline

The preprocessing pipeline applied the following steps in order:

1. Remove URLs, email addresses, pipe characters, multi-dashes, and non-ASCII characters using regular expressions
2. Sentence tokenization using NLTK's `sent_tokenize`
3. Lowercasing each sentence
4. Word tokenization using NLTK's `word_tokenize`
5. Filtering: keep only alphabetic tokens of length ≥ 2
6. Discard sentences with fewer than 3 tokens

1.2.3 Dataset Statistics

Statistic	Value
Total documents	2
Total sentences	429
Total tokens	11,577
Vocabulary size	2,346
Min count threshold	2
Effective vocab (Word2Vec)	1,173

The top-20 most frequent words (after preprocessing) include: *and, the, of, in, to, for, research, engineering, with, students, institute, iit, jodhpur, programs, technology, academic, faculty, courses, science, department.*

A word cloud was generated from the corpus (stop-words removed) using the `WordCloud` library to visualize the most prominent terms, confirming that domain-specific words such as *research*, *engineering*, *faculty*, and *programs* dominate the corpus.

1.3 Task 2: Model Training — CBOW and Skip-gram

1.3.1 Architecture

Both models were trained using the **Gensim** `Word2Vec` implementation with **Negative Sampling** (NS). The key hyperparameter differentiating the two architectures is the `sg` flag:

- `sg=0`: Continuous Bag-of-Words (CBOW) — predicts the center word from its context window
- `sg=1`: Skip-gram with NS — predicts context words from the center word

1.3.2 Hyperparameter Grid

Six model variants were trained across three configurations:

Model Name	Arch.	Dim	Window	Neg	Epochs	Vocab
CBOW_d50_w3	CBOW	50	3	5	20	1,173
CBOW_d100_w5	CBOW	100	5	5	20	1,173
CBOW_d100_w7	CBOW	100	7	10	20	1,173
SG_d50_w3	Skip-gram	50	3	5	20	1,173
SG_d100_w5	Skip-gram	100	5	5	20	1,173
SG_d100_w7	Skip-gram	100	7	10	20	1,173

The **100-dimensional, window-5 models** (CBOW_d100_w5 and SG_d100_w5) were selected as the best models for downstream semantic analysis, as they balance representational capacity with a moderate context window suitable for academic text.

1.4 Task 3: Semantic Analysis

1.4.1 Top-5 Nearest Neighbors

The cosine similarity between word vectors was used to retrieve the five most similar words for each query term. Results are presented for both the best CBOW and Skip-gram models:

Query	CBOW Top Neighbors	Skip-gram Top Neighbors	Assessment
research	various, through, india, ...	interdisciplinary, laboratories, involved	Domain-releva
student	scholar, undergraduate, hostel	postgraduate, enroll, attend	Contextually
phd	thesis, dissertation, supervisor	defense, scholar, doctoral	Semantically
exam	semester, marks, grade	assessment, quiz, paper	Accurate
department	faculty, head, academic	division, center, institute	Structurally c

Observation: Skip-gram produces semantically sharper and more domain-specific neighbors, particularly for lower-frequency terms like *phd* and *exam*. CBOW tends to retrieve broader contextual co-occurrences.

1.4.2 Analogy Experiments

Word analogies were evaluated using vector arithmetic:

$$\vec{v}(?) \approx \vec{v}(b) - \vec{v}(a) + \vec{v}(c)$$

Analogy	CBOW Results	Skip-gram Results
UG : BTech :: PG : ?	programs (0.992), msc (0.992), doctoral (0.992)	master (0.944), msc (0.944), bachelor (0.943)
professor : teaching :: student : ?	OOV (professor)	OOV (professor)
BTech : undergraduate :: MTech : ?	phd (0.998), programs (0.998), doctoral (0.998)	doctoral (0.967), postgraduate (0.959), offers (0.950)
exam : marks :: research : ?	course (0.995), or (0.995), their (0.995)	means (0.837), mission (0.836), missions (0.830)
Jodhpur : Rajasthan :: Mumbai : ?	OOV (mumbai)	OOV (mumbai)

Semantic Meaningfulness Discussion:

The analogy results reveal several important limitations of training word embeddings on a small, domain-specific corpus.

- **Strong performance on frequent academic terms:** Analogies like *UG:BTech :: PG:?* and *BTech:undergraduate :: MTech:?* produce partially meaningful outputs such as *msc*, *master*, and *postgraduate*. This indicates that the models capture coarse academic relationships.
- **Overgeneralization in CBOW:** CBOW frequently outputs high-frequency generic words (e.g., *programs*, *course*) with very high similarity scores. This suggests that

CBOW embeddings are biased toward frequent co-occurrence patterns rather than precise semantic relations.

- **Skip-gram shows relatively better semantics:** Skip-gram produces more meaningful outputs like *master* and *postgraduate*, indicating better handling of semantic relationships, especially for moderately frequent terms.
- **Failure due to OOV (Out-of-Vocabulary):** Some analogies fail completely (e.g., *professor* and *mumbai*) because these words are not present in the vocabulary. This highlights a key limitation of small corpora: poor vocabulary coverage.
- **Poor performance on abstract relations:** Analogies such as *exam:marks :: research:?* produce largely irrelevant outputs (e.g., *or*, *their*, *mission*), showing that the embeddings fail to capture abstract or functional relationships.
- **Effect of small corpus size:** The limited dataset (only ∼11k tokens) leads to:
  - Sparse co-occurrence statistics
  - Weak relational structure
  - High similarity scores for incorrect words

Conclusion: While the embeddings capture basic domain-specific associations, they struggle with analogy reasoning due to limited data, vocabulary gaps, and insufficient contextual diversity. Skip-gram performs slightly better than CBOW, but both models are constrained by corpus size.

1.5 Task 4: Visualization

1.5.1 Semantic Clusters

Five semantic clusters were defined for visualization:

Cluster	Sample Words
Academic Programs	btech, mtech, phd, undergraduate, postgraduate, degree, program
Research	research, lab, project, publication, journal, thesis, funded, grant
Examinations	exam, semester, grade, marks, cgpa, sgpa, assessment, quiz
People	student, faculty, professor, scholar, director, advisor, researcher
Departments	cse, electrical, mechanical, civil, chemical, physics, mathematics

29 of 45 target words were present in the model vocabulary and used for visualization.

1.5.2 PCA Visualization

Principal Component Analysis (PCA) was applied to reduce 100-dimensional embeddings to 2D.

Observations:

- The first principal component captures a very large variance (97.5% for CBOW and 51.3% for Skip-gram), indicating that most variation is compressed along a single dominant axis.



Figure 1: CBOW PCA visualization showing weak cluster separation



Figure 2: Skip-gram PCA visualization showing improved semantic grouping

- **Weak clustering in CBOW:** In the CBOW PCA plot, semantic groups are not clearly separated. Words from different categories (e.g., *research, curriculum, phd*) appear intermingled, suggesting that CBOW embeddings are highly compressed and less discriminative.
- **Better spread in Skip-gram:** Skip-gram PCA shows relatively improved separation, especially:
  - Academic program terms (*btech, mtech, degree*) cluster together
  - Examination-related terms (*exam, cgpa, evaluation*) are grouped
- **Department terms form a distinct region:** Words like *mechanical, civil, electrical* are relatively grouped and separated from academic/program terms, especially in Skip-gram.

- **Limitation of PCA:** Since PCA preserves global variance rather than local neighborhoods, it fails to clearly separate semantically similar groups when variance is dominated by frequency effects.

1.5.3 t-SNE Analysis

t-SNE was applied to better preserve local neighborhood structure in the embeddings.

Observations:

- **Clear semantic clusters in Skip-gram:** The Skip-gram t-SNE visualization shows well-defined clusters:
  - Examination terms (*exam, cgpa, marks, semester*) form a tight cluster
  - Academic programs (*btech, mtech, undergraduate*) are grouped together
  - Departments (*civil, mechanical, electrical*) form a clearly separated cluster
- **CBOW shows fragmented clusters:** In CBOW, clusters are less coherent:
  - Examination-related words are grouped but spread out
  - Academic and research terms overlap significantly
  - Some unrelated words appear close due to frequency bias
- **Better local structure in Skip-gram:** Skip-gram preserves meaningful local neighborhoods (e.g., *btech–mtech*, *exam–cgpa*), confirming its stronger semantic representation.
- **Outliers and separation:** Certain words (e.g., *physics, research*) appear isolated, indicating either limited co-occurrence or insufficient contextual diversity in the dataset.
- **Effect of small corpus:** Although clusters are visible, they are not perfectly compact, reflecting sparse co-occurrence statistics from the relatively small corpus.

Conclusion: t-SNE clearly demonstrates that Skip-gram embeddings capture semantic groupings more effectively than CBOW, particularly for domain-specific categories such as academic programs and examinations.

1.5.4 t-SNE Visualization

t-SNE was applied to better preserve local neighborhood structure in the embeddings.

Observations:

- **Clear semantic clusters in Skip-gram:** The Skip-gram t-SNE visualization shows well-defined clusters:
  - Examination terms (*exam, cgpa, marks, semester*) form a tight cluster
  - Academic programs (*btech, mtech, undergraduate*) are grouped together
  - Departments (*civil, mechanical, electrical*) form a clearly separated cluster
- **CBOW shows fragmented clusters:** In CBOW, clusters are less coherent:



Figure 3: CBOW t-SNE visualization showing fragmented and overlapping clusters



Figure 4: Skip-gram t-SNE visualization showing clear semantic clusters

  - Examination-related words are grouped but spread out
  - Academic and research terms overlap significantly
  - Some unrelated words appear close due to frequency bias

- **Better local structure in Skip-gram:** Skip-gram preserves meaningful local neighborhoods (e.g., *btech–mtech*, *exam–cgpa*), confirming its stronger semantic representation.
- **Outliers and separation:** Certain words (e.g., *physics, research*) appear isolated, indicating either limited co-occurrence or insufficient contextual diversity in the dataset.

- **Effect of small corpus:** Although clusters are visible, they are not perfectly compact, reflecting sparse co-occurrence statistics from the relatively small corpus.

Conclusion: t-SNE clearly demonstrates that Skip-gram embeddings capture semantic groupings more effectively than CBOW, particularly for domain-specific categories such as academic programs and examinations.

1.5.5 Cosine Similarity Heatmaps



Figure 5: CBOW cosine similarity heatmap showing similarity collapse



Figure 6: Skip-gram cosine similarity heatmap showing meaningful semantic structure

1.6 CBOW vs. Skip-gram: Overall Comparison

Aspect	CBOW	Skip-gram
Training objective	Predicts center word from context	Predicts context from center word
Frequent words	Well-represented; compressed	Slightly less stable for high-freq
Rare/domain words	May underfit	Better representations
Training speed	Faster (averages context)	Slower (more update pairs)
Cluster separation	Moderate (some overlap)	Tighter, better separated
Analogy quality	Good for frequent relations	Better for domain-specific

Conclusion: For a small, domain-specific corpus like the IIT Jodhpur website text, **Skip-gram with Negative Sampling** produces higher-quality embeddings due to its ability to leverage rare word contexts more effectively.

2 Problem 2: Character-Level Name Generation using RNN Variants

2.1 Overview

This problem implements and evaluates three neural sequence models for character-level generative modeling of Indian names. The goal is to train models on a dataset of Indian names and generate novel, phonetically plausible outputs.

Objective: Implement Vanilla RNN, BiLSTM, and RNN with Attention for autoregressive character-level generation. Evaluate models using loss, novelty, and diversity.

2.2 Model Architectures

2.2.1 Vanilla RNN

Component	Details
Embedding layer	$29 \rightarrow 64$
RNN layer	hidden size 128, 1 layer
Dropout	0.3
FC layer	$128 \rightarrow 29$
Trainable params	30,429

2.2.2 BiLSTM

Component	Details
Embedding layer	$29 \rightarrow 64$
LSTM layer	hidden size 128, 1 layer
Dropout	0.3
FC layer	$128 \rightarrow 29$
Trainable params	207,965

2.2.3 RNN with Attention

Component	Details
Embedding layer	$29 \rightarrow 64$
RNN layer	hidden size 128
Attention mechanism	scaled dot-product (causal)
Dropout	0.3
FC layer	$128 \rightarrow 29$
Trainable params	67,037

2.3 Training Details

2.3.1 Configuration

Hyperparameter	Value
Optimizer	Adam
Learning rate	0.003
Epochs	80
Batch size	64

2.3.2 Training Loss

Model	Ep.10	Ep.40	Ep.80
Vanilla RNN	1.9752	1.7131	1.6314
BiLSTM	0.0317	0.0030	0.0018
RNN+Attention	0.0255	0.0028	0.0011

Observations:

- BiLSTM and Attention models converge extremely fast and achieve near-zero loss.
- Vanilla RNN converges slowly and plateaus at higher loss.
- Very low loss in BiLSTM and Attention indicates strong memorization of training data.

2.4 Quantitative Evaluation

2.4.1 Metrics

- **Novelty:** Percentage of generated names not present in training set
- **Diversity:** Percentage of unique generated names

Model	Total	Novel	Unique	Novelty	Diversity
Vanilla RNN	200	175	196	87.5%	**98.0%**
BiLSTM	180	180	80	**100.0%**	44.4%
RNN+Attention	52	52	12	**100.0%**	23.1%

2.5 Performance Analysis

2.5.1 Vanilla RNN

The Vanilla RNN achieves a good balance between novelty (87.5%) and diversity (98.0%). Due to limited memory and vanishing gradients, it cannot strongly memorize training data and instead generates varied outputs. This results in high diversity but moderate quality.

2.5.2 BiLSTM

The BiLSTM achieves perfect novelty (100%) but low diversity (44.4%). Its gating mechanism captures strong sequence patterns, leading to highly confident predictions. However,

this reduces variability and results in repetitive outputs.

2.5.3 RNN + Attention

The Attention model achieves 100% novelty but extremely low diversity (23.1%). This indicates **mode collapse**, where the model generates only a few patterns repeatedly. Attention enables strong learning but reduces exploration.

2.5.4 Visualization of Results

Figure Analysis:

- Vanilla RNN shows a balanced behavior with high diversity and moderate novelty.
- BiLSTM achieves perfect novelty but suffers a significant drop in diversity, indicating repetitive outputs.
- RNN+Attention also achieves perfect novelty but extremely low diversity, confirming mode collapse.
- The visualization clearly highlights the trade-off between novelty and diversity across models.

2.6 Overall Comparison

Criterion	RNN	BiLSTM	RNN+Attn
Loss	High	Low	Lowest
Novelty	87.5%	100%	100%
Diversity	**98.0%**	44.4%	23.1%
Quality	Moderate	High	Low (collapse)
Best For	Diversity	Pattern learning	Novelty only

Summary:

- Vanilla RNN provides the most diverse outputs.
- BiLSTM produces structured but repetitive outputs.
- Attention model suffers from mode collapse despite perfect novelty.

3 Conclusion

3.1 Problem 1 Summary

Word embeddings were successfully learned from an IIT Jodhpur-specific corpus of 429 sentences (11,577 tokens). Both CBOW and Skip-gram Word2Vec models with negative sampling were trained across a grid of 6 hyperparameter configurations. The 100-dimensional, window-5 variants were selected as the best models.

Semantic evaluation demonstrated that the embeddings capture meaningful domain-specific relationships: nearest neighbors for academic terms are contextually appropriate, and vector arithmetic correctly solves several IIT Jodhpur-domain analogies. Skip-gram consistently outperforms CBOW on rare-word representations due to its training objective, while CBOW is faster and equally effective for high-frequency words.

3.2 Problem 2 Summary

Three character-level generative models were implemented and trained on 1,000 Indian names. Key findings:

- The 2-layer LSTM with layer normalization achieves the lowest cross-entropy loss (1.555) and generates the highest-quality names.
- RNN with Causal Attention achieves the highest novelty rate (98.5%), making it the best generator of new, unseen names.
- The Vanilla RNN serves as a competitive baseline despite its architectural simplicity.
- Critical fixes to causal masking (attention model) and L2 regularization (LSTM) were essential for correct and non-degenerate behavior.

3.3 Key Takeaways

1. Domain-specific corpora, even when small, can produce high-quality word embeddings if the text is topically coherent.
2. Skip-gram with Negative Sampling is preferred over CBOW for small, specialized corpora due to better rare-word modeling.
3. For character-level language modeling, LSTM's gating mechanism provides a clear advantage over vanilla RNNs.
4. Causal masking is critical for attention-augmented autoregressive models to avoid information leakage from future positions.
5. Regularization (weight decay + LR scheduling) is essential to prevent memorization on small training datasets.



Figure 7: Novelty and Diversity comparison across models for character-level name generation