

2.e. Finding Complexity using Counter Method

Aim: Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
    int rev = 0, remainder;
    while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n /= 10;
    }
    print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Algorithm:

```
function reverse(n) {
    initialize count to 0
    initialize rev to 0
    initialize remainder

    increment count by 1 // for initialization

    // loop until n is not equal to 0
    while n is not equal to 0 {
        increment count by 1 // start of loop

        remainder = n modulo 10
```

increment count by 1 // after calculating remainder

rev = rev * 10 + remainder

increment count by 1 // after updating rev

n = n divided by 10

increment count by 1 // after updating n

}

increment count by 1 // after loop ends

// simulate printing rev (e.g., print(rev))

increment count by 1 // for print statement

print count

}

Program:

```
#include<stdio.h>
```

```
void reverse(int n)
```

```
{
```

```
    int count=0;
```

```
    int rev = 0, remainder;
```

```
    count++;
```

```
    while (n != 0)
```

```
    {
```

```
        count++;
```

```
        remainder = n % 10;
```

```

        count++;

        rev = rev * 10 + remainder;

        count++;

        n/= 10;

        count++;

    }

    count++;

//print(rev);

count++;

printf("%d",count);

}

int main(){

    int n;

    scanf("%d",&n);

    reverse(n);

}

```

Output:

	Input	Expected	Got	
✓	12	11	11	✓
✓	1234	19	19	✓