



MAHAVASTU

REMEDY IMPLEMENTATION MANUAL

www.mahavastu.com

TABLE OF CONTENTS

Install poles for Road Hit	01
Embed metal studs for T-Hit	02
Colored Tapes for Entrance, Toilets and Balancing	03
Metal Strips for Entrance Toilets and Balancing	05
Metal Studs for Balancing	07
Springs to Change Polarity	08
Pyramids to Increase Zonal Strength	09
Gemstones to Increase Planetary Strength	10
Divs to Strengthen Devtas	11
Kitchen Groceries for Devtas	12

INSTALLING POLES FOR ROAD HIT

HOW TO INSTALL POLES FOR ROAD HIT?

1. Identify the Road Hit
2. Mark the centre and Edges of Road.
3. Extend the Centre and edges till compound wall.
4. Mark the sub-centre from centre till the edges
5. Collect 2 MS/PVC pipes of 5 feet each and one of 6 feet with diameter of 4-6 inches.
6. Install the 5 feet pipes on sub-centres and 6 feet pipe on Main centre point.
7. The depth of pipe should be 2 feet in the ground.
8. Fill the pipes with Sand or Concrete thoroughly to make them solid.
9. Colour the Poles with Colour of Next Element.

THINGS TO KEEP IN MIND:

1. Poles should be Installed outside the plot boundary.
2. Don't Install poles in front of Gate/Door.
3. Poles should be erected straight.

USING METAL STUDS FOR T-HIT

HOW TO RECTIFY THE EFFECT OF T-HIT WITH METAL STUDS?

1. Identify the Road Hit
2. Mark the centre and Edges of Road.
3. Extend the Centre and edges inside the building/flat.
4. Mark the Sub-centre from the centre till edges.
5. Ensure the marked points are not coming on Marma points.
6. Drill Metal Studs of Next Element on the marked points.

THINGS TO KEEP IN MIND:

1. This is an alternative remedy when the Pole treatment is not possible.

VASTU REMEDY USING COLORED TAPES

HOW TO APPLY COLORED TAPES ON THE ENTRANCE?

1. Clean the Surface below the door threshold and let it dry.
2. Mark the 2 Parallel Lines 3 inches apart with the help of Scale or thread.
3. Start pasting the tape from one end to the other on the marked area on the floor.
4. Paste some tape on the floor skirting as well.
5. Clean the floor with a dry cloth.

HOW TO APPLY COLORED TAPES IN THE TOILET?

1. Clean the Surface and let it dry.
2. Mark the 2 Parallel Lines 3 inches apart with the help of Scale or thread around the toilet seat.
3. Start pasting the tape from one end to the marked area.
4. Paste some tape on the floor skirting as well.
5. Clean the floor with a dry cloth.

HOW TO APPLY COLORED TAPES ON THE SKIRTING?

1. Clean the Surface and let it dry.
2. Mark the 2 Parallel Lines 3 inches apart with the help of Scale or thread.
3. Start pasting the tape from one end to the marked area.
4. Clean the skirting with a dry cloth.

VASTU REMEDY USING COLORED TAPES

THINGS TO KEEP IN MIND:

1. Vastu defect can arise due to the wrong Color tape in wrong direction in building.
2. Apply Color tape only after consulting Mahavastu Experts.
3. Check that the tape sticks well on the floor and there is no gap.
4. In case of Western Seat, apply colour tape on 3 sides and in Indian Seat, apply colour tape all 4 sides.

VASTU REMEDY USING METAL STRIPS

HOW TO APPLY METAL STRIPS ON THE ENTRANCE?

1. Identify the tile or stone Joints on the flooring.
2. Mark the lines to be cut with the help of Scale or thread.
3. Blades should be fine enough to cut the floor precisely.
4. Cut the stone or Tile with 1.5 inches blade.
5. Embed the strip vertically in the groove.
6. Insert the strip at least 1 inch along the wall on both sides.
7. Fill the groove with white cement along with the existing color of the floor.
8. Clean the floor with a dry cloth
9. Next day, clean with wet cloth by putting some water on the cut area.

HOW TO APPLY METAL STRIP IN TOILET?

1. Identify the tile or stone Joints on the flooring.
2. Mark the lines to be cut with the help of Scale or thread.
3. Blades should be fine enough to cut the floor precisely.
4. Cut the stone or Tile with 1.5 inches blade.
5. Embed the Strip Vertically in the groove
6. Fill the groove with white cement along with the existing color of the floor.
7. Clean the floor with a dry cloth
8. Next day, clean with wet cloth by putting some water on the cut area.

VASTU REMEDY USING METAL STRIPS

HOW TO APPLY METAL STRIP AROUND SEPTIC TANK AND UGWT ?

1. Identify the tile or stone Joints on the flooring.
2. Mark the lines to be cut with the help of Scale or thread.
3. Blades should be fine enough to cut the floor precisely.
4. Cut the stone or Tile by 1.5 inches blade.
5. Embed the Strip Vertically in the groove
6. Fill the groove with white cement along with the existing color of the floor.
7. Clean the floor with a dry cloth 8. Next day, clean with wet cloth by putting some water on the cut area.

THINGS TO KEEP IN MIND:

1. Metal Strip in wrong direction can cause Vastu defect in building.
2. Apply metal strips only after consulting with MahaVastu Experts.
3. Cut the floor or tiles with fine cutter on joints to retain the beauty of the floor.
4. Get the implementation done by a trained and skilled person.
5. Keep children to protect them from noise and dust.
6. Wear safety glasses if standing near the cutting area to protect your eyes from dust.
7. Ensure that the strip is embedded in the floor completely.

VASTU REMEDY USING METAL STUDS

HOW TO EMBED METAL STUDS IN THE FLOOR?

1. Check the Element of Stud.
2. Mark the Spot to Embed the metal stud.
3. Ensure the point is not falling on Marma.
4. Drill a hole of 3 inches with Drill Machine.
5. Insert the Stud in that hole.
6. Cover the hole with White cement.
7. Let the spot dry and then clean the floor.

HOW TO APPLY METAL STUDS IN THE WALL?

1. Check the Element of Stud.
2. Mark the Spot to Install the metal stud.
3. Ensure the point is not on Marma.
4. Drill a hole of 3 inches wide with Drill Machine.
5. Insert the Stud in that hole.
6. Fill and Cover the hole with White cement.
7. Let the spot dry and then clean the floor.

THINGS TO KEEP IN MIND:

1. Use the metal of Stud as per Zonal Element or Devta's Element.
2. It is advised to use Studs after consulting MahaVastu Experts/Acharyas.

CHANGE POLARITY OF BUILDING WITH SPRINGS

HOW TO APPLY METAL SPRINGS IN THE FLOOR?

1. Check the Polarity of the Springs by moving finger upwards along the spring.
2. Mark the Spot to Install the spring.
3. Ensure the point is not on Marma.
4. Drill a hole of 3 inches wide with Drill Machine.
5. Insert the Springs in that hole.
6. Fill and Cover the hole with White cement.
7. Let the spot dry and then clean the floor.

THINGS TO KEEP IN MIND:

1. Use the colour and shape of Springs as per Zonal Element or Devta's Element.
2. Its advised to use Springs after consulting with MahaVastu Experts/Acharyas.
3. Always check the Polarity of spring before Installing.

INCREASE DIRECTIONAL STRENGTH WITH PYRAMIDS

HOW TO PLACE PYRAMIDS ?

1. Identify the North - South axis.
2. Draw two Parallel lines on North - South axis on the floor.
3. Keep the Pyramid between those Parallel Lines.
4. Permissible zones: NNW,N,NE,NE,ENE and E.

THINGS TO KEEP IN MIND:

1. Placement of pyramid in wrong direction can cause vastu defect in building. Its advised to use pyramids after consulting MahaVastu Experts/Acharyas.
2. Always place the pyramid on the floor.
3. Always align it along the North-South axis
4. It should never be stuck on the wall, door or ceiling.
5. Use only one pyramid in one MahaVastu Zone.
6. Avoid using more than 3 pyramids in one premises.
7. Pyramids made up of non conducting material like wood or plastic are effective and give the desired results when placed appropriately.
8. Avoid using Pyramids in Fire, Earth and Space zones.

INCREASE PLANETARY STRENGTH WITH GEM STUDS

HOW TO APPLY GEM STUDS IN THE FLOOR?

1. Mark the Spot to Install the Gem Stud.
2. Ensure the point is not on Marma.
3. Drill a hole of 3 inches wide with Drill Machine.
4. Empty the Vial of the Gem Stone Powder in that hole.
5. Fill and cover the hole with White cement.
6. Let the spot dry and then clean the floor.

THINGS TO KEEP IN MIND:

1. Don't Insert the Vial as it is in floor.
2. Its advised to use Gem Studs after consulting MahaVastu Experts/Acharyas.

STRENGTHEN DEVTAS WITH DIVS

HOW TO INSTALL DEVTA DIVS IN THE FLOOR?

1. Mark the Spot to Install the Gem Stud.
2. Ensure the point is not on Marma.
3. Drill a hole of 3 inches wide with Drill Machine.
4. Empty the Vial of the Gem Stone Powder in that hole.
5. Fill and cover the hole with White cement.
6. Let the spot dry and then clean the floor.

THINGS TO KEEP IN MIND:

1. Use the Particular Devta DIV.
2. Its advised to use DIV after consulting MahaVastu Experts/Acharyas.
3. Keep the 4 dots of DIV downwards.

STRENGTHEN DEVTAS WITH KITCHEN GROCERIES

HOW TO ENABLE DEVTAS WITH KITCHEN GROCERY?

1. Mark the Point on floor.
2. Clean the area.
3. Keep Kitchen Grocery in glass bowl or on the floor directly.
4. Keep it for 3 days and then dispose it off.

THINGS TO KEEP IN MIND:

1. Throw in dustbin or in the running water after 3 days.
2. Don't consume any product after keeping it as remedy.