

**Create User Define Function in Apache Pig and execute it on map reduce****Aim:**

To create User Define Function in Apache Pig and execute it on map reduce

**Procedure:****1. Firstly install PIG**

**Step 1:** Login into Ubuntu

**Step 2:** Go to <https://pig.apache.org/releases.html> and copy the path of the latest version of pig that you want to install. Run the following command to download Apache Pig in Ubuntu:

\$ wget <https://dlcdn.apache.org/pig/pig-0.16.0/pig-0.16.0.tar.gz>

**Step 3:** To untar pig-0.16.0.tar.gz file run the following command:

\$ tar xvzf pig-0.16.0.tar.gz

**Step 4:** To create a pig folder and move pig-0.16.0 to the pig folder, execute the following command:

\$ sudo mv /home/hadoop/pig-0.16.0 /home/hadoop/pig

**Step 5:** Now open the .bashrc file to edit the path and variables/settings for pig. Run the following command:

\$ sudo nano .bashrc

Add the below given to .bashrc file at the end and save the file.

```
#PIG settings
export PIG_HOME=/home/hadoop/pig
export PATH=$PATH:$PIG_HOME/bin
export PIG_CLASSPATH=$PIG_HOME/conf:$HADOOP_INSTALL/etc/hadoop/export
export PIG_CONF_DIR=$PIG_HOME/conf
export JAVA_HOME=/usr/lib/jvm/java-8-openjdk-amd64
export PIG_CLASSPATH=$PIG_CONF_DIR:$PATH
#PIG setting ends
```

**Step 6:** Run the following command to make the changes effective in the .bashrc file:

\$ source .bashrc

**Step 7:** To start all Hadoop daemons, navigate to the hadoop-3.2.1/sbin folder and run the following commands:

\$ ./start-dfs.sh \$ ./start-yarn.sh

**Step 8:** Now you can launch pig by executing the following command:

\$ pig

**Step 9:** Now you are in pig and can perform your desired tasks on pig. You can come out of the pig by the quit command:

> quit;

## 2. Create UDF in Pig

### Create a sample text file

```
hadoop@Ubuntu:~/Documents$ nano
```

```
sample.txtPaste the below content to
```

```
sample.txt
```

```
1,John
```

```
2,Jane
```

```
3,Joe
```

```
4,Emma
```

```
hadoop@Ubuntu:~/Documents$ hadoop fs -put sample.txt /home/hadoop/piginput/
```

---

### Create PIG File

```
hadoop@Ubuntu:~/Documents$ nano demo_pig.pig
```

### paste the below the content to demo\_pig.pig

```
-- Load the data from HDFS
```

```
data = LOAD '/home/hadoop/piginput/sample.txt' USING PigStorage(',') AS (id:int>
```

```
-- Dump the data to check if it was loaded
```

```
correctlyDUMP data;
```

---

### Run the above file

```
hadoop@Ubuntu:~/Documents$ pig demo_pig.pig
```

```
2024-08-07 12:13:08,791 [main] INFO
```

```
org.apache.pig.backend.hadoop.executionengine.util.MapRedUtil
```

- Total input paths to process :

1(1,John)

(2,Jane)

(3,Joe)

(4,Emma)

---

### **Create udf file an save as uppercase\_udf.py**

uppercase\_udf.py

---

```
def
uppercase(text):
return
text.upper()

if __name__ == "__main__":
import sys
for line in sys.stdin:
line = line.strip()
result = uppercase(line)
print(result)
```

---

### **Create the udfs folder on hadoop**

**hadoop@Ubuntu:~/Documents\$ hadoop fs -mkdir /home/hadoop/udfs**

**put the uppertime\_udf.py in to the abv folder**

**hadoop@Ubuntu:~/Documents\$ hdfs dfs -put uppercase\_udf.py /home/hadoop/udfs/**

---

**hadoop@Ubuntu:~/Documents\$ nano**

**udf\_example.pigcopy and paste the below content on**

**udf\_example.pig**

-- Register the Python UDF script

```
REGISTER 'hdfs:///home/hadoop/udfs/uppercase_udf.py' USING jython AS udf;
```

-- Load some data

```
data = LOAD 'hdfs:///home/hadoop/sample.txt' AS (text:chararray);
```

-- Use the Python UDF

```
uppercased_data = FOREACH data GENERATE udf.uppercase(text) AS uppercase_text;
```

-- Store the result

```
STORE uppercased_data INTO 'hdfs:///home/hadoop/pig_output_data';
```

---

**place sample.txt file on hadoop**

```
hadoop@Ubuntu:~/Documents$ hadoop fs -put sample.txt /home/hadoop/
```

**To Run the pig file**

```
hadoop@Ubuntu:~/Documents$ pig -f udf_example.pig
```

**finally u**

**get**

**Success!**

**Job Stats (time in seconds):**

JobId Maps Reduces MaxMapTimeMinMapTime AvgMapTime

MedianMapTimeMaxReduceTime MinReduceTime AvgReduceTime

MedianReducetime

Alias Feature Outputs

job\_local1786848041\_0001 1 0 n/a n/a n/a n/a 00 0 0

data,uppercased\_data MAP\_ONLY

hdfs:///home/hadoop/pig\_output\_data,

Input(s):

Successfully read 4 records (42778068 bytes) from: "hdfs:///home/hadoop/sample.txt"

Output(s):

Successfully stored 4 records (42777870 bytes) in: "hdfs:///home/hadoop/pig\_output\_data"

Counters:

Total records written : 4

Total bytes written : 42777870

Spillable Memory Manager spill count :

0Total bags proactively spilled: 0

Total records proactively spilled: 0

Job DAG:

job\_local1786848041\_0001

2024-08-07 13:33:04,631 [main] WARN  
org.apache.hadoop.metrics2.impl.MetricsSystemImp

l -JobTracker metrics system already initialized!

2024-08-07 13:33:04,639 [main] WARN  
org.apache.hadoop.metrics2.impl.MetricsSystemImp

l -JobTracker metrics system already initialized!

2024-08-07 13:33:04,644 [main] WARN  
org.apache.hadoop.metrics2.impl.MetricsSystemImp

l -JobTracker metrics system already initialized!

2024-08-07 13:33:04,667 [main] INFO

org.apache.pig.backend.hadoop.executionengine.mapReduceLayer.MapReduceLaunche  
r -Success!

**Note :**

**If any error check jython package is installed and check the path specified on the  
abovesteps are give correctly**

-----  
**To check the output file is created**

hadoop@Ubuntu:~/Documents\$ hdfs dfs -ls  
/home/hadoop/pig\_output\_dataFound 2 items

If you need to examine the files in the output folder, use:

**To view the output**

```
hadoop@Ubuntu:~/Documents$ hdfs dfs -cat  
/home/hadoop/pig_output_data/part-m-00000
```

**OUTPUT:**

```
hadoop@Raghav:/mnt/d/DA/exp4$ hdfs dfs -cat /home/hadoop/pig_output_data/part  
-m-00000  
JOHN  
JANE  
JOE  
EMMA
```

**Result:**

Thus the User Define Function in Apache Pig and execute it on map reduce is executed successfully.