

Name :- Souvik Layek
EmpID:-85009903

Assignment Question Answer :-

The image displays three sequential screenshots of the Postman application interface, illustrating a REST client request and response cycle.

Top Screenshot: Shows a POST request to `https://reqbin.com/echo/post/json`. The request headers are configured as follows:

Key	Value	Description
Host	<calculated when request is sent>	
User-Agent	PostmanRuntime/7.54.0	
Accept	/*/*	
Accept-Encoding	gzip, deflate, br	
Connection	keep-alive	
Content-Type	application/json	

The body is set to `HTML` and contains the following content:

```
<!DOCTYPE html>
<html lang="en-US">
<head>
  <title>Just a moment...</title>
  <meta http-equiv="Content-Type" content="text/html; charset=UTF-8">
  <meta http-equiv="X-UA-Compatible" content="IE=Edge">
  <meta name="robots" content="noindex,nofollow">
</head>
</html>
```

The response status is `403 Forbidden` with a 400 ms duration and 7.7 KB size.

Middle Screenshot: Shows the response body in `JSON` format:

```
{
  "name": "Souvik Layek",
  "job": "Tester",
  "id": "22853288"
}
```

The response status is `403 Forbidden` with a 400 ms duration and 7.7 KB size.

Bottom Screenshot: Shows the console output for the POST request. The request headers are:

```
Content-Type: "application/json"
User-Agent: "PostmanRuntime/7.54.0"
Accept: "/*/*"
Cache-Control: "no-cache"
Postman-Token: "0a0c01a4-d7ab-4491-b88f-2dd8e678cb7c"
Host: "reqbin.com"
Accept-Encoding: "gzip, deflate, br"
Connection: "keep-alive"
```

The response headers are:

```
Date: "Fri, 19 Jun 2026 17:46:30 GMT"
Content-Type: "text/html; charset=UTF-8"
```