

Name - ASTHA
Employee No. - 85009828
Mail ID - astha@coforge.com

Assignment Operators and Operator Precedence

1. Which of these have highest precedence?

- a) ()
- b) ++
- c) *
- d) >>

Answer : a) ()

2. What should be expression1 evaluate to in using ternary operator as in this line?

expression1 ? expression2 : expression3

- a) Integer
- b) Floating – point numbers
- c) Boolean
- d) None of the mentioned

Answer : c) Boolean

3. What is the value stored in x in the following lines of Java code?

```
int x, y, z;  
x = 0;  
y = 1;  
x = y = z = 8;
```

- a) 0
- b) 1
- c) 9
- d) 8

Answer : d) 8

4. What is the order of precedence (highest to lowest) of following operators?

- 1. &
- 2. ^
- 3. ?:

- a) 1 -> 2 -> 3
- b) 2 -> 1 -> 3
- c) 3 -> 2 -> 1
- d) 2 -> 3 -> 1

Answer : a) 1 -> 2 -> 3

5. Which of these statements are incorrect?

- a) Equal to operator has least precedence
- b) Brackets () have highest precedence
- c) Division operator, /, has higher precedence than multiplication operator
- d) Addition operator, +, and subtraction operator have equal precedence

Answer : c) Division operator, /, has higher precedence than multiplication operator

6. What will be the output of the following Java code?

```
class operators
{
    public static void main(String args[])
    {
        int var1 = 5;
        int var2 = 6;
        int var3;
        var3 = ++ var2 * var1 / var2 + var2;
        System.out.print(var3);
    }
}
```

- a) 10
- b) 11
- c) 12
- d) 56

Answer : c) 12

7. What will be the output of the following Java code?

```
class operators
{
    public static void main(String args[])
    {
        int x = 8;
        System.out.println(++x * 3 + " " + x);
    }
}
```

- a) 24 8
- b) 24 9
- c) 27 8
- d) 27 9

Answer : d) 27 9

8. What will be the output of the following Java code?

```
class Output
{
    public static void main(String args[])
    {
```

```

        int x=y=z=20;

    }
}

```

- a) compile and runs fine
- b) 20
- c) run time error
- d) compile time error

Answer : d) compile time error

9. Which of these lines of Java code will give better performance?

1. `a | 4 + c >> b & 7;`
 2. `(a | ((( 4 * c ) >> b ) & 7 ))`
- a) 1 will give better performance as it has no parentheses
 - b) 2 will give better performance as it has parentheses
 - c) Both 1 & 2 will give equal performance
 - d) Dependent on the computer system

Answer : c) Both 1 & 2 will give equal performance

10. What will be the output of the following Java program?

```

class Output
{
    public static void main(String args[])
    {
        int a,b,c,d;
        a=b=c=d=20
        a+=b-=c*=d/=20
        System.out.println(a+" "+b+" "+c+" "+d);

    }
}

```

- a) compile time error
- b) runtime error
- c) a=20 b=0 c=20 d=1
- d) none of the mentioned

Answer : a) compile time error