

Started on	Tuesday, 21 May 2024, 11:36 PM
State	Finished
Completed on	Wednesday, 22 May 2024, 12:00 AM
Time taken	23 mins 52 secs
Marks	5.00/5.00
Grade	100.00 out of 100.00

Question 1

Correct

Mark 1.00 out of 1.00

Given an array of [strings](#) words, return the words that can be typed using letters of the alphabet on only one row of American keyboard like the image below.

In the **American keyboard**:

- the first row consists of the characters "qwertyuiop",
- the second row consists of the characters "asdfghjkl", and
- the third row consists of the characters "zxcvbnm".

~ ,	!	@	#	\$	%	^	&	*	()	-	+	Backspace
Tab	Q	W	E	R	T	Y	U	I	O	P	{	}	
Caps Lock	A	S	D	F	G	H	J	K	L	:	"	Enter	
Shift	Z	X	C	V	B	N	M	<	>	?	Shift		
Ctrl	Win Key	Alt								Alt	Win Key	Menu	Ctrl

Example 1:

Input: words = ["Hello", "Alaska", "Dad", "Peace"]

Output: ["Alaska", "Dad"]

Example 2:

Input: words = ["omk"]

Output: []

Example 3:

Input: words = ["adsdf", "sfd"]

Output: ["adsdf", "sfd"]

For example:

Input	Result
4 Hello Alaska Dad Peace	Alaska Dad
2 adsdf afd	adsdf afd

Answer: (penalty regime: 0 %)

```

1 A = int(input())
2 words = [input() for _ in range(A)]
3 rows = [set("qwertyuiop"), set("asdfghjkl"), set("zxcvbnm")]
4 result = [word for word in words if any(set(word.lower()).issubset(row) for row in rows)]
5 if result:
```

```

6 |         print("\n".join(result))
7 |     else:
8 |         print("No words")
9 |

```

	Input	Expected	Got	
✓	4 Hello Alaska Dad Peace	Alaska Dad	Alaska Dad	✓
✓	1 omk	No words	No words	✓
✓	2 adsfd afd	adsfd afd	adsfd afd	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 2

Correct

Mark 1.00 out of 1.00

There is a malfunctioning keyboard where some letter keys do not work. All other keys on the keyboard work properly.

Given a string text of words separated by a single space (no leading or trailing spaces) and a string brokenLetters of all distinct letter keys that are broken, return the number of words in text you can fully type using this keyboard.

Example 1:

Input: text = "hello world", brokenLetters = "ad"

Output:

1

Explanation: We cannot type "world" because the 'd' key is broken.

For example:

Input	Result
hello world ad	1
Faculty Upskilling in Python Programming ak	2

Answer: (penalty regime: 0 %)

```
1 A = input()
2 B = input()
3 C = set(B.lower() + B.upper())
4 words = A.split()
5 D = 0
6 for word in words:
7     if any(letter in C for letter in word):
8         continue
9     else:
10         D += 1
11 print(D)
12
13
14
15
16
17
18
19
20
```

	Input	Expected	Got	
✓	hello world ad	1	1	✓
✓	Welcome to REC e	1	1	✓
✓	Faculty Upskilling in Python Programming ak	2	2	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 3

Correct

Mark 1.00 out of 1.00

The **DNA sequence** is composed of a series of nucleotides abbreviated as 'A', 'C', 'G', and 'T'.

- For example, "ACGAATTCCG" is a **DNA sequence**.

When studying **DNA**, it is useful to identify repeated sequences within the DNA.

Given a string `s` that represents a **DNA sequence**, return all the **10-letter-long** sequences (substrings) that occur more than once in a DNA molecule. You may return the answer in **any order**.

Example 1:

Input: `s = "AAAAACCCCCAAAAACCCCCAAAAAGGGTTT"`

Output: `["AAAAACCCCC", "CCCCAAAAA"]`

Example 2:

Input: `s = "AAAAAAAAAAAA"`

Output: `["AAAAAAAAA"]`

For example:

Input	Result
AAAAACCCCCAAAAACCCCCAAAAAGGGTTT	AAAAACCCCC CCCCAAAAA

Answer: (penalty regime: 0 %)

```

1 | s = input()
2 | A = set()
3 | B = set()
4 | for i in range(len(s) - 9):
5 |     C = s[i:i + 10]
6 |     if C in A:
7 |         B.add(C)
8 |     else:
9 |         A.add(C)
10 | for seq in B:
11 |     print(seq)

```

	Input	Expected	Got	
✓	AAAAACCCCCAAAAACCCCCAAAAAGGGTTT	AAAAACCCCC CCCCAAAAA	AAAAACCCCC CCCCAAAAA	✓

	Input	Expected	Got	
✓	AAAAAAAAAAAAA	AAAAAAAAAA	AAAAAAAAAA	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 4

Correct

Mark 1.00 out of 1.00

Given an array of integers `nums` containing $n + 1$ integers where each integer is in the range $[1, n]$ inclusive. There is only **one repeated number** in `nums`, return *this repeated number*. Solve the problem using [set](#).

Example 1:

Input: `nums = [1,3,4,2,2]`

Output: 2

Example 2:

Input: `nums = [3,1,3,4,2]`

Output: 3

For example:

Input	Result
1 3 4 4 2	4

Answer: (penalty regime: 0 %)

```

1 nums = list(map(int, input().split()))
2 A = set()
3 for num in nums:
4     if num in A:
5         print(num)
6         break
7     A.add(num)
8

```

	Input	Expected	Got	
✓	1 3 4 4 2	4	4	✓
✓	1 2 2 3 4 5 6 7	2	2	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question 5

Correct

Mark 1.00 out of 1.00

Write a program to eliminate the common elements in the given 2 arrays and print only the non-repeating elements and the total number of such non-repeating elements.

Input Format:

The first line contains space-separated values, denoting the size of the two arrays in integer format respectively.

The next two lines contain the space-separated integer arrays to be compared.

[Sample](#) Input:

```
5 4
1 2 8 6 5
2 6 8 10
```

[Sample](#) Output:

```
1 5 10
3
```

[Sample](#) Input:

```
5 5
1 2 3 4 5
1 2 3 4 5
```

[Sample](#) Output:

```
NO SUCH ELEMENTS
```

For example:

Input	Result
5 4 1 2 8 6 5 2 6 8 10	1 5 10 3

Answer: (penalty regime: 0 %)

```
1 size1, size2 = map(int, input().split())
2
3 array1 = list(map(int, input().split()))
4 array2 = list(map(int, input().split()))
5 set1 = set(array1)
6 set2 = set(array2)
7 A = (set1.symmetric_difference(set2))
8 if A:
9     print(*A)
10    print(len(A))
11 else:
12     print("NO SUCH ELEMENTS")
13
```

	Input	Expected	Got	
✓	5 4 1 2 8 6 5 2 6 8 10	1 5 10 3	1 5 10 3	✓
✓	3 3 10 10 10 10 11 12	11 12 2	11 12 2	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.



[◀ Week7_MCQ](#)

Jump to...

[Dictionary ▶](#)