Demonstrate how to work with variables in Postman.

ws_simplilearn_aug_10 New Import

POST Create User | GET {{url}}/api/users | ⬚ dev | ⬚ prad | ⬚ qa | + ⋯ | No Environment ⌄

qa 🍴 Fork 0 💾 Save ↗ Share ⋯

+ ▽ Globals

🔍 Filter variables

dev
prad
qa
staging

	Variable	Type	Initial value	Current value	⋯
☑	url	default ⌄	https://qa.reqres.in	https://qa.reqres.in	
	Add new variable				

Collections
Environments
Monitors
History

ⓘ **Use variables to reuse values and protect sensitive data**
Store sensitive data in variable type secret to keep its values masked on the screen. Learn more about variable type ↗
Work with the current value of a variable to prevent sharing sensitive values with your team. Learn more about variable values ↗ ✕

⬚ Online 🔍 Find and replace ⬚ Console | ▶ Runner ⤢ Capture requests 🍪 Cookies 🗑 Trash

---

ws_simplilearn_aug_10 New Import

POST Create User | GET {{url}}/api/use | ⬚ dev | ⬚ prad | ⬚ qa | ⬚ staging | + ⋯ | No Environment ⌄

staging 🍴 Fork 0 💾 Save ↗ Share ⋯

+ ▽ Globals

🔍 Filter variables

dev
prad
qa
staging

	Variable	Type	Initial value	Current value	⋯
☑	url	default ⌄	https://stag.reqres.in	https://stag.reqres.in	
	Add new variable				

Collections
Environments
Monitors
History

ⓘ **Use variables to reuse values and protect sensitive data**
Store sensitive data in variable type secret to keep its values masked on the screen. Learn more about variable type ↗
Work with the current value of a variable to prevent sharing sensitive values with your team. Learn more about variable values ↗ ✕