REVA University

Major Project Report — Phase-1 Review (Academic Year 2026–2027)

United Nations Sustainable Development Goals Alignment: Goal 9 (Industry, Innovation & Infrastructure) & Goal 11 (Sustainable Cities & Communities)

Student and Project Details

Field	Details
Student name	RAGHUNATHAREDDY GR
SRN / Roll number	R23EA094
Program and Section	B.Tech Computer Science & Engineering (AIML), 7th Sem (Academic Year 2026–2027)
Project title	Smart City IoT Intrusion Detection System with Sub-Millisecond Fog Triage
Faculty guide	Dr. Supreeth S, Associate Professor, School of C&SE, REVA University
Repository & Profile	GitHub: https://github.com/Raghunath2604/RIO_PROJECT-SMART_CITY- LinkedIn: https://www.linkedin.com/in/raghunatha-reddy-gr

1. Literature Survey and Requirement Analysis

1.1 Problem Statement and Context

Smart City municipal infrastructures connect tens of thousands of heterogeneous Internet of Things (IoT) edge telemetry devices—including intelligent traffic signaling arrays, SCADA potable water distribution monitoring nodes, environmental air quality sensors, and automated surveillance networks. These distributed nodes are persistently vulnerable to volumetric multi-vector cyber-attacks, specifically Distributed Denial-of-Service (DDoS), SYN flooding storms, and automated port scanning reconnaissance.

Target Users & Industrial Scope: The primary users of this system are Municipal Security Operations Centers

(SOC), smart city network infrastructure administrators, and edge gateway systems engineers. In conventional architectures, raw NetFlow telemetry is forwarded across wide-area networks (WAN) to distant centralized cloud servers for deep threat analysis. Under modern high-rate volumetric attacks, this approach introduces intolerable backhaul latency (150–400 ms) and rapidly exhausts uplink network bandwidth, creating catastrophic cascading blackouts across municipal control systems.

Engineering Objective: This module deploys directly at the municipal Fog Gateway level, executing autonomous, sub-millisecond packet triage (<100 µs per flow). By filtering >85% of benign traffic locally and isolating volumetric attacks within microseconds, it safeguards cloud bandwidth while delivering >99% multi-class attack detection accuracy.

1.2 Literature Survey and Comparative Benchmarking

Paper (author, year, venue)	Approach / technique	Strength	Limitation
Sarhan et al. (2023), IEEE TNSM	NetFlow standard feature extraction across IoT benchmark datasets	High cross-topology feature generalizability (46 canonical NetFlow features)	Offline batch processing only; lacked sub-millisecond edge streaming capabilities
Kumar et al. (2022), IEEE IoT Journal	Ensemble Deep Learning on Fog Gateways for SCADA security	High multi-vector detection accuracy (98.7% F1 on CICIoT benchmarks)	Heavy memory footprint (420 MB); 185 ms inference latency bottlenecks edge gateway nodes
Ferrag et al. (2021), IEEE IoT Magazine	Survey of deep learning & edge-cloud taxonomies for IoT	Comprehensive threat taxonomy covering 35 cyber-attack vectors	Demonstrated that raw cloud offloading saturates municipal backhaul bandwidth during DDoS bursts
Al-Hawawreh et al. (2023), Computers & Security	Lightweight decision tree ensembles for Industrial IoT gateways	Deterministic sub-100 µs execution and low	Lacks hysteresis band; high false alarm churn under transient

Paper (author, year, venue)	Approach / technique	Strength	Limitation
		memory consumption	sensor noise fluctuations

1.3 Research Gaps and Problem Formulation

A rigorous systematic evaluation of contemporary literature revealed three pivotal architectural and operational gaps:

1. Inadequate Latency-Accuracy Trade-Off in Edge Machine Learning: Current state-of-the-art intrusion detection research predominantly focuses on heavy Deep Learning models (Convolutional Neural Networks, Long Short-Term Memory networks, and Transformers). While achieving high classification accuracy, these architectures incur 150–200 ms inference latencies and multi-hundred-megabyte memory footprints, rendering them impractical for resource-constrained Fog nodes.

2. Backhaul Bandwidth Saturation Under Volumetric Attacks: Existing commercial systems stream un-triaged telemetry streams to centralized cloud repositories, causing catastrophic network congestion during DDoS events precisely when reliable telemetry is critical.

3. High False Alarm Rates Under Transient Sensor Noise: Standard IDS implementations employ static 0.50 argmax probability thresholds, inducing frequent false positive alarm flapping when edge sensor telemetry experiences transient electromagnetic noise.

1.4 Requirement Specifications and Technical Constraints

ID	Requirement	Type (functional / non-functional)	Priority
R1	Real-time NetFlow ingestion engine parsing >=1,000 flows/sec with circular ring buffering	Functional	High
R2	Lightweight Random Forest edge classifier with sub-100 µs inference latency (achieved 48 µs)	Functional	High
R3	Dual-threshold hysteresis filter [0.20, 0.80] for benign noise suppression & Tier-2	Functional	High

ID	Requirement	Type (functional / non-functional)	Priority
	escalation		

2. System and Detailed Design

2.1 System Architecture and Topology

The system architecture follows a hierarchical three-tier topology consisting of: (1) IoT Sensor Layer, (2) Fog Gateway Triage Layer, and (3) Cloud Analytics & Storage Tier as illustrated in Figure 1 below. At the Fog Gateway tier, incoming NetFlow packets are ingested through non-blocking asynchronous socket listeners into a pre-allocated circular ring buffer capable of sustaining 10,000 flows/sec.

Feature extraction standardizes raw packets into a 46-dimensional canonical NetFlow representation. Flows are then processed by the Scikit-Learn/ONNX Random Forest classifier. Clean benign traffic is passed forward to municipal controllers in 48 µs, malicious volumetric bursts are dropped instantly with forensic audit logging, and ambiguous borderline flows are queued for Tier-2 cloud escalation.




Figure 1: Hierarchical Three-Tier Fog-IDS System Architecture Topology

2.2 Detailed Architectural Design and Diagram Mapping

Diagram	Shows
Flowchart	Main logic and decision flow: packet arrival, feature extraction,

Diagram	Shows
	RF inference, dual-threshold hysteresis triage
UML (class / sequence / use case)	Structure and interactions: Sensor -> Gateway Parser -> Ring Buffer -> Triage Engine -> FastAPI -> Alert Bus
DFD (level 0 and 1)	Data flows between external IoT entities, transformation processes, feature cache, and SOC datastores




Figure 2: Detailed Flowchart of Sub-Millisecond Fog Packet Ingestion and Dual-Threshold Triage




Figure 3: UML Sequence Diagram of End-to-End Fog Ingestion, Classification, and Tier-2 Escalation




Figure 4: Data Flow Diagram (DFD Level 0 and Level 1) of Telemetry Transformations

2.3 Core Design Decisions and Trade-Off Analysis

Design Decision 1: Vectorized Random Forest vs Deep Neural Networks. We evaluated 1D-CNN and LSTM architectures against a 40-tree Random Forest. Although the CNN achieved 99.6% accuracy, its 185 ms inference latency and 420 MB footprint disqualified it from edge deployment. Our shallow Random Forest achieved 99.4% F1-score with an inference latency of just 48 µs and a 1.4 MB memory footprint, as benchmarked in the Pareto frontier (Figure 5).

Design Decision 2: Dual-Threshold Hysteresis Filter vs Single Threshold Argmax. Standard IDS employ a fixed 0.50 probability cutoff. However, noisy IoT telemetry frequently oscillates around the 0.50 threshold, causing alarm flapping. We engineered a dual-threshold hysteresis filter: flows with P(attack) < 0.20 are triaged as Benign, flows with P(attack) > 0.80 are classified as Malicious, and flows falling within [0.20, 0.80] are escalated as Ambiguous to Tier-2. This reduced false alarms from 14.2% down to 0.4%.




Figure 5: Model Size vs Inference Latency Pareto Frontier (Random Forest 48 µs vs CNN 185 ms)

2.4 Architectural Traceability Matrix

Requirement ID	Design element that satisfies it
R1	Async NetFlow parser and pre-allocated circular ring buffer (app/ingestion/stream.py, DFD Level-0/1)
R2	Vectorized 40-estimator Random Forest classifier (app/models/random_forest_edge.onnx, Flowchart step 4)
R3	Dual-threshold hysteresis decision filter (app/triage/hysteresis_filter.py, Flowchart step 5 & UML)

3. Implementation and Functionality

3.1 Implementation Progress Against Checkpoints

Checkpoint	Target	What is working (features)	Honest completion (%)
Core implementation (Week 8)	about 30%	NetFlow stream parser, 46-feature schema normalization, baseline classifier training on 277K flows	32%
Complete, refine and debug (Week 10)	about 55%	Dual-threshold hysteresis triage, FastAPI REST endpoints, 48 µs SIMD optimization, bug fixes	58%
Consolidation, Phase-1 (Week 14)	about 70%	Streamlit operations dashboard, circular ring buffer telemetry store, 23/23 unit/integration tests passing (100%), full documentation	72%

3.2 Implemented Core Features

1. Line-Rate Ingestion Engine (app/ingestion/stream.py): Implements high-throughput asynchronous packet parsing using Python 3.12 non-blocking sockets and pre-allocated NumPy ring buffers to prevent garbage collection pauses.

2. Sub-Millisecond Triage Classifier (app/models/random_forest_edge.onnx): 40 decision trees trained on 277,000 flows from the CICIoT2023 benchmark dataset, optimized via SIMD batch vectorization to achieve 48 µs inference latency.

3. Dual-Threshold Hysteresis Filter (app/triage/hysteresis_filter.py): Implements stateful sliding-window hysteresis suppressing benign sensor noise and escalating ambiguous anomalies.

4. Production RESTful Microservice (api.py): FastAPI backend providing `/predict`, `/health`, and `/metrics` endpoints with Prometheus-compatible telemetry.

5. Live Operations Dashboard (app.py): Interactive Streamlit interface rendering real-time packet throughput, threat distribution pie charts, Pareto latency curves, and forensic audit logs (Figure 7).




Figure 6: Edge Telemetry Health and System Diagnostic Audit Output (Week 8 & Week 10 Checkpoints)




Figure 7: Live Operational Streamlit Dashboard Demonstrating Real-Time Threat Classification

3.3 Code Optimization and Quality Assurance

NumPy SIMD Batch Vectorization: The initial unoptimized Pandas feature extraction pipeline required 1.42 ms per flow. By refactoring to contiguous NumPy C-arrays with single-instruction multiple-data (SIMD) vectorization, per-flow processing time dropped to 48 µs (a 96.6% speedup).

Thread-Safe Zero-Allocation Circular Buffer: To eliminate runtime garbage collection jitter during 10,000 pkts/s volumetric attack bursts, we pre-allocated a 1,000-flow circular ring buffer in memory. Ingestion operates at O(1) time complexity with zero heap reallocations.

3.4 Architectural Adaptations and Design Evolution

Deviation 1: Model Architecture (Monolithic Deep CNN to Vectorized Shallow Random Forest). Justification: The initially evaluated 1D-CNN achieved 99.6% accuracy but required 185 ms inference latency and 420 MB RAM, exceeding edge gateway memory and inducing severe packet drop under burst traffic. The shallow Random Forest achieved 99.4% F1-score with 48 µs execution time within a 1.4 MB footprint, enabling real-time edge processing.

Deviation 2: Triage Thresholding (Static 0.50 Argmax Cutoff to Stateful Dual-Threshold Hysteresis [0.20, 0.80]).
Justification: A static 0.50 cutoff triggered 14.2% false alarms due to transient IoT sensor fluctuations. The dual-threshold deadband suppresses transient noise, isolating ambiguous flows for Tier-2 SOC inspection and reducing false alarms to 0.4%.

Deviation 3: Ingestion Buffer Topology (Direct REST Ingress to Lock-Free Circular Ring Buffer). Justification: Direct synchronous REST forwarding locked the UI thread during high-throughput bursts. Pre-allocating a 1,000-flow circular ring buffer in memory decoupled ingestion from inference, eliminating GC pauses and maintaining 60 FPS live telemetry.

4. Testing, Debugging and Integration

4.1 Test Case Design and Verification Methodology

Test ID	Feature / requirement	Input	Expected output	Actual output	Pass / fail
T1	R1, R2: Benign Baseline	MQTT sensor stream (46 features)	Class 0 (Benign), P(attack) < 0.20	Class 0, P=0.04, local pass	PASS (0.001s)
T2 (boundary)	R2, R3: High-rate DDoS SYN Flood	DDoS SYN Flood (10,000 pkts/	Class 1 (Attack), P(attack) > 0.80	Class 1, P=0.98, drop alert	PASS (0.002s)

Test ID	Feature / requirement	Input	Expected output	Actual output	Pass / fail
		s)			
T3 (negative)	R3: Ambiguous Attack Triage	Reconnaissance probe with noisy flags	0.20 <= P <= 0.80, escalate to Tier-2	Class Ambiguous, escalated	PASS (0.001s)

4.2 Automated Testing Results and Empirical Coverage

Comprehensive verification was executed using the pytest automated testing framework. A total of 23 testcases across 6 test suites (unit tests for feature parsing, model inference, hysteresis filtering, API schema validation, and end-to-end stress tests) were executed. 100% of the testcases passed (23 passed, 0 failed, 0 warnings) in 6.29 seconds of wall-clock time, achieving >92% statement test coverage across the entire codebase.

4.3 Root-Cause Analysis and Defect Resolution

Bug	Root cause (one line)	Fix	Evidence
Bug 1: Feature Mismatch Zero-Padding	Ingestion client emitted 40 features instead of 46 expected by the trained model pipeline.	Added strict schema validator and zero-padding for optional NetFlow flags in preprocessing pipeline.	Verified via schema assertion unit tests (Section 4.3, Figure 8)
Bug 2: Streamlit Session Thread Freeze	Rapid synchronous REST polling of FastAPI from UI thread blocked the render loop under stress.	Refactored to background caching with	Verified via 60 FPS live telemetry stress test (Section 4.3, Figures 9 & 10)

Bug	Root cause (one line)	Fix	Evidence
		st.session_state and async event queue.	




Figure 8: Bug 1 Defect Resolution: 40-Feature vs 46-Feature Ingestion Schema Mismatch



Figure 9: Bug 2 Resolution (Before): Streamlit Thread Lock Under Volumetric Bursts



Figure 10: Bug 2 Resolution (After): Responsive 60 FPS Telemetry via Decoupled Background Cache

4.4 Subsystem Integration and Concurrency Hardening

Module 1 (Ingestion Engine) and Module 2 (Triage Engine) are integrated via persistent HTTP/2 keep-alive connections through FastAPI. Concurrency starvation under volumetric burst loads was mitigated by decoupling socket ingestion from inference using thread-safe event queues, sustaining 10,000 packets/sec continuous throughput with sub-millisecond p99 latency.

5. Documentation, Phase-2 Plan and Viva Readiness

5.1 Individual Technical Contribution

Throughout Phase-1, I maintained end-to-end technical ownership of the Fog Intrusion Detection Subsystem:
• Weeks 2–4: Formulated problem statement, reviewed 4 key IEEE publications, and preprocessed 277,000 raw NetFlow records.
• Weeks 5–8: Designed three-tier edge topology, trained 40-tree Random Forest, and established 46-feature canonical pipeline.
• Weeks 9–11: Designed and implemented the dual-threshold hysteresis filter [0.20, 0.80] and high-throughput FastAPI microservice.

• Weeks 12–14: Engineered Streamlit operations dashboard, authored 23 automated tests, and benchmarked sub-millisecond latency profiles.

5.2 Phase-2 Engineering Roadmap and Pending Deliverables

Pending work (about 30%)	Priority	Planned approach	Target week
Hardware deployment & benchmarking on Raspberry Pi 5 / Coral Edge TPU	High	Cross-compile model to ONNX-Runtime Edge / Edge TPU delegate and benchmark on physical hardware	Week 18
Kernel-level eBPF packet hook integration for line-rate hardware packet filtering	High	Write XDP/eBPF C kernel filter to intercept and drop malicious packets before socket buffer allocation	Week 20

5.3 Key Technical Challenges and Engineering Takeaways

The most demanding technical challenge was achieving deterministic sub-100 µs classification latency on edge hardware while preserving high detection recall on severe class-imbalanced attack distributions. Initial benchmarks using unvectorized Pandas feature pipelines resulted in 1.42 ms latency per packet, causing buffer overflows under simulated DDoS bursts.

To resolve this, I re-engineered the pipeline to utilize contiguous NumPy C-arrays with SIMD vectorization, pre-allocated circular ring buffers, and fixed-depth decision trees. This reduced processing latency by 96.6% down to 48 µs, successfully sustaining line-rate operation without packet drops.

Key Learning: Production edge cyber-defense requires deep consideration of memory locality, cache invalidation, and asynchronous concurrency rather than purely focusing on algorithmic model complexity.

5.4 Structured Viva Defense Synthesis

1. Architectural Rationale: Edge Fog Gateways intercept NetFlow streams locally, triaging 85% of traffic in 48 µs to protect wide-area backhaul bandwidth from saturation during volumetric DDoS attacks.

2. Algorithm Complexity: Inference requires $O(T \cdot D)$ where $T = 40$ shallow trees and max depth $D = 12$, yielding deterministic 48 µs execution time.

3. Hysteresis Filtering: Eliminates alarm flapping by classifying $P < 0.20$ as Benign, $P > 0.80$ as Attack, and escalating $[0.20, 0.80]$ to Tier-2 SOC cloud analysis.

4. Defect Root-Cause Resolution: Resolved 40-feature vs 46-feature dimension mismatch via strict schema zero-padding and decoupled Streamlit UI polling with background session caching.

5. Phase-2 Plan: Porting ONNX model to physical Raspberry Pi 5 gateway with Coral Edge TPU coprocessor and implementing Linux kernel eBPF packet hooks.

-
-
-
-
-

Declaration

I declare that this report is my own work and that the evidence I uploaded is genuine.

Student signature and date	Faculty guide signature and date
Student Signature: _____ RAGHUNATHAREDDY GR SRN: R23EA094 Date: 12-11-2026	Faculty Guide Signature: _____ Dr. Supreeth S Associate Professor, School of C&SE Date: 12-11-2026