XenoStudio

Change Notes: every change from the fork to today

Covers v1.0.0 (2026-11-01) through v1.4.0 (2026-11-11)

Version summary

Version	Date	By	Headline
1.0.0	2026-11-01	Claude + Codex	Forked from XenoDuo into a separate, portable app: pinned CLIs, shared MCP list, shell commands, DeepSeek/Grok backup seats, prompt templates, much larger settings.
1.1.0	2026-11-09	Claude	Fixed Codex crashing ("The pipe is being closed"), multiple working folders (two drives), picture attachments, updated bundled Claude Code and Codex CLIs, text-encoding fixes.
1.2.0	2026-11-09	Claude + Codex	Single instance (no duplicate windows), automatic repair of stale MCP paths, crash-proof turns, retry once by default, remembered window position, crash log, drag-and-drop overlay and fixes.
1.3.0	2026-11-10	Claude + Codex	Cyberpunk and Hacker themes; the Windows 11 title bar and border follow the theme.
1.4.0	2026-11-11	Claude + Codex	Code workspace with the Monaco editor (from XenoEdit), code tiles, change cards and before/after diffs of every AI edit, live reload, Open in XenoEdit, safer updater, README with demo, private GitHub repo and release.

Who did what: **Claude** owns the C# backend (Settings.cs, Agents.cs, App/MainWindow) and did the web UI changes in 1.1.0 while Codex was down. **Codex** owns the web UI (web\) and did the 1.2.0 drag-and-drop work, the 1.3.0 theme styles and the 1.4.0 workspace UI.

v1.0.0: the fork from XenoDuo · 2026-11-01

XenoStudio was created as a copy of XenoDuo so new ideas could be tried without touching the stable app. XenoDuo itself was never edited. Everything below is what 1.0.0 added on top of XenoDuo.

Portable layout

- Everything lives next to the exe: `runtime\` (pinned `claude.exe` and `codex.exe`), `data\settings.json`, `data\chats\`, `data\profiles\claude-settings.json`.
- Pinned CLIs are never auto-updated; Settings → "Update bundled CLIs" copies installed versions in only when you choose.
- First run copies XenoDuo's settings as a starting point (read-only; XenoDuo's own files are untouched).
- Packaging script `_dev\package.ps1` builds a shareable zip (with or without the CLIs) and never includes `data\`.
- Command line: `XenoStudio.exe --send "message"` starts a new chat with that message.

MCP servers

- One shared server list (stdio or http/sse), each switchable on/off and per AI (Claude and/or Codex).
- Claude gets them through a generated `data\mcp-claude.json` (`--mcp-config`), with optional "strict" mode and auto-allow of the servers' tools.
- Codex gets them as `-c mcp_servers.<name>.*` overrides, so they work with or without `~/.codex/config.toml`.

- "Import" pulls servers from `~/.claude.json` and `~/.codex/config.toml`.

Chat

- `!command` runs a shell command (PowerShell, pwsh or cmd) in the working folder; output is shared with the AIs unless turned off.
- `@claude` / `@codex` / `@both` addressing, and AI-to-AI hand-off by @mention.
- DeepSeek and Grok backup seats over any OpenAI-compatible API (also local Ollama / LM Studio), with optional automatic fallback when Claude or Codex fails.
- Editable prompt template and footer with {placeholders}, plus a preview of exactly what each AI receives.
- Lost-session recovery: if a CLI session disappears, a fresh one starts with the recent history.

Settings added versus XenoDuo

- **General:** your name, extra instructions for both AIs, turn time limit, auto-export, shell on/off and which shell.
- **Claude:** on/off, bundled vs installed exe, model, fallback model, max agent steps, allowed/blocked tools, extra folders, own instructions, extra CLI args, environment variables, strict MCP, auto-allow MCP.
- **Codex:** on/off, bundled vs installed exe, model, reasoning effort, sandbox, load config.toml, own instructions, extra CLI args, environment variables.
- UI preferences (font size, accent, density, timestamps…) stored in `settings.ui`.

v1.1.0 · 2026-11-09 · Claude

Bug fixes

Problem	Cause	Fix
Codex failed every turn with "The pipe is being closed".	The working folder was set to `D:\,E:\`. It was passed to Codex as one folder path (`-C "D:\,E:\"`), which Windows rejects (os error 123). Codex quit instantly, and XenoStudio crashed writing to it.	Working folders are now a list (see New features). Reproduced and verified with the real CLI.
Real CLI errors were hidden.	When a CLI exited before reading its input, the write threw "The pipe is being closed" and masked the CLI's own message.	That write error is now ignored, so the CLI's actual error is shown.
Claude's extra folders were silently ignored.	That setting only understood `;`. `D:\,E:\` was treated as one non-existent folder.	Accepts `,`, `;` or `|`.
Garbled characters in the UI (âœ•, Browseâ€¦, "Version 1.0 ? Data").	Text-encoding damage in `index.html` and `app.js`.	Restored ×, Browse… and the · separator.

New: multiple working folders

- The shared working folder can list several folders: `D:\,E:\`. The first existing one is where the AIs start; the rest are added with `--add-dir` for both Claude and Codex.
- Shell commands, export, the Folder button and settings export use the first folder.
- Settings → General: "Add working folder…" now **adds** the picked folder to the list instead of replacing it; "Clear folders" empties it.

New: picture attachments

- Attach by pasting (Ctrl+V, including Win+Shift+S screenshots), dragging files onto the window, or the **+ Picture** button.
- Thumbnails above the message box with × to remove; pictures can be sent with or without text.
- Pictures show in the chat; click one to open it full size.
- Stored in `data\uploads\<chat>\` and deleted together with the chat. PNG, JPG, GIF, WebP, BMP; max 20 MB each.
- **Codex** receives the actual image (`-i`; tested: it correctly answered "Red" for a red test square). **Claude** gets the file path and opens it with its Read tool. DeepSeek/Grok get the path only (no file access).
- Markdown export includes the pictures.

Updates

Component	Before	After	Notes
Claude Code (bundled)	2.1.312	2.1.321	Official npm package, signature verified: Anthropic, PBC.
Codex CLI (bundled)	0.166.0-alpha.5.1	0.167.0-alpha.3.2	Copied with its helper exes from the installed Codex app.
XenoStudio	1.0.0	1.1.0	

Tooling

- `_update\apply-update.ps1`: installs a new build after XenoStudio closes (the app can't replace itself while running), backs up the old app files, keeps `data\` untouched, then reopens the app.
- Old CLIs kept in `_update\old-runtime\`.

v1.2.0 · 2026-11-09 · Claude + Codex

A full backup of the app as it was (1.1.0, including source, build, chats and settings) was made first: `Backups\XenoStudio-v1.1.0-20261109-175842` (1.9 GB).

Changes by Claude

#	Change	Details	Verified
1	Only one XenoStudio at a time	Launching the exe again brings the open window to the front instead of opening a second app. `--send "..."` from a second launch is handed to the open window. Per install folder, so XenoDuo or a test copy can still run.	Yes: second launch exited, one window
2	Stale MCP paths repaired automatically	The node_repl server pointed at a Codex install removed by a Codex app update. At startup, any server whose command or environment paths no longer exist is re-read from the Codex/Claude config, keeping your on/off choices. A notice says which.	Yes: refreshed to the current install
3	One AI crashing doesn't stop the others	A crash inside a turn used to end the whole queue with a system error. It now becomes that AI's turn error, so retry, backup fallback and the next AI still run.	Builds; only triggers on a real crash
4	Retry once by default	Retry on error changed from 0 to 1 (5 s delay) to catch network blips and brief overloads. Applied once to existing settings through a new settings-version upgrade; still adjustable in Settings.	Yes
5	Window position and size remembered	Saved to `data\window.json` on close, including maximized. Falls back to the default if that screen is gone.	Yes
6	Crash log	Unexpected errors are written to `data\crash.log` (capped at 1 MB) with a popup, instead of the app silently dying.	Builds; only triggers on a real crash
7	Version in the title bar	"XenoStudio 1.2.0".	Yes
8	Build cleanup	Test files in `_update\` are excluded from compilation.	Yes

Changes by Codex: drag-and-drop

- Full-window drop overlay: "Drop pictures to attach to your message".
- Pictures whose Windows file type comes through blank are recognized by their extension (.png, .jpg, .jpeg, .gif, .webp, .bmp).
- A message appears if a picture can't be read.
- Drop cursor shows "copy"; the overlay clears if the drag leaves the window or is cancelled; the message box gets focus after a drop.
- Codex checked dropped images, unsupported files and the 20 MB limit. Live dragging from the desktop has not been verified yet.

v1.3.0 · 2026-11-10 · Claude + Codex

New themes

Theme	Background	Text / accent	Window border
Dark	`#1e1f22`	Default dark grey	Follows Windows
Light	`#ffffff`	Default light	Follows Windows
Cyberpunk	`#0b0618`	Neon cyan `#05d9e8` with hot pink	Pink `#ff2a6d`
Hacker	`#020602`	Terminal green `#33ff66`	Green `#1f8f3a`

- **Codex**: the two new color sets in `web\style.css` and the theme picker in Settings.
- **Claude**: `ThemeChrome.cs` colors the Windows 11 caption bar, caption text and window border so the whole window matches the theme, not just the page. The window background matches too, so there's no white flash on open.
- Settings only accept the four known themes; anything else falls back to Dark.

v1.4.0 · 2026-11-11 · Claude + Codex

Goal: blend the editor into the chat so both you and the AIs can see code and every change they make. Backup taken first: `Backups\XenoStudio-v1.3.0-20261111-212123`.

Code workspace (UI by Codex, backend by Claude)

- A workspace panel beside the chat using **Monaco**, the VS Code editor, copied from XenoEdit into `web\lib\vs`: syntax highlighting, folding, minimap; follows the app theme.
- **Code tiles:** long code blocks in replies become compact tiles (`snippet.js · javascript · 9 lines`); click to open.
- **File links:** file names in messages and tool lines open the file in the workspace.
- **Edit code / Save file:** edit in place and save to disk. The chat gets a note such as edited src\cart.js in the editor (+1 −1) so both AIs know on their next turn. **Save as…** for code blocks.
- **Attach code to chat:** send a selection or the whole draft as context with your next message.
- **Open in XenoEdit:** hands the file (or an unsaved block) to XenoEdit. Found automatically from a Desktop / Start Menu shortcut or a running XenoEdit; can also be set in Settings. Never hardcoded.
- **Live reload:** an open file reloads when an AI changes it, and asks first if you have unsaved edits.
- File reading is capped at 2 MB and refuses binary files; relative paths resolve against the work folders.

AI change tracking (Claude: `EditTracker.cs`)

- Every file Claude or Codex edits during a reply gets a **change card** under that reply: who, which file, lines added/removed, created or deleted.
- Clicking a card opens a red/green **before/after diff**. Snapshots are stored per message in `data\snapshots\` and deleted with the chat.
- **Claude** reports an edit just before making it, so its before-state is exact.
- **Codex** reports an edit only after it lands. To still get an accurate before-state, XenoStudio snapshots likely files at the start of every turn: paths mentioned in the prompt and files edited earlier in the chat. A Codex edit to any other file is marked before not captured and shows the result.
- Verified with real edits from both AIs (+2 −1 each).
- Limit: files changed through shell commands (a script writing a file) aren't reported by the CLIs, so they get no card.

Backend requests added

Request / event	Does
`previewFile`	Read a file for the workspace (size and binary checks).
`saveCode`, `saveFile`	Save a code block (Save as… dialog) or the open file; saving adds the edit note to the chat.
`openInXenoEdit`, `xenoEditInfo`	Find and launch XenoEdit.
`fileDiff`	Return the before/after of one change card.
`watchFile`, `unwatchFile`	Watch the open file; pushes `fileChanged` when it changes on disk.
`aiFile` (push)	Tells the UI an AI is editing a file, live during the turn.

Fixes and tooling

Problem	Fix
The first 1.4.0 install half-failed: the app was reopened one second before files were copied, so they were locked.	`_update\apply-update.ps1` rewritten: if files are locked it waits for the app to close and retries (up to 20 times), and only restarts the app once every file is in place. The retry installed 1.4.0 cleanly.
Deleting a chat could leave its edit snapshots behind.	Snapshots are removed first, then the chat file and its pictures.

Documentation, GitHub and sharing

- `README.md` replaces README.txt: what the app is, a 2-minute demo, the full feature list, install/build steps, data and project layout. Screenshots in `docs\screenshots\` use a made-up demo project and demo chat (no real files or chats).
- Source is on GitHub in a **private** repository. Before every push the code was scanned so only the name Xeno appears: no real name, email, address, location or machine paths (the build strips local paths from the exe too). Commits use a GitHub no-reply identity.
- One invited collaborator can view and download the repository.
- **Release v1.4.0** on the private repo: `XenoStudio-v1.4.0-win-x64.zip` (3.7 MB), ready to run. It contains no `data\` folder (chats, settings, keys) and no CLI executables; users bring their own `claude.exe` / `codex.exe` and need the .NET 8 Desktop Runtime.
- Code signing (to stop the SmartScreen warning) is prepared but on hold: an individual certificate would show a legal name instead of Xeno.

Files changed

File	Version	What changed
`Settings.cs`	1.1.0, 1.2.0	Folder lists (PrimaryWorkDir, ExtraDirs), uploads path, stale-MCP refresh, settings version upgrade, retry default.
`Agents.cs`	1.1.0	Pipe-error fix, folder lists for both CLIs, pictures passed to the CLIs.
`MainWindow.xaml.cs`	1.1.0, 1.2.0	Picture save/serve/prompt/export, folder lists everywhere, second-launch hand-off, window bounds, crash-proof turns, title.
`App.xaml / App.xaml.cs`	1.2.0	Single-instance mutex + named pipe, crash log, app now opens the window itself.
`XenoStudio.csproj`	1.1.0, 1.2.0	Version numbers; `_update\` excluded from compile.
`web\app.js`	1.1.0, 1.2.0	Picture paste/drop/attach, thumbnails, encoding fix (Claude); drop overlay and file-type fixes (Codex).
`web\index.html`	1.1.0	+ Picture button, attachment strip, encoding fixes, folder hints.
`web\style.css`	1.1.0, 1.2.0	Attachment and thumbnail styles (Claude); drop overlay (Codex).
`web\settings.js`	1.1.0	Multi-folder labels, Add working folder..., Clear folders.
`runtime\*.exe`	1.1.0	Claude Code 2.1.321, Codex 0.167.0-alpha.3.2 and helpers.
`ThemeChrome.cs`	1.3.0	New: theme colors for the Windows title bar, caption text and border.
`CodePreview.cs`	1.4.0	New: workspace file reading, Save as, finding and opening XenoEdit, preview temp files.
`EditTracker.cs`	1.4.0	New: change cards, before/after snapshots, diffs.
`Agents.cs`	1.4.0	Reports file edits from Claude (before) and Codex (started / completed).
`MainWindow.xaml.cs`	1.3.0, 1.4.0	Theme chrome; workspace requests, file watching, per-turn edit tracking, editor edit notes, chat delete cleanup.
`Settings.cs`	1.3.0, 1.4.0	Theme validation; XenoEdit path setting.
`web\preview.js`	1.4.0	New (Codex): workspace, code tiles, change cards, diff view.
`web\lib\vs\`	1.4.0	Monaco editor, copied from XenoEdit.
`web\style.css`, `web\settings.js`	1.3.0, 1.4.0	Cyberpunk / Hacker themes, workspace styles, XenoEdit path field (Codex).
`_update\apply-update.ps1`	1.4.0	Retry loop when files are locked.
`README.md`, `docs\screenshots\`	1.4.0	New guide with demo and screenshots.

Backups and how to roll back

Backup	Contains
`Backups\XenoStudio-v1.1.0-20261109-175842`	Whole app at 1.1.0: source, build, runtime, chats, settings.
`_update\old-dist-20261109-175448`	App files of 1.0.0, replaced by the 1.1.0 install.
`_update\old-dist-20261109-180615`	App files of 1.1.0, replaced by the 1.2.0 install.
`_update\old-runtime\`	Claude Code 2.1.312 and Codex 0.166 executables.
`_update\apply-update.log`	Log of each install.
`_update\old-dist-20261110-193553`	App files of 1.2.0, replaced by the 1.3.0 install.
`Backups\XenoStudio-v1.3.0-20261111-212123`	Whole app at 1.3.0, taken before the 1.4.0 work.
`_update\old-dist-20261111-214311`	App files of 1.3.0, replaced by the 1.4.0 install.

To roll back: close XenoStudio and copy a backup's files over `dist\` (leave `dist\data\` in place).

Not yet verified

- Dragging a picture from the desktop into the running app (Codex's note).
- Clicking through the picture UI inside the app by hand: the code paths were tested outside the app.
- The crash log and crash-proof turns: they only run when something actually crashes.
- The Save as… dialog and launching XenoEdit from the workspace, clicked by hand in the installed app.