

EXP NO: 3

DATE: 29/7/25

Model Planning and Building

Aim:

To implement and compare machine learning models (Linear, Polynomial, and SVR) and apply KMeans clustering for data segmentation.

Program:

Step 1: Import Required Libraries

```
import pandas as pd import numpy as np import seaborn as sns import
matplotlib.pyplot as plt from sklearn.model_selection import train_test_split
from sklearn.linear_model import LinearRegression
from sklearn.preprocessing import PolynomialFeatures
from sklearn.svm import SVR from sklearn.pipeline
import Pipeline from sklearn.metrics import mean_absolute_error,
mean_squared_error
```

from sklearn.cluster import KMeans Step 2: Load and Explore the Dataset

```
df = pd.read_csv('Advertising.csv')
```

```
print("\nData Info:") df.info()
```

Step 3: Define Features and Target

```
X = df[['TV', 'Radio', 'Newspaper']]
y = df['Sales']
```

Step 4: Visualize Data Relationships

```
sns.pairplot(df, x_vars=['TV', 'Radio', 'Newspaper'], y_vars='Sales', height=4,
aspect=1, kind='reg') plt.show()
```

Step 5: Split Data into Training and Testing Sets

```
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=0.2,
random_state=42)
```

Step 6: Train Linear Regression Model

```
lr_model = LinearRegression()
lr_model.fit(X_train, y_train) y_pred_lr
= lr_model.predict(X_test)
```

Step 7: Train Polynomial Regression Model

```
poly_pipeline = Pipeline([
    ('poly_features', PolynomialFeatures(degree=2, include_bias=False)),
    ('linear_regression', LinearRegression())
```

```
]
poly_pipeline.fit(X_train, y_train) y_pred_poly
= poly_pipeline.predict(X_test) Step 8: Train
```

Support Vector Regression (SVR) Model

```
svr_model = SVR(kernel='rbf') y_train) y_pred_svr =
svr_model.predict(X_test)
```

Step 9: Evaluate All Models

```
models = {

    'Linear Regression': y_pred_lr,
    'Polynomial Regression': y_pred_poly,
    'Support Vector Regression': y_pred_svr
}
evaluation_results = {}
for name, y_pred in models.items():
    mae = mean_absolute_error(y_test, y_pred)
    mse = mean_squared_error(y_test, y_pred)
    rmse = np.sqrt(mse)
    evaluation_results[name] = {'MAE': mae, 'MSE': mse, 'RMSE': rmse}
print(f"\n---{name}---")
print(f"MAE:{mae:.4f}")
print(f"MSE:{mse:.4f}")
print(f"RMSE:{rmse:.4f}") Step10: Visualize Model
```

Comparison

```
results_df = pd.DataFrame(evaluation_results).T
results_df['RMSE'].plot(kind='bar', figsize=(10, 6))
plt.title('Model Comparison by RMSE')
plt.ylabel('Root Mean Squared Error')
plt.xticks(rotation=0) plt.show()
```

Step 11: Apply K-Means Clustering

```
kmeans = KMeans(n_clusters=3, random_state=42, n_init=10)
df['Cluster'] = kmeans.fit_predict(X) Step 12: Visualize
```

Clusters


```
plt.figure(figsize=(12, 8))
sns.scatterplot(data=df, x='TV', y='Sales', hue='Cluster', palette='viridis',
s=100, alpha=0.7)
plt.title('TV vs Sales by Cluster') plt.show()
```

Output:

```
--- 2. Explore and Preprocess Data ---
```

```
Data Info:  
<class 'pandas.core.frame.DataFrame'>  
RangeIndex: 200 entries, 0 to 199  
Data columns (total 5 columns):  
#   Column      Non-Null Count  Dtype  
---  ---  
0   Unnamed: 0    200 non-null    int64  
1   TV            200 non-null    float64  
2   Radio         200 non-null    float64  
3   Newspaper     200 non-null    float64  
4   Sales         200 non-null    float64  
dtypes: float64(4), int64(1)  
memory usage: 7.9 KB
```

Generating Pair Plot...



```
---
```

```
--- 6. Evaluate Models ---
```

```
--- Linear Regression Metrics ---
```

```
MAE: 1.4608  
MSE: 3.1741  
RMSE: 1.7816
```


```
--- Polynomial Regression Metrics ---
```


```
MAE: 0.5262  
MSE: 0.4129  
RMSE: 0.6426
```

```
--- Support Vector Regression Metrics ---
```

```
MAE: 1.5144  
MSE: 4.0060  
RMSE: 2.0015
```

Generating Model Comparison Plot...





Result:

The models were successfully trained, evaluated, and visualized. K-Means clustering grouped the data into three meaningful clusters based on sales and advertising features.