

Adjusting the screen resolution

Due to the nature of liquid crystal display (LCD) technology, the picture resolution is always fixed. For the best display performance, please set the display to its maximum resolution that is the same with the monitor aspect ratio. This is called "Native Resolution" or maximal resolution – that is, the clearest picture. Lower resolutions are displayed on a full screen through an interpolation circuit. Image blurring across pixel boundaries can occur with the interpolated resolution depending upon the image type and its initial resolution.



To find out the monitor aspect ratio and native resolution of the purchased model, please check the Specification on the website.



- To take full advantage of LCD technology you should select the native resolution setting of your PC screen as described below. Be aware that not all PC video cards provide this resolution value. If yours doesn't, check with the video card manufacturer's website for an updated driver for your particular model PC video card which supports this resolution. Software video drivers are often updated and available for new hardware video resolutions. If necessary, you may need to replace and update the PC video card hardware to be able to support the native resolution of the monitor.
- Depending on the operating system on your PC, different procedures should be followed to adjust the screen resolution. Refer to the help document of your operating system for details.

1. Open **Display Properties** and select the **Settings** tab.

You can open **Display Properties** by right-clicking on the Windows desktop and selecting **Properties** from the pop-up menu.

2. Use the slider in the 'Screen area' section to adjust the screen resolution.

Select the recommended resolution (maximum resolution) then click **Apply**.



If you select some other resolution, be aware that this other resolution is interpolated and may not accurately display the screen image as well as it could do at the native resolution setting.

3. Click **OK** then **Yes**.

4. Close the **Display Properties** window.

If your input source does not provide an image which is the same with the monitor aspect ratio, the displayed image may appear stretched or distorted. To maintain the original aspect ratio, image scaling options can be found in the "Display Mode" adjustment. See the user manual for more information.

Adjusting the screen refresh rate

You don't have to choose the highest possible refresh rate on an LCD display, because it is not technically possible for an LCD display to flicker. The best results are obtained by using the factory modes already set in your computer.



Depending on the operating system on your PC, different procedures should be followed to adjust the screen resolution. Refer to the help document of your operating system for details.

1. Double click the **Display** icon in **Control Panel**.
2. From the **Display Properties** window, select the **Settings** tab and click the **Advanced** button.
3. Select the **Adapter** tab, and select an appropriate refresh rate to match one of the applicable factory modes as listed in the specification table.
4. Click **Change**, **OK**, then **Yes**.
5. Close the **Display Properties** window.

Preset display modes

RD280UG EDID Timing Support							
PC/Video Signal Support		PIP / PBP = OFF and PIP Main Window (Support HDR10 / Support FreeSync)			PIP Sub Window (Support HDR10 / No support FreeSync)		
		Input			Input		
Resolution	Frame Frequency	DisplayPort 1.4	HDMI 2.1	USB-C	DisplayPort 1.4	HDMI 2.1	USB-C
640x480	60	V	V	V	V	V	V
640x480	75	V	V	V	V	V	V
720x400	70	V	V	V	V	V	V
720x480	60	V	V	V	V	V	V
720x576	50	V	V	V	V	V	V
800x600	60	V	V	V	V	V	V
800x600	75	V	V	V	V	V	V
832x624	75	V	V	V	V	V	V
960x2560	60						
960x2560	100						
960x2560	120						
1024x768	60	V	V	V	V	V	V
1024x768	75	V	V	V	V	V	V
1024x768	120				V	V	V
1152x870	75	V	V	V	V	V	V
1280x720	50	V	V	V	V	V	V
1280x720	60	V	V	V	V	V	V
1280x720	120				V	V	V
1280x800	60	V	V	V	V	V	V
1280x960	60	V	V	V	V	V	V
1280x1024	60	V	V	V	V	V	V
1280x1024	75	V	V	V	V	V	V
1280x1024	120				V	V	V
1280x2560	60						
1280x2560	100						
1280x2560	120						
1440x900	60	V	V	V	V	V	V
1600x900	60	V	V	V	V	V	V
1680x1050	60	V	V	V	V	V	V
1920x1080	24	V	V	V	V	V	V
1920x1080	25	V	V	V	V	V	V
1920x1080	30	V	V	V	V	V	V
1920x1080	50	V	V	V	V	V	V
1920x1080	60	V	V	V	V	V	V
1920x1080	100	V	V	V	V	V	V
1920x1080	120	V	V	V	V	V	V
1920x1200	60	V	V	V			

RD280UG EDID Timing Support							
PC/Video Signal Support		PIP / PBP = OFF and PIP Main Window (Support HDR10 / Support FreeSync)			PIP Sub Window (Support HDR10 / No support FreeSync)		
		Input			Input		
Resolution	Frame Frequency	DisplayPort 1.4	HDMI 2.1	USB-C	DisplayPort 1.4	HDMI 2.1	USB-C
1920x2560	60						
1920x2560	100						
1920x2560	120						
2560x1440	60	V	V	V			
2560x1440	120	V	V	V			
2560x1600	60	V	V	V			
2560x2560	60						
2560x2560	100						
2560x2560	120						
2880x2560	60						
2880x2560	100						
2880x2560	120						
3840x2160	24	V	V	V			
3840x2160	25	V	V	V			
3840x2160	30	V	V	V			
3840x2160	50	V	V	V			
3840x2160	60	V	V	V			
3840x2160	120	V	V	V			
3840x2560	50	V	V	V			
3840x2560	60	V	V	V			
3840x2560	100	V	V	V			
3840x2560	120	V	V	V			

RD280UG EDID Timing Support				
PC/Video Signal Support		PBP (1:1) Evenly split screen (1920x2560) (Support HDR10/ No support FreeSync)		
		Input		
Resolution	Frame Frequency	DisplayPort 1.4	HDMI 2.1	USB-C
640x480	60	V	V	V
640x480	75	V	V	V
720x400	70	V	V	V
720x480	60	V	V	V
720x576	50	V	V	V
800x600	60	V	V	V
800x600	75	V	V	V
832x624	75	V	V	V
960x2560	60			
960x2560	100			
960x2560	120			
1024x768	60	V	V	V
1024x768	75	V	V	V
1024x768	120			
1152x870	75	V	V	V
1280x720	50	V	V	V
1280x720	60	V	V	V
1280x720	120			
1280x800	60	V	V	V
1280x960	60	V	V	V
1280x1024	60	V	V	V
1280x1024	75	V	V	V
1280x1024	120			
1280x2560	60			
1280x2560	100			
1280x2560	120			
1440x900	60	V	V	V
1600x900	60	V	V	V
1680x1050	60	V	V	V
1920x1080	24	V	V	V
1920x1080	25	V	V	V
1920x1080	30	V	V	V
1920x1080	50	V	V	V
1920x1080	60	V	V	V
1920x1080	100	V	V	V
1920x1080	120	V	V	V
1920x1200	60	V	V	V
1920x2560	60	V	V	V
1920x2560	100	V	V	V

RD280UG EDID Timing Support				
PC/Video Signal Support		PBP (1:1) Evenly split screen (1920x2560) (Support HDR10/ No support FreeSync)		
		Input		
Resolution	Frame Frequency	DisplayPort 1.4	HDMI 2.1	USB-C
1920x2560	120	V	V	V

RD280UG EDID Timing Support							
PC/Video Signal Support		PBP (2:1) - The bigger screen (2560x2560) (Support HDR10/ No support FreeSync)			PBP (2:1) - The smaller screen (1280x2560) (Support HDR10/ No support FreeSync)		
		Input			Input		
Resolution	Frame Frequency	DisplayPort 1.4	HDMI 2.1	USB-C	DisplayPort 1.4	HDMI 2.1	USB-C
640x480	60	V	V	V	V	V	V
640x480	75	V	V	V	V	V	V
720x400	70	V	V	V	V	V	V
720x480	60	V	V	V	V	V	V
720x576	50	V	V	V	V	V	V
800x600	60	V	V	V	V	V	V
800x600	75	V	V	V	V	V	V
832x624	75	V	V	V	V	V	V
960x2560	60						
960x2560	100						
960x2560	120						
1024x768	60	V	V	V			
1024x768	75	V	V	V			
1024x768	120						
1152x870	75	V	V	V			
1280x720	50	V	V	V			
1280x720	60	V	V	V			
1280x720	120						
1280x800	60	V	V	V			
1280x960	60	V	V	V			
1280x1024	60	V	V	V			
1280x1024	75	V	V	V			
1280x1024	120						
1280x2560	60				V	V	V
1280x2560	100				V	V	V
1280x2560	120				V	V	V
1440x900	60	V	V	V			
1600x900	60	V	V	V			
1680x1050	60	V	V	V			
1920x1080	24	V	V	V			
1920x1080	25	V	V	V			
1920x1080	30	V	V	V			
1920x1080	50	V	V	V			
1920x1080	60	V	V	V			
1920x1080	100	V	V	V			
1920x1080	120	V	V	V			
1920x1200	60	V	V	V			
1920x2560	60						

RD280UG EDID Timing Support							
PC/Video Signal Support		PBP (2:1) - The bigger screen (2560x2560) (Support HDR10/ No support FreeSync)			PBP (2:1) - The smaller screen (1280x2560) (Support HDR10/ No support FreeSync)		
		Input			Input		
Resolution	Frame Frequency	DisplayPort 1.4	HDMI 2.1	USB-C	DisplayPort 1.4	HDMI 2.1	USB-C
1920x2560	100						
1920x2560	120						
2560x1440	60	V	V	V			
2560x1440	120	V	V	V			
2560x1600	60						
2560x2560	60	V	V	V			
2560x2560	100	V	V	V			
2560x2560	120	V	V	V			

RD280UG EDID Timing Support							
PC/Video Signal Support		PBP (3:1) - The bigger screen (2880x2160) (Support HDR10/ No support FreeSync)			PBP (3:1) - The smaller screen (960x2160) (Support HDR10/ No support FreeSync)		
		Input			Input		
Resolution	Frame Frequency	DisplayPort 1.4	HDMI 2.1	USB-C	DisplayPort 1.4	HDMI 2.1	USB-C
640x480	60	V	V	V	V	V	V
640x480	75	V	V	V	V	V	V
720x400	70	V	V	V	V	V	V
720x480	60	V	V	V	V	V	V
720x576	50	V	V	V	V	V	V
800x600	60	V	V	V	V	V	V
800x600	75	V	V	V	V	V	V
832x624	75	V	V	V	V	V	V
960x2560	60				V	V	V
960x2560	100				V	V	V
960x2560	120				V	V	V
1024x768	60	V	V	V			
1024x768	75	V	V	V			
1024x768	120						
1152x870	75	V	V	V			
1280x720	50	V	V	V			
1280x720	60	V	V	V			
1280x720	120						
1280x800	60	V	V	V			
1280x960	60	V	V	V			
1280x1024	60	V	V	V			
1280x1024	75	V	V	V			
1280x1024	120						
1280x2560	60						
1280x2560	100						
1280x2560	120						
1440x900	60	V	V	V			
1600x900	60	V	V	V			
1680x1050	60	V	V	V			
1920x1080	24	V	V	V			
1920x1080	25	V	V	V			
1920x1080	30	V	V	V			
1920x1080	50	V	V	V			
1920x1080	60	V	V	V			
1920x1080	100	V	V	V			
1920x1080	120	V	V	V			
1920x1200	60	V	V	V			
1920x2560	60						

RD280UG EDID Timing Support							
PC/Video Signal Support		PBP (3:1) - The bigger screen (2880x2160) (Support HDR10/ No support FreeSync)			PBP (3:1) - The smaller screen (960x2160) (Support HDR10/ No support FreeSync)		
		Input			Input		
Resolution	Frame Frequency	DisplayPort 1.4	HDMI 2.1	USB-C	DisplayPort 1.4	HDMI 2.1	USB-C
1920x2560	100						
1920x2560	120						
2560x1440	60	V	V	V			
2560x1440	120	V	V	V			
2560x1600	60						
2560x2560	60						
2560x2560	100						
2560x2560	120						
2880x2560	60	V	V	V			
2880x2560	100	V	V	V			
2880x2560	120	V	V	V			



- To obtain the best image quality, refer to the above table to set the timing and the resolution of the input source.
- To make sure the above timing works, check the compatibility and specifications of your graphic card first.
- The timing needs to work with the specified input ports. Available input ports and signals vary by model.

Video input

Color space	YCbCr 4:2:0											
Max. bit	8 bit				10 bit				12 bit			
Frame frequency	24, 25, 30	50, 60	100	120	24, 25, 30	50, 60	100	120	24, 25, 30	50, 60	100	120
HDMI		v(*)		v(*)		v(*)		v(*)		v(*)		v(*)
DisplayPort		v(*)		v(*)		v(*)		v(*)		v(*)		v(*)
USB-C™ (DP Alt mode)		v(*)		v(*)		v(*)		v(*)		v(*)		v(*)

Color space	YCbCr 4:2:2											
Max. bit	8 bit				10 bit				12 bit			
Frame frequency	24, 25, 30	50, 60	100	120	24, 25, 30	50, 60	100	120	24, 25, 30	50, 60	100	120
HDMI	v	v	v	v	v	v	v	v	v	v	v	v
DisplayPort	v	v	v	v	v	v	v	v	v	v	v	v
USB-C™ (DP Alt mode)	v	v	v	v	v	v	v	v	v	v	v	v

Color space	YCbCr 4:4:4 / RGB 4:4:4											
Max. bit	8 bit				10 bit				12 bit			
Frame frequency	24, 25, 30	50, 60	100	120	24, 25, 30	50, 60	100	120	24, 25, 30	50, 60	100	120
HDMI	v	v	v	v	v	v	v	v	v	v	v	v
DisplayPort	v	v	v	v	v	v	v	v	v	v	v	v
USB-C™ (DP Alt mode)	v	v	v	v	v	v	v	v	v	v	v	v



- The monitor receives 12-bit data and displays 10-bit colors.
- (*): Only support for 3840x2160.