Comprehensive Analysis of Privacy-Preserving Architectures and Adversarial Mitigation Strategies in Federated Learning Systems

The paradigm of machine learning has undergone a fundamental transformation with the advent of Federated Learning (FL), moving away from the risky centralization of data toward a decentralized model of collaborative training. Originally proposed to address the growing tension between the data requirements of deep learning and the stringent mandates of privacy regulations such as the General Data Protection Regulation (GDPR), FL ensures that raw data remains resident on local devices.[1] However, as the field has matured, it has become evident that the mere decentralization of data does not constitute a complete privacy solution. The exchange of model gradients and weight updates serves as a potent side-channel, often leaking as much information as the raw data itself.[4] Consequently, the development of state-of-the-art (SOTA) privacy-preserving methods—including differential privacy, homomorphic encryption, secure multi-party computation, and trusted execution environments—has become the primary frontier in securing the next generation of artificial intelligence.[6]

The Adversarial Landscape of Distributed Learning

Understanding the defense mechanisms requires a rigorous deconstruction of the attack vectors they are designed to neutralize. In a federated environment, the threat model assumes a spectrum of adversaries, from "honest-but-curious" central servers to fully malicious clients aiming to corrupt the global model or extract sensitive participant details.[9]

Information Disclosure via Gradient Leakage

Gradient leakage, or data reconstruction from gradients, is perhaps the most direct threat to the core promise of FL. The mechanism involves an adversary—typically the central server or an eavesdropper—observing the gradient updates $g = \nabla_w \mathcal{L}(w, x)$ sent by a client.[5] By initializing a dummy input x' and dummy label y', the attacker can iteratively minimize the distance between the dummy gradient g' and the observed gradient g using optimization techniques.[13]

The evolution of these attacks has followed the increasing complexity of neural architectures. Early Deep Leakage from Gradients (DLG) and its variant iDLG focused on recovering small

batches of image data.[4] Modern SOTA methods have expanded this capability significantly. The FILM (Feature-Independent Leakage Method) and DAGER (Data Aggregation and Gradient Evaluation) approaches utilize search-based optimization to scale reconstruction to batch sizes of 128, a significant jump from the batch limits of 1 to 8 seen in earlier methods.[4] In the domain of Large Language Models (LLMs), FedSpy-LLM exploits the rank deficiency and subspace structure of gradients to extract specific tokens from fine-tuned models, even when the gradients are highly compressed.[4] This implies that the transition to larger models does not inherently provide more privacy; rather, the increased parameter space may offer more "bits" of information for a sophisticated attacker to exploit.[4]

Overfitting as a Proxy for Membership Inference

Membership Inference Attacks (MIAs) exploit the fundamental gap between a model's performance on seen training data versus unseen test data. In FL, this risk is heightened because the adversary can observe the model's evolution over multiple training rounds.[15] A sample is identified as a training member if the model's prediction on that sample is disproportionately confident or if its loss is significantly lower than average.[15]

State-of-the-art MIAs, such as DSMIM-MIA, have moved beyond simple thresholding to more sophisticated "difficulty calibration." By distilling the target model into multiple shadow models, the attacker can quantify how "difficult" a sample is to learn across a general distribution and then subtract this bias from the target model's output.[17] Another advanced approach involves meta-feature engineering, where an attacker queries the model with a sample and extracts an 8-dimensional feature vector consisting of membership probabilities from diverse estimators like Random Forests, Neural Networks, and Gradient Boosting models, as well as the sample's cross-entropy loss.[16]

Attack Category	Specific SOTA Method	Mechanism of Breach	Data Modality Impacted
Gradient Leakage	FILM / DAGER	Optimization of dummy inputs to match observed gradients.[4]	High-resolution Images [13]
Gradient Leakage	FedSpy-LLM	Exploitation of rank deficiency in LLM gradients.[4]	Textual Sequences / Tokens [4]
Membership	DSMIM-MIA	Knowledge distillation and	Structured and Unstructured Data

Inference		difficulty calibration.[17]	[17]
Membership Inference	Meta-Classifier MIA	Meta-learning on multi-estimator outputs and loss features.[16]	Genomics / Medical Records [16]
Property Inference	FedMeta-CTGAN	Deduce dataset properties (e.g., race) from gradient drift.[18]	Flight Operations / Demographics [18]

Backdoor Attacks and Model Poisoning

Model integrity is compromised when malicious clients attempt to insert "backdoors" into the global model. These are specific triggers—such as a specific pixel pattern in an image or a keyword in a sentence—that cause the model to output an adversary-chosen label.[10] The challenge in FL is that a small fraction of malicious clients (as low as 20-30%) can effectively poison the model if their updates are sufficiently "boosted" to survive the aggregation process.[11]

SOTA backdoor attacks like 3DFed utilize an adaptive indicator mechanism. The attacker monitors whether the server has accepted its previous malicious update and then dynamically optimizes the next update to stay just within the boundaries of the server's anomaly detection filters.[10] Furthermore, Distributed Backdoor Attacks (DBA) split a single trigger into multiple components, with each malicious client injecting only one piece.[10] This reduces the statistical outlier-ness of any single update, making conventional Byzantine-robust aggregation methods like Multi-KRUM or Trimmed Mean less effective.[10]

Differential Privacy: Mathematical Foundations and SOTA Implementations

Differential Privacy (DP) provides a formal, quantifiable guarantee of privacy by ensuring that the inclusion or exclusion of any single data point does not significantly alter the probability distribution of the model's output.[9] The (ϵ, δ)-DP framework defines the privacy budget ϵ, where smaller values signify stronger protection.[9]

Local vs. Central Differential Privacy

In FL, DP is typically applied at two levels. Central Differential Privacy (CDP) assumes a trusted server that adds noise to the aggregated updates before broadcasting the global model to

clients.[12] This protects against external eavesdroppers but not a curious server. Conversely, Local Differential Privacy (LDP) requires clients to perturb their updates before transmission.[12] While LDP offers the strongest protection against an untrusted server, it significantly degrades model accuracy because the noise added by each client compounds during aggregation.[12]

Advanced Noise Injection and Adaptive Clipping

The primary trade-off in DP is the utility-privacy balance. Standard implementations use fixed clipping thresholds C for gradients, which can lead to high information loss if C is too small, or excessive noise if C is too large.[9] SOTA methods like DP-FedACN (Adaptive gradient Clipping based on gradient Norm) address this by calculating a decay rate for the clipping threshold based on the overall trend of gradient changes across training rounds.[23] This allows the model to preserve more signal in the early stages of training and apply more stringent clipping as the model converges.[23]

For personalized settings, DP-Ditto extends the concept of DP to meta-learning, where the goal is to find a global model that can be quickly adapted to local data.[24] It analyzes the convergence upper bound under the constraints of a privacy budget ϵ, helping to derive the optimal number of global aggregations to maximize accuracy while ensuring fairness across heterogeneous clients.[24]

DP Method	Target Problem	Core Mathematical/Algorithmic Innovation
DP-FedAvg	Base Privacy	Standard Gaussian noise injection with fixed C.[9]
DP-FedACN	Accuracy Loss	Adaptive decay rate for clipping threshold based on norm trends.[23]
DP-Ditto	Personalization	Joint optimization for convergence, fairness, and (ϵ, δ)-DP.[24]
FedCRAP	Sparse Data Leakage	Strategic perturbation of high-information-density

		pixels guided by gradients.[13]
FedEM	Utility-Privacy Gap	Structured perturbations embedded in the client data space rather than gradient space.[13]

The Impact of DP on Convergence and Fairness

The addition of noise $\sigma \geq C\sqrt{2\ln(1.25/\delta)}/\epsilon$ introduces variance that can lead to unstable training.[9] Empirical findings indicate that under DP, models often require significantly more communication rounds to reach the same level of accuracy as non-private models. For the MNIST dataset, a 10-client setup requires 50 rounds without DP, but with DP ($\epsilon \approx 10 - 100$), accuracy drops from 95% to approximately 75%, and convergence may be entirely lost in non-i.i.d. scenarios like FEMNIST.[9] This "utility tax" is particularly heavy on small or highly skewed datasets, potentially rendering the model nonviable for medical or industrial applications where precision is paramount.[9]

Cryptographic Security: Homomorphic Encryption and SMPC

Cryptographic methods provide a way to achieve privacy without the stochastic degradation inherent in DP. These techniques ensure that the central server aggregates updates without ever "seeing" the plaintext values.[3]

Homomorphic Encryption (HE) Mechanisms

Homomorphic Encryption allows mathematical operations to be performed directly on ciphertext. In FL, clients encrypt their model updates $Enc(x_i)$, and the server computes the aggregate $Enc(\sum x_i)$.[1] SOTA implementations use schemes like CKKS (Cheon-Kim-Kim-Song), which is specifically designed for approximate arithmetic on floating-point numbers, making it highly suitable for neural network weights.[3]

However, HE is computationally expensive. Fully Homomorphic Encryption (FHE) can be orders of magnitude slower than plaintext operations, often requiring dedicated hardware or specialized libraries to be practical.[6] To mitigate this, hybrid architectures like the one proposed in the cloud-edge-end framework use HE only for "shallow" model training on edge servers, while using more efficient secret sharing for "deep" model training on the cloud.[7] This tiered approach can reduce computational overhead by 20-30% compared to monolithic HE

systems.[7]

Secure Multi-Party Computation (SMPC)

SMPC splits data into "shares" distributed among multiple non-colluding servers. No single server can reconstruct the original update, but they can collectively compute the aggregate.[6] While SMPC is generally faster than HE for computation, it requires significant communication bandwidth between the participating servers, creating a network bottleneck.[2]

The GHEFL method combines HE with grouping strategies to validate updates, preventing the server from maliciously stealing privacy data or performing biased aggregations.[25] Meanwhile, the FedSP framework offers a lightweight alternative by using an adaptive clustering strategy during secure aggregation to handle the inconsistencies caused by statistical heterogeneity in participant data.[25]

Cryptographic Protocol	Accuracy Impact	Primary Constraint	Deployment Scenario
CKKS (HE)	None	CPU Intensive; High modular arithmetic load.[3]	High-privacy Cloud-Edge offloading [7]
Additive Secret Sharing	None	Network Bandwidth; Multi-server requirement.[21]	Institutional collaboration (e.g., Banks) [5]
CP-ABE	None	Complexity of attribute-based access control.[25]	Secure Internet of Medical Things (IoMT) [25]
GHEFL	None	Grouping overhead and validation logic.[25]	Malicious Server Prevention [25]

Architectural Integrity: Blockchain and Trusted Execution Environments

A major vulnerability in traditional FL is the "Single Point of Failure" (SPOF) represented by the central parameter server. If the server is compromised or goes offline, the entire training

process is halted or corrupted.[21]

Blockchain-Enabled Federated Learning (BCFL)

Blockchain replaces the central server with a decentralized, immutable ledger. Every update is recorded as a transaction, providing traceability and auditability.[26] Smart contracts can automate the aggregation process and implement "reputation scores" to identify and exclude malicious nodes.[25]

The impact of blockchain on performance is non-trivial. Consensus mechanisms and the overhead of recording every update on a ledger typically increase training time by 4% to 24%.[30] However, the security gains are significant: BCFL systems are inherently resilient to Byzantine failures and can provide transparent incentive mechanisms, such as rewards proportional to the quality of training samples provided.[26] Frameworks like FedChain further optimize this by introducing clustered semi-asynchronous aggregation, allowing different groups of clients to update at their own pace without stalling the entire network.[27]

Trusted Execution Environments (TEE)

TEEs, such as Intel SGX and ARM TrustZone, provide a hardware-isolated "enclave" within the processor where code and data are protected from the host operating system and even physical attackers.[8] In Confidential Federated Learning (CFL), the aggregation logic is moved inside an enclave, ensuring that the gradients are decrypted only within the secure hardware boundary.[33]

The performance of TEEs is limited by "enclave transitions" and memory constraints. For example, switching between the enclave and the normal operating system (Ecall/Ocall) can take over 14,000 CPU cycles, compared to just 150 cycles for a standard system call.[8] Furthermore, early versions of SGX were limited to 93 MB of protected memory (the Enclave Page Cache), which is insufficient for many large-scale machine learning models, forcing slow and costly page swapping.[8] Newer VM-based TEEs, like Intel TDX (Trust Domain eXtensions), offer a higher level of isolation by encrypting the entire virtual machine, significantly reducing the porting effort and providing more flexible resource allocation.[32]

Interaction with Local Computer Resources

The feasibility of privacy-preserving FL depends on the local resource budget—CPU, memory, and energy—of the participating devices, which are often resource-constrained IoT nodes or mobile devices.[8]

CPU and Latency Benchmarks

Computation time is the sum of local training time and the overhead of the privacy mechanism. DP is the most lightweight, adding minimal arithmetic operations for clipping and noise

generation.[9] In contrast, HE and TEE-based solutions place a heavy load on the processor. Benchmarks on real IoT hardware, such as Raspberry Pi and Jetson Nano, show that while increased network depth provides accuracy gains, it exponentially increases task latency.[37] A lightweight model like MobileNetV3-Small can finish an inference task in 1001 seconds on the CIFAR-100 dataset, while a more complex ConvNeXt-Small model requires over 21,096 seconds.[37]

Memory Footprint and Out-of-Memory (OOM) Risks

Memory usage is a hard constraint for small-scale devices. Analysis of Meta-Continual Learning (Meta-CL) on devices ranging from 512 MB to 4 GB of RAM revealed that up to 50% of SOTA methods cause OOM failures on sub-1 GB devices.[34] Memory usage for standard CNN architectures is relatively consistent, ranging from 5.84 GB to 7.09 GB, which underscores the need for "lightweight" and "edge-optimized" architectures like EfficientNet-B0V2 or NASNet-Mobile in federated settings.[37]

Energy Consumption and Sustainability

Energy is the most critical constraint for battery-powered devices. The "useful work per unit of energy" (Task/J) is the primary metric for sustainability.

1. **DP Impact**: Enabling DP on a client increases energy consumption by up to 300% due to the extra computational steps and the increased number of communication rounds needed for convergence.[36]
2. **Hardware Efficiency**: Specialized hardware can drastically change the energy profile. Implementing federated learning on an FPGA platform can achieve real-time performance at just 18.7W, which is 4.2x more energy-efficient than typical GPU-based solutions that consume between 150W and 300W.[38]
3. **Model Selection**: The choice of neural network architecture is the largest factor in energy usage. MobileNetV3-Small consumes approximately 124,356 J for training on CIFAR-100, while ConvNeXt-Small consumes 2,777,480 J—a nearly 22-fold increase for a marginal gain in accuracy.[37]

Comprehensive Relationship and Trade-off Matrix

The following table summarizes the systemic interactions between privacy mechanisms and model/system performance metrics.

Privacy Method	SOTA Implementation Example	Accuracy Impact	Convergence Speed	CPU Usage	Memory Usage	Energy Impact	Primary Attack Vector Neutralized
Differential Privacy (DP)	**DP-FedACN** [23]	Moderate to High (Noise dependent)	Significantly Slower	Low	Low	Moderate (+300%) [36]	Membership Inference, Reconstruction [9]
Homomorphic Encryption (HE)	**CKKS / GHEFL** [3]	None	Very Slow (Compute)	Very High	High	High	Gradient Leakage, Curiously Honest Server [6]
Secure Aggregation (SMPC)	**e-SeaFL / FedSP** [22]	None	Slower (Network latency)	Moderate	Moderate	Moderate	Server-side Model Inversion [6]
Trusted Execution (TEE)	**Intel SGX / TDX** [32]	None	Near-Native	High (Transitions)	High (EPC limited)	Moderate	Malicious OS, Physical Tampering [8]
Blockchain	**FedChain / BCFL** [27]	Minimal	Slower (Consensus)	Moderate	Moderate	High (Cumulative)	Single Point of Failure, Byzantine Clients

							[26]
Robust Aggregation	**MARS / DnC** [10]	Minimal (Filters outliers)	Stable	Low	Low	Low	Backdoors, Data/Model Poisoning [10]
Knowledge Distillation	**DSMIM-MIA** [17]	High (Used for Attack)	N/A	High (Shadow models)	High	High	**Target:** MIA effectiveness [17]
Architectural Split	**VAEFL** [5]	Minimal	Stable	Moderate	Moderate	Moderate	Gradient Leakage [5]

Synthesis of Robust Defense Strategies

The multi-faceted nature of attacks in federated learning implies that no single defense is a panacea. A truly resilient system must employ a "defense-in-depth" strategy, combining multiple techniques to address the vulnerabilities at different stages of the training lifecycle.[1]

Combating Malicious Updates: A Multi-Metric Approach

To defend against malicious updates and poisoning, simply filtering by the magnitude of the update is no longer sufficient, as SOTA attacks like DBA hide within the benign distribution.[10] The most effective defenses now utilize clustering analysis on the gradients of the output layer. Because the primary impact of label-flipping and backdoor attacks is observed in the neurons associated with the attacked category, clustering algorithms using the Gap Statistic can effectively isolate malicious updates into distinct groups.[39] Furthermore, methods like MARS track "backdoor energy" at the neuron level, using Wasserstein distance-based clustering to identify backdoor models even in collusion-heavy environments.[10]

Addressing the Convergence-Privacy Paradox

One of the most profound insights from recent research is that privacy and fairness are often in conflict. The noise added by DP disproportionately affects the minority classes in a dataset, potentially leading to models that are private but biased.[24] To address this, Hierarchical Federated Edge Learning (HFEL) frameworks are emerging. By performing cluster-level aggregation before global aggregation and using lightweight, adaptive DP mechanisms, HFEL

achieves a 31.8% improvement in model accuracy and reduces communication overhead by 36.2% compared to standard flat FL architectures.[40]

The Role of Hardware-Software Co-Design

As model sizes continue to grow, the reliance on purely software-based privacy mechanisms will likely encounter a "scalability wall" due to the excessive energy and time overhead.[35] The future of privacy-preserving FL lies in hardware-software co-design. This includes the use of FPGAs for energy-efficient secure computation, the adoption of confidential GPUs to allow enclaves to access massive parallel processing power, and the integration of 6G-ready blockchain systems for real-time auditability in high-velocity IoT environments.[25]

In conclusion, the evolution of privacy-preserving federated learning is a race between increasingly sophisticated adversarial methods and robust, resource-aware defensive architectures. While gradient leakage and membership inference pose existential threats to data confidentiality, the combination of advanced differential privacy accounting, cryptographic secure aggregation, and hardware-based isolation offers a viable path forward. The successful deployment of these systems in real-world scenarios—from smart health systems to industrial automation—will depend on the ability of researchers to maintain a fine-grained trade-off between the mathematical rigor of the privacy guarantee and the practical constraints of accuracy, latency, and energy consumption.[2]

Works cited

1. (PDF) A Survey of Federated Learning Privacy Preservation ..., accessed April 19, 2026, https://www.researchgate.net/publication/392460028_A_Survey_of_Federated_Learning_Privacy_Preservation_Techniques_for_Malicious_Behavior_Detection
2. Balancing privacy and performance in federated learning - DiVA portal, accessed April 19, 2026, https://www.diva-portal.org/smash/get/diva2:1872879/FULLTEXT01.pdf
3. A Review of Research on Secure Aggregation for Federated Learning, accessed April 19, 2026, https://www.mdpi.com/1999-5903/17/7/308
4. FedSpy-LLM: Towards Scalable and Generalizable Data Reconstruction Attacks from Gradients on LLMs - arXiv, accessed April 19, 2026, https://arxiv.org/html/2604.06297v1
5. VAEFL: Integrating variational autoencoders for privacy preservation and performance retention in federated learning | Security and Safety (S&S), accessed April 19, 2026, https://sands.edpsciences.org/articles/sands/full_html/2024/01/sands20230029/sands20230029.html
6. Privacy in Federated Learning | IntechOpen, accessed April 19, 2026, https://www.intechopen.com/chapters/1190994
7. Privacy-Preserving Machine Learning in Cloud-Edge-End Collaborative

Environments | Request PDF - ResearchGate, accessed April 19, 2026, https://www.researchgate.net/publication/387297861_Privacy-Preserving_Machine_Learning_in_Cloud-Edge-End_Collaborative_Environments
8. Analysis and Evaluation of Intel Software Guard Extension-Based ..., accessed April 19, 2026, https://www.mdpi.com/1999-5903/17/1/32
9. DP-FL: Trade-offs, Methods & Benchmarks - Emergent Mind, accessed April 19, 2026, https://www.emergentmind.com/topics/differential-privacy-for-federated-learning
10. MARS: A Malignity-Aware Backdoor Defense in Federated Learning - arXiv, accessed April 19, 2026, https://arxiv.org/html/2509.20383v1
11. Fighting Back Against Attacks in Federated Learning | Towards Data Science, accessed April 19, 2026, https://towardsdatascience.com/fighting-back-against-attacks-in-federated-learning/
12. Does Differential Privacy Really Protect Federated Learning From ..., accessed April 19, 2026, https://www.computer.org/csdl/journal/tm/2024/12/10568968/1Y2gZH8n7pK
13. FEDCRAP: FEDERATED CRITICAL-REGION-AWARE PERTURBATIONS FOR REFINED PRIVACY-PRESERVING FEDERATED LEARNING - OpenReview, accessed April 19, 2026, https://openreview.net/pdf/6486d36ec125e261f07426b5fca377b9587b99dc.pdf
14. The Gradient Puppeteer: Adversarial Domination in Gradient Leakage Attacks Through Model Poisoning - Tianwei Zhang, accessed April 19, 2026, https://tianweiz07.github.io/Papers/25-tifs-4.pdf
15. Poisoning as a Post-Protection: Mitigating Membership Privacy Leakage From Gradient and Prediction of Federated Models, accessed April 19, 2026, https://www.chenwang.net.cn/publications/P2-Protection-TDSC25.pdf
16. Evaluating Differential Privacy Against Membership Inference in Federated Learning: Insights from the NIST Genomics Red Team Challenge - arXiv, accessed April 19, 2026, https://arxiv.org/html/2604.12737v1
17. Optimizing membership inference attacks against low self-influence samples by distilled shadow models and inference models - PeerJ, accessed April 19, 2026, https://peerj.com/articles/cs-3269/
18. Defend Against Property Inference Attack for Flight Operations Data Sharing in FedMeta Framework - MDPI, accessed April 19, 2026, https://www.mdpi.com/2226-4310/12/1/41
19. NeurIPS Poster Privacy Backdoors: Enhancing Membership Inference through Poisoning Pre-trained Models, accessed April 19, 2026, https://neurips.cc/virtual/2024/poster/95643
20. DABD: Direction Alignment–Based Backdoor Defense with Sign Consensus in Federated Learning - ResearchGate, accessed April 19, 2026, https://www.researchgate.net/publication/401669245_DABD_Direction_Alignment-Based_Backdoor_Defense_with_Sign_Consensus_in_Federated_Learning
21. A Verifiable, Privacy-Preserving, and Poisoning Attack-Resilient Federated

Learning Framework - MDPI, accessed April 19, 2026, https://www.mdpi.com/2504-2289/9/4/85
22. “Balancing Accuracy and Privacy: The Role of Differential Privacy and Secure Aggregation in Federated Learning” | by Siddhartha Pramanik | Medium, accessed April 19, 2026, https://medium.com/@siddharthapramanik771/balancing-accuracy-and-privacy-the-role-of-differential-privacy-and-secure-aggregation-in-14e6d064478f
23. Exploring the Privacy-Accuracy Trade-off Using Adaptive Gradient Clipping in Federated Learning - Temple CIS, accessed April 19, 2026, https://cis.temple.edu/~jiewu/research/publications/Publication_files/TNSE-Final%20Files.pdf
24. Convergence-Privacy-Fairness Trade-Off in Personalized Federated Learning - Macquarie University, accessed April 19, 2026, https://researchers.mq.edu.au/files/496106449/496086963.pdf
25. A survey on privacy-preserving federated learning against poisoning ..., accessed April 19, 2026, https://www.semanticscholar.org/paper/0f7ca71506ecaeb22e30fb22c441187a63b7a87a
26. Blockchain-Based Federated Learning: A Survey and New Perspectives - MDPI, accessed April 19, 2026, https://www.mdpi.com/2076-3417/14/20/9459
27. A Blockchain System for Clustered Federated Learning with Peer-to-Peer Knowledge Transfer - VLDB Endowment, accessed April 19, 2026, https://www.vldb.org/pvldb/vol17/p966-hu.pdf
28. Blockchain-Enabled Federated Learning: A Survey on System Design, Key Challenges, and Future Directions - MDPI, accessed April 19, 2026, https://www.mdpi.com/2079-9292/15/8/1572
29. Blockchain for federated learning toward secure distributed machine learning systems: a systemic survey - PMC, accessed April 19, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC8605788/
30. A study on the Impact of Blockchain to Secure Federated Learning, accessed April 19, 2026, https://thesis.unipd.it/handle/20.500.12608/82528
31. Trusted execution environment - Wikipedia, accessed April 19, 2026, https://en.wikipedia.org/wiki/Trusted_execution_environment
32. Trusted Execution Environment (TEE) - Azure - Microsoft Learn, accessed April 19, 2026, https://learn.microsoft.com/en-us/azure/confidential-computing/trusted-execution-environment
33. A performance analysis of VM-based Trusted Execution Environments for Confidential Federated Learning This work has been partly supported by the Spoke ”FutureHPC & BigData” of the ICSC – Centro Nazionale di Ricerca in ”High Performance Computing, Big Data and Quantum Computing”, funded by European Union – NextGenerationEU, and by the Horizon2020 RIA EPI project - arXiv, accessed April 19, 2026, https://arxiv.org/html/2501.11558v1
34. MetaCLBench: Meta Continual Learning Benchmark on Resource-Constrained Edge Devices - arXiv, accessed April 19, 2026, https://arxiv.org/html/2504.00174v2

35. Comparative Study on Energy Consumption of Neural Networks by Scaling of Weight-Memory Energy Versus Computing Energy for Implementing Low-Power Edge Intelligence - MDPI, accessed April 19, 2026, https://www.mdpi.com/2079-9292/14/13/2718
36. Federated Computing Systems In The Context of ... - mediaTUM, accessed April 19, 2026, https://mediatum.ub.tum.de/doc/1729060/57j9tmm1dgjgcvo3300gbw0bu.Ren%C3%A9%20Karsten%20Schwermer%20final.pdf
37. Towards Sustainable AI: Benchmarking Energy Efficiency of Deep ..., accessed April 19, 2026, https://www.mdpi.com/2078-2489/17/4/380
38. A Hardware-Accelerated Federated Learning With Intuitionistic Fuzzy Security Measures for AI Adaptive Image Computing - IEEE Xplore, accessed April 19, 2026, https://ieeexplore.ieee.org/iel8/6287639/10820123/11248855.pdf
39. A defense method against multi-label poisoning attacks in federated learning - PMC, accessed April 19, 2026, https://pmc.ncbi.nlm.nih.gov/articles/PMC12274368/
40. (PDF) Edge computing and federated learning for privacy-preserving IoT analytics, accessed April 19, 2026, https://www.researchgate.net/publication/398378132_Edge_computing_and_federated_learning_for_privacy-preserving_IoT_analytics