

Title

Guido Zuidhof

Supervisors:

Radboud Universiteit Nijmegen

`guido.zuidhof@student.ru.nl`

December 15, 2014

Abstract

1 Introduction

1.1 Cognitive load

1.2 Physiological response to cognitive load

How a human body responds to cognitive load/stress.

1.3 Determining cognitive load

How this cognitive load could be determined, i.e. by measurement.

1.3.1 Measurement of physiological response

Measuring heart rate, breathing, eeg, gsr, etc.

With an increasing variety in consumer

1.3.2 Classification

How sense can be made from this data

1.3.3 Applications

How this can be used.

1.4 Research aim

Using features extracted from GSR data to determine cognitive load, data gathered from experiment.

2 Methods

2.1 Experiment

The experiment is mostly based on the arithmetic task experiment conducted by Nourbakhsh et al., `_meer uitleg todo_`

2.1.1 Apparatus

The task was displayed in a 15.6" laptop screen, input was given using a standard computer mouse. Two galvanic skin response sensors were used in this experiment. The participants wore both at the same time on the left arm.

2.1.2 Participants

Six participants took part in this experiment, five male and one female. Their ages ranged between 21 and 25 at the time of the experiment. They were not compensated.

2.1.3 Affectiva Q Sensor

This sensor is embedded in a wrist band, it uses a dry electrode. The sensor side of the wrist was placed on the bottom of the wrist. The sampling rate of this sensor was set to 8 samples per second.

2.1.4 BIOPAC MP30

The BIOPAC MP30 was used in conjunction with finger GSR sensors. This sensor wraps around two fingers, in this experiment the index and ring finger. It uses gel electrodes, Grass EC33 Electrode Paste was used.

The sampling rate was set to 1000 samples per second.

2.1.5 Task

2.1.6 Experimental design

The task consisted of 12 arithmetic tasks, with 4 difficulty levels. Three of every difficulty level were completed by the participants, in a random order.

The task consisted of adding up three numbers, and selecting the right answer from three options. The numbers to add were showed one by one, for four seconds. Before a task starts, a number of stars is shown equal to the difficulty level, for eight seconds. The tasks followed each other without breaks. There was no time limit for selecting the answer, there was no feedback whether the selected answer was correct.

2.1.7 Procedure

The participants were first explained the task and seated in front of the laptop. Then the sensors were applied to the left hand and wrist. The participant is then instructed to place the left hand on the table in front of them and not to move it, in order to prevent movement or motion artifacts.

2.2 Analysis

2.2.1 Affectiva Q Sensor Data

The data gathered from the Affectiva Q Sensor proved unusable. In most participants no proper contact seemed to have been made with the skin during the full experiment. Dry GSR sensors need some sweat to ensure a good connection with both electrodes. Given the short experiment duration (a few of minutes) this connection was likely never made.

In hindsight the participants could have worn the device longer before the first task start, or they could have been asked to perform some light exercise.

Any data discussed from here on is solely that collected using the BIOPAC MP30 and it's finger electrodes.

2.2.2 Preprocessing

The collected data contained a DC current, which was smoothed by filtering and resampling to 100 samples per second using Savitzky-Golay filtering. The data per subject was then cut into separate frames, the tasks.

The data was then normalized per subject over all datapoints in all tasks. This was done by dividing every data point of the subject by the average of the subject over all tasks. The reason for this division instead of ordinary normalization where all points are put between 0 and 1, is so that outliers can't totally influence all datapoints.

These tasks were then smoothed one last time, to get rid of a small remaining amount of DC noise. This was again done using a Savitzky-Golay filter.

2.2.3 Transformation

From the measurements from every task features were extracted.

The extracted time domain features:

- Average over all points in the task.
- Accumulative of all points in the task.
- Standard deviation of all points in the task.
- Difference between first and last point of the task.
- Peaks

2.2.4 Data mining

2.2.5 Interpretation

3 Results

3.1 ..?

3.2 ..?

4 Discussion

4.1 Viability

The results show that from the results

Unfortunately I can not make any conclusions regarding

4.1.1 Task bleeding

Another explanation may be the bleeding of tasks into other tasks. If for instance a subject first gets two hard tasks, and then an easy one, it is imaginable that the subjects GSR value for that easy task is higher than it would have been without first having done harder tasks.

This is mitigated by the random order in which the tasks are presented and the time between tasks, however with the relatively small subject pool it is not unimaginable this has had its effect on the classification accuracy.

4.2 Future research

Future research could include investigating how viable this method is given more portable (consumer) sensors in a real life setting.

5 Conclusion