



Basic information

DLT: fabric  
Name: journey-schedule-benchmark  
Description: Benchmarking the Hyperledger Fabric network with the JourneySchedule function  
Benchmark Rounds: 3  
[Details](#)

Benchmark results

[Summary](#)  
[journey-schedule-1-100 bytesize](#)  
[journey-schedule-2-1000 bytesize](#)  
[journey-schedule-3-2000 bytesize](#)

System under test

[Details](#)

Caliper report

Summary of performance metrics

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
journey-schedule-1-100 bytesize	154	1	155.5	2.21	0.13	0.71	49.4
journey-schedule-2-1000 bytesize	182	1	183.4	2.28	0.13	0.74	57.0
journey-schedule-3-2000 bytesize	172	1	171.5	2.25	0.13	0.70	54.2

Benchmark round: journey-schedule-1-100 bytesize

Benchmarking the JourneySchedule function with specific parameters.

```
txDuration: 1
rateControl:
  type: fixed-rate
  opts:
    tps: 1000
```

Performance metrics for journey-schedule-1-100 bytesize

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
journey-schedule-1-100 bytesize	154	1	155.5	2.21	0.13	0.71	49.4

Resource utilization for journey-schedule-1-100 bytesize

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-e961b826e2a1772403fa1461dc69e5cc120473a06e4fe1c3c9cd9eb35cdb2ab3
		dev-peer0.org2.example.com-basic_1.0-e961b826e2a1772403fa1461dc69e5cc120473a06e4fe1c3c9cd9eb35cdb2ab3
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-e961b826e2a1772403fa1461dc69e5cc120473a06e4fe1c3c9cd9eb35cdb2ab3
		dev-peer0.org2.example.com-basic_1.0-e961b826e2a1772403fa1461dc69e5cc120473a06e4fe1c3c9cd9eb35cdb2ab3
		orderer.example.com



Basic information

DLT: fabric  
Name: journey-schedule-benchmark  
Description: Benchmarking the Hyperledger Fabric network with the JourneySchedule function  
Benchmark Rounds: 3  
[Details](#)

Benchmark results

[Summary](#)  
[journey-schedule-1-100 bytesize](#)  
[journey-schedule-2-1000 bytesize](#)  
[journey-schedule-3-2000 bytesize](#)

System under test

[Details](#)

		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Benchmark round: journey-schedule-2-1000 bytesize

Another test case for JourneySchedule function.

```
txDuration: 1
rateControl:
  type: fixed-rate
  opts:
    tps: 1000
```

Performance metrics for journey-schedule-2-1000 bytesize

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
journey-schedule-2-1000 bytesize	182	1	183.4	2.28	0.13	0.74	57.0

Resource utilization for journey-schedule-2-1000 bytesize

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-e961b826e2a1772403fa1461dc69e5cc120473a06e4fe1c3c9cd9eb35cdb2ab3
		dev-peer0.org2.example.com-basic_1.0-e961b826e2a1772403fa1461dc69e5cc120473a06e4fe1c3c9cd9eb35cdb2ab3
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-e961b826e2a1772403fa1461dc69e5cc120473a06e4fe1c3c9cd9eb35cdb2ab3



Basic information

DLT: fabric  
Name: journey-schedule-benchmark  
Description: Benchmarking the Hyperledger Fabric network with the JourneySchedule function  
Benchmark Rounds: 3  
[Details](#)

Benchmark results

[Summary](#)  
[journey-schedule-1-100 bytesize](#)  
[journey-schedule-2-1000 bytesize](#)  
[journey-schedule-3-2000 bytesize](#)

System under test

[Details](#)

		dev-peer0.org2.example.com-basic_1.0-e961b826e2a1772403fa1461dc69e5cc120473a06e4fe1c3c9cd9eb35cdb2ab3
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Benchmark round: journey-schedule-3-2000 bytesize

Yet another test case for JourneySchedule function.

```
txDuration: 1
rateControl:
  type: fixed-rate
  opts:
    tps: 1000
```

Performance metrics for journey-schedule-3-2000 bytesize

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
journey-schedule-3-2000 bytesize	172	1	171.5	2.25	0.13	0.70	54.2

Resource utilization for journey-schedule-3-2000 bytesize

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-e961b826e2a1772403fa1461dc69e5cc120473a06e4fe1c3c9cd9eb35cdb2ab3
		dev-peer0.org2.example.com-basic_1.0-e961b826e2a1772403fa1461dc69e5cc120473a06e4fe1c3c9cd9eb35cdb2ab3
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer



Basic information

DLT: fabric  
Name: journey-schedule-benchmark  
Description: Benchmarking the Hyperledger Fabric network with the JourneySchedule function  
Benchmark Rounds: 3  
[Details](#)

Benchmark results

[Summary](#)  
[journey-schedule-1-100 bytesize](#)  
[journey-schedule-2-1000 bytesize](#)  
[journey-schedule-3-2000 bytesize](#)

System under test

[Details](#)

		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-e961b826e2a1772403fa1461dc69e5cc120473a06e4fe1c3c9cd9eb35cdb2ab3
		dev-peer0.org2.example.com-basic_1.0-e961b826e2a1772403fa1461dc69e5cc120473a06e4fe1c3c9cd9eb35cdb2ab3
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Test Environment

benchmark config

```
name: journey-schedule-benchmark
description: Benchmarking the Hyperledger Fabric network with the JourneySchedule function
workers:
  number: 1
rounds:
  - label: journey-schedule-1-100 bytesize
    description: Benchmarking the JourneySchedule function with specific parameters.
    chaincodeID: basic
    txDuration: 1
    rateControl:
      type: fixed-rate
      opts:
        tps: 1000
    workload:
      module: benchmarks/datamanagement/workloads/create-journey.js
      arguments:
        chaincodeID: basic
        byteSize: 100
  - label: journey-schedule-2-1000 bytesize
    description: Another test case for JourneySchedule function.
    chaincodeID: basic
    txDuration: 1
    rateControl:
      type: fixed-rate
      opts:
        tps: 1000
    workload:
      module: benchmarks/datamanagement/workloads/create-journey.js
      arguments:
        chaincodeID: basic
        byteSize: 1000
  - label: journey-schedule-3-2000 bytesize
    description: Yet another test case for JourneySchedule function.
    chaincodeID: basic
    txDuration: 1
    rateControl:
      type: fixed-rate
      opts:
        tps: 1000
    workload:
      module: benchmarks/datamanagement/workloads/create-journey.js
      arguments:
        chaincodeID: basic
        byteSize: 2000
```



SUT

not provided

Basic information

DLT: fabric  
Name: journey-schedule-benchmark  
Description: Benchmarking the Hyperledger Fabric network with the JourneySchedule function  
Benchmark Rounds: 3  
[Details](#)

Benchmark results

[Summary](#)  
[journey-schedule-1-100 bytesize](#)  
[journey-schedule-2-1000 bytesize](#)  
[journey-schedule-3-2000 bytesize](#)

System under test

[Details](#)