



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertHistoricalDataHash function
Benchmark Rounds: 8
[Details](#)

Benchmark results

- [Summary](#)
- [insert-data-offer](#)
- [insert-data-offer-100](#)
- [insert-data-offer-1000](#)
- [insert-data-offer-4000](#)
- [insert-data-offer-8000](#)
- [insert-data-offer-13000](#)
- [insert-data-offer-32000](#)
- [insert-data-offer-64000](#)

System under test

[Details](#)

Caliper report

Summary of performance metrics

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer	910	0	15.1	0.51	0.12	0.32	15.1
insert-data-offer-100	2128	0	36.3	2.24	0.12	0.35	35.2
insert-data-offer-1000	2663	0	45.5	2.16	0.13	0.41	44.0
insert-data-offer-4000	2902	0	49.8	2.26	0.14	0.51	48.0
insert-data-offer-8000	2905	0	48.9	2.33	0.15	0.72	47.9
insert-data-offer-13000	2987	0	49.7	2.29	0.16	0.95	48.9
insert-data-offer-32000	3024	0	51.1	2.36	0.22	1.15	49.5
insert-data-offer-64000	2991	0	50.7	2.34	0.19	1.23	48.7

Benchmark round: insert-data-offer

Benchmarking the InsertHistoricalDataHash function with specific parameters.

```
txDuration: 60
rateControl:
  type: fixed-rate
  opts:
    tps: 15
```

Performance metrics for insert-data-offer

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer	910	0	15.1	0.51	0.12	0.32	15.1

Resource utilization for insert-data-offer

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertHistoricalDataHash function
Benchmark Rounds: 8
[Details](#)

Benchmark results

- [Summary](#)
- [insert-data-offer](#)
- [insert-data-offer-100](#)
- [insert-data-offer-1000](#)
- [insert-data-offer-4000](#)
- [insert-data-offer-8000](#)
- [insert-data-offer-13000](#)
- [insert-data-offer-32000](#)
- [insert-data-offer-64000](#)

System under test

[Details](#)

		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Benchmark round: insert-data-offer-100

Test InsertHistoricalDataHash function with data hash size 100 bytes

```
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 10
    startingTps: 1
```

Performance metrics for insert-data-offer-100

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer-100	2128	0	36.3	2.24	0.12	0.35	35.2

Resource utilization for insert-data-offer-100

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertHistoricalDataHash function
Benchmark Rounds: 8
[Details](#)

Benchmark results

- [Summary](#)
- [insert-data-offer](#)
- [insert-data-offer-100](#)
- [insert-data-offer-1000](#)
- [insert-data-offer-4000](#)
- [insert-data-offer-8000](#)
- [insert-data-offer-13000](#)
- [insert-data-offer-32000](#)
- [insert-data-offer-64000](#)

System under test

[Details](#)

CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Benchmark round: insert-data-offer-1000

Test InsertHistoricalDataHash function with data hash size 1000 bytes

```
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 20
    startingTps: 1
```

Performance metrics for insert-data-offer-1000

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer-1000	2663	0	45.5	2.16	0.13	0.41	44.0

Resource utilization for insert-data-offer-1000

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertHistoricalDataHash function
Benchmark Rounds: 8
[Details](#)

Benchmark results

- [Summary](#)
- [insert-data-offer](#)
- [insert-data-offer-100](#)
- [insert-data-offer-1000](#)
- [insert-data-offer-4000](#)
- [insert-data-offer-8000](#)
- [insert-data-offer-13000](#)
- [insert-data-offer-32000](#)
- [insert-data-offer-64000](#)

System under test

[Details](#)

		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Benchmark round: insert-data-offer-4000

Test InsertHistoricalDataHash function with data hash size 4000 bytes

```
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 30
    startingTps: 1
```

Performance metrics for insert-data-offer-4000

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer-4000	2902	0	49.8	2.26	0.14	0.51	48.0

Resource utilization for insert-data-offer-4000

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertHistoricalDataHash function
Benchmark Rounds: 8
[Details](#)

Benchmark results

- [Summary](#)
- [insert-data-offer](#)
- [insert-data-offer-100](#)
- [insert-data-offer-1000](#)
- [insert-data-offer-4000](#)
- [insert-data-offer-8000](#)
- [insert-data-offer-13000](#)
- [insert-data-offer-32000](#)
- [insert-data-offer-64000](#)

System under test

[Details](#)

		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Benchmark round: insert-data-offer-8000

Test InsertHistoricalDataHash function with data hash size 8000 bytes

```
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 50
    startingTps: 1
```

Performance metrics for insert-data-offer-8000

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer-8000	2905	0	48.9	2.33	0.15	0.72	47.9

Resource utilization for insert-data-offer-8000

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertHistoricalDataHash function
Benchmark Rounds: 8
[Details](#)

Benchmark results

- [Summary](#)
- [insert-data-offer](#)
- [insert-data-offer-100](#)
- [insert-data-offer-1000](#)
- [insert-data-offer-4000](#)
- [insert-data-offer-8000](#)
- [insert-data-offer-13000](#)
- [insert-data-offer-32000](#)
- [insert-data-offer-64000](#)

System under test

[Details](#)

		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Benchmark round: insert-data-offer-13000

Test InsertHistoricalDataHash function with data hash size 13000 bytes

```
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 70
    startingTps: 1
```

Performance metrics for insert-data-offer-13000

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer-13000	2987	0	49.7	2.29	0.16	0.95	48.9

Resource utilization for insert-data-offer-13000

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertHistoricalDataHash function
Benchmark Rounds: 8
[Details](#)

Benchmark results

- [Summary](#)
- [insert-data-offer](#)
- [insert-data-offer-100](#)
- [insert-data-offer-1000](#)
- [insert-data-offer-4000](#)
- [insert-data-offer-8000](#)
- [insert-data-offer-13000](#)
- [insert-data-offer-32000](#)
- [insert-data-offer-64000](#)

System under test

[Details](#)

Memory (MB)		
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Benchmark round: insert-data-offer-32000

Test InsertHistoricalDataHash function with data hash size 32000 bytes

```
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 90
    startingTps: 1
```

Performance metrics for insert-data-offer-32000

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer-32000	3024	0	51.1	2.36	0.22	1.15	49.5

Resource utilization for insert-data-offer-32000



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertHistoricalDataHash function
Benchmark Rounds: 8
[Details](#)

Benchmark results

- [Summary](#)
- [insert-data-offer](#)
- [insert-data-offer-100](#)
- [insert-data-offer-1000](#)
- [insert-data-offer-4000](#)
- [insert-data-offer-8000](#)
- [insert-data-offer-13000](#)
- [insert-data-offer-32000](#)
- [insert-data-offer-64000](#)

System under test

[Details](#)

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Benchmark round: insert-data-offer-64000

Test InsertHistoricalDataHash function with data hash size 64000 bytes

```
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 100
    startingTps: 1
```

Performance metrics for insert-data-offer-64000

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer-	2991	0	50.7	2.34	0.19	1.23	48.7



64000							
-------	--	--	--	--	--	--	--

Resource utilization for insert-data-offer-64000

Resource monitor: prometheus

Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertHistoricalDataHash function
Benchmark Rounds: 8
[Details](#)

Benchmark results

[Summary](#)
[insert-data-offer](#)
[insert-data-offer-100](#)
[insert-data-offer-1000](#)
[insert-data-offer-4000](#)
[insert-data-offer-8000](#)
[insert-data-offer-13000](#)
[insert-data-offer-32000](#)
[insert-data-offer-64000](#)

System under test

[Details](#)

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		dev-peer0.org2.example.com-basic_1.0-637b908e08b257332d955d5b7eadeac170c68a9499b6070bb44fcd2688726576
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Test Environment

benchmark config

```
name: insert-data-offer-benchmark
description: >-
  Benchmarking the Hyperledger Fabric network with the InsertHistoricalDataHash
  function
workers:
  number: 10
rounds:
  - label: insert-data-offer
    description: >-
      Benchmarking the InsertHistoricalDataHash function with specific
```



Basic information

DLT: fabric

Name: insert-data-offer-benchmark

Description: Benchmarking the Hyperledger Fabric network with the InsertHistoricalDataHash function

Benchmark Rounds: 8

[Details](#)

Benchmark results

[Summary](#)

[insert-data-offer](#)

[insert-data-offer-100](#)

[insert-data-offer-1000](#)

[insert-data-offer-4000](#)

[insert-data-offer-8000](#)

[insert-data-offer-13000](#)

[insert-data-offer-32000](#)

[insert-data-offer-64000](#)

System under test

[Details](#)

```

parameters:
chaincodeID: basic
txDuration: 60
rateControl:
  type: fixed-rate
  opts:
    tps: 15
workload:
  module: benchmarks/datamanagement/workloads/insert-data-offer.js
  arguments:
    chaincodeID: basic
- label: insert-data-offer-100
  description: Test InsertHistoricalDataHash function with data hash size 100
bytes
chaincodeID: basic
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 10
    startingTps: 1
workload:
  module: benchmarks/datamanagement/workloads/insert-data-offer.js
  arguments:
    chaincodeID: basic
    byteSize: 100
- label: insert-data-offer-1000
  description: Test InsertHistoricalDataHash function with data hash size 1000
bytes
chaincodeID: basic
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 20
    startingTps: 1
workload:
  module: benchmarks/datamanagement/workloads/insert-data-offer.js
  arguments:
    chaincodeID: basic
    byteSize: 1000
- label: insert-data-offer-4000
  description: Test InsertHistoricalDataHash function with data hash size 4000
bytes
chaincodeID: basic
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 30
    startingTps: 1
workload:
  module: benchmarks/datamanagement/workloads/insert-data-offer.js
  arguments:
    chaincodeID: basic
    byteSize: 4000
- label: insert-data-offer-8000
  description: Test InsertHistoricalDataHash function with data hash size 8000
bytes
chaincodeID: basic
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 50
    startingTps: 1
workload:
  module: benchmarks/datamanagement/workloads/insert-data-offer.js
  arguments:
    chaincodeID: basic
    byteSize: 8000
- label: insert-data-offer-13000
  description: Test InsertHistoricalDataHash function with data hash size 13000
bytes
chaincodeID: basic
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 70
    startingTps: 1
workload:
  module: benchmarks/datamanagement/workloads/insert-data-offer.js
  arguments:
    chaincodeID: basic
    byteSize: 13000
- label: insert-data-offer-32000
  description: Test InsertHistoricalDataHash function with data hash size 32000
bytes
chaincodeID: basic
txDuration: 60
rateControl:
  type: fixed-load
  opts:
    transactionLoad: 90
    startingTps: 1
workload:
  module: benchmarks/datamanagement/workloads/insert-data-offer.js
  arguments:
    chaincodeID: basic
    byteSize: 32000
- label: insert-data-offer-64000
  description: Test InsertHistoricalDataHash function with data hash size 64000
bytes
chaincodeID: basic
txDuration: 60
rateControl:
  type: fixed-load
  opts:

```



```
transactionLoad: 100
startingTps: 1
workload:
  module: benchmarks/datamanagement/workloads/insert-data-offer.js
  arguments:
    chaincodeID: basic
    byteSize: 64000
```

Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertHistoricalDataHash function
Benchmark Rounds: 8
[Details](#)

SUT

not provided

Benchmark results

- [Summary](#)
 - [insert-data-offer](#)
 - [insert-data-offer-100](#)
 - [insert-data-offer-1000](#)
 - [insert-data-offer-4000](#)
 - [insert-data-offer-8000](#)
 - [insert-data-offer-13000](#)
 - [insert-data-offer-32000](#)
 - [insert-data-offer-64000](#)
-

System under test

[Details](#)
