



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertDataOffer function
Benchmark Rounds: 4
[Details](#)

Benchmark results

[Summary](#)
[insert-data-offer](#)
[insert-data-offer-100](#)
[insert-data-offer-1000](#)
[insert-data-offer-2000](#)

System under test

[Details](#)

Caliper report

Summary of performance metrics

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer	3610	0	59.9	1.18	0.13	0.47	59.1
insert-data-offer-100	3610	0	60.0	6.94	0.21	3.08	54.2
insert-data-offer-1000	3610	0	60.0	11.26	0.15	5.65	50.7
insert-data-offer-2000	3610	0	60.0	13.61	0.19	6.99	49.0

Benchmark round: insert-data-offer

Benchmarking the InsertDataOffer function with specific parameters.

```
txDuration: 60
rateControl:
  type: fixed-rate
  opts:
    tps: 60
```

Performance metrics for insert-data-offer

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer	3610	0	59.9	1.18	0.13	0.47	59.1

Resource utilization for insert-data-offer

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+",}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		dev-peer0.org2.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+",}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		dev-peer0.org2.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		orderer.example.com



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertDataOffer function
Benchmark Rounds: 4
[Details](#)

Benchmark results

- [Summary](#)
- [insert-data-offer](#)
- [insert-data-offer-100](#)
- [insert-data-offer-1000](#)
- [insert-data-offer-2000](#)

System under test

[Details](#)

		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Benchmark round: insert-data-offer-100

Test InsertDataOffer function with data hash size 100 bytes

```
txDuration: 60
rateControl:
  type: fixed-rate
  opts:
    tps: 60
```

Performance metrics for insert-data-offer-100

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer-100	3610	0	60.0	6.94	0.21	3.08	54.2

Resource utilization for insert-data-offer-100

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		dev-peer0.org2.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertDataOffer function
Benchmark Rounds: 4
[Details](#)

Benchmark results

[Summary](#)
[insert-data-offer](#)
[insert-data-offer-100](#)
[insert-data-offer-1000](#)
[insert-data-offer-2000](#)

System under test

[Details](#)

		dev-peer0.org2.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Benchmark round: insert-data-offer-1000

Test InsertDataOffer function with data hash size 1000 bytes

```
txDuration: 60
rateControl:
  type: fixed-rate
  opts:
    tps: 60
```

Performance metrics for insert-data-offer-1000

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer-1000	3610	0	60.0	11.26	0.15	5.65	50.7

Resource utilization for insert-data-offer-1000

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		dev-peer0.org2.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertDataOffer function
Benchmark Rounds: 4
[Details](#)

Benchmark results

- [Summary](#)
- [insert-data-offer](#)
- [insert-data-offer-100](#)
- [insert-data-offer-1000](#)
- [insert-data-offer-2000](#)

System under test

[Details](#)

		couchdb1
		dev-peer0.org1.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		dev-peer0.org2.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+"}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Benchmark round: insert-data-offer-2000

Test InsertDataOffer function with data hash size 2000 bytes

```
txDuration: 60
rateControl:
  type: fixed-rate
  opts:
    tps: 60
```

Performance metrics for insert-data-offer-2000

Name	Succ	Fail	Send Rate (TPS)	Max Latency (s)	Min Latency (s)	Avg Latency (s)	Throughput (TPS)
insert-data-offer-2000	3610	0	60.0	13.61	0.19	6.99	49.0

Resource utilization for insert-data-offer-2000

Resource monitor: prometheus

Metric	Prometheus Query	Name
Avg Memory (MB)	sum(container_memory_rss{name=~".+"}) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		dev-peer0.org2.example.com-basic_1.0-06ae9571ee4eeadc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		orderer.example.com
		peer0.org1.example.com



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertDataOffer function
Benchmark Rounds: 4
[Details](#)

Benchmark results

[Summary](#)
[insert-data-offer](#)
[insert-data-offer-100](#)
[insert-data-offer-1000](#)
[insert-data-offer-2000](#)

System under test

[Details](#)

		peer0.org2.example.com
CPU (%)	sum(rate(container_cpu_usage_seconds_total{name=~".+",}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		dev-peer0.org1.example.com-basic_1.0-06ae9571ee4e6dc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		dev-peer0.org2.example.com-basic_1.0-06ae9571ee4e6dc6e98048d50ab0d2f300beed87dbecb5f570d58cf7a4fc8e8
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Write (MB)	sum(rate(container_fs_writes_bytes_total{name=~".+",}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com
Disc Read (MB)	sum(rate(container_fs_reads_bytes_total{name=~".+",}[1m])) by (name)	ca_orderer
		couchdb0
		couchdb1
		orderer.example.com
		peer0.org1.example.com
		peer0.org2.example.com

Test Environment

benchmark config

```
name: insert-data-offer-benchmark
description: Benchmarking the Hyperledger Fabric network with the InsertDataOffer function
workers:
  number: 10
rounds:
  - label: insert-data-offer
    description: Benchmarking the InsertDataOffer function with specific parameters.
    chaincodeID: basic
    txDuration: 60
    rateControl:
      type: fixed-rate
      opts:
        tps: 60
    workload:
      module: benchmarks/datamanagement/workloads/insert-data-offer.js
      arguments:
        chaincodeID: basic
  - label: insert-data-offer-100
    description: Test InsertDataOffer function with data hash size 100 bytes
    chaincodeID: basic
    txDuration: 60
    rateControl:
      type: fixed-rate
      opts:
        tps: 60
    workload:
      module: benchmarks/datamanagement/workloads/insert-data-offer.js
      arguments:
        chaincodeID: basic
        byteSize: 100
  - label: insert-data-offer-1000
    description: Test InsertDataOffer function with data hash size 1000 bytes
    chaincodeID: basic
    txDuration: 60
    rateControl:
      type: fixed-rate
      opts:
        tps: 60
```



Basic information

DLT: fabric
Name: insert-data-offer-benchmark
Description: Benchmarking the Hyperledger Fabric network with the InsertDataOffer function
Benchmark Rounds: 4
[Details](#)

Benchmark results

- [Summary](#)
- [insert-data-offer](#)
- [insert-data-offer-100](#)
- [insert-data-offer-1000](#)
- [insert-data-offer-2000](#)

System under test

[Details](#)

```
workload:
  module: benchmarks/datamanagement/workloads/insert-data-offer.js
  arguments:
    chaincodeID: basic
    byteSize: 1000
- label: insert-data-offer-2000
  description: Test InsertDataOffer function with data hash size 2000 bytes
  chaincodeID: basic
  txDuration: 60
  rateControl:
    type: fixed-rate
    opts:
      tps: 60
workload:
  module: benchmarks/datamanagement/workloads/insert-data-offer.js
  arguments:
    chaincodeID: basic
    byteSize: 2000
```

SUT

not provided