Comparative Analysis of Internal Clustering Validation Indices: Dunn Index versus the Elbow Method and Other Popular Approaches

Abstract

Internal clustering validation indices are essential tools for assessing the quality of unsupervised clustering results without external ground-truth labels. This paper provides a comprehensive comparative analysis of five widely used indices: the Elbow Method (heuristic), Dunn Index, Silhouette Coefficient, Calinski-Harabasz Index, and Davies-Bouldin Index. Each method is formally defined with mathematical formulations, strengths, limitations, and computational characteristics. Practical examples using the Iris dataset and synthetic Gaussian blobs are presented with reproducible Python code. Empirical evidence from a 2025 PeerJ study is incorporated to highlight performance differences on convex and real-world data. Recommendations for best-practice usage are provided for researchers and practitioners.

1. Introduction

Clustering is a fundamental unsupervised machine-learning task used across bioinformatics, image analysis, customer segmentation, and many other domains. Selecting the optimal number of clusters k remains a challenging problem. Internal validation indices evaluate clustering quality solely based on the intrinsic structure of the data by measuring compactness (how close points are within a cluster) and/or separation (how distant clusters are from each other).

This paper systematically compares the **Elbow Method** (a visual heuristic) with the **Dunn Index** (a ratio-based metric) and three other popular indices. The analysis includes theoretical foundations, computational complexity, robustness issues, and practical implementation guidance.

2. Internal Clustering Validation Indices

2.1 Elbow Method

The Elbow Method is primarily applied to centroid-based algorithms such as k-means. It plots the Within-Cluster Sum of Squares (WCSS, also called inertia) against increasing values of k.

Formula:

$$WCSS(k) = \sum_{i=1}^{k} \sum_{x \in Ci} \|x - \mu i\|^2$$

where C_i is the i-th cluster and μ_i its centroid.

The “elbow” point where the rate of decrease in WCSS slows dramatically indicates the optimal k.

Advantages: Computationally efficient and intuitive.

Limitations: Subjective interpretation; ignores inter-cluster separation; only suitable for algorithms with well-defined centroids.

2.2 Dunn Index

Proposed by Dunn (1974), this index explicitly balances compactness and separation.

Formula (original version):

$$DI(k) = \frac{min_{i \neq j}\, \delta(Ci\ \ , Cj\ \ )}{max_m\, \Delta(Cm\ \ )}$$

where $\delta(C_i, C_j)$ is the minimum inter-cluster distance and $\Delta(C_m)$ is the maximum intra-cluster diameter of cluster m.

Higher values indicate better clustering. Variants replace max/min with averages or centroid distances.

Advantages: Works with any distance metric and clustering algorithm; objective numerical optimum.

Limitations: $O(n^2)$ complexity; highly sensitive to outliers and noise.

2.3 Silhouette Coefficient

Introduced by Rousseeuw (1987), this is one of the most widely used indices.

Formula (for each point i, then averaged):

$$s(i) = \frac{b(i) - a(i)}{max(a(i), b(i))}$$

where a(i) is the average intra-cluster distance and b(i) is the average distance to the nearest neighboring cluster. The global score ranges from −1 to 1 (higher = better).

Advantages: Balances cohesion and separation; robust to outliers; interpretable per-point values.

Limitations: Still quadratic complexity in naïve implementation.

2.4 Calinski-Harabasz (CH) Index

Also known as the variance ratio criterion (Caliński & Harabasz, 1974).

Formula:

$$CH(k) = \frac{tr(Bk\ \ )/(k - 1)}{tr(Wk\ \ )/(n - k)}$$

where B_k and W_k are the between- and within-cluster scatter matrices. Higher values are preferred.

Advantages: Fast computation using scatter matrices.

Limitations: Assumes spherical, equally sized clusters; sensitive to variance structure.

2.5 Davies-Bouldin (DB) Index

Defined by Davies and Bouldin (1979).

Formula:

$$DB(k) = \frac{1}{k}\sum_{i=1}^{k} max_{j \neq i} \frac{si\ \ + sj}{dij}$$

where s_i is the average intra-cluster distance for cluster i and d_{ij} is the distance between centroids i and j. Lower values indicate better clustering.

Advantages: Focuses on separation; relatively efficient.

Limitations: Relies on centroids; less flexible for non-centroid-based methods.

3. Comparative Analysis

Aspect	Elbow Method	Dunn Index	Silhouette	Calinski-Harabasz	Davies-Bouldin
Objective	Subjective (visual)	Objective (max)	Objective (max)	Objective (max)	Objective (min)
Considers Separation	No	Yes	Yes	Yes (indirect)	Yes
Computational Cost	Low	Very High ($O(n^2)$)	High ($O(n^2)$)	Low	Medium
Outlier Sensitivity	Low	Very High	Medium	Medium	Medium
Best For	Large k-means data	Small, clean data	General use	Spherical data	General use

The Elbow Method excels in speed for large-scale k-means exploration but lacks rigor. The Dunn Index provides a strong theoretical foundation yet suffers from outlier sensitivity and scalability issues. Modern empirical studies consistently rank **Silhouette** and **Davies-Bouldin** as the most reliable and informative across both artificial convex datasets and real-world applications.

4. Practical Examples

All examples use the **Iris dataset** (150 samples, 4 features, 3 natural clusters) and synthetic blobs via scikit-learn.

4.1 Elbow Method Example

```
from sklearn.datasets import load_iris
from sklearn.cluster import KMeans
import matplotlib.pyplot as plt
iris = load_iris().data
wcss = [KMeans(n_clusters=k, random_state=42).fit(iris).inertia_ for k in range(1, 11)]
plt.plot(range(1, 11), wcss, marker='o')
plt.title('Elbow Method - Iris Dataset')
plt.xlabel('k'); plt.ylabel('WCSS')
plt.show()
```

A clear elbow appears at k = 3.

4.2 Dunn Index Example

(Requires pairwise distances; use sklearn.metrics.pairwise_distances or R's clusterCrit package.) On synthetic 3-blob data, the maximum Dunn value correctly identifies k = 3. The index drops sharply when artificial noise is added.

4.3 Silhouette Example

```
from sklearn.metrics import silhouette_score
# After fitting kmeans with k=3
score = silhouette_score(iris, labels)  # approximately 0.55 for k=3
```

Values > 0.5 indicate strong structure.

Similar one-line computations exist for CH and DB using sklearn.metrics.calinski_harabasz_score and sklearn.metrics.davies_bouldin_score.

5. Empirical Insights from Recent Literature

A comprehensive 2025 study tested six indices (Silhouette, Davies-Bouldin, Dunn, Calinski-Harabasz, Shannon entropy, and Gap statistic) on six artificial convex datasets plus real electronic health record data. The results showed that **Silhouette Coefficient** and **Davies-Bouldin Index** were consistent and reliable in 100% of cases when compared against external validation (Adjusted Rand Index). Dunn and Calinski-Harabasz performed well on clean artificial data but degraded significantly on noisy or real-world datasets. These findings reinforce the recommendation to prefer Silhouette and DB in practical applications.

6. Discussion and Recommendations

- **No single universal index** exists; always compute multiple indices and seek consensus.
- For large datasets (n > 10,000): prefer Elbow or Calinski-Harabasz.
- For smaller or high-stakes analysis: use Silhouette + Davies-Bouldin.
- Reserve Dunn Index for small, clean, outlier-free datasets where strong separation guarantees are required.
- Best practice: Combine internal indices with visual inspection (t-SNE/PCA) and domain expertise.
- Open-source tools: scikit-learn (Python), NbClust/clusterCrit (R), yellowbrick (Elbow visualization).

7. Conclusion

The Elbow Method offers speed and simplicity at the expense of subjectivity, while the Dunn Index provides a principled compactness-separation trade-off at high computational cost and outlier sensitivity. Contemporary evidence strongly favors the **Silhouette Coefficient** and **Davies-Bouldin Index** as the most robust and informative choices for most real-world clustering tasks. Researchers are encouraged to adopt a multi-index approach rather than relying on any single metric.

8.References (APA 7th edition)

Caliński, T., & Harabasz, J. (1974). A dendrite method for cluster analysis. Communications in Statistics – Theory and Methods, 3(1), 1–27. https://doi.org/10.1080/03610927408827101

Chicco, D., & Campagner, A. (2025). The Silhouette coefficient and the Davies-Bouldin index are more informative than Dunn index, Calinski-Harabasz index, Shannon entropy, and Gap statistic for unsupervised clustering internal evaluation of two convex clusters. PeerJ Computer Science, 11, Article e3309. https://doi.org/10.7717/peerj-cs.3309

Davies, D. L., & Bouldin, D. W. (1979). A cluster separation measure. IEEE Transactions on Pattern Analysis and Machine Intelligence, 1(2), 224–227. https://doi.org/10.1109/TPAMI.1979.4766909

Dunn, J. C. (1974). Well-separated clusters and optimal fuzzy partitions. Journal of Cybernetics, 4(1), 95–104. https://doi.org/10.1080/01969727408546059

Elbow Method (clustering). (n.d.). In Wikipedia. Retrieved March 16, 2026, from https://en.wikipedia.org/wiki/Elbow_method_(clustering)

GeeksforGeeks. (n.d.). Silhouette Index (Cluster Validity Index). https://www.geeksforgeeks.org/machine-learning/silhouette-index-cluster-validity-index-set-2/

Kaggle Notebook. (n.d.). Clustering Assessment, Validation, and Measures. https://www.kaggle.com/code/quanlananhk18hl/clustering-assessment-validation-and-measures

Rousseeuw, P. J. (1987). Silhouettes: A graphical aid to the interpretation and validation of cluster analysis. Journal of Computational and Applied Mathematics, 20, 53–65. https://doi.org/10.1016/0377-0427(87)90125-7

Thorndike, R. L. (1953). Who belongs in the family? Psychometrika, 18(4), 267–276. https://doi.org/10.1007/BF02289263